REQUEST FOR BIDS

PEPPER TREE ENVELOPE

19926 Ballinger Way NE Shoreline, WA 98155

RELEASED BY:



CAPITAL CONSTRUCTION DEPARTMENT

700 ANDOVER PARK WEST, SUITE C TUKWILA, WA 98188

BID DATES

ISSUANCE DATE: AUGUST 23, 2023

DUE DATE: SEPTEMBER 13, 2023

TIME: 1:00PM

CAPITAL CONSTRUCTION DEPARTMENT

TABLE OF CONTENTS SECTIONS

- A. INFORMATIONAL FORMS
- B. BID PROPOSAL
- **BB.** NO PARTICIPATION RESPONSE FORM
- C. CONTRACT DOCUMENTS
- D. THIRD PARTY REPORTS
- E. DRAWINGS AND SPECIFICATIONS



A - SECTION

INFORMATIONAL FORMS

- A.1 Invitation to Bid
- A.2 Notice to All Bidders
- **A.3** Instructions to Bidders for Contracts (form HUD 5369)
- A.4 Fair Housing / Accessibility Notice
- A.5 Pre-Bid Conference MANDATORY ATTENDANCE
- A.6 Project Wage Rates
- A.7 Tax Applications
- A.8 Section 3
 - a. Clause
 - b. Supplemental Instruction to Bidders
- A.9 Progress Payment Suspension Criteria
- A.10 Executive Order 11246 (as Amended)
- A.11 Compliance with Executive Order 13496
- A.12 Requirements for Public Works Jobs
 - a. Requirements for Public Works Jobs
 - b. Screenshots of Intent
 - c. Davis Bacon & Related Acts Provisions; Contract Work Hours & Safety Standards Act; General Information



INVITATION FOR BID DUE DATE: SEPTEMBER 13, 2023

The King County Housing Authority (KCHA) will accept bids from qualified general contractors to furnish labor, materials and necessary equipment to perform the following:

SCOPE OF WORK:

Pepper Tree apartments is located in the City of Shoreline, built in 1985, and consists of a three (3) story multifamily building which house 30 individual residential units. The existing structure consist of 2x framing, batt insulation, gwb, weather resistant barrier and fiber cement siding. All of which will be removed down to the existing framing and reinsulated with new batt insulation between the stud bays, ½" fire-retardant wall sheathing, 1" Mineral fiber board insulation, 1x4 furring strips, Tyvek drain wrap and fiber cement siding and trim. The existing roof, barge boards, fascia and soffits will remain in place. The soffits and fascia board, and barge boards will be repainted.

Exterior work will include:

- Installation of structural floor-to-floor hold-downs to the upper roof section per structural drawings and details.
- Demo and framing of existing deck walls and reconstruction to incorporate new fiberglass railings.
- Demo of existing deck surface application. This removal will include grinding to remove any adhesion, patching, or floating to ensure proper application of new fluid applied deck coating.
- Removal of windows, patio doors and patio storage doors, mechanical and electrical room doors.
- Electrical Panel block out and trim at selective elevations, blocking installation at hose bibs, light fixture, GFI outlets, and building signs.
- The Contractor will add an electrical extension box as required to accommodate the new wall assembly and added blocking,
- Existing hose bibs will be removed, extended, and reinstalled to incorporate new wall assembly.
- All building lights and fire alarm apparatuses will be removed and reinstalled to incorporate the new building assembly.
- Sand, prep, and paint all existing metal handrails at the east and west entry buildings and along the walkway at the West elevation.

For complete scope, please see E.1 Scope of Work and Technical Specifications

DRAWINGS - PROJECT MANUAL DISTRIBUTION:

Drawing and bid documents can be downloaded from:

https://www.kcha.org/business/construction/open

PRE-BID CONFERENCE:

Date: August 30, 2023
Time: 11:00 AM

Jobsite Address: 19926 Ballinger Way NE, Shoreline, WA 98155

Notation: Attendance of the Pre-Bid Site Visit is MANDATORY.

Questions / Direct Questions, Requests or Clarification by Email or Fax to:

Contact Person: Project Manager: Amy Kurtz

Email Address:amyk@kcha.orgPhone Number:206-574-1283No Later Than:September 6, 2023

Invitation to Bid Page 1 of 4 KCHA / 07-19-23

Informational Form A.1



Website Posting: https://www.kcha.org/business/construction/open

All responses shall be in the form of Addenda

All Addenda(s) will post As Occurs Plan Holder's List posts every Friday

BIDS ARE DUE:

Date: SEPTEMBER 13, 2023

Time: **1:00 pm**

Address: King County Housing Authority

600 Andover Park West, Tukwila, WA 98188

Submittal Procedure: **Envelope MUST BE:**

a. Sealed

b. List Name and Address of your Firm/Company

c. List Due Date and Timed. List Project Name:

PEPPER TREE ENVELOPE

e. Mailing / Shipping Package or Wrapping **must also be marked** with this

information.

KCHA Process: All Bids MUST BE Time and Date Stamped at King County Housing

Authority's Central Campus by the above Due Date and Time.

- a. No Bids will be accepted after that Date and Time.
- b. No Bids Faxed or Emailed will be accepted.
- A KCHA representative will be present at the front desk at
 600 Andover Park West, Tukwila, WA 98188 to time stamp bids.
- d. Bids will be accepted between **NOON 1:00PM ONLY**.
- e. At 1:00PM bidding will be closed and no further bids will be accepted.
- f. Bids received on or before 1:00 PM will be opened and read in the presence of one or more witnesses which includes KCHA staff (project manager and project specialist). Bidding Contractors are invited to attend the public opening.
- g. Bids will be tabulated and bidders notified by email of the bid results. **NOTE: Contractors have the option to mail in bids, but bids must be received by the deadline of 1:00PM. KCHA does not recommend mailing in bids due to possible complications or difficulties that may arise with the mail delivery.

BID BOND OR CERTIFIED CHECK:

Amount: Five (5%) Percent of the Total bid must accompany Each Bid greater than one

hundred fifty (\$150,000) dollars.

Payable to: King County Housing Authority

Process: Bid Bond or Certified Check will be returned to the Unsuccessful Bidders within

Ten (10) Days after the Contract Award.

BONDS MUST BE ORIGINAL, NO PHOTOCOPIES OR SCANNED BONDS WILL BE ALLOWED

MASKING COMPLIANCE

Contractor's employees and all sub-contractors' employees will be required to wear a mask if they are asked to do so by a resident or property manager while in a building or a resident's unit.

ASSURANCE OF COMPLETION:

Projects valued over one hundred fifty thousand (\$150,000) dollars **require** a one hundred (100%) percent Performance and Payment Bond. (See Section C – Contract Documents)



BONDING CAPACITY:

Provide **with your bid proposal**, a written statement from the contractor's bonding agent of the contractor's ability and capacity for providing a one hundred (100%) percent Performance and Payment Bond for the project. The statement shall be made on the official letterhead of the bonding company and signed by an authorized agent of the bonding company.

BONDING & INSURANCE FOR CONTRACT AWARD:

The contract award will be contingent on full performance bonding, or equivalent and contractor's ability to meet KCHA insurance requirements as outlined in the bid documents.

HUD NON-ROUTINE MAINTENANCE WAGE RATES:

Bidders should note that the current HUD Non-Routine Maintenance wage rates and weekly payroll reporting requirements apply to this project.

WASHINGTON STATE REQUIREMENT:

All contractors and subcontractors working on this project are required to file a "Statement of Intent to Pay Prevailing Wages", "Affidavit of Wages Paid" and certified payroll with L&I. (See Form A.12 for additional information.)

EEOE:

The King County Housing Authority is an Equal Employment Opportunity Employer and strongly encourages minority-owned and women-owned businesses, socially and economically disadvantaged businesses, and small businesses to submit bids or to participate as subcontractors and suppliers on KCHA Contracts.

KCHA RESERVED RIGHTS:

The King County Housing Authority reserves the right to reject any or all bids or to waive any informality in the bidding. No bid shall be withdrawn for a period of thirty (30) calendar days subsequent to the opening of the bids without the written consent of KCHA.

The King County Housing Authority also reserves the right to reject all bids, for any reason, prior to Contract Execution.

PUBLIC RECORDS:

All information submitted to KCHA will become public records, as per RCW 42.56. If you are submitting information, which you think is confidential and/or proprietary to your business, KCHA recommends that you do not submit that information, as KCHA cannot guarantee that type of information will be withheld from a public disclosure request.

PLAN CENTERS:

Bid documents, including drawings, specifications and conditions of the agreements may be examined at the following offices:

BUILDERS EXCHANGE OF WA 2607 Wetmore Ave.

Everett, WA 98201 www.bxwa.com

425-258-1303

CONTRACTOR PLAN CENTER 5468 SE International Way

Milwaukie, OR 97222

www.contractorplancenter.com 503-650-0148



DAILY JOURNAL OF COMMERCE

DODGE CONSTRUCTION NETWORK

ISQFT

www.djc.com 206-622-8272 www.construction.com 877-784-9556 www.isqft.com 800-364-2059 x7051

The King County Housing Authority is an Equal Employment Opportunity Employer and strongly encourages minority-owned and women-owned businesses, socially and economically disadvantaged businesses, and small businesses to submit bids or to participate as subcontractors and suppliers on KCHA Contracts.

The King County Housing Authority reserves the right to reject any or all bids or to waive any informality in the bidding. No bid shall be withdrawn for a period of thirty (30) calendar days subsequent to the opening of the bids without the written consent of KCHA.

PUBLICATION: Daily Journal of Commerce Daily

The Seattle Medium Wednesday
Northwest Asian Weekly Thursday

KCHA Web Site www.kcha.org/business/construction/open

CONTACT PERSON:

Amy Kurtz Project Manager 206-574-1283 Phone Number Amy K@kcha.org Email Address

EXAMPLE OF SEALED ENVELOPE PROCEDURE / PREPARATION:

FROM:

ENTER YOUR COMPANY NAME Street Address City, State, Zip Code

TO:

KING COUNTY HOUSING AUTHORITY CAPITAL CONSTRUCTION DEPARTMENT

700 Andover Park West, Suite C

Tukwila, WA 98188

BID DUE:

Date: SEPTEMBER 13, 2023

Time: 1:00 PM

PROJECT NAME: PEPPER TREE ENVELOPE

Upon Receipt, the Envelope will be Time and Date Stamped by King County Housing Authority



NOTICE TO ALL BIDDERS

In order to be considered as **RESPONSIVE BIDS**, all bidders <u>MUST</u> submit Signed Section B forms no later than the **Bid Due Date and Time**:

- B.1 Bid Form
- **B.2** Bidder's Experience Record
- **B.3** Contractor Certification
- **B.4** Non-Collusive Affidavit
- **B.5** Equal Opportunity
- B.6 Bid Security (Submit only for bids greater than \$150,000)
- **B.7** Debarment / Suspension Compliance Certification
- **B.8** Proposed Subcontractor List
- B.9 Section 3
 - a. Business Certification
 - b. Subcontractor Work Plan
- **B.10** Harassment and Discrimination Policies
- **B.11** WMBE Survey (Form is not required to be responsive, but requested)
- **B.12** Preliminary Project Schedule Provided by Contractor

FORM 5369

From HUD Website 2021

U.S. Department of Housing and Urban Development

Office of Public and Indian Housing

Instructions to Bidders for Contracts Public and Indian Housing Programs

Instructions to Bidders for Contracts

Public and Indian Housing Programs

Table of Contents

Cla	use	Page
1.	Bid Preparation and Submission	1
2.	Explanations and Interpretations to Prospective Bidders	1
3.	Amendments to Invitations for Bids	1
4.	Responsibility of Prospective Contractor	1
5.	Late Submissions, Modifications, and Withdrawal of Bid	s 1
6.	Bid Opening	2
7.	Service of Protest	2
8.	Contract Award	2
9.	Bid Guarantee	3
10.	Assurance of Completion	3
11.	Preconstruction Conference	3
12.	Indian Preference Requirements	3

1. Bid Preparation and Submission

- (a) Bidders are expected to examine the specifications, drawings, all instructions, and, if applicable, the construction site (see also the contract clause entitled **Site Investigation and Conditions Affecting the Work** of the *General Conditions of the Contract for Construction*). Failure to do so will be at the bidders' risk.
- (b) All bids must be submitted on the forms provided by the Public Housing Agency/Indian Housing Authority (PHA/IHA). Bidders shall furnish all the information required by the solicitation. Bids must be signed and the bidder's name typed or printed on the bid sheet and each continuation sheet which requires the entry of information by the bidder. Erasures or other changes must be initialed by the person signing the bid. Bids signed by an agent shall be accompanied by evidence of that agent's authority. (Bidders should retain a copy of their bid for their records.)
- (c) Bidders must submit as part of their bid a completed form HUD-5369-A, "Representations, Certifications, and Other Statements of Bidders."
- (d) All bid documents shall be sealed in an envelope which shall be clearly marked with the words "Bid Documents," the Invitation for Bids (IFB) number, any project or other identifying number, the bidder's name, and the date and time for receipt of bids.
- (e) If this solicitation requires bidding on all items, failure to do so will disqualify the bid. If bidding on all items is not required, bidders should insert the words "No Bid" in the space provided for any item on which no price is submitted.
- (f) Unless expressly authorized elsewhere in this solicitation, alternate bids will not be considered.
- (g) Unless expressly authorized elsewhere in this solicitation, bids submitted by telegraph or facsimile (fax) machines will not be considered.
- (h) If the proposed contract is for a Mutual Help project (as described in 24 CFR Part 905, Subpart E) that involves Mutual Help contributions of work, material, or equipment, supplemental information regarding the bid advertisement is provided as an attachment to this solicitation.

HUD 5369-A is covered by other forms within this project Bid Document. See last page for listing.

2. Explanations and Interpretations to Prospective Bidders

- (a) Any prospective bidder desiring an explanation or interpretation of the solicitation, specifications, drawings, etc., must request it at least 7 days before the scheduled time for bid opening. Requests may be oral or written. Oral requests must be confirmed in writing. The only oral clarifications that will be provided will be those clearly related to solicitation procedures, i.e., not substantive technical information. No other oral explanation or interpretation will be provided. Any information given a prospective bidder concerning this solicitation will be furnished promptly to all other prospective bidders as a written amendment to the solicitation, if that information is necessary in submitting bids, or if the lack of it would be prejudicial to other prospective bidders.
- (b) Any information obtained by, or provided to, a bidder other than by formal amendment to the solicitation shall not constitute a change to the solicitation.

3. Amendments to Invitations for Bids

- (a) If this solicitation is amended, then all terms and conditions which are not modified remain unchanged.
- (b) Bidders shall acknowledge receipt of any amendment to this solicitation (1) by signing and returning the amendment, (2) by identifying the amendment number and date on the bid form, or (3) by letter, telegram, or facsimile, if those methods are authorized in the solicitation. The PHA/IHA must receive acknowledgement by the time and at the place specified for receipt of bids. Bids which fail to acknowledge the bidder's receipt of any amendment will result in the rejection of the bid if the amendment(s) contained information which substantively changed the PHA's/IHA's requirements.
- (c) Amendments will be on file in the offices of the PHA/IHA and the Architect at least 7 days before bid opening.

4. Responsibility of Prospective Contractor

- (a) The PHA/IHA will award contracts only to responsible prospective contractors who have the ability to perform successfully under the terms and conditions of the proposed contract. In determining the responsibility of a bidder, the PHA/IHA will consider such matters as the bidder's:
 - (1) Integrity;
 - (2) Compliance with public policy;
 - (3) Record of past performance; and
 - (4) Financial and technical resources (including construction and technical equipment).
- (b) Before a bid is considered for award, the bidder may be requested by the PHA/IHA to submit a statement or other documentation regarding any of the items in paragraph (a) above. Failure by the bidder to provide such additional information shall render the bidder nonresponsible and ineligible for award.

5. Late Submissions, Modifications, and Withdrawal of Bids

- (a) Any bid received at the place designated in the solicitation after the exact time specified for receipt will not be considered unless it is received before award is made and it:
- (1) Was sent by registered or certified mail not later than the fifth calendar day before the date specified for receipt of offers (e.g., an offer submitted in response to a solicitation requiring receipt of offers by the 20th of the month must have been mailed by the 15th);
- (2) Was sent by mail, or if authorized by the solicitation, was sent by telegram or via facsimile, and it is determined by the PHA/IHA that the late receipt was due solely to mishandling by the PHA/IHA after receipt at the PHA/IHA; or
- (3) Was sent by U.S. Postal Service Express Mail Next Day Service Post Office to Addressee, not later than 5:00 p.m. at the place of mailing two working days prior to the date specified for receipt of proposals. The term "working days" excludes weekends and observed holidays.
- (b) Any modification or withdrawal of a bid is subject to the same conditions as in paragraph (a) of this provision.
- (c) The only acceptable evidence to establish the date of mailing of a late bid, modification, or withdrawal sent either by registered or certified mail is the U.S. or Canadian Postal Service postmark both on the envelope or wrapper and on the original receipt from the U.S. or Canadian Postal Service. Both postmarks must show a legible date or the bid, modification, or withdrawal shall be processed as if mailed late. "Postmark" means a printed, stamped, or otherwise placed impression (exclusive of a postage meter machine impression) that is readily identifiable without further action as having been supplied and affixed by employees of the U.S. or Canadian Postal Service on the date of mailing. Therefore, bidders should request the postal clerk to place a hand cancellation bull's-eye postmark on both the receipt and the envelope or wrapper.
- (d) The only acceptable evidence to establish the time of receipt at the PHA/IHA is the time/date stamp of PHA/IHA on the proposal wrapper or other documentary evidence of receipt maintained by the PHA/IHA.
- (e) The only acceptable evidence to establish the date of mailing of a late bid, modification, or withdrawal sent by Express Mail Next Day Service-Post Office to Addressee is the date entered by the post office receiving clerk on the "Express Mail Next Day Service-Post Office to Addressee" label and the postmark on both the envelope or wrapper and on the original receipt from the U.S. Postal Service. "Postmark" has the same meaning as defined in paragraph (c) of this provision, excluding postmarks of the Canadian Postal Service. Therefore, bidders should request the postal clerk to place a legible hand cancellation bull's eye postmark on both the receipt and Failure by a bidder to acknowledge receipt of the envelope or wrapper.
- (f) Notwithstanding paragraph (a) of this provision, a late modification of an otherwise successful bid that makes its terms more favorable to the PHA/IHA will be considered at any time it is received and may be accepted.
- (g) Bids may be withdrawn by written notice, or if authorized by this solicitation, by telegram (including mailgram) or facsimile machine transmission received at any time before the exact time set for opening of bids; provided that written confirmation of telegraphic or facsimile withdrawals over the signature of the bidder is mailed and postmarked prior to the specified bid opening time. A bid may be withdrawn in person by a bidder or its authorized representative if, before the exact time set for opening of bids, the identity of the person requesting withdrawal is established and the person signs a receipt for the bid.

6. Bid Opening

All bids received by the date and time of receipt specified in the solicitation will be publicly opened and read. The time and place of opening will be as specified in the solicitation. Bidders and other interested persons may be present.

7. Service of Protest

(a) Definitions. As used in this provision:

"Interested party" means an actual or prospective bidder whose direct economic interest would be affected by the award of the contract.

"Protest" means a written objection by an interested party to this solicitation or to a proposed or actual award of a contract pursuant to this solicitation.

(b) Protests shall be served on the Contracting Officer by obtaining written and dated acknowledgement from —

Contracting Officer
Capital Construction Department
King County Housing Authority
600 Andover Park West
Tukwila, WA 98188

[Contracting Officer designate the official or location where a protest may be served on the Contracting Officer]

(c) All protests shall be resolved in accordance with the PHA's/IHA's protest policy and procedures, copies of which are maintained at the PHA/IHA.

8. Contract Award

- (a) The PHA/IHA will evaluate bids in response to this solicitation without discussions and will award a contract to the responsible bidder whose bid, conforming to the solicitation, will be most advantageous to the PHA/IHA considering only price and any price-related factors specified in the solicitation.
- (b) If the apparent low bid received in response to this solicitation exceeds the PHA's/IHA's available funding for the proposed contract work, the PHA/IHA may either accept separately priced items (see 8(e) below) or use the following procedure to determine contract award. The PHA/IHA shall apply in turn to each bid (proceeding in order from the apparent low bid to the high bid) each of the separately priced bid deductible items, if any, in their priority order set forth in this solicitation. If upon the application of the first deductible item to all initial bids, a new low bid is within the PHA's/IHA's available funding, then award shall be made to that bidder. If no bid is within the available funding amount, then the PHA/IHA shall apply the second deductible item. The PHA/IHA shall continue this process until an evaluated low bid, if any, is within the PHA's/IHA's available funding. If upon the application of all deductibles, no bid is within the PHA's/IHA's available funding, or if the solicitation does not request separately priced deductibles, the PHA/IHA shall follow its written policy and procedures in making any award under this solicitation.
- (c) In the case of tie low bids, award shall be made in accordance with the PHA's/IHA's written policy and procedures.
- (d) The PHA/IHA may reject any and all bids, accept other than the lowest bid (e.g., the apparent low bid is unreasonably low), and waive informalities or minor irregularities in bids received, in accordance with the PHA's/IHA's written policy and procedures.

- (e) Unless precluded elsewhere in the solicitation, the PHA/IHA may accept any item or combination of items bid.
- (f) The PHA/IHA may reject any bid as nonresponsive if it is materially unbalanced as to the prices for the various items of work to be performed. A bid is materially unbalanced when it is based on prices significantly less than cost for some work and prices which are significantly overstated for other work.
- (g) A written award shall be furnished to the successful bidder within the period for acceptance specified in the bid and shall result in a binding contract without further action by either party.
- 9. Bid Guarantee (applicable to construction and equipment contracts exceeding \$25,000)

KCHA Procurement Policy requires Bid Guarantees for Projects valued at \$150,000 or more.

All bids must be accompanied by a negotiable bid guarantee which shall not be less than five percent (5%) of the amount of the bid. The bid guarantee may be a certified check, bank draft, U.S. Government Bonds at par value, or a bid bond secured by a surety company acceptable to the U.S. Government and authorized to do business in the state where the work is to be performed. In the case where the work under the contract will be performed on an Indian reservation area, the bid guarantee may also be an irrevocable Letter of Credit (see provision 10, Assurance of Completion, below). Certified checks and bank drafts must be made payable to the order of the PHA/IHA. The bid guarantee shall insure the execution of the contract and the furnishing of a method of assurance of completion by the successful bidder as required by the solicitation. Failure to submit a bid guarantee with the bid shall result in the rejection of the bid. Bid guarantees submitted by unsuccessful bidders will be returned as soon as practicable after bid opening.

10. Assurance of Completion

- (a) Unless otherwise provided in State law, the successful bidder shall furnish an assurance of completion prior to the execution of any contract under this solicitation. This assurance may be [Contracting Officer check applicable items] —
- [X] (1) a performance and payment bond in a penal sum of 100 percent of the contract price; or, as may be required or permitted by State law:
- [] (2) separate performance and payment bonds, each for 50 percent or more of the contract price;
- [] (3) a 20 percent cash escrow;
- [] (4) a 25 percent irrevocable letter of credit; or,
- [] (5) an irrevocable letter of credit for 10 percent of the total contract price with a monitoring and disbursements agreement with the IHA (applicable only to contracts awarded by an IHA under the Indian Housing Program).
- (b) Bonds must be obtained from guarantee or surety companies acceptable to the U.S. Government and authorized to do business in the state where the work is to be performed. Individual sureties will not be considered. U.S. Treasury Circular Number 570, published annually in the Federal Register, lists companies approved to act as sureties on bonds securing Government contracts, the maximum underwriting limits on each contract bonded, and the States in which the company is licensed to do business. Use of companies listed in this circular is mandatory. Copies of the circular may be downloaded on the U.S. Department of Treasury website http://www.fms.treas.gov/c570/index.html, or ordered for a minimum fee by contacting the Government Printing Office at (202) 512-2168.

- (c) Each bond shall clearly state the rate of premium and the total amount of premium charged. The current power of attorney for the person who signs for the surety company must be attached to the bond. The effective date of the power of attorney shall not precede the date of the bond. The effective date of the bond shall be on or after the execution date of the contract.
- (d) Failure by the successful bidder to obtain the required assurance of completion within the time specified, or within such extended period as the PHA/IHA may grant based upon reasons determined adequate by the PHA/IHA, shall render the bidder ineligible for award. The PHA/IHA may then either award the contract to the next lowest responsible bidder or solicit new bids. The PHA/IHA may retain the ineligible bidder's bid guarantee.

Preconstruction Conference (applicable to construction contracts)

After award of a contract under this solicitation and prior to the start of work, the successful bidder will be required to attend a preconstruction conference with representatives of the PHA/IHA and its architect/engineer, and other interested parties convened by the PHA/IHA. The conference will serve to acquaint the participants with the general plan of the construction operation and all other requirements of the contract (e.g., Equal Employment Opportunity, Labor Standards). The PHA/IHA will provide the successful bidder with the date, time, and place of the conference.

- **12. Indian Preference Requirements** (applicable only if this solicitation is for a contract to be performed on a project for an Indian Housing Authority)
- (a) HUD has determined that the contract awarded under this solicitation is subject to the requirements of section 7(b) of the Indian Self-Determination and Education Assistance Act (25 U.S.C. 450e(b)). Section 7(b) requires that any contract or subcontract entered into for the benefit of Indians shall require that, to the greatest extent feasible
- (1) Preferences and opportunities for training and employment (other than core crew positions; see paragraph (h) below) in connection with the administration of such contracts or subcontracts be given to qualified "Indians." The Act defines "Indians" to mean persons who are members of an Indian tribe and defines "Indian tribe" to mean any Indian tribe, band, nation, or other organized group or community, including any Alaska Native village or regional or village corporation as defined in or established pursuant to the Alaska Native Claims Settlement Act, which is recognized as eligible for the special programs and services provided by the United States to Indians because of their status as Indians; and,
- (2) Preference in the award of contracts or subcontracts in connection with the administration of contracts be given to Indian organizations and to Indian-owned economic enterprises, as defined in section 3 of the Indian Financing Act of 1974 (25 U.S.C. 1452). That Act defines "economic enterprise" to mean any Indianowned commercial, industrial, or business activity established or organized for the purpose of profit, except that the Indian ownership must constitute not less than 51 percent of the enterprise; "Indian organization" to mean the governing body of any Indian tribe or entity established or recognized by such governing body; "Indian" to mean any person who is a member of any tribe, band, group, pueblo, or community which is recognized by the Federal Government as eligible for services from the Bureau of Indian Affairs and any "Native" as defined in the Alaska Native Claims Settlement Act; and Indian "tribe" to mean any Indian tribe, band, group, pueblo, or community including Native villages and Native groups (including

Treasury website: https://www.fiscal.treasury.gov/surety-bonds/

- corporations organized by Kenai, Juneau, Sitka, and Kodiak) as defined in the Alaska Native Claims Settlement Act, which is recognized by the Federal Government as eligible for services from the Bureau of Indian Affairs.
- (b) (1) The successful Contractor under this solicitation shall comply with the requirements of this provision in awarding all subcontracts under the contract and in providing training and employment opportunities.
- (2) A finding by the IHA that the contractor, either (i) awarded a subcontract without using the procedure required by the IHA, (ii) falsely represented that subcontracts would be awarded to Indian enterprises or organizations; or, (iii) failed to comply with the contractor's employment and training preference bid statement shall be grounds for termination of the contract or for the assessment of penalties or other remedies.
- (c) If specified elsewhere in this solicitation, the IHA may restrict the solicitation to qualified Indian-owned enterprises and Indian organizations. If two or more (or a greater number as specified elsewhere in the solicitation) qualified Indian-owned enterprises or organizations submit responsive bids, award shall be made to the qualified enterprise or organization with the lowest responsive bid. If fewer than the minimum required number of qualified Indian-owned enterprises or organizations submit responsive bids, the IHA shall reject all bids and readvertise the solicitation in accordance with paragraph (d) below.
- (d) If the IHA prefers not to restrict the solicitation as described in paragraph (c) above, or if after having restricted a solicitation an insufficient number of qualified Indian enterprises or organizations submit bids, the IHA may advertise for bids from non-Indian as well as Indian-owned enterprises and Indian organizations. Award shall be made to the qualified Indian enterprise or organization with the lowest responsive bid if that bid is
- (1) Within the maximum HUD-approved budget amount established for the specific project or activity for which bids are being solicited; and
- (2) No more than the percentage specified in 24 CFR 905.175(c) higher than the total bid price of the lowest responsive bid from any qualified bidder. If no responsive bid by a qualified Indian-owned economic enterprise or organization is within the stated range of the total bid price of the lowest responsive bid from any qualified enterprise, award shall be made to the bidder with the lowest bid.
- (e) Bidders seeking to qualify for preference in contracting or subcontracting shall submit proof of Indian ownership with their bids. Proof of Indian ownership shall include but not be limited to:
- (1) Certification by a tribe or other evidence that the bidder is an Indian. The IHA shall accept the certification of a tribe that an individual is a member.
- (2) Evidence such as stock ownership, structure, management, control, financing and salary or profit sharing arrangements of the enterprise.

- (f) (1) All bidders must submit with their bids a statement describing how they will provide Indian preference in the award of subcontracts. The specific requirements of that statement and the factors to used by the IHA in determining the statement's adequacy are included as an attachment to this solicitation. Any bid that fails to include the required statement shall be rejected as nonresponsive. The IHA may require that comparable statements be provided by subcontractors to the successful Contractor, and may require the Contractor to reject any bid or proposal by a subcontractor that fails to include the statement.
- (2) Bidders and prospective subcontractors shall submit a certification (supported by credible evidence) to the IHA in any instance where the bidder or subcontractor believes it is infeasible to provide Indian preference in subcontracting. The acceptance or rejection by the IHA of the certification shall be final. Rejection shall disqualify the bid from further consideration.
- (g) All bidders must submit with their bids a statement detailing their employment and training opportunities and their plans to provide preference to Indians in implementing the contract; and the number or percentage of Indians anticipated to be employed and trained. Comparable statements from all proposed subcontractors must be submitted. The criteria to be used by the IHA in determining the statement(s)'s adequacy are included as an attachment to this solicitation. Any bid that fails to include the required statement(s), or that includes a statement that does not meet minimum standards required by the IHA shall be rejected as nonresponsive.
- (h) Core crew employees. A core crew employee is an individual who is a bona fide employee of the contractor at the time the bid is submitted; or an individual who was not employed by the bidder at the time the bid was submitted, but who is regularly employed by the bidder in a supervisory or other key skilled position when work is available. Bidders shall submit with their bids a list of all core crew employees.
- (i) Preference in contracting, subcontracting, employment, and training shall apply not only on-site, on the reservation, or within the IHA's jurisdiction, but also to contracts with firms that operate outside these areas (e.g., employment in modular or manufactured housing construction facilities).
- (j) Bidders should contact the IHA to determine if any additional local preference requirements are applicable to this solicitation.
- (k) The IHA [] does [] does not [Contracting Officer check applicable box] maintain lists of Indian-owned economic enterprises and Indian organizations by specialty (e.g., plumbing, electrical, foundations), which are available to bidders to assist them in meeting their responsibility to provide preference in connection with the administration of contracts and subcontracts.

The following documents cover all sections in HUD form HUD-5369-A:

- Bid Form (Return Form B.1)
- Contractor Certification (Return Form B.3)
- Non-Collusive Affidavit (Return Form B.4)
- Equal Opportunity Form (Return Form B.5)
- WMBE (Return Form B.11)
- Certification of Payments to Influence Federal Transactions (Contract Form C.7)
- Disclosure of Lobbying Activities (Contract Form C.8)



FAIR HOUSING/ACCESSIBILITY NOTICE

A. SUBJECT:

Accessibility Notice: Section 504 of the Rehabilitation Act of 1973; the Americans with Disabilities Act of 1990; the Architectural Barriers Act of 1968 and the Fair Housing Act of 1988.

B. PURPOSE:

The purpose of this Notice is to remind recipients of Federal funds (in this instance, the Public Housing Authority) of their obligation to comply with pertinent laws and implementing regulations which provide for non-discrimination and accessibility in Federally funded housing and non-housing programs for people with disabilities.

C. NOTIFICATIONS:

Public housing agencies (PHAs) and other recipients of Federal PIH funds are responsible for providing this Notice to all current and future contractors participating in covered programs / activities or performing work covered under the above subject legislation and implementing regulations.

D. TO READ THE FULL TEXT OF THE NOTICE:

Go to www.kcha.org/business/requirements

Scroll down to Fair Housing Laws and Read: Fair Housing / Accessibility Notice



PRE-BID CONFERENCE

There will be a Pre-Bid Conference prior to the date of the bid opening for the purpose of providing a general discussion and review of any questions that might pertain to the bidding documents and procedures. All interested contractors are required to attend this meeting after reading the Project Manual. Please bring Project Manual and drawings, if any, to this conference. ATTENDANCE OF THE PRE-BID CONFERENCE IS REQUIRED FOR ACCEPTANCE OF BID FROM THE CONTRACTOR.

PROJECT SITE ADDRESS: Pepper Tree Apts

19926 Ballinger Way NE Shoreline, WA 98155

CONFERENCE DATE: August 30, 2023

TIME: 11:00 AM

CONTACT NAME: Amy Kurtz

EMAIL: AmyK@kcha.org



PROJECT WAGE RATES

- A. DAVIS BACON WAGE RATES (NA)
- **B. HUD NON-ROUTINE MAINTENANCE WAGES**

TYPE OF WAGE RATES: <u>HUD NON-ROUTINE MAINTENANCE</u>

WAGE DATE: 02-01-23

For contracts entered into pursuant to competitive bidding procedures, the bid opening date "locks-in" the Non-Routine Maintenance Wage Rates that will be used during the course of the project.

NOTE: The awarded bidder will be required to submit, along with other contractual documentation, Form C.9 Certification of Compliance with Washington State Wage Payment Statutes.

Maintenance Wage Rate Determination	U.S. Department of Housing and Urban Development Office of Labor Relations	
Agency Name:	LR 2000 Agency ID No:	Wage Decision Type:
King County Housing Authority 600 Andover Park W. Tukwila, WA 98188	WA23-ALL	☐ Routine Maintenance✓ Nonroutine Maintenance
(Sedro Woolley, King County HA)	Effective Date:	Expiration Date:
, J.	February 1, 2023	December 31, 2025

The following wage rate determination is made pursuant to Section 12(a) of the U.S. Housing Act of 1937, as amended, (public housing agencies), or pursuant to Section 104(b) of the Native American Housing Assistance and Self-determination Act of 1996, as amended, (Indian housing agencies). The agency and its contractors may pay to maintenance laborers and mechanics no less than the wage rate(s) indicated for the type of work they actually perform.

Melanie Hertelrevised 1.23.2023HUD Labor RelationsDate(Name, Title, Signature)

WORK OF VESTER VIOLES	HOURLY WAGE RATES				
WORK CLASSIFICATION(S)	BASIC WAGE	FRINGE BENEFIT(S) (if any)			
Asphalt Painter	\$23.57	\$6.30			
Asphalt Raker	\$23.57	\$6.30			
Asphalt Roller/Cement Mixer over 16yds.	\$32.24	\$10.49			
Backhoe Operator	\$30.52	\$8.85			
Carpenter	\$32.24	\$10.49			
Cement Mason - Finisher	\$32.24	\$10.49			
Concrete Saw Operator	\$30.52	\$8.85			
Drywaller	\$30.52	\$8.85			
Electrician	\$32.24	\$10.49			
Elevator Mechanic	\$56.22	\$39.76			
Fence Erector	\$23.57	\$6.30			
Glazier	\$30.52	\$8.85			
HVAC/Furnace Mechanic	\$32.24	\$10.49			
Ironworker	\$46.76	\$31.00			
Laborer	\$30.10	\$8.27			
Low Voltage Technician	\$32.24	\$10.49			
Motor Grader	\$30.52	\$8.85			
Nozzleman for Cement Mixer	\$30.52	\$8.85			
		The agency employee benefit program has been determined by HUD to be acceptable for meeting the prevailing fringe benefit requirements. (HUD Labor Relations: If applicable, check box and initial below.) LR Staff Initial FOR HUD USE ONLY			
		LR2000: Log in:			
		Log Out:			

PREVIOUS EDITION IS OBSOLETE Form HUD-52158 (04/2005)

Maintenance Wage Rate Determination	U.S. Department of Housing and Urban Development Office of Labor Relations			
Agency Name:	LR 2000 Agency ID No:	Wage Decision Type:		
King County Housing Authority 600 Andover Park W. Tukwila, WA 98188	WA23-ALL	☐ Routine Maintenance✓ Nonroutine Maintenance		
(Sedro Woolley, King County HA)	Effective Date: February 1, 2023	Expiration Date: December 31, 2025		
or pursuant to Section 104(b) of the Native America	rrsuant to Section 12(a) of the U.S. Housing Act of 1937, can Housing Assistance and Self-determination Act of 1 by to maintenance laborers and mechanics no less than	996, as amended, (Indian housing		
work they actually perform.		,		
/s/ Melanie Hertel HUD Labor Relations (Name, Title, Signature)	Revised 1.23.2023 Date	<u> </u>		

WORK CLASSIFICATION(S)	HOURLY WAGE RATES				
WORK CLASSIFICATION(S)	BASIC WAGE	FRINGE BENEFIT(S) (if any)			
Painter	\$30.52	\$8.85			
Paver/Roller/(Sakai Roller)	\$32.24	\$10.49			
Paving Machine Operator – Self Propelled	\$30.52	\$8.85			
Pipefitter	\$23.57	\$6.30			
Pipe Reliner	\$32.24	\$10.49			
Plumber	\$32.24	\$10.49			
Pressure Washer	\$23.57	\$6.30			
Refrigeration Mechanic	\$32.24	\$10.49			
Roofer	\$30.52	\$8.85			
Roto-mill/Roto-grinder Operator	\$30.52	\$8.85			
Screedman	\$30.52	\$8.85			
Sheet Metal Worker	\$32.24	\$10.49			
Soft Floor Layer	\$30.52	\$8.85			
Tree Trimmer/Tree Climber	\$23.57	\$6.30			
Truck Driver – All Yardage	\$30.52	\$8.85			
Welder	\$56.68	\$28.02			
		The agency employee benefit program has been determined by HUD to be acceptable for meeting the prevailing fringe benefit requirements. (HUD Labor Relations: If applicable, check beyond initial below)			
		box and initial below.) LR Staff Initial			
		FOR HUD USE ONLY LR2000:			
		Log in:			
		Log Out:			

PREVIOUS EDITION IS OBSOLETE Form HUD-52158 (04/2005)



TAX APPLICATIONS

TAX APPLICATIONS

If you have questions regarding the application of the retail sales tax exemption to the King County Housing Authority, please call your personal tax advisor or the Washington State Department of Revenue Office toll-free for one-on-one help: Telephone Information Center 1-800-647-7706.

WAC 458-20-17001

Government contracting -- Construction, installations, or improvements to government real property.

- (1) Special business and occupation tax applications and special sales/use tax applications pertain for prime and subcontractors who perform certain construction, installation, and improvements to real property of or for the United States, its instrumentalities, or a county or city housing authority created pursuant to chapter 35.82 RCW. These specific construction activities are excluded from the definition of "sale at retail" under RCW 82.04.050. All other sales to the United States, its agencies or instrumentalities are taxable as retail sales or wholesale sales, as appropriate. See WAC 458-20-190.
- (2) The definitions of terms and general provisions contained in WAC 458-20-170 apply equally for this rule, as appropriate. In addition, the terms, "clearing land" and "moving earth" include well drilling, core drilling, and hole digging, whether or not casing materials are installed and any grading or clearing of land, including the razing of buildings or other structures.

Business and Occupation Tax

- (3) Amounts derived from constructing, repairing, decorating, or improving new or existing buildings or other structures, including installing or attaching tangible personal property therein or thereto, and clearing land or moving earth, of or for the United States, its instrumentalities, or county or city housing authorities of chapter 35.82 RCW are taxable under the government contracting classification of business and occupation tax. The measure of the tax is the gross contract price.
- (4) Government contractors who manufacture or produce any tangible personal property for their own commercial or industrial use as consumers in performing government contracting activities are subject to the manufacturing classification of business and occupation tax measured by the value of the property manufactured or produced. See also, WAC 458-20-134. The manufacturing tax applies even though the property manufactured or produced for commercial use may be subsequently incorporated into buildings or other structures under the government contract and may thereby enhance the gross contract price.

Retail Sales Tax

(5) The retail sales tax does not apply to the gross contract price, or any part thereof, for any business activities taxable under the government contracting classification. Prime and subcontractors who perform such activities are themselves included within the statutory definition of "consumer" under RCW 82.04.190 and are required to pay retail sales tax upon all purchases of materials, including prefabricated and precast items, equipment, and other tangible personal property which is installed, applied, attached, or otherwise incorporated in their government contracting work. This applies for all such purchases of tangible personal property for installation, etc., even though the full purchase price of such property will be reimbursed by the government or housing authority in the gross contract price. It also applies notwithstanding that the contract may contain an immediate title vesting clause which provides that the title to the property vests in the government or housing authority immediately upon its acquisition by the contractor.

KCHA – PEPPER TREE ENVELOPE CAPITAL CONSTRUCTION DEPARTMENT

(6) Also, the retail sales tax must be paid by government contractors upon their purchases and leases or rentals of tools, consumables, and other tangible personal property used by them as consumers in performing government contracting.

Use Tax

- (7) The use tax applies upon the value of all materials, equipment, and other tangible personal property purchased at retail, acquired as a bailee or donee, or manufactured or produced by the contractor for commercial or industrial use in performing government contracting and upon which no retail sales tax has been paid by the contractor, its bailor or donor.
- (8) Thus the use tax applies to all property provided by the federal government to the contractor for installation or inclusion in the contract work as well as to all government provided tooling.
- (9) The use tax is to be reported and paid by the government contractor who actually installs or applies the property to the contract. Where the actual installing contractor pays the tax, no further use tax is due upon such property by any other contractor.
- (10) Note to contractors: The United States Supreme Court has sustained the government contracting tax applications for this state, even though the ultimate economic burden of the tax is borne by the United States Government (Washington v. US, 75 L.Ed 2d 264, 1983).
- (11) This rule does not apply to public road construction. See WAC 458-20-171. [Statutory Authority: RCW 82.32.300. 86-10-016 (Order ET 86-9), § 458-20-17001, filed 5/1/86.]



SECTION 3 - CLAUSE

- A. The work to be performed under this contract is subject to the requirements of Section 3 of the Housing and Urban Development Act of 1968, as amended, 12 U.S.C. 1701u (Section 3) as implemented by HUD under 24 CFR Part 75 (collectively, the "Section 3 Regulations"). The purpose of Section 3 is to ensure that employment and other economic opportunities generated by HUD assistance or HUD- assisted projects covered by Section 3, shall, to the greatest extent feasible, be directed to low- and very low-income persons, including persons who are recipients of HUD assistance for housing, with preference for both targeted workers living in the service area or neighborhood of the Development and YouthBuild participants.
- B. The parties to this contract agree to comply with Section 3 Regulations. As evidenced by their execution of this contract, the parties to this contract certify that they are under no contractual obligation or other impediment that would prevent them from complying with Section 3 Regulations.
- C. The Contractor agrees to send to each labor organization or representative of workers with which the Contractor has a collective bargaining agreement or other understanding, if any, a notice advising the labor organization or workers' representative of the Contractor's commitments under this Section 3 clause, and will post copies of the notice in conspicuous places at the work site where both employees and applicants for training and employment positions can see the notice. The notice shall describe the Section 3 preference, shall set forth minimum number and job titles subject to hire, availability of apprenticeship and training positions, the qualifications for each; and the name and location of the person(s) taking applications for each of the positions; and the anticipated date the work shall begin.
- D. The Contractor agrees to include this Section 3 clause in every subcontract subject to compliance with Section 3 Regulations, and agrees to take appropriate action, as provided in an applicable provision of the subcontract or in this Section 3 clause, upon a finding that the subcontractor is in violation of Section 3 Regulations. The Contractor will not subcontract with any subcontractor where the Contractor has notice or knowledge that the subcontractor has been found in violation of Section 3 Regulations.
- E. The Contractor will certify that any vacant employment positions, including training positions, that are filled; (1) after the Contractor is selected but before the contract is executed, and (2) with persons other than those to whom Section 3 Regulations require employment opportunities to be directed, were not filled to circumvent the Contractor's obligations under Section 3 Regulations.
- F. Noncompliance with HUD's Section 3 Regulations may result in sanctions, termination of this contract for default, and debarment or suspension from future HUD assisted contracts.
- G. Section 3 Employment and Training. Without limiting Contractor's obligation to comply with Section 3 Regulations, the Contractor specifically agrees to use best efforts to provide employment and training opportunities to Section 3 workers in the following order of priority:
 - 1. To residents of the KCHA development where the work is being performed;
 - 2. To residents of other KCHA developments or for residents of Section 8-assisted housing managed by KCHA;
 - 3. To participants in YouthBuild programs; and



- 4. To low- and very low-income persons residing within the Puget Sound Region.
- H. Section 3 Contracting. Without limiting Contractor's obligation to comply with Section 3 Regulations, Contractor specifically agrees to use best efforts to award contracts and subcontracts to business concerns that provide economic opportunities to Section 3 workers in the following order of priority:
 - 1. To Section 3 business concerns that provide economic opportunities for KCHA residents of the development where the work is being performed;
 - 2. To Section 3 business concerns that provide economic opportunities for KCHA residents of other KCHA developments or Section–8 assisted housing managed by KCHA;
 - 3. To YouthBuild programs; and
 - 4. To Section 3 business concerns that provide economic opportunities to Section 3 workers residing within the Puget Sound Region.



SECTION 3 – SUPPLEMENTAL INSTRUCTIONS TO BIDDERS

LOCAL RESIDENT HIRING AND CONTRACTING (SECTION 3) REQUIREMENTS:

The Owner's or King County Housing Authority's (KCHA) goal for this project is to participate in Section 3 activities by including efforts that will provide employment opportunities to Section 3 workers and contracting opportunities to Section 3 businesses. (Section 3 workers and Section 3 Businesses are defined below and in 24 CFR 75.)

The Contractor and its Subcontractors at all tiers for this specific contract will partner with the Owner to contribute to the Owner's overall "Section 3" goals, as described below.

Because local hiring and contracting requirements are defined under Section 3 of the Housing and Community Development Act of 1968, these requirements are commonly referred to as Section 3. The definitions and goals are defined in Sections A and B below. Section C describes the process. Section D discusses consequences of non-compliance with Section 3 goals and Section E describes some local hiring resources. For more information on the Owner's employment and training efforts, or compliance with Section 3, please contact KCHA by email at Section3@kcha.org.

A. Section 3 Definitions

For the purposes of this solicitation:

- 1. "Section 3 worker" means any worker who currently fits or when hired within the past five years fit at least one of the following categories, as documented:
 - a. The worker's income for the previous or annualized calendar year is below the income limit established by HUD. (See Pg. 4 of this section for HUD income limits)
 - b. The worker is employed by a Section 3 business concern.
 - c. The worker is a YouthBuild participant.
- 2. "Targeted Section 3 worker" means a Section 3 worker who is:
 - a. A worker employed by a Section 3 business concern; or
 - b. A worker who currently fits or when hired fit at least one of the following categories, as documented within the past five years:
 - i. A resident of public housing or Section 8–assisted housing;
 - ii. A resident of other public housing projects or Section 8-assisted housing managed by the PHA that is providing the assistance; or
 - iii. A YouthBuild participant.
- 3. "Business concern" means a business entity formed in accordance with State law, and which is licensed under State, county, or municipal law to engage in the type of business activity for which it was formed.
- 4. "Section 3 business concern" means a business concern meeting at least one of the following criteria, documented within the last six-month period:
 - a. It is at least 51 percent owned and controlled by low- or very low-income persons;
 - b. Over 75 percent of the labor hours performed for the business over the prior three-month period are performed by Section 3 workers; or
 - c. It is a business at least 51 percent owned and controlled by current public housing residents or residents who currently live in Section 8–assisted housing.
- 5. The greatest extent feasible means:
 - a. Completing and submitting a Section 3 Work Plan to designated Owner staff prior to contract signing (template to be provided by the Owner).
 - b. If contracting with Section 3 business concerns:
 - i. Placing qualified business enterprises on solicitation lists.



- ii. Dividing total requirements, when economically feasible, into smaller tasks or quantities to permit maximum participation of qualified Section 3 businesses.
- iii. Using the services and assistance of the U.S. Small Business Administration, the Minority Business Development Agency of the U.S. Department of Commerce and State and local governmental small business agencies to identify potential Section 3 businesses.
- iv. Ensuring that small and minority businesses and women's business enterprises are solicited whenever they are potential sources.
- c. If hiring Section 3 workers:
 - i. Post job opportunities for a mutually agreed upon length of time through the Owner's employment agency service partners and at project site as appropriate.
 - ii. Conduct interviews with qualified Section 3 workers.
 - iii. Notify designated Owner (KCHA) staff of all new hires.
- d. For both: Complete Section 3 compliance and tracking paperwork as necessary.

B. Section 3 Goals

The Owner will require, to the greatest extent feasible, for the Contractor to demonstrate participation in the local hiring and contracting requirements as defined under Section 3 of the Housing and Community Development Act of 1968.

- 1. Bidders shall demonstrate compliance with the Section 3 goals by making a best faith effort to achieve the following benchmarks:
 - a. Twenty-five (25) percent or more of the total number of labor hours worked by all workers are Section 3 workers; and
 - b. Five (5) percent or more of the total number of labor hours worked by all workers are Targeted Section 3 workers.
- 2. The successful bidder and covered subcontractors shall direct their efforts to provide Section 3 employment opportunities to Section 3 workers in the following order of priority:
 - a. First Priority: Current residents of KCHA development(s) benefitting from project.
 - b. Second Priority: Other Owner public housing and Section 8 voucher- assisted residents.
 - c. Third Priority: Participants in HUD Youthbuild programs.
 - d. Fourth Priority: Other low or very low income individuals in the Housing Authorities metropolitan area (Puget Sound region) who are at or below the Area's Low Income calculation.
- 3. The Contractor and covered subcontractors shall direct their efforts to award contracts to Section 3 business concerns in the following order of priority:
 - a. First Priority: To Section 3 business concern that provides economic opportunities for KCHA residents at the site(s) where the work will take place.
 - b. Second Priority: To Section 3 business concerns that provide economic opportunities for residents of other KCHA developments or Section–8 assisted housing managed by KCHA.
 - c. Third Priority: A subcontractor that is a HUD Youthbuild company.
 - d. Fourth Priority: To Section 3 business concerns that provide economic opportunities to Section 3 workers residing within the metropolitan area (Puget Sound).

4. Sealed Bidding

In order for KCHA to meet or exceed its adopted goal that 3% of all non-construction contracts and 10% of construction contracts paid in whole or in part with HUD funds be awarded to Section 3 businesses, KCHA may elect, on a contract-by-contract basis, to award a competitively bid contract to a responsible bidder other than the lowest responsive bidder by using the following procedure:

Bids shall be solicited from both Section 3 and non-Section 3 business concerns. KCHA may award the contract to the qualified Section 3 business concern with the highest priority ranking



and with the lowest responsive bid if:

- a. the specific project or KCHA as an agency is otherwise not expected to meet Section 3 utilization goals; and,
- b. the bid is within the maximum total contract price established in KCHA's budget for the specific project for which bids are being taken; and,
- c. the sources of funds for the project are such that there are no conflicts between this procedure and applicable state law; and,
- d. the bid is not more than five percent (5%) higher than the total bid price for the lowest responsive bid from any responsible, bidder.

If no responsive bid by a Section 3 business concern meets the requirements above, the contract shall be awarded to a responsible bidder with the lowest responsive bid.

C. The Process

- 1. Contract is awarded to lowest responsible Bidder.
- 2. Section 3 orientation with Owner. Once the Notice of Intent to Award has been issued to the successful Bidder, Owner's staff will contact that Bidder and arrange for a meeting to discuss local hiring and contracting goals and strategies in greater detail. At this meeting, the Contractor will be provided a packet that will include a Section 3 overview, Section 3 certification form, and all Section 3 compliance and tracking forms that will be used throughout the contract.
- 3. Contractor reports on Section 3 activities monthly.

D. Penalties for Non-compliance

Owner's commitment to this program is reflected in part by the cost of administering the program. Failure to make a good faith effort to the greatest extent feasible negates such funding and impairs the Owner's efforts to promote workforce diversity and to provide fair and equal opportunities to the public as a whole as a result of the expenditure of public funds. Therefore, if awarded this contract, the parties will mutually agree that failure to meet the requirements, including but not limited to the submission of required documentation, constitutes a material breach of contract. In the event of such breach, Owner may take any or all of the actions as contained in the Contract Documents.

E. Local Hiring Resources

Contact KCHA by email at Section3@kcha.org to obtain a list of local hiring resources.

SECTION 3 – 2023 INCOME GUIDELINES

	Income Limit 1 person			
Location	Extremely Low Income		Very Low Income	Low Income
Kitsap County (Bremerton, Silverdale)	\$22,900		\$38,150	\$61,000
King/ Snohomish Counties (Seattle, Bellevue, Everett)	\$28,800		\$47,950	\$70,650
Pierce County (Tacoma)	\$22,600		\$37,650	\$60,200
Skagit County (Sedro-Woolley)	\$19,150		\$31,900	\$51,050
Thurston County (Olympia, Tumwater)	\$21,550		\$35,900	\$57,400



PROGRESS PAYMENT SUSPENSION CRITERIA

CRITERIA will include:

- 1. Non-submittal of Certified Payroll documents (see Informational Form A.12)
- 2. Non-submittal of Section 3 Labor Hours Benchmark Status Report (see Section C for sample)
- 3. No lien release with Application for Payment
- 4. Insurance expires
- 5. Federal and/or State liens on general contractor
- 6. Suspension/expiration of WA State contractor's license
- 7. Work not accomplished
- 8. Work not approved/accepted
- 9. Repeated safety violations not resolved if warnings from KCHA are ignored
- 10. Incorrect Application for Payment or invoice (whichever is applicable)
- 11. Non-submittal of the GC Certification Upon Application for Payment (see Section E, Division 1 for sample of KCHA Pay Application which includes the continuation sheet, the payment application and the GC Certification)



EXECUTIVE ORDER 11246 (as AMENDED)

---DISCLAIMER--- http://www.dol.gov/general/disclaim#statutory

Executive Order 11246 - Equal Employment Opportunity

SOURCE: The provisions of Executive Order 11246 of Sept. 24, 1965, appear at 30 FR 12319, 12935, 3 CFR, 1964-1965 Comp., p.339, unless otherwise noted.

Under and by virtue of the authority vested in me as President of the United States by the Constitution and statutes of the United States, it is ordered as follows:

Part I - Nondiscrimination in Government Employment

[Part I superseded by EO 11478 of Aug. 8, 1969, 34 FR 12985, 3 CFR, 1966-1970 Comp., p. 803]

Part II - Nondiscrimination in Employment by Government Contractors and Subcontractors Subpart A - Duties of the Secretary of Labor

SEC. 201.The Secretary of Labor shall be responsible for the administration and enforcement of Parts II and III of this Order. The Secretary shall adopt such rules and regulations and issue such orders as are deemed necessary and appropriate to achieve the purposes of Parts II and III of this Order.

[Sec. 201 amended by EO 12086 of Oct. 5, 1978, 43 FR 46501, 3 CFR, 1978 Comp., p. 230]

Subpart B - Contractors' Agreements

SEC. 202. Except in contracts exempted in accordance with Section 204 of this Order, all Government contracting agencies shall include in every Government contract hereafter entered into the following provisions:

During the performance of this contract, the contractor agrees as follows:

- (1) The contractor will not discriminate against any employee or applicant for employment because of race, color, religion, sex, or national origin. The contractor will take affirmative action to ensure that applicants are employed, and that employees are treated during employment, without regard to their race, color, religion, sex or national origin. Such action shall include, but not be limited to the following: employment, upgrading, demotion, or transfer; recruitment or recruitment advertising; layoff or termination; rates of pay or other forms of compensation; and selection for training, including apprenticeship. The contractor agrees to post in conspicuous places, available to employees and applicants for employment, notices to be provided by the contracting officer setting forth the provisions of this nondiscrimination clause.
- (2) The contractor will, in all solicitations or advancements for employees placed by or on behalf of the contractor, state that all qualified applicants will receive consideration for employment without regard to race, color, religion, sex or national origin.
- (3) The contractor will send to each labor union or representative of workers with which he has a collective bargaining agreement or other contract or understanding, a notice, to be provided by the agency contracting officer, advising the labor union or workers' representative of the contractor's commitments under Section 202 of Executive Order No. 11246 of September 24, 1965, and shall post copies of the notice in conspicuous places available to employees and applicants for employment.
- (4) The contractor will comply with all provisions of Executive Order No. 11246 of Sept. 24, 1965, and of the rules, regulations, and relevant orders of the Secretary of Labor.

KCHA – PEPPER TREE ENVELOPE CAPITAL CONSTRUCTION DEPARTMENT

- (5) The contractor will furnish all information and reports required by Executive Order No. 11246 of September 24, 1965, and by the rules, regulations, and orders of the Secretary of Labor, or pursuant thereto, and will permit access to his books, records, and accounts by the contracting agency and the Secretary of Labor for purposes of investigation to ascertain compliance with such rules, regulations, and orders.
- (6) In the event of the contractor's noncompliance with the nondiscrimination clauses of this contract or with any of such rules, regulations, or orders, this contract may be cancelled, terminated, or suspended in whole or in part and the contractor may be declared ineligible for further Government contracts in accordance with procedures authorized in Executive Order No. 11246 of Sept. 24, 1965, and such other sanctions may be imposed and remedies invoked as provided in Executive Order No. 11246 of September 24, 1965, or by rule, regulation, or order of the Secretary of Labor, or as otherwise provided by law.
- (7) The contractor will include the provisions of paragraphs (1) through (7) in every subcontract or purchase order unless exempted by rules, regulations, or orders of the Secretary of Labor issued pursuant to Section 204 of Executive Order No. 11246 of September 24, 1965, so that such provisions will be binding upon each subcontractor or vendor. The contractor will take such action with respect to any subcontract or purchase order as may be directed by the Secretary of Labor as a means of enforcing such provisions including sanctions for noncompliance: Provided, however, that in the event the contractor becomes involved in, or is threatened with, litigation with a subcontractor or vendor as a result of such direction, the contractor may request the United States to enter into such litigation to protect the interests of the United States."

[Sec. 202 amended by EO 11375 of Oct. 13, 1967, 32 FR 14303, 3 CFR, 1966-1970 Comp., p. 684, EO 12086 of Oct. 5, 1978, 43 FR 46501, 3 CFR, 1978 Comp., p. 230]

- **SEC. 203.** Each contractor having a contract containing the provisions prescribed in Section 202 shall file, and shall cause each of his subcontractors to file, Compliance Reports with the contracting agency or the Secretary of Labor as may be directed. Compliance Reports shall be filed within such times and shall contain such information as to the practices, policies, programs, and employment policies, programs, and employment statistics of the contractor and each subcontractor, and shall be in such form, as the Secretary of Labor may prescribe.
- (b) Bidders or prospective contractors or subcontractors may be required to state whether they have participated in any previous contract subject to the provisions of this Order, or any preceding similar Executive order, and in that event to submit, on behalf of themselves and their proposed subcontractors, Compliance Reports prior to or as an initial part of their bid or negotiation of a contract.
- (c) Whenever the contractor or subcontractor has a collective bargaining agreement or other contract or understanding with a labor union or an agency referring workers or providing or supervising apprenticeship or training for such workers, the Compliance Report shall include such information as to such labor union's or agency's practices and policies affecting compliance as the Secretary of Labor may prescribe: Provided, That to the extent such information is within the exclusive possession of a labor union or an agency referring workers or providing or supervising apprenticeship or training and such labor union or agency shall refuse to furnish such information to the contractor, the contractor shall so certify to the Secretary of Labor as part of its Compliance Report and shall set forth what efforts he has made to obtain such information.
- (d) The Secretary of Labor may direct that any bidder or prospective contractor or subcontractor shall submit, as part of his Compliance Report, a statement in writing, signed by an authorized officer or agent on behalf of any labor union or any agency referring workers or providing or supervising apprenticeship or other training, with which the bidder or prospective contractor deals, with supporting information, to the effect that the signer's practices and policies do not discriminate on the grounds of race, color, religion, sex or national origin, and that the signer either will affirmatively cooperate in the implementation of the policy and provisions of this Order or that it consents and agrees that recruitment, employment, and the terms and conditions of employment under the proposed contract shall be in accordance with the purposes and

KCHA – PEPPER TREE ENVELOPE CAPITAL CONSTRUCTION DEPARTMENT

provisions of the order. In the event that the union, or the agency shall refuse to execute such a statement, the Compliance Report shall so certify and set forth what efforts have been made to secure such a statement and such additional factual material as the Secretary of Labor may require.

[Sec. 203 amended by EO 11375 of Oct. 13, 1967, 32 FR 14303, 3 CFR, 1966-1970 Comp., p. 684; EO 12086 of Oct. 5, 1978, 43 FR 46501, 3 CFR, 1978 Comp., p. 230]

- **SEC. 204** (a) The Secretary of Labor may, when the Secretary deems that special circumstances in the national interest so require, exempt a contracting agency from the requirement of including any or all of the provisions of Section 202 of this **Order** in any specific contract, subcontract, or purchase **order**.
- (b) The Secretary of Labor may, by rule or regulation, exempt certain classes of contracts, subcontracts, or purchase orders (1) whenever work is to be or has been performed outside the United States and no recruitment of workers within the limits of the United States is involved; (2) for standard commercial supplies or raw materials; (3) involving less than specified amounts of money or specified numbers of workers; or (4) to the extent that they involve subcontracts below a specified tier.
- (c) Section 202 of this **Order** shall not apply to a Government contractor or subcontractor that is a religious corporation, association, educational institution, or society, with respect to the employment of individuals of a particular religion to perform work connected with the carrying on by such corporation, association, educational institution, or society of its activities. Such contractors and subcontractors are not exempted or excused from complying with the other requirements contained in this **Order**.
- (d) The Secretary of Labor may also provide, by rule, regulation, or **order**, for the exemption of facilities of a contractor that are in all respects separate and distinct from activities of the contractor related to the performance of the contract: provided, that such an exemption will not interfere with or impede the effectuation of the purposes of this **Order**: and provided further, that in the absence of such an exemption all facilities shall be covered by the provisions of this **Order**."

[Sec. 204 amended by EO 13279 of Dec. 16, 2002, 67 FR 77141, 3 CFR, 2002 Comp., p. 77141 - 77144]

Subpart C - Powers and Duties of the Secretary of Labor and the Contracting Agencies

SEC. 205. The Secretary of Labor shall be responsible for securing compliance by all Government contractors and subcontractors with this Order and any implementing rules or regulations. All contracting agencies shall comply with the terms of this Order and any implementing rules, regulations, or orders of the Secretary of Labor. Contracting agencies shall cooperate with the Secretary of Labor and shall furnish such information and assistance as the Secretary may require.

[Sec. 205 amended by EO 12086 of Oct. 5, 1978, 43 FR 46501, 3 CFR, 1978 Comp., p. 230]

- **SEC. 206.** The Secretary of Labor may investigate the employment practices of any Government contractor or subcontractor to determine whether or not the contractual provisions specified in Section 202 of this Order have been violated. Such investigation shall be conducted in accordance with the procedures established by the Secretary of Labor.
- (b) The Secretary of Labor may receive and investigate complaints by employees or prospective employees of a Government contractor or subcontractor which allege discrimination contrary to the contractual provisions specified in Section 202 of this Order.

[Sec. 206 amended by EO 12086 of Oct. 5, 1978, 43 FR 46501, 3 CFR, 1978 Comp., p. 230]

SEC. 207. The Secretary of Labor shall use his/her best efforts, directly and through interested Federal, State, and local agencies, contractors, and all other available instrumentalities to cause any labor union

KCHA – PEPPER TREE ENVELOPE CAPITAL CONSTRUCTION DEPARTMENT

engaged in work under Government contracts or any agency referring workers or providing or supervising apprenticeship or training for or in the course of such work to cooperate in the implementation of the purposes of this Order. The Secretary of Labor shall, in appropriate cases, notify the Equal Employment Opportunity Commission, the Department of Justice, or other appropriate Federal agencies whenever it has reason to believe that the practices of any such labor organization or agency violate Title VI or Title VII of the Civil Rights Act of 1964 or other provision of Federal law.

[Sec. 207 amended by EO 12086 of Oct. 5, 1978, 43 FR 46501, 3 CFR, 1978 Comp., p. 230]

SEC. 208. The Secretary of Labor, or any agency, officer, or employee in the executive branch of the Government designated by rule, regulation, or order of the Secretary, may hold such hearings, public or private, as the Secretary may deem advisable for compliance, enforcement, or educational purposes.

(b) The Secretary of Labor may hold, or cause to be held, hearings in accordance with Subsection of this Section prior to imposing, ordering, or recommending the imposition of penalties and sanctions under this Order. No order for debarment of any contractor from further Government contracts under Section 209(6) shall be made without affording the contractor an opportunity for a hearing.

Subpart D - Sanctions and Penalties

SEC. 209. In accordance with such rules, regulations, or orders as the Secretary of Labor may issue or adopt, the Secretary may:

- (1) Publish, or cause to be published, the names of contractors or unions which it has concluded have complied or have failed to comply with the provisions of this Order or of the rules, regulations, and orders of the Secretary of Labor.
- (2) Recommend to the Department of Justice that, in cases in which there is substantial or material violation or the threat of substantial or material violation of the contractual provisions set forth in Section 202 of this Order, appropriate proceedings be brought to enforce those provisions, including the enjoining, within the limitations of applicable law, of organizations, individuals, or groups who prevent directly or indirectly, or seek to prevent directly or indirectly, compliance with the provisions of this Order.
- (3) Recommend to the Equal Employment Opportunity Commission or the Department of Justice that appropriate proceedings be instituted under Title VII of the Civil Rights Act of 1964.
- (4) Recommend to the Department of Justice that criminal proceedings be brought for the furnishing of false information to any contracting agency or to the Secretary of Labor as the case may be.
- (5) After consulting with the contracting agency, direct the contracting agency to cancel, terminate, suspend, or cause to be cancelled, terminated, or suspended, any contract, or any portion or portions thereof, for failure of the contractor or subcontractor to comply with equal employment opportunity provisions of the contract. Contracts may be cancelled, terminated, or suspended absolutely or continuance of contracts may be conditioned upon a program for future compliance approved by the Secretary of Labor.
- (6) Provide that any contracting agency shall refrain from entering into further contracts, or extensions or other modifications of existing contracts, with any noncomplying contractor, until such contractor has satisfied the Secretary of Labor that such contractor has established and will carry out personnel and employment policies in compliance with the provisions of this Order.
- (b) Pursuant to rules and regulations prescribed by the Secretary of Labor, the Secretary shall make reasonable efforts, within a reasonable time limitation, to secure compliance with the contract provisions of this Order by methods of conference, conciliation, mediation, and persuasion before proceedings shall be instituted under subsection (a)(2) of this Section, or before a contract shall be cancelled or terminated in whole or in part under subsection (a)(5) of this Section.



[Sec. 209 amended by EO 12086 of Oct. 5, 1978, 43 FR 46501, 3 CFR, 1978 Comp., p. 230]

SEC. 210. Whenever the Secretary of Labor makes a determination under Section 209, the Secretary shall promptly notify the appropriate agency. The agency shall take the action directed by the Secretary and shall report the results of the action it has taken to the Secretary of Labor within such time as the Secretary shall specify. If the contracting agency fails to take the action directed within thirty days, the Secretary may take the action directly.

[Sec. 210 amended by EO 12086 of Oct. 5, 1978, 43 FR 46501, 3 CFR, 1978 Comp., p 230]

SEC. 211. If the Secretary shall so direct, contracting agencies shall not enter into contracts with any bidder or prospective contractor unless the bidder or prospective contractor has satisfactorily complied with the provisions of this Order or submits a program for compliance acceptable to the Secretary of Labor. [Sec. 211 amended by EO 12086 of Oct. 5, 1978, 43 FR 46501, 3 CFR, 1978 Comp., p. 230]

SEC. 212. When a contract has been cancelled or terminated under Section 209(a)(5) or a contractor has been debarred from further Government contracts under Section 209(a)(6) of this Order, because of noncompliance with the contract provisions specified in Section 202 of this Order, the Secretary of Labor shall promptly notify the Comptroller General of the United States.

[Sec. 212 amended by EO 12086 of Oct. 5, 1978, 43 FR 46501, 3 CFR, 1978 Comp., p. 230]

Subpart E - Certificates of Merit

SEC. 213. The Secretary of Labor may provide for issuance of a United States Government Certificate of Merit to employers or labor unions, or other agencies which are or may hereafter be engaged in work under Government contracts, if the Secretary is satisfied that the personnel and employment practices of the employer, or that the personnel, training, apprenticeship, membership, grievance and representation, upgrading, and other practices and policies of the labor union or other agency conform to the purposes and provisions of this Order.

SEC. 214. Any Certificate of Merit may at any time be suspended or revoked by the Secretary of Labor if the holder thereof, in the judgment of the Secretary, has failed to comply with the provisions of this Order.

SEC. 215. The Secretary of Labor may provide for the exemption of any employer, labor union, or other agency from any reporting requirements imposed under or pursuant to this Order if such employer, labor union, or other agency has been awarded a Certificate of Merit which has not been suspended or revoked.

Part III - Nondiscrimination Provisions in Federally Assisted Construction Contracts

SEC. 301. Each executive department and agency, which administers a program involving Federal financial assistance shall require as a condition for the approval of any grant, contract, loan, insurance, or guarantee thereunder, which may involve a construction contract, that the applicant for Federal assistance undertake and agree to incorporate, or cause to be incorporated, into all construction contracts paid for in whole or in part with funds obtained from the Federal Government or borrowed on the credit of the Federal Government pursuant to such grant, contract, loan, insurance, or guarantee, or undertaken pursuant to any Federal program involving such grant, contract, loan, insurance, or guarantee, the provisions prescribed for Government contracts by Section 202 of this Order or such modification thereof, preserving in substance the contractor's obligations thereunder, as may be approved by the Secretary of Labor, together with such additional provisions as the Secretary deems appropriate to establish and protect the interest of the United States in the enforcement of those obligations. Each such applicant shall also undertake and agree (1) to assist and cooperate actively with the Secretary of Labor in obtaining the compliance of contractors and subcontractors with those contract provisions and with the rules, regulations and relevant orders of the Secretary, (2) to obtain and to furnish to the Secretary of Labor such information as the Secretary may require

KCHA – PEPPER TREE ENVELOPE CAPITAL CONSTRUCTION DEPARTMENT

for the supervision of such compliance, (3) to carry out sanctions and penalties for violation of such obligations imposed upon contractors and subcontractors by the Secretary of Labor pursuant to Part II, Subpart D, of this Order, and (4) to refrain from entering into any contract subject to this Order, or extension or other modification of such a contract with a contractor debarred from Government contracts under Part II, Subpart D, of this Order.

[Sec. 301 amended by EO 12086 of Oct. 5, 1978, 43 FR 46501, 3 CFR, 1978 Comp., p. 230]

- **SEC. 302.** "Construction contract" as used in this Order means any contract for the construction, rehabilitation, alteration, conversion, extension, or repair of buildings, highways, or other improvements to real property.
- (b) The provisions of Part II of this Order shall apply to such construction contracts, and for purposes of such application the administering department or agency shall be considered the contracting agency referred to therein.
- (c) The term "applicant" as used in this Order means an applicant for Federal assistance or, as determined by agency regulation, other program participant, with respect to whom an application for any grant, contract, loan, insurance, or guarantee is not finally acted upon prior to the effective date of this Part, and it includes such an applicant after he/she becomes a recipient of such Federal assistance.
- **SEC. 303.** The Secretary of Labor shall be responsible for obtaining the compliance of such applicants with their undertakings under this Order. Each administering department and agency is directed to cooperate with the Secretary of Labor and to furnish the Secretary such information and assistance as the Secretary may require in the performance of the Secretary's functions under this Order.
- (b) In the event an applicant fails and refuses to comply with the applicant's undertakings pursuant to this Order, the Secretary of Labor may, after consulting with the administering department or agency, take any or all of the following actions: (1) direct any administering department or agency to cancel, terminate, or suspend in whole or in part the agreement, contract or other arrangement with such applicant with respect to which the failure or refusal occurred; (2) direct any administering department or agency to refrain from extending any further assistance to the applicant under the program with respect to which the failure or refusal occurred until satisfactory assurance of future compliance has been received by the Secretary of Labor from such applicant; and (3) refer the case to the Department of Justice or the Equal Employment Opportunity Commission for appropriate law enforcement or other proceedings.
- (c) In no case shall action be taken with respect to an applicant pursuant to clause (1) or (2) of subsection (b) without notice and opportunity for hearing.

[Sec. 303 amended by EO 12086 of Oct. 5, 1978, 43 FR 46501, 3 CFR, 1978 Comp., p. 230]

SEC. 304. Any executive department or agency which imposes by rule, regulation, or order requirements of nondiscrimination in employment, other than requirements imposed pursuant to this Order, may delegate to the Secretary of Labor by agreement such responsibilities with respect to compliance standards, reports, and procedures as would tend to bring the administration of such requirements into conformity with the administration of requirements imposed under this Order: Provided, That actions to effect compliance by recipients of Federal financial assistance with requirements imposed pursuant to Title VI of the Civil Rights Act of 1964 shall be taken in conformity with the procedures and limitations prescribed in Section 602 thereof and the regulations of the administering department or agency issued thereunder.

Part IV - Miscellaneous

SEC. 401. The Secretary of Labor may delegate to any officer, agency, or employee in the Executive branch of the Government, any function or duty of the Secretary under Parts II and III of this Order.



[Sec. 401 amended by EO 12086 of Oct. 5, 1978, 43 FR 46501, 3 CFR, 1978 Comp., p. 230]

SEC. 402. The Secretary of Labor shall provide administrative support for the execution of the program known as the "Plans for Progress."

SEC. 403. Executive Orders Nos. 10590 (January 19, 1955), 10722 (August 5, 1957), 10925 (March 6, 1961), 11114 (June 22, 1963), and 11162 (July 28, 1964), are hereby superseded and the President's Committee on Equal Employment Opportunity established by Executive Order No. 10925 is hereby abolished. All records and property in the custody of the Committee shall be transferred to the Office of Personnel Management and the Secretary of Labor, as appropriate.

(b) Nothing in this Order shall be deemed to relieve any person of any obligation assumed or imposed under or pursuant to any Executive Order superseded by this Order. All rules, regulations, orders, instructions, designations, and other directives issued by the President's Committee on Equal Employment Opportunity and those issued by the heads of various departments or agencies under or pursuant to any of the Executive orders superseded by this Order, shall, to the extent that they are not inconsistent with this Order, remain in full force and effect unless and until revoked or superseded by appropriate authority. References in such directives to provisions of the superseded orders shall be deemed to be references to the comparable provisions of this Order.

[Sec. 403 amended by EO 12107 of Dec. 28, 1978, 44 FR 1055, 3 CFR, 1978 Comp., p, 264]

SEC. 404. The General Services Administration shall take appropriate action to revise the standard Government contract forms to accord with the provisions of this Order and of the rules and regulations of the Secretary of Labor.

SEC. 405. This Order shall become effective thirty days after the date of this Order.



EXECUTIVE ORDER 13496

New Employee Notification Requirements for Federal Contractors and Subcontractors

Under Department of Labor regulations, www.gpo.gov/fdsys/pkg/FR-2010-05-20/pdf/2010-11639.pdf, contractors holding contracts with the Federal government and their subcontractors are required, beginning on June 21, 2010, to post notices informing employees of their rights under the National Labor Relations Act (NLRA). The notice to employees required by the regulations inform employees about their rights under the NLRA to form, join and assist a union and to bargain collectively with their employer; provides examples of unlawful employer and union conduct that interferes with those rights; and indicates how employees can contact the National Labor Relations Board, the Federal agency that enforces those rights, with questions or to file complaints. Contractors that violate the Labor Department's regulations requiring employee notification of these rights may be subject to sanctions, including suspension or cancellation of the contract.

The regulations require Federal contractors:

- to post the required employee notice conspicuously in and around their plants and offices so that it is prominent and readily seen by employees who are covered by the NLRA and who engage in contract-related activity;
- 2. to post the required notice electronically if they communicate with employees electronically, which requires posting a link to the Department of Labor's website containing the employee notice where they customarily place other electronic notices to employees about their jobs; and
- 3. to insert provisions in their subcontracts that require their subcontractors to comply with the same posting requirements as well.

Contractors and subcontractors may obtain the required poster in any of the three ways. The Labor Department will print posters and provide them to Federal contracting departments and agencies for supply to contractors and subcontractors. In addition, contractors and subcontractors can request posters from the field offices of the Labor Department's Office of Federal Contract Compliance Programs (http://www.dol.gov/ofccp/contacts/ofnation2.htm), or Office of Labor-Management Standards (OLMS) (http://www.dol.gov/olms/contacts/lmskeyp.htm). Finally, contractors and subcontractors can acquire the poster from OLMS' website by downloading it from http://www.dol.gov/olms or by calling (202) 693-0123. Compliance information for contractors and subcontractors can be found at OFCCP's website Construction Compliance Checks Frequently Asked Questions | U.S. Department of Labor (dol.gov)

EXECUTIVE ORDER 13496 - FREQUENTLY ASKED QUESTIONS

Executive Order 13496 Frequently Asked Questions | U.S. Department of Labor (dol.gov)



REQUIREMENTS FOR PUBLIC WORKS PROJECTS

REQUIREMENTS FOR PUBLIC WORKS PROJECTS – All projects require that the contractor and all subcontractors performing labor on the project site must file the Statement of Intent with L&I regardless of the wage determination is set as HUD Non-Routine Maintenance, State Prevailing wages or Davis-Bacon.

Statement of Intent to Pay Prevailing Wages - filed at the start of the project

- A. **Filed Immediately** after the contract is awarded and before work begins, if that is possible. **NO PAYMENTS CAN BE MADE** until the contractor has submitted an Intent form that has been approved by the Industrial Statistician.
- B. SUBCONTRACTORS must file using the PRIME CONTRACTOR'S "Form ID Number" after the PRIME has received approval for their Statement of Intent.
- C. Wage payment requirements for this project are determined to be

HUD Non-Routine Maintenance

- a. The Intent is then filed with the question "Is this a Housing Act of 1937 Project?" answered as Yes.
- b. See the Informational Form A.13b for the sample of Intent to Pay Prevailing Wages with the highlighted statement shown on the form.

Certified Payroll - filed each week for the duration of the project

- A. Submitted on a weekly basis, beginning with the first week that the Contractor works on the Project, and for every week afterward until the Contractor completes the Work.
- B. Consisting of a certified payroll report and a statement of compliance.
- C. See Informational Form A.13c for more information.

 NOTE: These requirements will also apply to HUD Non-Routine Maintenance Wages.

Affidavit of Wages Paid - filed at the end of the project

A. Submitted at the end of the project once all of the work has been completed, showing the wages paid to employees who worked on the project.

SCREEN SHOTS OF INTENT

File Intent: Enter the Project Details



Project Details	
Contract Type	Bid-Build (Traditional)
Bid Due Date (required) (i)	mm/dd/yyyy
contract Award Date (required) (1)	mm/dd/yyyy
Awarding Agency	KING COUNTY HOUSING AUTHORITY
Awarding Agency Address	700 ANDOVER PARK SW TUKWILA, WA – 98188
Awarding Agency Contact Name (required)	
Awarding Agency Contact Phone Number (required)	Ext
Awarding Agency Contract Number (required) (
Project Name (<mark>required</mark>)	
s apprentice utilization required? (required)	○ Yes ○ No
s OMWBE utilization required? (required)	
s this a Housing Act of 1937 project? (required)	Yes No
Project Site Address or Directions i	
	0/1000



DAVIS BACON & RELATED ACTS PROVISIONS; CONTRACT WORK HOURS & SAFETY STANDARDS ACT: GENERAL INFORMATION

A. The Davis-Bacon Act (DBA)*

The DBA, enacted in 1931, applies to contracts in excess of \$2,000 for construction, alteration, and/or repair of public buildings or public works, including painting and decorating, to which the United States or the District of Columbia is a party. This type of applicability is referred to as direct Davis-Bacon Act or DBA coverage. An example of DBA coverage is when HUD contracts directly for repairs to HUD-owned properties. HUD's Office of the Chief Procurement Officer manages these types of contracts. The DBA requires that the advertised specifications for such contracts contain a provision stating that the minimum wages to be paid to various classes of laborers and mechanics must be based upon the wages found to be prevailing by the Secretary of Labor.

Most HUD construction work is not covered by the DBA since HUD does not usually contract directly for construction work. Rather, Davis-Bacon wage rates apply to HUD programs because of prevailing wage requirements expressed in HUD "Related Acts" such as the U. S. Housing Act of 1937 and the Housing and Community Development Act of 1974, as amended. The Related Acts (referred to throughout this Guide as the Davis-Bacon and Related Acts or DBRA) are discussed further in Section 5.9.

The DBA includes provisions that:

- 1. Require the contractor or subcontractor to pay all mechanics and laborers at least once per week;
- 2. Prohibit contractors or subcontractors from taking deductions or rebates from wages earned by laborers and mechanics;
- 3. Require the contractor or subcontractor to pay Davis-Bacon wages to all laborers and mechanics employed on the site of the work regardless of their skill level, and regardless of any contractual relationship alleged to exist between the laborers and mechanics and the contractor or subcontractor;
- 4. Require the contractor or subcontractor to post the scale of wages to be paid (i.e., the applicable Davis-Bacon wage decision) in a prominent and accessible place at the work site;
- 5. Define prevailing wages to include fringe benefits;
- 6. Permit the withholding of payments due to the contractor on account of wage restitution that may be found due to the laborers and mechanics;
- 7. Permit the payment of wage restitution from amounts withheld from contract payments;
- 8. Permit the termination of the contract where it is found that any laborer or mechanic is underpaid; and
- 9. Permit the debarment of persons or firms found to have disregarded their obligations to employees and subcontractors.

B. The Contract Work Hours and Safety Standards Act (CWHSSA)

The CWHSSA applies to both direct federal contracts and to federally-assisted contracts where those contracts require or involve the employment of laborers and mechanics and where federal wage standards (e.g., Davis-Bacon or HUD-determined prevailing wage rates) are applicable.

CWHSSA provisions apply to all laborers and mechanics, including watchmen and guards, employed by any contractor or subcontractor. CWHSSA also applies to maintenance laborers and mechanics employed by contractors or subcontractors engaged in the operation of Public Housing Agencies (PHA), Tribally Designated Housing Entities (TDHE), and Indian Housing Agencies

King County Housing Authority

KCHA – PEPPER TREE ENVELOPE CAPITAL CONSTRUCTION DEPARTMENT

(IHA) developments. CWHSSA O/T provisions do not apply to laborers and mechanics employed directly by PHAs or IHAs. However, O/T provisions generally apply to these workers under the Fair Labor Standards Act (FLSA). HUD does not have authority to enforce FLSA violations. Refer complaints of FLSA violations to DOL, Wage and Hour Division.

CWHSSA provides that all O/T hours (defined as hours worked in excess of 40 during any workweek on the CWHSSA-covered project site) must be compensated at a rate not less than one and one-half times the regular basic rate of pay. Where CWHSSA O/T provisions are applicable, compensatory time in lieu of premium pay for O/T hours is not permissible. In the event of O/T violations, the CWHSSA renders the contractor liable to the underpaid workers for wage restitution and to the United States Government for liquidated damages computed per person per day at a rate that DOL publishes annually. It is a federal criminal misdemeanor to intentionally violate CWHSSA standards.

Exemptions:

- 1. CWHSSA O/T provisions do not apply where the federal assistance is only in the nature of a loan guarantee or insurance.
- 2. CWHSSA O/T provisions do not apply to prime contracts of \$100,000 or less.

*The Davis Bacon provisions also apply to HUD-determined prevailing wage rates.

http://www.ecfr.gov/current/title-29

C. GENERAL INFORMATION

1. Employer Responsibilities

- a. All employers (contractors, subcontractors, and any lower-tier subcontractors) are required to pay all laborers and mechanics employed or working on the site of the work unconditionally and not less often than once per week the full amount of wages and bona fide fringe benefits computed at rates not less than those contained in the wage decision.
- b. Employers must prepare, certify, and submit weekly payroll reports reflecting all the laborers and mechanics (employees) engaged in construction on the site of the work.
- c. Employers may also be required to submit related documentation in order to demonstrate compliance.

2. Agency Responsibilities

- a. State, tribal, and local contracting agencies (LCAs) that administer HUD programs agree to administer and enforce Davis-Bacon requirements as a condition for receiving HUD program assistance. LCAs have the following responsibilities:
- b. Conduct on-site inspections including interviews with laborers and mechanics employed on the construction project. Ensure that the applicable Davis-Bacon wage decision, DOL's Davis-Bacon poster (Form WH-1321), and additional classifications are displayed at the job site.
- c. Review certified payroll reports (CPRs) and related documentation. Identify any discrepancies and/or violations. Ensure that any needed corrections are made promptly, including the payment of wage restitution as needed, and the assessment and collection of liquidated damages, as appropriate.
- d. Comply with all HUD requirements concerning statutory, program, and/or other requirements.



3. **Definitions**

a. Employee

Every person who performs the work of a laborer or mechanic is "employed" regardless of any contractual relationship that may be alleged to exist between a contractor or subcontractor and such person.

b. Working subcontractors

Persons who perform the work of laborers or mechanics and who represent themselves to be owners of businesses, sole proprietors, or self-employed are not exempt from prevailing wage requirements. These laborers and mechanics are "employed" and are entitled to the prevailing wage for the type of work they perform, and must be reported on the payroll report for their craft, hours of work, and wages paid.

c. Apprentice

A person employed and individually registered in a bona fide apprenticeship program. Bona fide programs are those that have been registered with DOL, Employment and Training Administration, Office of Apprenticeship, or with a DOL-recognized State Apprenticeship Agency (SAA). (Note that an SAA must also partner with a State Apprenticeship Council (SAC). The SAC must consist of an equal number of representatives of employer and employee organizations.)

d. Prevailing wages or wage rates

Davis-Bacon prevailing wage rates generally appear as a basic hourly rate plus fringe benefits, if any. "Prevailing wage" is made up of two interchangeable components: the basic hourly wage, and fringe benefits. The total of the basic hourly wage and fringe benefits comprises the "prevailing wage" obligation. This obligation may be met by any combination of cash wages and creditable "bona fide" fringe benefits provided by the employer.

e. Overtime

Overtime (O/T) hours are defined as all hours worked in excess of 40 hours in any workweek. Where governed by Federal labor standards, O/T hours shall be compensated at not less than one and one-half times the regular rate of basic pay plus the straight-time (S/T) rate of any required fringe benefits.

f. Site of work

The "site of work" is limited to the physical place or places where the construction called for in the contract will remain when work on it has been completed. "Site of work" includes other adjacent or nearby properties used by the contractor/subcontractor in the construction of the project (e.g., fabrication sites) provided they are dedicated exclusively or nearly so to the performance of the contract or project, and are so located in proximity to the actual construction location that it would be reasonable to include them.

g. Proper designation of trade

Each laborer and mechanic shall be classified in accordance with the work classifications listed on the wage decision and the actual type of work they perform and shall be paid the appropriate wage rate and fringe benefits for the classification regardless of their level of skill. In other words, if someone is performing carpentry work on the project, they must be paid no less than the wage rate on the wage decision for carpenters even if they aren't considered by the employer to be fully trained as a carpenter. The only people who can be paid less than the rate for their craft are apprentices and trainees registered in approved programs.



h. Split classification

Laborers and mechanics that perform work in more than one classification may be compensated at the rate specified for each classification provided that the employer maintains time records that accurately set forth the time spent in each classification in which the work was performed. If accurate time records are not maintained, the employee shall be compensated at the highest of all wage rates for the classifications in which work was performed.



B - **SECTION**

PEPPER TREE ENVELOPE

19926 Ballinger Way NE, Shoreline, WA 98155

DUE DATE: September 13, 2023

TIME: 1:00 pm

In order to be considered as **RESPONSIVE BIDS**, all bidders **MUST** submit the following <u>Signed</u> <u>Documents (each single sided)</u> no later than the **Bid Due Date and Time**.

Forms to Return if Bidding

- B.1 Bid Form
- **B.2** Bidder's Experience Record
- **B.3** Contractor Certification
- **B.4** Non-Collusive Affidavit
- **B.5** Equal Opportunity
- B.6 Bid Security (Submit only for bids greater than \$150,000)
- **B.7** Debarment / Suspension Compliance Certification
- **B.8** Proposed Subcontractor List
- B.9 Section 3
 - a. Business Certification
 - b. Subcontractor Work Plan
- **B.10** Harassment and Discrimination Policies
- **B.11** WMBE Survey (Form is not required to be responsive, but requested)
- **B.12** Preliminary Project Schedule Provided by Contractor



BID FORM – RETURN EACH FORM SINGLE SIDED

BID TO:

KING COUNTY HOUSING AUTHORITY CAPITAL CONSTRUCTION DEPARTMENT 700 Andover Park West, Suite C * Tukwila, WA 98188

PROJECT NAME AND LOCATION:

Pepper Tree Envelope 19926 Ballinger Way NE, Shoreline, WA 98155

SCOPE OF WORK:

Pepper Tree apartments is located in the City of Shoreline, built in 1985, and consists of a three (3) story multifamily building which house 30 individual residential units. The existing structure consist of 2x framing, batt insulation, gwb, weather resistant barrier and fiber cement siding. All of which will be removed down to the existing framing and reinsulated with new batt insulation between the stud bays, ½" fire-retardant wall sheathing, 1" Mineral fiber board insulation, 1x4 furring strips, Tyvek drain wrap and fiber cement siding and trim. The existing roof, barge boards, fascia and soffits will remain in place. The soffits and fascia board, and barge boards will be repainted.

Exterior work will include:

- Installation of structural floor-to-floor hold-downs to the upper roof section per structural drawings and details.
- Demo and framing of existing deck walls and reconstruction to incorporate new fiberglass railings.
- Demo of existing deck surface application. This removal will include grinding to remove any adhesion, patching, or floating to ensure proper application of new fluid applied deck coating.
- Removal of windows, patio doors and patio storage doors, mechanical and electrical room doors.
- Electrical Panel block out and trim at selective elevations, blocking installation at hose bibs, light fixture, GFI outlets, and building signs.
- The Contractor will add an electrical extension box as required to accommodate the new wall assembly and added blocking,
- Existing hose bibs will be removed, extended, and reinstalled to incorporate new wall assembly.
- All building lights and fire alarm apparatuses will be removed and reinstalled to incorporate the new building assembly.
- Sand, prep, and paint all existing metal handrails at the east and west entry buildings and along the walkway at the West elevation.

For complete scope, please see E.1 Scope of Work and Technical Specifications

BASE BID:

Bidders must provide a cost for **each and every** bid item (even if the amount is **\$0.00**), for the bid to be considered responsive. Where conflict occurs between the bid item values entered and the total amount written, the bid item price(s) shall prevail, and totals will be corrected to conform thereto. The work of the various items is described throughout the Contract Documents.

Bidding Contractor's Company Name:	Initials:
	 <u> </u>

KCHA – PEPPER TREE ENVELOPE King County CAPITAL CONSTRUCTION DEPARTMENT CAPITAL CONSTRUCTION DEPARTMENT

Total Base Bid Lump Sum Amount (Gross Contract Price) should include all applicable taxes. King County Housing Authority (KCHA) will only pay this Gross Contract Price. Contractors shall review the State of Washington Department of Revenue Ruling WAC 458-20-17001 (included in bid documents) and all other applicable documents for tax obligations.

Contractor must pay the attached Non-Routine Maintenance as the Minimum Wages and Fringe Benefits for the construction workers under this contract.

The Bidder agrees to accept as full payment for the Work, as specified in the Contract Documents, and based upon the undersigned's own estimate of quantities and costs, the following stipulated sums.

BASE BID PRICE				
Α.	Materials, including all applicable Taxes	\$		
В.	Labor	\$		
С.	O & P, including all applicable Fees	\$		
D.	Owner Allowance for added work contingency, as authorized by KCHA	\$76,000.00		
TOTAL	TOTAL BID AMOUNT: (all costs inclusive – A, B, C& D) Round to Nearest Dollar			
And No/100 Dollars				
PRINT (in words) Total Bid Amount. Sample – Three Hundred Thousand, Two Hundred Sixty-Six				

UNIT PRICES:

Unit prices are considered for use when small quantities are needed and additional competitive bidding is not required for price justification. An unforeseen condition requiring large quantities resulting in a substantial change in scope of new work will not be considered applicable for unit pricing. Large deviations in the scope of work will be addressed and evaluated through a bid process or on a Time Material basis as stipulated in the contract documents. Acceptance of any unit pricing is at the Owner's discretion.

COMPLETE BID:

Contractor shall include all costs of doing the work shown, described, and intended by the Contract Documents, within the lump sum bid prices in the Proposal.

LOW BIDDER DETERMINATION:

The determination of the Low Bidder will be determined on the basis of the Grand Total of the Total Base Bid Price plus Owner-Directed Work Total. The Owner reserves the right to accept any, all, or no Additive items at the time of Award, or at any time thereafter.

RIGHT TO AWARD THE CONTRACT:

KCHA reserves the right to award the Contract to the Contractor based on the Contractor's Qualifications, Bonding Capacity and ability to Complete the Project within the Completion Time allowed for project. If written notice of the acceptance of this bid is mailed, or delivered to the undersigned within Seven (7) days after the opening thereof, or at any time thereafter before this bid is withdrawn, the undersigned agrees to execute and deliver a Contract in the prescribed form within Seven (7) calendar days after the Contract is presented for signature.

Bidding Contractor's Company Name:	Initials:	

Bid Form Page 2 of 8 KCHA / 06-06-22

King County Housing Authority

KCHA – PEPPER TREE ENVELOPE CAPITAL CONSTRUCTION DEPARTMENT

RIGHT TO REJECT BIDS:

ADDENDUM RECEIPT:

KCHA Reserves the Right to Reject any and all Bids and select any bid options (Base Bid/Alternate Bid or both). In addition, KCHA Reserves the Right to Refuse to Award a Bid to a Contractor based on the Contractor's Past Performance, and/or Unresolved Issues with KCHA, as well as unresolved issues with Washington State Labor & Industries. No Extension of Completion is allowed.

KCHA also Reserves the Right to Reject all bids, for any reason, prior to Contract Execution.

The undersigned hereby agrees that this proposal shall be a Valid and Firm Offer for the following calendar days from the date of the Bid Opening.

Calendar Days: <u>SIXTY (60)</u>

If the Contractor's Bid is determined to be "Not Responsible", KCHA will issue in writing the specific reasons for this determination. Your company will be allowed to appeal this decision. The appeal must be in writing. The appeal must be delivered to KCHA at the address provided in the determination of 'Not Responsible' within two (2) business days after KCHA makes the decision. The appeal may include additional information that was not included in the original Bid Documents. KCHA will make a final determination after the receipt of the appeal. The final determination may not be appealed.

(Receipt of the following Addenda is acknowledged)

Addendum No.:	Date:	
Addendum No.:	Date:	
Addendum No.:	Date:	
Addendum No.:	Date:	
NO ADDENDA were received		
START TIME OF CONSTRUC Construction for the project must by KCHA.	CTION: be started in accordance with the written	en Notice to Proceed Date issued
duration (Construction Period/I work required under the Contraction)	to significantly complete the project volumentary. Ouration: NTP "construction start" et and in accordance with the Contra unch list items) shall be the following manufacture.	to physical completion) all the ct Documents. Time allowed to
	ONE HUNDRED FIFTY (150 d does not include any delays that may	
PRELIMINARY SCHEDULE:		
	is to provide a preliminary Master Proj	act Schadula in Microsoft Project
	ude task durations and a project duration	
Bidding Contractor's Company Name	e:	Initials:
Bid Form	Page 3 of 8	KCHA / 06-06-22

Bid Form Page 3 of 8 KC Return Form - B.1

King County Housing

KCHA – PEPPER TREE ENVELOPE CAPITAL CONSTRUCTION DEPARTMENT

METHOD OF PAYMENT:

Contract Amount shall be paid by KCHA to the Contractor monthly from the date of Contract, based on Contractor's Invoice of percentage of 'Completion'. Contractor shall use the AIA-G702 and G703 forms for Application and Certificate for Payment for Invoice Submittal.

CONTRACT RETENTION:

KCHA will withhold Contract Retention at the following Rate, pursuant to the General Conditions and will be released upon receipt of the Proper clearances from all pertinent state agencies. Release of Retention will not be made until All Requirements for Release, including clearances from State Agencies are received.

Retention Rate: <u>FIVE PERCENT (5%)</u>

CLOSEOUT PERCENTAGE:

Contractor to include in his Schedule of Values **Closeout Costs**; this is a percentage of the contract bid amount for costs associated with closing out the project as described in Section 01 77 00.

Closeout Percentage: TWO AND ONE-HALF PERCENT (2.5%)

LIQUIDATED DAMAGES:

Return Form - B.1

Timely performance and completion of the Work is essential to the Owner and time limits stated in the Agreement are of the essence. Owner will incur serious and substantial damages if Substantial Completion of the Work or Contract Completion of the entire project does not occur in the time limits defined in the Contract or subsequent change order. Liquidated damages are not assessed as a penalty, but as liquidated damages for breach of contract. The amount is fixed and agreed upon by the Contractor and Owner due to the extreme difficulty and impracticability of fixing and ascertaining the actual damages the Owner would sustain.

This amount is construed as actual amount of damages to the Owner and may be retained by the Owner and deducted from any payments to the Contractor. Assessment of liquidated damages does not release the Contractor for obligations in the Agreement. If different and separate completion dates are stated in the Agreement (or subsequent change order) for separate parts or stages of the Work, the amount of liquidated damages shall apply and may be assessed on those parts or stages of the Work which are delays.

If the Contractor fails to complete the Work by the Time for Substantial Completion stated above (or amended by a subsequent change order), then the Contractor agrees to abide by all provision of the Liquidated Damages clause to the Contract. Liquidated Damages shall be in the following DOLLAR AMOUNT per Calendar Days and will be assessed for each day that the Contractor exceeds the time for substantial completion stated above as follows:

Dollar Amount: FIVE HUNDRED DOLLARS AND NO/100 (\$500.00)

Bidding Contractor's Company Name:		Initials:
Bid Form	Page 4 of 8	KCHA / 06-06-22

King County Housing Authority

KCHA – PEPPER TREE ENVELOPE CAPITAL CONSTRUCTION DEPARTMENT

INDEMNIFICATION AND HOLD HARMLESS:

The Contractor hereby agrees that, to the fullest extent permitted by law, it will defend, indemnify and hold KCHA and its officials, partners, volunteers, agents and employees (the "Indemnities") harmless from and against any and all claims, losses, damages and expenses, including attorney's fees incurred with respect thereto or in enforcing this indemnity, which in any manner arise out of or in connection with, or result from:

- 1. The Work to be performed pursuant to this contract (the 'Work'), or
- 2. Any Act or Omission of:
 - a. The Contractor;
 - b. Any Subcontractor, Lower Tier Contractor, or Supplier engaged with respect to the Work;
 - c. Any other party acting at the direction, at the request or under the control of the Contractor with respect to this contract or the Work; or
 - d. The Officers, Directors, Partners, Employees, Volunteers or Agents of any of the foregoing, or the successors in interest of any of them.

Notwithstanding the foregoing, however, the Contractor shall not be required to indemnify and Indemnitee against liability for damages arising out of bodily injury to persons or damage to property caused by or resulting from the intentional misconduct or sole negligence of the Indemnitee, and if such damages are caused by or result from the concurrent negligence of the Indemnitee and the Contractor or its employees or agents, then the Contractor's indemnity hereunder shall be limited to the extent of the negligence of the Contractor or its employees or agents. For purposes of this Indemnity, the Contractor waives its immunity under industrial insurance, Title 51 of the Revised Code of Washington, and acknowledges that the parties have negotiated this waiver for the purposes of this agreement.

The Contractor hereby agrees to require all its Subcontractors or anyone acting under its direction or control or on its behalf in connection with or incidental to the performance of this contract to execute an indemnity agreement substantively identical to the proceeding one, specifically naming KCHA as an indemnitee, and the Contractor's failure to do so shall constitute a material breach of this contract by the Contractor.

LOCAL RESIDENCE HIRING AND CONTRACTING REQUIREMENTS FOR SECTION 3:

The undersigned agrees to adhere to the Local Resident Hiring and Contracting Requirements as defined in the Section 3 Documents. Failure to comply with this program "to the greatest extent feasible" may result in the withholding of progress payments until the breach of the contract is remedied. See Section 3 Certification Forms attached.

I certify, under	r penalty of perjury, that my company	Is a Section 3 Business
		Is Not a Section 3 Business
(For further cl	arification for Section 3 Certification, refe	r to Sections A.8 and B.10.a)
BID WITHD	RAWAL AFTER BID OPENING:	
1.	the bid bond. The bid withdrawal is pe bid and the mistake is readily apparent f	bid may withdraw the bid at the risk of forfeiting rmissible if there was an obvious error in the low from the bid itself. The bidder must notify KCHA twenty-four (24) hours of the bid opening.
2.	Evaluating factors for return or forfeitur a. Whether the bidder acted in good	
Bidding Contract	ctor's Company Name:	Initials:

Bid Form Page 5 of 8 KCHA / 06-06-22



- b. Whether the bidder acted without gross negligence;
- c. Whether the bidder gave prompt notice of the error;
- d. Whether the bidder will suffer substantial detriment by forfeiture;
- e. Whether KCHA's status has not greatly changed, and no substantial hardship will be caused.
- 3. Any low bidder who withdraws its bid is prohibited from bidding on the same project if it is subsequently re-solicited.

NOTIFICATION:

Contractors submitting bids must have current industrial insurance and not be disqualified from bidding (not suspended or debarred by any federal, state, or other public agency).

All or a portion of this contract is paid for by Federal Funds. As a result, Successful Contractors are subject to the following statures: Section 504 of the Rehabilitation Act of 1973; the Americans with Disabilities Act of 1990; the Architectural Barriers Act of 1968 and the Fair Housing Act of 1988.

It will be the Contractor's obligation to comply with pertinent laws and implementing regulations, which provide for non-discrimination and accessibility in Federally Funded Housing and Non-Housing Programs for people with Disabilities. To read the full text of the Notice go to Go to www.kcha.org/business/requirements Scroll down to Fair Housing Laws and Read: Fair Housing / Accessibility Notice

The undersigned acknowledges:

- 1. To have carefully reviewed and understood the scope of work and requirements under the Contract Documents and the complete scope of work as required under the Bid Proposal,
- 2. To have been provided the opportunity to physically assess the project site,
- 3. And affirms that the bid entered herein, shall be a complete bid in accordance with the terms of the Contract Documents,
- 4. That no person or company was employed or retained to solicit or obtain this contract and no payment of, or agreement to pay any person or company to solicit or obtain this contract any commission, percentage, brokerage, or other fee contingent upon or resulting from the award of this contract.
 - a. Should any misrepresentation of the bidder be found, KCHA will have the right to 1) terminate the contract; 2) at its discretion, deduct from the contract payment amounts the amount of any commission, percentage, brokerage, or other contingent fee; or 3) any other remedy pursuant to the contract.
- 5. And hereby agrees to complete the Work required under the terms of the Contract Documents by the Completion Dates enumerated therein, and
- 6. That all Documents Submitted to KCHA will become Public Records, as per RCW 42.56. If you are submitting information, which you think is confidential and / or proprietary to your business; KCHA recommends that you do not submit that information, as KCHA cannot guarantee that type of information will be withheld from a public disclosure request.

Bidding Contractor's Company Name:		Initials:	_
------------------------------------	--	-----------	---



$\textbf{COMPANY INFORMATION} \ (please \ print \ all \ information):$

Name of Bidder's Company	
Physical Street Address: (Contractor MUST have a Physical Street Address)	
City-State-Zip:	
Mailing Address if different than Physical:	
City-State-Zip:	
Telephone: Name of Person Authorized to Sign Contract: (if Company is Awarded Contract) Title of Person Authorized to Sign Contract: (if Company is Awarded Contract) Email Address of Person Authorized to Sign Contract:	
(if Company is Awarded Contract)	
Website:	
Contractor's License (WA State) Number:	
UBI (Unified Business License) Number:	
Employment Security Account Number:	
State Excise Tax Registration Number:	
Federal Tax I.D. Number:	
Public Works Training (RCW39.04.350):	 □ Exempt □ Not Exempt – signed Compliance Statement in Accordance with RCW 9A.72.085 is provided
Bidding Contractor's Company Name:	Initials:

Bid Form Return Form - B.1

King County Housing Authority

KCHA – PEPPER TREE ENVELOPE CAPITAL CONSTRUCTION DEPARTMENT

	Check Box if your company is a Corporate	tion and name the State Incorporated in below.			
	Check Box if your company is a Partners parties below.	Check Box if your company is a Partnership and provide Full Name(s) and Address of all parties below.			
	Check Box if your company is also know	n as (aka) and list that name and address below.			
NOTE: The p	penalty for making false statements in offer	is prescribed in 18 U.S.C. 1001.			
SUBMITTED	ON: Day of	, 20			
Signature of Bidde	ler	Print Name and Title			

Bidding Contractor's Company Name:______ Initials:_____



Return Form – B.2

BIDDER'S EXPERIENCE RECORD – RETURN EACH FORM SINGLE SIDED

KCHA WILL AWARD CONTRACTS ONLY TO RESPONSIBLE PROSPECTIVE CONTRACTORS WHO HAVE THE ABILITY TO PERFORM SUCCESSFULLY UNDER THE TERMS AND CONDITIONS OF THE PROPOSED CONTRACT. $PRINT\ ALL\ INFORMATION$.

ATTACH ADDITIONAL SHEETS AS NECESSARY TO FULLY PROVIDE THE INFORMATION REQUIRED.

NAME OF BIDDER:				
PHYSICAL ADDRESS	5:			
CITY-STATE-ZIP:				
MAILING ADDRESS:				
CITY-STATE-ZIP:				
CONTRACTOR'S LICENSE NUMBER: BOND REGISTRATION NUMBER:	(Must be a valid WA State License)	L&I's WORKERS'		
L&I PUBLIC WORKS TRAINING:	YES NO	_		
BIDDER IS A(N):	INDIVIDUAL	PARTNERSHIP		
	JOINT VENTURE	INCORPORATION	IN STATE OF	
CONTINUOUSLY	Y BEEN IN BUSINESS FROM YEAR	NO. OF REGU	ULAR FULL TIME EMPLOYEES _	
TOTAL NUMBER OF I	PROJECT COMPLETED IN TI	HE PAST 5 YEARS		
NUMBER OF PROJEC	TS COMPLETED	_ AHEAD C	ON-TIME	BEHIND
BIDDER HAS HAD EX	PERIENCE IN WORK COMP	ARABLE TO THAT REQU	JIRED FOR THIS PRO	OJECT
AS FOLLOWS: AS P	RIME CONTRACTOR:NO	AS SUB-CO	NTRACTOR:	
	NO	O. OF YEARS	NO.	OF YEARS
BIDDERS LIST THE FO	OLLOWING INFORMATION:	PRINT ALL INFORMAT	TION	
NAME OF BONDING	COMPANY:			
	ADDRESS:			
PHON				
CONTAC				
BONDING	CAPACITY:			
Bidding Contractor's Compa Bidders Experience	ny Name:Page	e 1 of 4	Initials: _ KCHA /	01-03-23



LIST THE SUPERVISORY PERSONNEL TO BE EMPLOYED BY THE BIDDER AND AVAILABLE FOR, AND INTENDED TO WORK ON THIS PROJECT (PROJECT MANAGER, PRINCIPAL FOREPERSON, SUPERINTENDENTS AND ENGINEERS): **PRINT ALL INFORMATION**

NAME	TITLE	HOW LONG WITH BIDDER
LIST ALL PUBLICLY FUNDED PROJECTS OF WITHIN THE PAST 5 YEARS. INCLUDE A I SEPARATE SHEET(S), USING THE FORMAT BI	REFERENCE FOR EACH. IF	NECESSARY, ATTACH A
PROJECT NAME:		
OWNER/CONTACT NAME & NUMBER:		
TOTAL CONTRACT AMOUNT:		
IF SUB, YOUR CONTRACT AMOUNT:		
YEAR PROJECT COMPLETED:		
PROJECT NAME:		
OWNER/CONTACT NAME & NUMBER:		
TOTAL CONTRACT AMOUNT:		
IF SUB, YOUR CONTRACT AMOUNT:		
YEAR PROJECT COMPLETED:		
PROJECT NAME:		
OWNER/CONTACT NAME & NUMBER:		
TOTAL CONTRACT AMOUNT:		
IF SUB, YOUR CONTRACT AMOUNT:		
YEAR PROJECT COMPLETED:		
PROJECT NAME:		
OWNER/CONTACT NAME & NUMBER:		
IF SUB, YOUR CONTRACT AMOUNT:		
YEAR PROJECT COMPLETED:		
Bidding Contractor's Company Name:		Initials:

Bidding Contractor's Con Bidders Experience Return Form – B.2

KCHA / 01-03-23



Return Form – B.2

		CTS LISTED ABOVE KPLAIN WHY: PRIN		APLETED WITHIN TH FION	HEIR ORIGINALLY
FINAL SE				IICH HAVE RESULTE R LITIGATION IN TH	
NA	ME OF CLIENT	& PROJECT	CONTRACT AMT.	TOTAL CLAIM ARBITRATED / LITIGATED	AMT. OF SETTLEMENTS OF CLAIM
		INFORMATION		REOF, EVER FAILED	
NO	YES	IF YES, EXPI	LAIN		
	BIDDER EVER		T / PERFORMANCI	E BOND CALLED AS A	A RESULT OF THIS
NO		S, COMPLETE THE F		WALCE DA DEST	DOND AMOUNT
	PROJECT NA		CONTRACT	ING PARTY	BOND AMOUNT
	DER EVER BEE		OF VIOLATING AN	NY STATE OR FEDER	AL EMPLOYMENT
NO	YES	IF YES, EXPI	LAIN		
				ANY PROVISION O	
NO	YES	IF YES, EXPI	AIN		
Bidding Co Bidders Ex	ntractor's Company	Name:	Page 3 of 4		Initials: KCHA / 01-03-23



Return Form – B.2

HAS ANY ADVERSE LEGAL JUDGEMENT RELATED TO CONSTRUCTION BEEN RENDERED AGAINST THE BIDDER IN THE LATE 5 YEARS? **PRINT ALL INFORMATION**

NO	YES	IF YES, EXPLAIN	N		
WORKER'	S COMPENS	IY OF ITS EMPLOYEES SATION OR OTHER INSU SMEMBERMENT IN THE F	RANCE COMPANY	FOR ACCIDENTS	RESULTING IN
NO	YES IF	YES, COMPLETE THE FOLI	LOWING:		
DAT	<u>E</u>	TYPE OF INJUR	Y	AGENCY RECE	IVING CLAIM
	R IS SELF-IN	E MODIFICATION RATE (SURED, ATTACH PROOF		2021 SHOWING COMPLE	2022 TE WORKSHEET
to disqualify EXCEEDS DESCRIBE	y Bidders when 1.0. KCHA not a ALL VIOLA	SAFETY IS A PRIMARY bere either the current or three that require additional information of the current of three that require additional information of the current of the	(3) year average of thation from Bidders the DAGAINST BIDD	ne Experience Modificat have an EMR of mo	cation Rate (EMR) ore than 1.0.
INFORMA	ATION	VIOLATION	DATE OF INSPECTION / INCIDENT	OSHA ACTIVITY NO.	CLOSED / PENDING
	NAL INFOR	MATION: SIDERED FOR AWARD, TH	HE BIDDER MAY BE	E REOUESTED BY K	CHA TO SUBMIT
A STATEN LISTED AI	MENT OR O' BOVE. FAIL	THER DOCUMENTATION URE BY THE BIDDER TO NON-RESPONSIVE AND	REGARDING ANY PROVIDE SUCH A	OF THE BASIC Q DDITIONAL INFOR	UALIFICATIONS MATION SHALL
INFORMA' UNDERSIO INFORMA'	TION IS CON GNED AUTI TION CONT	WARRANTS UNDER MPLETE, TRUE AND ACCU HORIZES THE KING C AINED HEREIN. (IF THIS ISIDERED NON-RESPONS	URATE TO THE BESTOUNTY HOUSING INFORMATION IS	ST OF HIS / HER KN G AUTHORITY TO	OWLEDGE. THE VERIFY ALL
	BIDDE	ER'S SIGNATURE	В	IDDER'S NAME (PLEAS)	E PRINT)
	BIDDER'S T	TTLE (PLEASE PRINT)		DATE	
Bidding Con Bidders Exp		any Name:P	age 4 of 4		Initials:



CONTRACTOR CERTIFICATION – RETURN EACH FORM SINGLE SIDED

PRO	OJECT NAME:	PEPPER TREE ENVE	LOPE	
NAN	ME OF COMPANY:			
PHY	SICAL STREET AD	DRESS:		
CITY	Y – STATE – ZIP:			
MAI	LING ADDRESS:			
CITY	Y – STATE – ZIP:			
РНО	NE NUMBER:			
FED	ERAL TAX ID NO.:		WA STATE UBI NO.:	
ГҮРЕ	OF BUSINESS:	CORPORATION	LLC - PARTNERSHIP	SOLE PROPRIETOR
OWN necessar		IPANY (List All Owners from	the inception of the Company. Use an add	litional sheet of paper if
	NAME O	F OWNER(S)	DATE(S) OF OWNER	RSHIP (from – to)
1.	There are no contr	actual obligation or other disa nined in the Bid Documents to	We hereby certify that: (Check the abilities that would prevent the achieve the greatest extent feasible and with	vement of the various
2.	location where seg		, nor permitMy /Our ended, except for separate or single-user the sexes.	
3.		in the performance of this pr list of violating facilities; and	ojectIs / Is Not listed o	on the Environmental
4.	Environmental Pro	tection Agency indicating that	TO award, of the receipt of any contany facility proposed to be used in the EPA List of Violating Facilities; and,	
5.	I/We	e will include a certification sul	ostantially the same as this certification	n in every non-exempt
6.			ave Not participated in an Equal Emp	• • • •
	-	_Have / Have Not file	e Government; and that ifI/d all reports due. If not, the reports w	



7.	The number shown on this form is the correct Taxpay Identification Number is listed, a notarized explanation as to			
8.	I / We further certify thatI / We	are not subject to Backup Withholding because;		
	Exempt from Backup Withholding, or No notification from the Internal Revenue Serv dividends, or	vice (IRS) for failing to report all interest or		
	No long subject to Backup Withholding per no	tification from the IRS		
	(If you ARE subject to Backup Withholding, l	leave \$5 blank and go to #6)		
9. of c sub	I / We have been notified by the IRS that I Am / We Are currently subject to Backup Withholding because of under reporting interest or dividends. (If you filled out #5 – you are NOT subject to Backup Withholding, leave #6 blank) , who is by title the of our firm/company and has been designated, as the responsible official to ensure required reports are submitted, and record keeping complies with all the applicable regulations.			
AUTHO	ORIZED OFFICIAL:			
SIGNAT	TURE	NAME (PLEASE PRINT)		
TITLE (F	(PLEASE PRINT)	DATE		

Return Form – B.3



NON-COLLUSIVE AFFIDAVIT – RETURN EACH FORM SINGLE SIDED

FOR CONTRACTS AND EQUIPMENT \$50	0,000 AND ABOVE
STATE OF WASHINGTON)	
COUNTY OF KING) ss	
	, being first duly sworn, deposes and says:
That he / she is a Partner or Officer of the Fir	m of, etc.
sham; that said bidder has not colluded, conbidder or person, to put in a sham bid or to indirectly, sought by agreement or collusion, bid price of affiant or of any other bidder, or to f that of any other bidder, or to secure any accordance in the said bidder.	id, that such proposal or bid is genuine and not collusive or a spired, connived or agreed, directly or indirectly, with any refrain from bidding, and has not in any manner, directly or or communication or conference, with any person, to fix the to fix any overhead, profit or cost element of said bid price, or dvantage against KING COUNTY HOUSING AUTHORITY aract; and that all statements in said proposal or bid are true.
	SIGNATURE OF AUTHORIZED OFFICIAL
	Bidder, if the Bidder is an Individua
	Partner, if the Bidder is a Partnership
	Officer, if the Bidder is a Corporation
SUBSCRIBED AND SWORN to before me:	
this day of, 20	
(Signature)	
(Print Name)	
My Commission Expires:	, 20
Bidding Contractor's Company Name:	Initials:



EQUAL OPPORTUNITY CLAUSE - RETURN EACH FORM SINGLE SIDED

DURING THE PERFORMANCE OF THIS CONTRACT, THE CONTRACTOR AGREES AS FOLLOWS:

- 1. The Contractor will not discriminate against any employee or applicant for employment because of race, color, religion, sex, or national origin, citizenship status, creed, age, marital status, physical or mental disability, sexual orientation, political ideology, or status as a Vietnam era or specially disabled veteran. The Contractor will take affirmative action to ensure that applicants are employed and the employees are treated during employment without regard to the aforementioned conditions. Such action shall include, but not be limited to, the following: Employment, upgrading, demotion, or transfer; recruitment or recruitment advertising; layoff or termination; rates of pay or other forms of compensation; and selection for training, including apprenticeship. The Contractor agrees to post in conspicuous places, available to employees and applicants for employment, notices to be provided by the Contracting Officer setting forth the provisions of this nondiscrimination clause.
- 2. The Contractor will, in all solicitations or advertisements for employees placed by or on behalf of the Contractor, state that all qualified applicants will receive consideration for employment without regard to the aforementioned conditions of paragraph 1 above.
- 3. The Contractor will send to each labor union or representative of workers with which he/she has a collective bargaining agreement or other contract or understanding, a notice advising the labor union or workers' representative of the Contractor's commitments under Section 202 of Executive Order 11246 of September 24, 1965, and shall post copies of the notice in conspicuous places available to employees and applicants for employment.
- 4. The Contractor will comply with all provisions of Executive Order 11246 of September 24, 1965, and of the rules, regulations and relevant orders of the Secretary of Labor.
- 5. The Contractor will furnish all information and reports required by Executive Order 11246 of September 24, 1965, and by the rules, regulations and relevant orders of the Secretary of Labor, or pursuant thereto, and will permit access to his/her books, records and accounts by the Owner and the Secretary of Labor for purposes of investigation to ascertain compliance with such rules, regulations and orders.
- 6. In the event of the Contractor's non-compliance with the non-discrimination clauses of the Contract or with any of such rules, regulations or orders, this Contract may be canceled, terminated or suspended in whole or in part and the Contractor may be declared ineligible for further Government Contracts, in accordance with procedures authorized in Executive Order 11246 of September 24, 1965, and such other sanctions may be imposed and remedies invoked as provided in Executive Order 11246 of September 24, 1965, or by rules, regulation, or order of the Secretary of Labor, or as otherwise provided by law.
- 7. The Contractor will include the provisions of paragraphs (1) through (7) in every subcontract or purchase order unless exempted by rules, regulation, or order of the Secretary of Labor issued pursuant to Section 204 of Executive Order 11246 of September 24, 1965, so that such provisions will be binding upon each subcontractor or vendor. The Contractor will take such action with respect to any subcontract or purchase order as the Owner may direct as a means of enforcing such provisions including sanctions for noncompliance: Provided, however, that in the event the Contractor becomes involved in, or is threatened with, litigation with a subcontractor or vendor as a result of such direction by the Owner, the Contractor may request the United States to enter into such litigation to protect the interests of the United States.

AUTHORIZED OFFICIAL:

SIGNATURE	NAME (PLEASE PRINT)
TITLE (PLEASE PRINT)	DATE
Bidding Contractor's Company Name:	Initials:



The	DEPOSIT: undersigned Principal hereby deposits a Bid Deposit with the King Coo of a cash deposit, certified or cashier's check, or postal money order in	the a	mount of	:
	Do	mars	(p)
	OR			
	BOND:		,	Duinainal) and
The	undersigned,		((Principal), and
	(Surety), are held	and f	irmly bo	und unto the
King	County Housing Authority (Owner) in the penal sum of:		J	
	Do	llars	(\$),
succe	th for the payment of which Principal and Surety bind themselves, their hassors and assigns, jointly and severally. The liability of surety under the enal sum of this Bid Bond.			
The lany A by P	ADITIONS: Bid Deposit or Bid Bond shall be an amount not less than five percent (Alternates, Additives, and Owner-Directed Work, if any, including sale rincipal to Owner in connection with a Proposal in according to the tements for:	s tax	if any, a	and is submitted
	PEPPER TREE ENVELOPE			
	V THEREFORE:			
a. b.	If Principal requests, in writing, to withdraw its Bid, prior to Bid Op If the Proposal is rejected by Owner, or	ening	g, or	
c.	Owner in accordance with the terms of the Proposal and furni performance of said Project and for the payment of all persons performance of the Proposal and furnity pe		ning labo	

materials in connection therewith, with Surety or Sureties approved by Owner,

then this Bid Security shall be released; otherwise it shall remain in full force and effect and Principal shall forfeit the Bid Deposit or Surety shall immediately pay and forfeit to Owner the amount of the Bid Bond, as penalty and liquidated damages.

The obligations of Surety and its Bid Bond shall be in no way impaired or affected by any extension of time within which Owner may accept bids; and Surety does hereby waive notice of any such extension.

Bidding Contractor's Company Name:		Initials:
Bid Security	Page 1 of 2	KCHA / 10-20-2



SIGNED AND DATED THIS	Day of	
		ATTEST to Principal's Signature:
PRINCIPAL (Print Company Name)		
Signature of Authorized Official		Signature
Printed Name		Printed Name
Title (Please Print)		Title (Please Print)
Corporate Seal (if Applicable)		
		ATTEST to Surety's Signature:
SURETY (Print Company Name)		
Signature of Authorized Official		Signature
Printed Name		Printed Name
Title (Please Print)		Title (Please Print)
Corporate Seal (if Applicable)		The above is Attorney in Fact:
		Yes No (If Yes, attach Power of Attorney)
Local Office of Agent and / or Surety Comp	pany (please	print):
Name	e: -	
Stree	et Address: _	
City,	State, Zip: _	
Power of Attorney of person signing for Suret	y Company n	nust be attached to this Bond Form.
Surety Companies executing Bonds must app Washington.	ear on the cu	rrent Authorized Insurance List in the State of
Bidding Contractor's Company Name:		Initials:

Bid Security Return Form – B.6



DEBARMENT / SUSPENSION COMPLIANCE CERTIFICATION RETURN EACH FORM SINGLE SIDED

The Bidder certifies to the best of its knowledge and belief, that it and its principals:

- 1. Are not presently debarred, suspended, proposed for debarment, declared ineligible, or voluntarily excluded from covered transactions by any federal department or agency;
- 2. Have not within a three (3) -year period preceding this proposal been convicted of or had a civil judgment rendered against them for commission of fraud or a criminal offense in connection with obtaining, attempting to obtain, or performing a public (federal, state or local) transaction or contract under a public transaction; violation of federal or state antitrust statutes or commission of embezzlement, theft, forgery, bribery, falsification or destruction of records, making false statements, or receiving stolen property;
- 3. Are not presently indicted for or otherwise criminally or civilly charged by a governmental entity (federal, state, or local) with commission of any of the offenses enumerated in paragraph (2) of this certification; and
- 4. Have not within a three-year period preceding this application/proposal had one or more public transactions (federal, state or local) terminated for cause or default.

BIDDING COMPANY

Company Name			
Physical Street Address			
City / State / Zip			
Print Name of Authorized Official	Title		
Signature of Authorized Official	Date		
SUBSCRIBED AND SWORN to before me:			
this day of, 20			
(Signature)	_		
(Print Name)			
My Commission Expires:, 20			
Bidding Contractor's Company Name:		Initials:	

SU	BCONTRACTOR – FIRST TIE	ER – LISTING – RETURN EACH FORM SINGLE SIDED	
NAMI	E OF BIDDING COMPANY:		
PHYS	ICAL STREET ADDRESS:		
CITY	/ STATE / ZIP:		
1.	List Approximate Percent (%) of Wor	rk Your Company will actually Perform:	
2.	Do You Intend on using Subcontractor	or(s) for this Project? Yes No	
3.	(If Yes, you must show on this form the name and information of All First Tier Subcontractors performs work that will be associated with this Bid.) Attach additional sheets if necessary. This form needs to completed to the best of the Bidder's ability at time of bid. If Bidder is Awarded Contract a firsubcontractor list will be submitted prior to Notice to Proceed. PRINT ALL INFORMATION		
	SUBCONT	TRACTOR – FIRST TIER - LIST	
Bus	iness Name:	Trade:	
	Address:		
	Phone:		
	UBI No.:		
Bus	iness Name:	Trade:	
	Address:		
	Phone:		
	UBI No.:		
Bus	iness Name:	Trade:	
	Address:		
	Phone:	Years of Experience:	
	UBI No.:		
Bus	iness Name:	Trade:	
	Address:	Contact:	
	Phone:	Years of Experience:	
	UBI No.:		
	idder hereby certifies that the information, is accurate, complete, and current:	n contained in this Proposed Subcontractor List, including any attached	
Print N	ame of Authorized Official	Title	
Signatu	ire	Date	
Biddin	ng Contractor's Company Name:	Initials:	



SECTION 3 – BUSINESS CERTIFICATION RETURN FORM SINGLE SIDED

THIS FORM MUST BE SIGNED AND RETURNED

	Project Name:		
C	Company Name:		
			Contact Title:
	Contact Phone:		Contact Email:
T	ype of Trade or B	usiness:	
Cı	urrent Number of	Regula	r, Full Time Employees (Puget Sound Region):
1.	Have over 75 pe been performed		f the labor hours performed for your business over the prior three-month period ion 3 workers?
	Yes	No	If "yes" is checked, submit the section 3 Individual Certification form(s) for all the regular, full-time employees (Puget Sound Region).
2.			r business owned and controlled by low- or very low-income persons (persons of the median income level for the past 12 months - see attached income
	Yes	No	If "yes" is checked, submit either the section 3 Individual Certification form(s) or the Section 3 Subcontractor Business Work Plan form.
3.	Does your busin will take place?	ess prov	vide economic opportunities for KCHA residents at the site(s) where the work
	Yes	No	If "yes" is checked, please provide supporting documentation.
4.			wide economic opportunities for residents of other KCHA developments or ng managed by KCHA?
	Yes	No	If "yes" is checked, please provide supporting documentation.
5.	•	•	rovide economic opportunities to Section 3 workers residing within the t Sound Region)?
	Yes	No	If "yes" is checked, please provide supporting documentation.



I certify, under penalty of perjury, that my compan	ny Is Is Not a Section 3 Business.			
I further certify that, if my company is awarded the bid, and needs to hire additional employees for the project , we will carry out Section 3 hiring, training and subcontracting requirements to the best of our ability.				
Signature	Name			
Title	Date			
Phone Number	Email Address			

If you have more specific questions about Section 3 requirements, contact KCHA at section3@kcha.org.

SECTION 3 – 2023 INCOME GUIDELINES

	Income Limit 1 person				
Location	Extremely Low Income		Very Low Income		Low Income
Kitsap County (Bremerton, Silverdale)	\$22,900		\$38,150		\$61,000
King/ Snohomish Counties (Seattle, Bellevue, Everett)	\$28,800		\$47,950		\$70,650
Pierce County (Tacoma)	\$22,600		\$37,650		\$60,200
Skagit County (Sedro-Woolley)	\$19,150		\$31,900		\$51,050
Thurston County (Olympia, Tumwater)	\$21,550		\$35,900		\$57,400



SECTION 3 – SUBCONTRACTOR WORK PLAN RETURN FORM SINGLE SIDED

RETURN THIS FORM WITH THE BID **IF:**

	CLAIMING <u>YES</u> TO QUESTION 3 or 4 on th			1
	Project Name: Company Name:			
	Company Name:Address:			
	Contact Name:			
	Contact Phone:			
	SECTION 3 BUSINESS CONCERN	SUBCONTRACTED TASK(S)	SUBCONTRACT AMOUNT	% OF OVERALL CONTRACT
	Subcontractor's Name:			
1.	Subcontractor's Address:			
	Subcontractor's Phone No.:			
	Subcontractor's Name:			
2.	Subcontractor's Address:			
	Subcontractor's Phone No.:			
	Subcontractor's Name:			
3.	Subcontractor's Address:			
	Subcontractor's Phone No.:			
	Subcontractor's Name:			
4.	Subcontractor's Address:			
	Subcontractor's Phone No.:			
TC	OTAL CONTRACT VALUE:	TOTAL SUBCONTRACT	「VALUE:	
F	PERCENTAGE OF To			
	attps://portalapps.hud.gov/Sec3BusReg/BRegistry			

Section 3 Business Certification Return Form B.9.b



SUMMARY OF HARASSMENT AND DISCRIMINATION RETURN EACH FORM SINGLE SIDED

KCHA prohibits harassment and discrimination based on race, color, national origin, citizenship status, creed, religion, sex, age, marital or veteran's status, physical or mental disability, sexual orientation, political ideology, or any other basis protected by law ("protected status"). This policy applies to KCHA's employees, vendors, contractors, visitors and others who conduct business with KCHA. The following are examples of prohibited conduct. This list is not exclusive; employees should see KCHA's Personnel Policies and Procedures for more details and vendors/contractors should contact the Human Resources Department for more details:

- Unwelcome conduct based on protected status when sufficiently severe or pervasive to create a hostile work environment; or a supervisor's improper conduct results in a tangible change in an employee's status or benefits (demotion, termination, etc.).
- Unwelcome sexual advances, requests for sexual favors and other verbal or physical conduct of a sexual nature when (1) submission to such conduct is made an implicit or explicit condition of employment; (2) submission to or rejection of such conduct affects employment opportunities or decisions; or (3) such conduct interferes with an employee's work or creates an intimidating, hostile or offensive work environment.
- Sexually suggestive or racially derogatory words, pictures, videos, cartoons, emails, etc.
- Leering, staring in a sexually suggestive manner or making offensive remarks about looks, clothing, or body.
- Touching in a way that may make an individual feel uncomfortable, such as patting, pinching or intentional brushing against another's body.
- Gestures, pictures or drawings which would offend a particular racial or ethnic group or other protected class.
- Comments about an individual's skin color, accent, or other racial/ethnic characteristics.
- Disparaging remarks or stereotypes about an individual's gender, race, birthplace, ethnicity or ancestry.
- Negative comments about an individual's religious beliefs (or lack of religious beliefs).
- Negative comments regarding an individual's age if age 40 and over.
- Derogatory or intimidating references to an employee's mental or physical impairment.

Anyone who has been harassed and/or discriminated against is expected to promptly report the alleged incident(s) to the Supervisor, Department Director, Director of Human Resources, Deputy Executive Director/Chief Administrative Officer or the Executive Director. KCHA will protect the confidentiality of such complaints to the extent possible. Complaints will be promptly, thoroughly and impartially investigated and KCHA will take immediate and appropriate corrective action when it determines that harassment has occurred. Individuals who make complaints or provide information related to complaints will be protected from retaliation.

The Bidder hereby certifies that the information contained above is understood and agreed upon.

Bidder's Company Name:	
Print Name of Authorized Official	Title
Signature	Date
Bidding Contractor's Company Name:	Initials:
TI . 1D' ' ' ' D 1 C1	WCHA / 10 20 20



WMBE SURVEY – RETURN EACH FORM SINGLE SIDED

PLEASE COMPLETE THIS SURVEY AND RETURN WITH YOUR BID / PROPOSAL DOCUMENTS.

NOT SUBMITTING THIS SURVEY WILL <u>NOT DISQUALIFY</u> YOUR BID/PROPOSAL.

THIS IS FOR INFORMATIONAL PURPOSES <u>ONLY</u>.

Bidding Company Name: Address: City / State / Zip:				
Type of Business:		_ Incorporated — Federal = _ Sole Proprietorship — St _ Other — Describe:	S#:	
WMBE:		_Yes	. No	
Describe:		Disadvantage Owned (I Women Owned (WBE) Minority Owned (MBE		
_	1.	White American	4.	Hispanic American
_	2.	Black American	5.	Asian – Pacific American
	3.	Native American	6.	Hasidic Jew
Registered WMBE:	Yes	No		_ Registration in Progress
Authorized Signer		Print Name and Title		Date
FOR KCHA USE ONLY: IF T TO: Tim Baker – KCHA Se Phone: 206-574-1111	enior Manage	ment Analyst	THE CONTRAC	CT, FORWARD THIS FORM

Bidding Contractor's Company Name: Initials:



CONTRACTOR'S SUPPLIED SCHEDULE - RETURN EACH FORM SINGLE SIDED

- A. Gantt-Chart Schedule: Submit to the Owner a comprehensive, fully developed, horizontal Gantt-chart-type, Contractor's Final Master Project Schedule within fourteen (14) days of date after Letter of Award. Base schedule on the Preliminary Master Project Schedule and whatever updating and feedback was received since the start of Project. The Gantt-Chart Final Master Project Schedule can be either in MS Project or equivalent format.
- B. Preparation: Indicate each significant construction activity separately. Identify first workday of each week with a continuous vertical line.
 - 1. For construction activities that require three (3) months or longer to complete, indicate an estimated completion percentage in ten (10%) percent increments within time bar.
- C. Contractor's Final Master Project Schedule Updating: At two (2) week intervals, update schedule to reflect actual construction progress and activities. Issue schedule three (3) days before each regularly scheduled progress meeting.
 - 1. Revise schedule immediately after each meeting or other activity where revisions have been recognized or made. Issue updated schedule concurrently with the report of each such meeting.
 - 2. Include a report with updated schedule that indicates every change, including, but not limited to, changes in logic, durations, actual starts and finishes, and activity durations.
 - 3. As the Work progresses, indicate Actual Completion percentage for each activity.

CONTRACTOR
TO INSERT
PRELIMINARY
MASTER PROJECT
SCHEDULE HERE
MUST BE IN
MICROSOFT PROJECT,
PRIMAVERA or SIMILAR

Ridding Contractor's Company Name:	Initials



BB - SECTION

NO PARTICIPATION for Bid Package

BB.1 No Participation Form



NO PARTICIPATION RESPONSE FORM

<u>IF YOU CHOOSE NOT TO BID ON THIS PROJECT</u> RETURN ONLY THIS FORM PRIOR TO THE BID DUE DATE.

(NOT RETURNING THIS DOCUMENT COULD RESULT IN YOUR NAME BEING REMOVED FROM FURTHER KCHA SOLICITATIONS.)

BID DUE DATE:		<u>September 13, 2023</u>			
PROJECT NAME:		Pepper Tree Envelope			
RETURN FORM TO:		amyk@kcha.org			
be received by the de	eadline of 1:00PM.	to mail in the No Participation Response For KCHA does not recommend mailing in the rise with the mail delivery.			
If using the mail please	e return the form to:	KING COUNTY HOUSING AUTHORITY ATTN: Amy Kurtz, Project Manager 700 Andover Park West, Suite C Tukwila, WA 98188			
1. My Company is NO	OT BIDDING on this	Contract because: (check all response(s) that ap	oply:		
Does not perf	form the requested type	pe of work			
Has other wor	rk which would interf	fere with the proposed work schedule			
☐ Job is too big					
☐ Job is too sma	all				
Can't meet th	Can't meet the bonding and/or insurance requirements				
☐ The documents were not received in time to prepare a bid					
☐ The specifications were not clear. Please describe:					
Other:					
2. I would have Bid on this Contract if:					
COMPANY NAME:					
ADDRESS:					
CITY-STATE-ZIP					
SIGNATURE:	PRINCIPAL OR OFFICE	ER .	DATE		



C - SECTION

CONTRACT DOCUMENTS for Bid Package

C.1	Construction Contract and General Conditions – Sample Template
C.2	Performance and Payment Bond with Directions (for projects \$35,000 & over)
C.3	Certificate as to Corporate Principal (If Performance & Payment Bonds are required)
C.4	Instructions to Bidders for Insurance Requirements
C.5	Site Specific Safety Plan – List of Plan Requirements
C.6	Subcontractor Verification
C.7	Certification of Payments to Influence Federal Transactions (for all subcontracts \$100,000 & over)
C.8	Disclosure of Lobbying Activities (for all subcontracts \$100,000 & over)
C.9	Certification of Compliance with Washington State Wage Payment Statutes
C.10	Vendor Set Up Form
C.11	Section 3 Individual Certification Form and FAQ's
C.12	Section 3 Labor Hours Benchmark Status Report – Sample Template

If selected, the documents that are numbered 2 through 9 will need to be submitted prior to the "Notice of Award" along with a copy of the completed Statement of Intent to Pay Prevailing Wages that you have filed with the Washington State Department of Labor and Industries.



CONSTRUCTION CONTRACT / GENERAL CONDITION SAMPLES

PLEASE SEE ATTACHED AIA DOCUMENTS

DRAFT AIA Document A101™ - 2017

Standard Form of Agreement Between Owner and Contractor

where the basis of payment is a Stipulated Sum

AGREEMENT made as of the «» day of «» in the year «» (*In words, indicate day, month and year.*)

CONTRACT NUMBER: «»

BETWEEN the Owner:

(Name, legal status, address and other information)

KING COUNTY HOUSING AUTHORITY

600 Andover Park West Tukwila, Washington 98188

and the Contractor:

(Name, legal status, address and other information)

NAME OF CONTRACTOR

Street Address City, State Zip

for the following Project:

(Name, location and detailed description)

NAME OF SITE

Street Address
City, State Zip
PROJECT NAME:

The Architect and/or The Engineer:

(Name, legal status, address and other information)

NAME OF ARCHITECT OR ENGINEER

Street Address City, State Zip

The Owner and Contractor agree as follows.

In consideration of the mutual covenants and agreements herein contained, the Contractor agrees to furnish all labor, material, tools, equipment, and other items necessary to perform and complete all work described in the contract documents. This agreement includes Owner Directed Work Items. The Owner Directed Work Items may or may not be completed under this agreement. If the Owner elects to exclude any or all Owner Directed Work Items, an adjustment shall be made to this Agreement.

ADDITIONS AND DELETIONS:

The author of this document has added information needed for its completion. The author may also have revised the text of the original AIA standard form. An Additions and Deletions Report that notes added information as well as revisions to the standard form text is available from the author and should be reviewed.

This document has important legal consequences. Consultation with an attorney is encouraged with respect to its completion or modification.

AIA Document A201™-2017, General Conditions of the Contract for Construction, is adopted in this document by reference. Do not use with other general conditions unless this document is modified.



{426/612.052/02533546-2} ELECTRONIC COPYING of

any portion of this AIA® Document to another electronic file is prohibited and constitutes a violation of copyright laws as set

1

TABLE OF ARTICLES

- 1 THE CONTRACT DOCUMENTS
- THE WORK OF THIS CONTRACT 2
- 3 DATE OF COMMENCEMENT AND SUBSTANTIAL COMPLETION
- **CONTRACT SUM**
- **PAYMENTS** 5
- DISPUTE RESOLUTION
- 7 **TERMINATION OR SUSPENSION**
- 8 **MISCELLANEOUS PROVISIONS**
- **ENUMERATION OF CONTRACT DOCUMENTS**

THE CONTRACT DOCUMENTS

The Contract Documents consist of this Agreement, Conditions of the Contract (General, Supplementary, and other Conditions), Drawings, Specifications, Addenda issued prior to execution of this Agreement, other documents listed in this Agreement, and Modifications issued after execution of this Agreement, all of which form the Contract, and are as fully a part of the Contract as if attached to this Agreement or repeated herein. The Contract represents the entire and integrated agreement between the parties hereto and supersedes prior negotiations, representations, or agreements, either written or oral. An enumeration of the Contract Documents, other than a Modification, appears in Article 9.

THE WORK OF THIS CONTRACT

The Contractor shall fully execute the Work described in the Contract Documents, except as specifically indicated in the Contract Documents to be the responsibility of others. The Contractor shall comply with the Detailed Summary of the Scope of Work per Exhibit A.

ARTICLE 3 DATE OF COMMENCEMENT AND SUBSTANTIAL COMPLETION

§ 3.1 The date of commencement of the Work shall be: (Check one of the following boxes.)

[« »] The date of this Agreement.

[**X**] A date set forth in a notice to proceed issued by the Owner.

[« »] Established as follows: (Insert a date or a means to determine the date of commencement of the Work.)

§ 3.2 The Contract Time shall be measured from the date of commencement of the Work, as indicated in the Notice to Proceed.

§ 3.3 Substantial Completion

§ 3.3.1 Subject to adjustments of the Contract Time as provided in the Contract Documents, the Contractor shall achieve Substantial Completion of the entire Work no later than the date stipulated in the **Notice to Proceed**.

User Notes:

Portion of Work Dates Month, Day, Year **Contract – Start Date** Month, Day, Year to Month, Day, Year **Construction Period Substantial Completion Date** Month, Day, Year **Physical Completion Date** Month, Day, Year (Liquidated Damages Start) **Contract – Final Completion Date** Month, Day, Year

§ 3.3.3 If the Contractor fails to achieve Substantial Completion as provided in this Section 3.3, liquidated damages, if any, shall be assessed as set forth in Section 4.5.

ARTICLE 4 CONTRACT SUM

§ 4.1 The Owner shall pay the Contractor the Contract Sum in current funds for the Contractor's performance of the Contract. The Contract Sum shall be «» (\$ «»), subject to additions and deductions as provided in the Contract Documents.

§ 4.2 Alternates

§ 4.2.1 Alternates, if any, included in the Contract Sum:

Alternate Number and Description

§ 4.2.2 Subject to the conditions noted below, the following alternates may be accepted by the Owner following execution of this Agreement. Upon acceptance, the Owner shall issue a Modification to this Agreement. (Insert below each alternate and the conditions that must be met for the Owner to accept the alternate.)

Conditions for Acceptance **Item Price** NA § 4.3 Allowances, if any, included in the Contract Sum: (*Identify each allowance.*) **Allowance Description Price Owner's Contingency**

§ 4.4 Unit prices, if any:

(Identify the item and state the unit price and quantity limitations, if any, to which the unit price will be applicable.) Unit prices will be used for unforeseen conditions where small quantities are needed. An unforeseen condition requiring large quantities resulting in a substantial change in the scope of work will not be considered applicable for unit pricing. Large deviations in the Scope of Work will be evaluated and addressed through a change order process as stipulated in the Contract Documents.

Price per Unit (\$0.00) **Unit Item Description**

§ 4.5 Liquidated damages, if any:

(Insert terms and conditions for liquidated damages, if any.)

Timely performance and completion of the Work is essential to the Owner and Time limits stated in the Agreement are of the essence. Owner will incur serious and substantial damages if Substantial Completion of the Work or Contract Completion of the entire project does not occur in the time limits defined in the Agreement. Liquidated Damages will not be assessed as a penalty, but as Liquidated Damages for breach of contract. The amount is fixed and agreed upon by the Contractor and Owner due to the extreme difficulty and impracticability of fixing and ascertaining the actual damages the Owner would sustain. This amount is construed as an actual amount of damages to the Owner and may be retained by the Owner and deducted from any payment to the Contractor for obligations in the Agreement. If different and separate completion dates are stated in the Agreement for separate parts or stages of the Work, the amount of Liquidated Damages shall apply and may be assessed on those parts or those stages of the Work which are delayed. The Owner therefore may impose and assess Liquidated Damages in the following amount per calendar day:

§ 4.6 Other:

(Insert provisions for bonus or other incentives, if any, that might result in a change to the Contract Sum.)

NA

ARTICLE 5 PAYMENTS

§ 5.1 Progress Payments

- § 5.1.1 Based upon Applications for Payment submitted to the Owner by the Contractor, the Owner shall make progress payments on account of the Contract Sum to the Contractor as provided below and elsewhere in the Contract Documents.
- § 5.1.2 The period covered by each Application for Payment shall be one calendar month ending on the last day of the month, or as follows:

NA

§ 5.1.3 Provided that an Application for Payment is received by the Owner not later than the 25th day of a month, the Owner shall make payment of the amount certified to the Contractor not later than the 25th day of the following month.

(Federal, state or local laws may require payment within a certain period of time.)

- § 5.1.3.1 Applications for Payment may be delayed by Owner should any criteria listed in A201TM-2017 General Conditions Section 9.5.1 be evident or if the As-Built Documents have not been updated per Division 01 10 10 Scope of Work Section 2.0.B.6.
- § 5.1.4 Each Application for Payment shall be based on the most recent schedule of values submitted by the Contractor in accordance with the Contract Documents. The schedule of values shall allocate the entire Contract Sum among the various portions of the Work. The schedule of values shall be prepared in such form, and supported by such data to substantiate its accuracy. This schedule, unless objected to by the Owner, shall be used as a basis for reviewing the Contractor's Applications for Payment.
- § 5.1.5 Applications for Payment shall show the percentage of completion of each portion of the Work as of the end of the period covered by the Application for Payment.
- § 5.1.6 In accordance with AIA Document A201TM–2017, General Conditions of the Contract for Construction, and subject to other provisions of the Contract Documents, the amount of each progress payment shall be computed as follows:
- § 5.1.6.1 The amount of each progress payment shall first include:
 - That portion of the Contract Sum properly allocable to completed Work;
 - .2 That portion of the Contract Sum properly allocable to materials and equipment delivered and suitably stored at the site for subsequent incorporation in the completed construction, or, if approved in advance by the Owner, suitably stored off the site at a location agreed upon in writing.; and
- § 5.1.6.2 The amount of each progress payment shall then be reduced by:
 - The aggregate of any amounts previously paid by the Owner;
 - .2 The amount, if any, for Work that remains uncorrected and for which the Owner has previously withheld an Application for Payment as provided in Article 9 of AIA Document A201–2017;
 - .3 Any amount for which the Contractor does not intend to pay a Subcontractor or material supplier, unless the Work has been performed by others the Contractor intends to pay;
 - .4 For Work performed or defects discovered since the last payment application, any amount for which the Owner may withhold payment, or nullify an Application of Payment in whole or in part, as provided in Article 9 of AIA Document A201-2017; and
 - .5 Retainage withheld pursuant to Section 5.1.7.

User Notes:

- § 5.1.6.3 The General Contractor Certification upon the Application for Payment form, per Exhibit B will accompany each Application for Payment. By submitting an Application for Payment, the Contractor certifies, agrees and warrants to the Owner as follows:
- The Contractor has made full payment to all laborers, subcontractors and suppliers of material and equipment whose charges were included in any prior Application for Payment, subject only to (a) retainage at the contract rate, and (b) the matters set forth below or on an attachment hereto.
- The Contractor knows of no one making a claim for payment other than those included in the current Application for Payment, who will be paid when the current Application for Payment is paid by the Owner, except as noted below or on an attachment hereto.
- In consideration of payments made by the Owner, the Contractor hereby waives and releases any and all claims and demands against Owner and the Project for all periods up to and including the period covered by this Application for Payment, subject only to (a) receipt of payment of the current Application, (b) applicable retainage, and (c) the matters set forth below or on an attachment hereto.

§ 5.1.7 Retainage

§ 5.1.7.1 For each progress payment made prior to Substantial Completion of the Work, the Owner may withhold the following amount, as retainage, from the payment otherwise due:

(Insert a percentage or amount to be withheld as retainage from each Application for Payment. The amount of retainage may be limited by governing law.)

«Five Percent » « 5% »

§ 5.1.7.1.1 The following items are not subject to retainage:

(Insert any items not subject to the withholding of retainage, such as general conditions, insurance, etc.)

« NA »

§ 5.1.7.2 Reduction or limitation of retainage, if any, shall be as follows:

(If the retainage established in Section 5.1.7.1 is to be modified prior to Substantial Completion of the entire Work, including modifications for Substantial Completion of portions of the Work as provided in Section 3.3.2, insert provisions for such modifications.)

$\ll NA \gg$

- § 5.1.7.3 Retainage shall be held at the rate stated in § 5.1.7.1 for the duration of the project. There shall be no reduction or limitation of retainage. There shall also be no early release of retainage by the Owner to the Contractor. The Owner must obtain all releases in relation to Contractor Compliance from the Washington State Department of Revenue, the Washington State Department of Labor and Industries, and the Washington State Department of Employment Security prior to any release of retention by the Owner to the Contractor.
- § 5.1.8 If final completion of the Work is materially delayed through no fault of the Contractor, the Owner shall pay the Contractor any additional amounts in accordance with Article 9 of AIA Document A201-2017.
- § 5.1.9 Except with the Owner's prior approval, the Contractor shall not make advance payments to suppliers for materials or equipment which have not been delivered and stored at the site.

§ 5.2 Final Payment

- § 5.2.1 Final payment, constituting the entire unpaid balance of the Contract Sum, shall be made by the Owner to the Contractor when
 - the Contractor has fully performed the Contract except for the Contractor's responsibility to correct .1 Work as provided in Article 12 of AIA Document A201–2017, and to satisfy other requirements, if any, which extend beyond final payment; and
 - .2 a final Application for Payment has been approved by the Owner;
 - verification of final Affidavits of Wages Paid (L&I) is provided by the Contractor to the Owner; .3
 - final Review and Approval of all Certified Payroll Documents for all Prevailing Wages.

User Notes:

(2034653549)

§ 5.2.2 The Owner's final payment to the Contractor shall be made no later than 30 days after the Owner's approval of the Final Application for Payment,

ARTICLE 6 DISPUTE RESOLUTION

§ 6.1 Any claim between the Owner and Contractor shall be resolved in accordance with the provisions set forth in Article 15 of AIA Document A201–2017.

ARTICLE 7 TERMINATION OR SUSPENSION

§ 7.1 The Contract may be terminated by the Owner or the Contractor as provided in Article 14 of AIA Document A201–2017.

§ 7.2 The Work may be suspended by the Owner as provided in Article 14 of AIA Document A201–2017.

ARTICLE 8 MISCELLANEOUS PROVISIONS

§ 8.1 Where reference is made in this Agreement to a provision of AIA Document A201–2017 or another Contract Document, the reference refers to that provision as amended or supplemented by other provisions of the Contract Documents.

§ 8.2 The Owner's representative:

(Name, address, email address, and other information)

Nikki Parrott, Director of Capital Construction & Weatherization

- «», Project Manager
- «», Construction Coordinator
- «», Project Engineer

§ 8.3 The Contractor's representative:

(Name, address, email address, and other information)

«», President

§ 8.4 Neither the Owner's nor the Contractor's representative shall be changed without ten days' prior notice to the other party.

§ 8.5 Insurance and Bonds

§ 8.5.1 The Contractor shall purchase and maintain insurance as set forth in AIA Document A101TM 2017, Standard Form of Agreement Between Owner and Contractor where the basis of payment is a Stipulated Sum.

Type of insurance or bond

Limit of liability or bond amount (\$0.00)

Certificate of Liability Insurance Requirements:

Limit
Coverage
(Exhibit - C)
Coverage
Requirements:

Coverage
Completed Value of Project
Performance and Payment Bond:
Gross Contract Amount
100%

§ 8.6 Other provisions:

§ 8.6.1 Section 3: Instruction, Requirements and Income Guidelines

§ 8.6.1.1 The Contractor shall comply with all requirements of the Section 3 Program for Economic Opportunities providing to the greatest extent possible, job training, employment and contract opportunities for low and very low income residents including persons who are recipients of HUD assistance for housing, with preference for both targeted workers living in the service area or neighborhood of the Development and Youthbuild participants, as defined at 24 CFR Part 75 per Exhibit D.1-D.3 and as designated in AIA A201-2017, Section 18 of the General Conditions.

§ 8.6.2 Davis-Bacon / HUD Non-Routine Maintenance / State Prevailing Wage Certified Payroll

§ 8.6.2.1 The Contractor shall comply with requirements and regulations of the Davis-Bacon Act per E.0 & E.1.

.1 Payment of Wages to Workers shall be weekly.

User Notes:

- .2 Certified Payroll Reports recording wages paid to each worker will be submitted to the Owner
- .3 Failure to submit weekly Certified Payroll Reports or errors in payroll reports for the Contractor and any and all Subcontractors, and any Lower Tier Subcontractors will be cause for the Owner to suspend or delay Contract Progress Payments.
- .4 The Owner shall withhold progress payments until all issues regarding full compliance with the submission of Certified Payroll Reports are resolved to the complete and full satisfaction of the
- .5 The Contractor is required and shall perform a complete review of all Certified Payroll Reports including those of the Contractor, and all Subcontractors and any and all Lower Tier Subcontractors prior to the submission of the reports by the Contractor to the Owner.
- The Wage Decision for this project is:

(Check one of the following boxes.)

[«»] Davis-Bacon

Construction Type «» Decision No. «» Modification No. «», Date «»

[«»] HUD Non-Routine Maintenance Date «»

[«»] WA State Prevailing Effective Date «» County «»

§ 8.6.3 Prevailing Wage Exemption

§ 8.6.3.1 For all contracts with a Bid Date of May 15, 2011 or later:

- When a Contractor claims an exemption from State Prevailing Wage Requirements on HUD Projects, the Contractor and all Subcontractors and all tiers must file an Intent and Affidavit with the Washington State Department of Labor and Industries for that project.
- .2 The Statement of Intent must also include an Exemption Claim stating that the project is exempt from the payment of State Prevailing Wage Rates based on the Housing Act of 1937 and 24CFR 965.101 and further stating that all workers will be paid in accordance with the requirements of the Davis-Bacon Wage Requirements, per Exhibit E.2.
- Pursuant to RCW 39.12.040, the Owner will not make any payments to a Contractor who has not submitted an Intent Form that has been approved by the Washington State Department of Labor and Industries Industrial Statistician, or release funds retained until the Contractor and all subcontractors have submitted Affidavit forms that have been certified by the Industrial Statistician.

ARTICLE 9 **ENUMERATION OF CONTRACT DOCUMENTS**

§ 9.1 This Agreement is comprised of the following documents:

- AIA Document A101TM–2017, Standard Form of Agreement Between Owner and Contractor .1
- .2 AIA Document A201TM–2017, General Conditions of the Contract for Construction
- .3 Drawings

Number Title **Date** Refer to Exhibit F **Drawings Table of Contents**

Specifications

Section Title **Date Pages** Refer to Exhibit G **Specifications Table of Contents**

.5 Addenda, if any:

> Number **Date Pages**

Portions of Addenda relating to bidding or proposal requirements are not part of the Contract Documents unless the bidding or proposal requirements are also enumerated in this Article 9.

Other documents, if any, listed below:

(List here any additional documents that are intended to form part of the Contract Documents. AIA Document A201TM–2017 provides that the advertisement or invitation to bid, Instructions to Bidders, sample forms, the Contractor's bid or proposal, portions of Addenda relating to bidding or proposal requirements, and other information furnished by the Owner in anticipation of receiving bids or proposals, are not part of the Contract Documents unless enumerated in this Agreement. Any such documents should be listed here only if intended to be part of the Contract Documents.)

Bid Documents			
.1	Contractor's Bid Documents	Exhibit H	
.2	Contractor's Company COVID – 19 Protection Protocols	Exhibit I	
.3	Contractor's Site Specific COVID- 19 Safety Plan	Exhibit J	

User Notes:

This Agreement entered into as of the day and year first written above.

KING COUNTY HOUSING AUTHORITY

XXX CONSTRUCTION COMPANY

OWNER (Sign	nature)	CONTRACTOR (Signature)		
Name (Print)		Name (Print)		
Title (Print)		Title (Print)		
		Contractor's License No.: «»		
EXHIBIT OVE	RVIEW:			
DESCRIPTION	ī	CROSS REFERENCE		
Exhibit – A Exhibit – B Exhibit – C Exhibit – D.1 Exhibit – D.2 Exhibit – D.3 Exhibit – E.0 Exhibit – E.1 Exhibit – E.2 Exhibit – F Exhibit – G Exhibit – H Exhibit – I Exhibit – J	Detailed Summary of Scope of Work Application for Payment Insurance Requirements Section 3 Documents Section 3 Documents Section 3 Documents Certified Payroll Certified Payroll Prevailing Wage Exemption Drawings Specifications Contractor's Bid Documents Contractor's Company COVID-19 Prote Contractor's Site Specific COVID-19 S			

DRAFT AIA Document A201™ - 2017

General Conditions of the Contract for Construction

CONTRACT NUMBER:

for the following PROJECT:

(Name and location or address)

NAME OF SITE

Street Address City, State Zip **PROJECT NAME:**

THE OWNER:

(Name, legal status and address)

KING COUNTY HOUSING AUTHORITY

600 Andover Park West Tukwila, Washington 98188

THE CONTRACTOR:

(Name, legal status and address)

CONTRACTOR'S NAME

Address City, State Zip

THE ARCHITECT and/or THE ENGINEER:

(Name, legal status and address)

ARCHITECT/ENGINEER NAME

Address City, State Zip

ADDITIONS AND DELETIONS:

The author of this document has added information needed for its completion. The author may also have revised the text of the original AIA standard form. An Additions and Deletions Report that notes added information as well as revisions to the standard form text is available from the author and should be reviewed.

This document has important legal consequences. Consultation with an attorney is encouraged with respect to its completion or modification.

For guidance in modifying this document to include supplementary conditions, see AIA Document A503™, Guide for Supplementary Conditions.



{426/612.052/02533547-2} ELECTRONIC COPYING of

any portion of this AIA® Document to another electronic file is prohibited and constitutes a violation of copyright laws as set

TABLE OF ARTICLES

- **GENERAL PROVISIONS** 1
- 2 **OWNER**
- 3 **CONTRACTOR**
- **ARCHITECT**
- 5 **SUBCONTRACTORS**
- CONSTRUCTION BY OWNER OR BY SEPARATE CONTRACTORS 6
- 7 **CHANGES IN THE WORK**
- 8 TIME
- 9 **PAYMENTS AND COMPLETION**
- 10 PROTECTION OF PERSONS AND PROPERTY
- 11 **INSURANCE AND BONDS**
- **UNCOVERING AND CORRECTION OF WORK** 12
- **MISCELLANEOUS PROVISIONS** 13
- TERMINATION OR SUSPENSION OF THE CONTRACT 14
- 15 **CLAIMS AND DISPUTES**
- 16 **FEDERAL PROVISIONS**
- 17 **AUDITS AND INSPECTIONS**
- 18 **SECTION 3**



User Notes:

INDEX Architect's Authority to Reject Work (Topics and numbers in bold are Section headings.) 3.5, 4.2.6, 12.1.2, 12.2.1 Architect's Copyright 1.1.7, 1.5 Acceptance of Nonconforming Work Architect's Decisions 9.6.6, 9.9.3, **12.3** 3.7.4, 4.2.6, 4.2.7, 4.2.11, 4.2.12, 4.2.13, 4.2.14, 6.3, Acceptance of Work 7.3.4, 7.3.9, 8.1.3, 8.3.1, 9.2, 9.4.1, 9.5, 9.8.4, 9.9.1, 9.6.6, 9.8.2, 9.9.3, 9.10.1, 9.10.3, 12.3 13.4.2, 15.2 Architect's Inspections Access to Work 3.7.4, 4.2.2, 4.2.9, 9.4.2, 9.8.3, 9.9.2, 9.10.1, 13.4 **3.16**, 6.2.1, 12.1 **Accident Prevention** Architect's Instructions 3.2.4, 3.3.1, 4.2.6, 4.2.7, 13.4.2 Acts and Omissions Architect's Interpretations 3.2, 3.3.2, 3.12.8, 3.18, 4.2.3, 8.3.1, 9.5.1, 10.2.5, 4.2.11, 4.2.12 10.2.8, 13.3.2, 14.1, 15.1.2, 15.2 Architect's Project Representative Addenda 4.2.10 1.1.1 Architect's Relationship with Contractor Additional Costs, Claims for 1.1.2, 1.5, 3.1.3, 3.2.2, 3.2.3, 3.2.4, 3.3.1, 3.4.2, 3.5, 3.7.4, 3.7.5, 10.3.2, 15.1.5 3.7.4, 3.7.5, 3.9.2, 3.9.3, 3.10, 3.11, 3.12, 3.16, 3.18, 4.1.2, 4.2, 5.2, 6.2.2, 7, 8.3.1, 9.2, 9.3, 9.4, 9.5, 9.7, **Additional Inspections and Testing** 9.4.2, 9.8.3, 12.2.1, **13.4** 9.8, 9.9, 10.2.6, 10.3, 11.3, 12, 13.3.2, 13.4, 15.2 **Additional Time, Claims for** Architect's Relationship with Subcontractors 3.2.4, 3.7.4, 3.7.5, 3.10.2, 8.3.2, **15.1.6** 1.1.2, 4.2.3, 4.2.4, 4.2.6, 9.6.3, 9.6.4, 11.3 **Administration of the Contract** Architect's Representations 3.1.3, **4.2**, 9.4, 9.5 9.4.2, 9.5.1, 9.10.1 Advertisement or Invitation to Bid Architect's Site Visits 3.7.4, 4.2.2, 4.2.9, 9.4.2, 9.5.1, 9.9.2, 9.10.1, 13.4 1.1.1 Aesthetic Effect 4.2.13 10.3.1 Allowances Attorneys' Fees 3.18.1, 9.6.8, 9.10.2, 10.3.3 **Applications for Payment** Award of Separate Contracts 4.2.5, 7.3.9, 9.2, **9.3**, 9.4, 9.5.1, 9.5.4, 9.6.3, 9.7, 9.10 6.1.1, 6.1.2 Award of Subcontracts and Other Contracts for Portions of the Work 2.1.1, 2.3.1, 2.5, 3.1.3, 3.10.2, 3.12.8, 3.12.9, 3.12.10.1, 4.2.7, 9.3.2, 13.4.1 5.2 **Basic Definitions Arbitration** 8.3.1, 15.3.2, **15.4** 1.1 **ARCHITECT Bidding Requirements** 1.1.1 Architect, Definition of Binding Dispute Resolution 8.3.1, 9.7, 11.5, 13.1, 15.1.2, 15.1.3, 15.2.1, 15.2.5, Architect, Extent of Authority 15.2.6.1, 15.3.1, 15.3.2, 15.3.3, 15.4.1 2.5, 3.12.7, 4.1.2, 4.2, 5.2, 6.3, 7.1.2, 7.3.4, 7.4, 9.2, Bonds, Lien 9.3.1, 9.4, 9.5, 9.6.3, 9.8, 9.10.1, 9.10.3, 12.1, 12.2.1, 7.3.4.4, 9.6.8, 9.10.2, 9.10.3 Bonds, Performance, and Payment 13.4.1, 13.4.2, 14.2.2, 14.2.4, 15.1.4, 15.2.1 Architect, Limitations of Authority and 7.3.4.4, 9.6.7, 9.10.3, **11.1.2**, 11.1.3, **11.5 Building Permit** Responsibility 2.1.1, 3.12.4, 3.12.8, 3.12.10, 4.1.2, 4.2.1, 4.2.2,3.7.1 4.2.3, 4.2.6, 4.2.7, 4.2.10, 4.2.12, 4.2.13, 5.2.1, 7.4, Capitalization 9.4.2, 9.5.4, 9.6.4, 15.1.4, 15.2 Architect's Additional Services and Expenses Certificate of Substantial Completion 2.5, 12.2.1, 13.4.2, 13.4.3, 14.2.4 9.8.3, 9.8.4, 9.8.5 Architect's Administration of the Contract **Certificates for Payment** 4.2.1, 4.2.5, 4.2.9, 9.3.3, **9.4**, 9.5, 9.6.1, 9.6.6, 9.7, 3.1.3, 3.7.4, 15.2, 9.4.1, 9.5 Architect's Approvals 9.10.1, 9.10.3, 14.1.1.3, 14.2.4, 15.1.4 2.5, 3.1.3, 3.5, 3.10.2, 4.2.7 Certificates of Inspection, Testing or Approval

{426/612.052/02533547-2} AIA Document A201™ - 2017. Copyright © 1911, 1915, 1918, 1925, 1937, 1951, 1958, 1961, 1963, 1966, 1970, 1976, 1987, 1997, 2007 and 2017 by The American Institute of Architects. All rights reserved. WARNING: This AIA® Document is protected by U.S. Copyright Law and International Treaties. Unauthorized reproduction or

User Notes:

distribution of this AIA® Document, or any portion of it, may result in severe civil and criminal penalties, and will be prosecuted to the maximum extent possible under the law. This draft was produced by AIA software at 18:17:19 on 06/29/2018 under Order No.5266129296 which expires on 06/07/2019, and is not for resale.

13.4.4

Certificates of Insurance Consolidation or Joinder 15.4.4 9.10.2 **Change Orders** CONSTRUCTION BY OWNER OR BY 1.1.1, 3.4.2, 3.7.4, 3.8.2.3, 3.11, 3.12.8, 4.2.8, 5.2.3, SEPARATE CONTRACTORS 7.1.2, 7.1.3, **7.2**, 7.3.2, 7.3.7, 7.3.9, 7.3.10, 8.3.1, 9.3.1.1, 9.10.3, 10.3.2, 11.2, 11.5, 12.1.2 Construction Change Directive, Definition of Change Orders, Definition of 7.2.1 **Construction Change Directives CHANGES IN THE WORK** 1.1.1, 3.4.2, 3.11, 3.12.8, 4.2.8, 7.1.1, 7.1.2, 7.1.3, 3.11, 4.2.8, **7**, 7.2.1, 7.3.1, 7.4, 8.3.1, 9.3.1.1, 11.5 **7.3**, 9.3.1.1 Claims, Definition of Construction Schedules, Contractor's 15.1.1 3.10, 3.11, 3.12.1, 3.12.2, 6.1.3, 15.1.6.2 Claims, Notice of **Contingent Assignment of Subcontracts** 1.6.2, 15.1.3 **5.4**. 14.2.2.2 **CLAIMS AND DISPUTES Continuing Contract Performance** 3.2.4, 6.1.1, 6.3, 7.3.9, 9.3.3, 9.10.4, 10.3.3, **15**, 15.4 15.1.4 Claims and Timely Assertion of Claims Contract, Definition of 15.4.1 1.1.2 CONTRACT, TERMINATION OR **Claims for Additional Cost** 3.2.4, 3.3.1, 3.7.4, 7.3.9, 9.5.2, 10.2.5, 10.3.2, **15.1.5** SUSPENSION OF THE 5.4.1.1, 5.4.2, 11.5, **14 Claims for Additional Time** 3.2.4, 3.3.1, 3.7.4, 6.1.1, 8.3.2, 9.5.2, 10.3.2, **15.1.6 Contract Administration** Concealed or Unknown Conditions, Claims for 3.1.3, 4, 9.4, 9.5 Contract Award and Execution, Conditions Relating 3.7.4 Claims for Damages 3.2.4, 3.18, 8.3.3, 9.5.1, 9.6.7, 10.2.5, 10.3.3, 11.3, 3.7.1, 3.10, 5.2, 6.1 Contract Documents, Copies Furnished and Use of 11.3.2, 14.2.4, 15.1.7 Claims Subject to Arbitration 1.5.2, 2.3.6, 5.3 15.4.1 Contract Documents, Definition of **Cleaning Up** 1.1.1 **3.15**, 6.3 **Contract Sum** Commencement of the Work, Conditions Relating to 3.7.4, 3.7.5, 3.8, 3.10.2, 5.2.3, 7.3, 7.4, **9.1**, 9.2, 9.4.2, 2.2.1, 3.2.2, 3.4.1, 3.7.1, 3.10.1, 3.12.6, 5.2.1, 5.2.3, 9.5.1.4, 9.6.7, 9.7, 10.3.2, 11.5, 12.1.2, 12.3, 14.2.4, 6.2.2, 8.1.2, 8.2.2, 8.3.1, 11.1, 11.2, **15.1.5** 14.3.2, 15.1.4.2, **15.1.5, 15.2.5** Commencement of the Work, Definition of Contract Sum, Definition of 8.1.2 9.1 **Communications** Contract Time 1.1.4, 2.2.1, 3.7.4, 3.7.5, 3.10/2, 5.2.3, 6.1.5, 7.2.1.3, 3.9.1, 4.2.4 Completion, Conditions Relating to 7.3.1, 7.3.5, 7.3.6, 7, 7, 7.3.10, 7.4, 8,1.1, 8.2.1, 8.2.3, 3.4.1, 3.11, 3.15, 4.2.2, 4.2.9, 8.2, 9.4.2, 9.8, 9.9.1, 8.3.1, 9.5.1, 9.7, 10.3.2, 12.1.1, 12.1.2, 14.3.2, 9.10, 12.2, 14.1.2, 15.1.2 15.1.4.2, 15.1.6.1, 15.2.5 COMPLETION, PAYMENTS AND Contract Time, Definition of 8.1.1 Completion, Substantial **CONTRACTOR** 3.10.1, 4.2.9, 8.1.1, 8.1.3, 8.2.3, 9.4.2, 9.8, 9.9.1, 3 9.10.3, 12.2, 15.1.2 Contractor, Definition of 3.1, 6.1.2 Compliance with Laws 2.3.2, 3.2.3, 3.6, 3.7, 3.12.10, 3.13, 9.6.4, 10.2.2, **Contractor's Construction and Submittal** 13.1, 13.3, 13.4.1, 13.4.2, 13.5, 14.1.1, 14.2.1.3, **Schedules** 15.2.8, 15.4.2, 15.4.3 **3.10**, 3.12.1, 3.12.2, 4.2.3, 6.1.3, 15.1.6.2 Concealed or Unknown Conditions Contractor's Employees 3.3.2, 3.4.3, 3.8.1, 3.9, 3.18.2, 4.2.3, 4.2.6, 10.2, 10.3, 3.7.4, 4.2.8, 8.3.1, 10.3

3.4.2, 3.14.2, 4.1.2, 9.8.5, 9.9.1, 9.10.2, 9.10.3, 13.2,

15.4.4.2

Consent, Written 3.7.4, 3.12.8, 3.14.2, 9.3.2, 11.3.1,

Contractor's Liability Insurance

11.3, 14.1, 14.2.1.1

Contractor's Relationship with Separate Contractors and Owner's Forces

3.12.5, 3.14.2, 4.2.4, 6, 11.3, 12.2.4

Conditions of the Contract

1.1.1, 6.1.1, 6.1.4

User Notes:

Contractor's Relationship with Subcontractors Date of Commencement of the Work, Definition of 1.2.2, 3.3.2, 3.18.1, 3.18.2, 4.2.4, 5, 9.6.2, 9.6.7, 8.1.2 9.10.2, 11.2, 11.3, 11.4 Date of Substantial Completion, Definition of Contractor's Relationship with the Architect 8.1.3 1.1.2, 1.5, 3.1.3, 3.2.2, 3.2.3, 3.2.4, 3.3.1, 3.4.2, 3.5.1, Day, Definition of 3.7.4, 3.10, 3.11, 3.12, 3.16, 3.18, 4.2, 5.2, 6.2.2, 7, 8.1.4 8.3.1, 9.2, 9.3, 9.4, 9.5, 9.7, 9.8, 9.9, 10.2.6, 10.3, Decisions of the Architect 3.7.4, 4.2.6, 4.2.7, 4.2.11, 4.2.12, 4.2.13, 6.3, 7.3.4, 11.3, 12, 13.4, 15.1.3, 15.2.1 Contractor's Representations 7.3.9, 8.1.3, 8.3.1, 9.2, 9.4, 9.5.1, 9.8.4, 9.9.1, 13.4.2, 3.2.1, 3.2.2, 3.5, 3.12.6, 6.2.2, 8.2.1, 9.3.3, 9.8.2 14.2.2, 14.2.4, 15.1, 15.2 Contractor's Responsibility for Those Performing the **Decisions to Withhold Certification** 9.4.1, **9.5**, 9.7, 14.1.1.3 3.3.2, 3.18, 5.3, 6.1.3, 6.2, 9.5.1, 10.2.8 Defective or Nonconforming Work, Acceptance, Contractor's Review of Contract Documents Rejection and Correction of 2.5, 3.5, 4.2.6, 6.2.3, 9.5.1, 9.5.3, 9.6.6, 9.8.2, 9.9.3, 3.2 Contractor's Right to Stop the Work 9.10.4, 12.2.1 **Definitions** Contractor's Right to Terminate the Contract 1.1, 2.1.1, 3.1.1, 3.5, 3.12.1, 3.12.2, 3.12.3, 4.1.1, 5.1, 6.1.2, 7.2.1, 7.3.1, 8.1, 9.1, 9.8.1, 15.1.1 **Delays and Extensions of Time** Contractor's Submittals 3.10, 3.11, 3.12, 4.2.7, 5.2.1, 5.2.3, 9.2, 9.3, 9.8.2, **3.2**, **3.7.4**, 5.2.3, 7.2.1, 7.3.1, **7.4**, **8.3**, 9.5.1, **9.7**, 9.8.3, 9.9.1, 9.10.2, 9.10.3 10.3.2, **10.4**, 14.3.2, **15.1.6**, 15.2.5 Contractor's Superintendent **Disputes** 6.3, 7.3.9, 15.1, 15.2 3.9, 10.2.6 Contractor's Supervision and Construction **Documents and Samples at the Site** Procedures 3.11 1.2.2, 3.3, 3.4, 3.12.10, 4.2.2, 4.2.7, 6.1.3, 6.2.4, **Drawings**, Definition of 7.1.3, 7.3.4, 7.3.6, 8.2, 10, 12, 14, 15.1.4 1.1.5 Coordination and Correlation Drawings and Specifications, Use and Ownership of 1.2, 3.2.1, 3.3.1, 3.10, 3.12.6, 6.1.3, 6.2.1 Copies Furnished of Drawings and Specifications Effective Date of Insurance 8.2.2 1.5, 2.3.6, 3.11 Copyrights **Emergencies** 1.5, 3.17 **10.4**, 14.1.1.2, **15.1.5** Correction of Work Employees, Contractor's 2.5, 3.7.3, 9.4.2, 9.8.2, 9.8.3, 9.9.1, 12.1.2, **12.2**, 12.3, 3.3.2, 3.4.3, 3.8.1, 3.9, 3.18.2, 4.2.3, 4.2.6, 10.2, 15.1.3.1, 15.1.3.2, 15.2.1 10.3.3, 11.3, 14.1, 14.2.1.1 **Correlation and Intent of the Contract Documents** Equipment, Labor, or Materials 1.1.3, 1.1.6, 3.4, 3.5, 3.8.2, 3.12, 3.13, 3.15.1, 4.2.6, 1.2 4.2.7, 5.2.1, 6.2.1, 7.3.4, 9.3.2, 9.3.3, 9.5.1.3, 9.10.2, Cost, Definition of 7.3.4 10.2.1, 10.2.4, 14.2.1.1, 14.2.1.2 Costs 7 Execution and Progress of the Work 2.5, 3.2.4, 3.7.3, 3.8.2, 3.15.2, 5.4.2, 6.1.1, 6.2.3, 1.1.3, 1.2.1, 1.2.2, 2.3.4, 2.3.6, 3.1, 3.3.1, 3.4.1, 3.7.1, 7.3.3.3, 7.3.4, 7.3.8, 7.3.9, 9.10.2, 10.3.2, 10.3.6, 3.10.1, 3.12, 3.14, 4.2, 6.2.2, 7.1.3, 7.3.6, 8.2, 9.5.1, 11.2, 12.1.2, 12.2.1, 12.2.4, 13.4, 14 9.9.1, 10.2, 10.3, 12.1, 12.2, 14.2, 14.3.1, 15.1.4 **Cutting and Patching** Extensions of Time 3.2.4, 3.7.4, 5.2.3, 7.2.1, 7.3, 7.4, 9.5.1, 9.7, 10.3.2, **3.14**, 6.2.5 Damage to Construction of Owner or Separate 10.4, 14.3, 15.1.6, **15.2.5** Contractors **Failure of Payment** 3.14.2, 6.2.4, 10.2.1.2, 10.2.5, 10.4, 12.2.4 9.5.1.3, **9.7**, 9.10.2, 13.5, 14.1.1.3, 14.2.1.2 Damage to the Work Faulty Work 3.14.2, 9.9.1, 10.2.1.2, 10.2.5, 10.4, 12.2.4 (See Defective or Nonconforming Work) Damages, Claims for **Final Completion and Final Payment** 3.2.4, 3.18, 6.1.1, 8.3.3, 9.5.1, 9.6.7, 10.3.3, 11.3.2, 4.2.1, 4.2.9, 9.8.2, **9.10**, 12.3, 14.2.4, 14.4.3 Financial Arrangements, Owner's 11.3, 14.2.4, 15.1.7 Damages for Delay 2.2.1, 13.2.2, 14.1.1.4 6.2.3, 8.3.3, 9.5.1.6, 9.7, 10.3.2, 14.3.2 **GENERAL PROVISIONS**

{426/612.052/02533547-2} AIA Document A201™ - 2017. Copyright © 1911, 1915, 1918, 1925, 1937, 1951, 1958, 1961, 1963, 1966, 1970, 1976, 1987, 1997, 2007 and 2017 by The American Institute of Architects. All rights reserved. WARNING: This AIA® Document is protected by U.S. Copyright Law and International Treaties. Unauthorized reproduction or distribution of this AIA® Document, or any portion of it, may result in severe civil and criminal penalties, and will be prosecuted to the maximum extent possible under the law. This draft was produced by AIA software at 18:17:19 on 06/29/2018 under Order No.5266129296 which

expires on 06/07/2019, and is not for resale. (1936282232) User Notes:

Governing Law Interpretations, Written 13.1 4.2.11, 4.2.12 Guarantees (See Warranty) Judgment on Final Award **Hazardous Materials and Substances** 15.4.2 Labor and Materials, Equipment 10.2.4. **10.3** Identification of Subcontractors and Suppliers 1.1.3, 1.1.6, **3.4**, 3.5, 3.8.2, 3.12, 3.13, 3.15.1, 5.2.1, 5.2.1 6.2.1, 7.3.4, 9.3.2, 9.3.3, 9.5.1.3, 9.10.2, 10.2.1, Indemnification 10.2.4, 14.2.1.1, 14.2.1.2 7.3.7 3.17, **3.18**, 9.6.8, 9.10.2, 10.3.3, 11.3 Labor Disputes Information and Services Required of the Owner 8.3.1 2.1.2, **2.2**, 2.3, 3.2.2, 3.12.10.1, 6.1.3, 6.1.4, 6.2.5, Laws and Regulations 4.1.1 9.6.1, 9.9.2, 9.10.3, 10.3.3, 11.2, 13.4.1, 13.4.2, 1.5, 2.3.2, 3.2.3, 3.2.4, 3.6, 3.7, 3.12.10, 3.13, 9.6.4, 9.9.1, 10.2.2, 13.1, 13.3.1, 13.4.2, 13.5, 14, 15.2.8, 14.1.1.4, 14.1.4, 15.1.4 **Initial Decision** 15.4 15.2 Liens 2.1.2, 9.3.1, 9.3.3, 9.6.8, 9.10.2, 9.10.4, 15.2.8 Initial Decision Maker, Decisions Limitations, Statutes of 14.2.4, 15.1.4.2, 15.2.1, 15.2.2, 15.2.3, 15.2.4, 15.2.5 12.2.5, 15.1.2, 15.4.1.1 Initial Decision Maker, Extent of Authority Limitations of Liability 3.2.2, 3.5, 3.12.10, 3.12.10.1, 3.17, 3.18.1, 4.2.6,14.2.4, 15.1.4.2, 15.2.1, 15.2.2, 15.2.3, 15.2.4, 15.2.5 4.2.7, 6.2.2, 9.4.2, 9.6.4, 9.6.7, 9.6.8, 10.2.5, 10.3.3, **Injury or Damage to Person or Property 10.2.8**, 10.4 11.3, 12.2.5, 13.3.1 Inspections Limitations of Time 3.1.3, 3.3.3, 3.7.1, 4.2.2, 4.2.6, 4.2.9, 9.4.2, 9.8.3, 2.1.2, 2.2, 2.5, 3.2.2, 3.10, 3.11, 3.12.5, 3.15.1, 4.2.7, 9.9.2, 9.10.1, 12.2.1, 13.4 5.2, 5.3, 5.4.1, 6.2.4, 7.3, 7.4, 8.2, 9.2, 9.3.1, 9.3.3, Instructions to Bidders 9.4.1, 9.5, 9.6, 9.7, 9.8, 9.9, 9.10, 12.2, 13.4, 14, 15, 1.1.1 15.1.2, 15.1.3, 15.1.5 Instructions to the Contractor Materials, Hazardous 3.2.4, 3.3.1, 3.8.1, 5.2.1, 7, 8.2.2, 12, 13.4.2 10.2.4, **10.3 Instruments of Service**, Definition of Materials, Labor, Equipment and 1.1.7 1.1.3, 1.1.6, 3.4.1, 3.5, 3.8.2, 3.12, 3.13, 3.15.1, 5.2.1, Insurance 6.2.1, 7.3.4, 9.3.2, 9.3.3, 9.5.1.3, 9.10.2, 10.2.1.2, 6.1.1, 7.3.4, 8.2.2, 9.3.2, 9.8.4, 9.9.1, 9.10.2, 10.2.5, 10.2.4, 14.2.1.1, 14.2.1.2 Means, Methods, Techniques, Sequences and Insurance, Notice of Cancellation or Expiration Procedures of Construction 3.3.1, 3.12.10, 4.2.2, 4.2.7, 9.4.2 11.1.4, 11.2.3 Insurance, Contractor's Liability Mechanic's Lien 2.1.2, 9.3.1, 9.3.3, 9.6.8, 9.10.2, 9.10.4, 15.2.8 11.1 Insurance, Effective Date of Mediation 8.2.2, 14.4.2 8.3.1, 15.1.3.2, 15.2.1, 15.2.5, 15.2.6, **15.3**, 15.4.1, Insurance, Owner's Liability 15.4.1.1 11.2 **Minor Changes in the Work Insurance, Property** 1.1.1, 3.4.2, 3.12.8, 4.2.8, 7.1, **7.4 10.2.5**, 11.2, 11.4, 11.5 MISCELLANEOUS PROVISIONS Insurance, Stored Materials 9.3.2 Modifications, Definition of 1.1.1 **INSURANCE AND BONDS** Modifications to the Contract 11 1.1.1, 1.1.2, 2.5, 3.11, 4.1.2, 4.2.1, 5.2.3, 7, 8.3.1, 9.7, Insurance Companies, Consent to Partial Occupancy 10.3.2 Insured loss, Adjustment and Settlement of **Mutual Responsibility** 6.2 Intent of the Contract Documents Nonconforming Work, Acceptance of

{426/612.052/02533547-2}

1.2.3, **1.4**, 4.1.1, 5.1, 6.1.2, 15.1.1

1.2.1, 4.2.7, 4.2.12, 4.2.13

Interest

Interpretation

13.5

AIA Document A201™ - 2017. Copyright © 1911, rights reserved. WARNING: This AIA® Document is protected by U.S. Copyright Law and International Treaties. Unauthorized reproduction or distribution of this AIA® Document, or any portion of it, may result in severe civil and criminal penalties, and will be prosecuted to the maximum extent possible under the law. This draft was produced by AIA software at 18:17:19 on 06/29/2018 under Order No.5266129296 which expires on 06/07/2019, and is not for resale. (1936282232) User Notes:

12.2

9.6.6, 9.9.3, 12.3

Nonconforming Work, Rejection and Correction of

2.4, 2.5, 3.5, 4.2.6, 6.2.4, 9.5.1, 9.8.2, 9.9.3, 9.10.4,

Notice Patching, Cutting and **1.6**, 1.6.1, 1.6.2, 2.1.2, 2.5, 3.2.4, 3.3.1, 3.7.4, 3.7.5, **3.14**, 6.2.5 3.9.2, 3.12.9, 3.12.10, 5.2.1, 7.4, 8.2.2 9.6.8, 9.7, **Patents** 9.10.1, 10.2.8, 10.3.2, 11.5, 12.2.2.1, 13.4.1, 13.4.2, 3.17 Payment, Applications for 14.1, 14.2.2, 14.4.2, 15.1.3, 15.1.5, 15.1.6, 15.4.1 Notice of Cancellation or Expiration of Insurance 4.2.5, 7.3.9, 9.2, **9.3**, 9.4, 9.5, 9.6.3, 9.7, 9.8.5, 9.10.1, 11.1.4, 11.2.3 14.2.3, 14.2.4, 14.4.3 **Notice of Claims Payment, Certificates for** 1.6.2, 2.1.2, 3.7.4, 9.6.8, 10.2.8, **15.1.3**, 15.1.5, 4.2.5, 4.2.9, 9.3.3, **9.4**, 9.5, 9.6.1, 9.6.6, 9.7, 9.10.1, 15.1.6, 15.2.8, 15.3.2, 15.4.1 9.10.3, 14.1.1.3, 14.2.4 Notice of Testing and Inspections Payment, Failure of 13.4.1, 13.4.2 9.5.1.3, **9.7**, 9.10.2, 13.5, 14.1.1.3, 14.2.1.2 Observations, Contractor's Payment, Final 4.2.1, 4.2.9, **9.10**, 12.3, 14.2.4, 14.4.3 3.2, 3.7.4 Payment Bond, Performance Bond and Occupancy 2.3.1, 9.6.6, 9.8 7.3.4.4, 9.6.7, 9.10.3, **11.1.2** Orders, Written Payments, Progress 1.1.1, 2.4, 3.9.2, 7, 8.2.2, 11.5, 12.1, 12.2.2.1, 13.4.2,9.3, **9.6**, 9.8.5, 9.10.3, 14.2.3, 15.1.4 PAYMENTS AND COMPLETION 14.3.1 2 **OWNER** Payments to Subcontractors 2 Owner, Definition of 5.4.2, 9.5.1.3, 9.6.2, 9.6.3, 9.6.4, 9.6.7, 14.2.1.2 **PCB Owner, Evidence of Financial Arrangements** 10.3.1 **2.2**, 13.2.2, 14.1.1.4 **Performance Bond and Payment Bond** Owner, Information and Services Required of the 7.3.4.4, 9.6.7, 9.10.3, **11.1.2** 2.1.2, **2.2**, 2.3, 3.2.2, 3.12.10, 6.1.3, 6.1.4, 6.2.5, Permits, Fees, Notices and Compliance with Laws 9.3.2, 9.6.1, 9.6.4, 9.9.2, 9.10.3, 10.3.3, 11.2, 13.4.1, 2.3.1, **3.7**, 3.13, 7.3.4.4, 10.2.2, 7.3.7.4 13.4.2, 14.1.1.4, 14.1.4, 15.1.4 PERSONS AND PROPERTY, PROTECTION OF Owner's Authority 1.5, 2.1.1, 2.4, 2.5, 3.4.2, 3.8.1, 3.12.10, 3.14.2, 4.1.2, Polychlorinated Biphenyl 4.2.4, 4.2.9, 5.2.1, 5.2.4, 5.4.1, 6.1, 6.3, 7.2.1, 7.3.1, 10.3.1 8.2.2, 8.3.1, 9.3.2, 9.5.1, 9.6.4, 9.9.1, 9.10.2, 10.3.2, Product Data, Definition of 11.4, 11.5, 12.2.2, 12.3, 13.2.2, 14.3, 14.4, 15.2.7, **Owner's Insurance** 3.12.2 **Product Data and Samples, Shop Drawings** 11.2 Owner's Relationship with Subcontractors 3.11, **3.12**, 4.2.7 **Progress and Completion** 1.1.2, 5.2, 5.3, 5.4, 9.6.4, 9.10.2, 14.2.2 Owner's Right to Carry Out the Work 4.2.2, **8.2**, 9.8, 9.9.1, 14.1.4, **15**.1.4 **2.5**, 14.2.2 **Progress Payments** Owner's Right to Clean Up 9.3, **9.6**, 9.8.5, 9.10.3, 14.2.3, 15.1.4 **Project**, Definition of Owner's Right to Perform Construction and to 1.1.4 **Award Separate Contracts Project Representatives** 4.2.10 Owner's Right to Stop the Work **Property Insurance** 10.2.5, **11.2** Owner's Right to Suspend the Work **Proposal Requirements** 14.3 PROTECTION OF PERSONS AND PROPERTY Owner's Right to Terminate the Contract 14.2, 14.4 10 Ownership and Use of Drawings, Specifications Regulations and Laws 1.5, 2.3.2, 3.2.3, 3.6, 3.7, 3.12.10, 3.13, 9.6.4, 9.9.1, and Other Instruments of Service 1.1.1, 1.1.6, 1.1.7, **1.5**, 2.3.6, 3.2.2, 3.11, 3.17, 4.2.12, 10.2.2, 13.1, 13.3, 13.4.1, 13.4.2, 13.5, 14, 15.2.8, 5.3 15.4

Partial Occupancy or Use

9.6.6, **9.9**

User Notes:

1915, 1918, 1925, 1937, 1951, 1958, 1961, 1963, 1966, 1970, 1976, 1987, 1997, 2007 and 2017 by The American Institute of Architects. All rights reserved. WARNING: This AIA® Document is protected by U.S. Copyright Law and International Treaties. Unauthorized reproduction or distribution of this AIA® Document, or any portion of it, may result in severe civil and criminal penalties, and will be prosecuted to the maximum extent possible under the law. This draft was produced by AIA software at 18:17:19 on 06/29/2018 under Order No.5266129296 which expires on 06/07/2019, and is not for resale.

Rejection of Work

4.2.6, 12.2.1

Releases and Waivers of Liens Specifications, Definition of 9.3.1, 9.10.2 1.1.6 Representations **Specifications** 3.2.1, 3.5, 3.12.6, 8.2.1, 9.3.3, 9.4.2, 9.5.1, 9.10.1 1.1.1, **1.1.6**, 1.2.2, 1.5, 3.12.10, 3.17, 4.2.14 Representatives Statute of Limitations 2.1.1, 3.1.1, 3.9, 4.1.1, 4.2.10, 13.2.1 15.1.2, 15.4.1.1 Responsibility for Those Performing the Work Stopping the Work 3.3.2, 3.18, 4.2.2, 4.2.3, 5.3, 6.1.3, 6.2, 6.3, 9.5.1, 10 2.4, 9.7, 10.3, 14.1 Retainage Stored Materials 9.3.1, 9.6.2, 9.8.5, 9.9.1, 9.10.2, 9.10.3 6.2.1, 9.3.2, 10.2.1.2, 10.2.4 **Review of Contract Documents and Field** Subcontractor, Definition of **Conditions by Contractor** 5.1.1 **3.2**, 3.12.7, 6.1.3 **SUBCONTRACTORS** Review of Contractor's Submittals by Owner and Subcontractors, Work by Architect 1.2.2, 3.3.2, 3.12.1, 3.18, 4.2.3, 5.2.3, 5.3, 5.4, 3.10.1, 3.10.2, 3.11, 3.12, 4.2, 5.2, 6.1.3, 9.2, 9.8.2 Review of Shop Drawings, Product Data and 9.3.1.2, 9.6.7 Samples by Contractor **Subcontractual Relations 5.3**, 5.4, 9.3.1.2, 9.6, 9.10, 10.2.1, 14.1, 14.2.1 3.12 **Rights and Remedies Submittals** 1.1.2, 2.4, 2.5, 3.5, 3.7.4, 3.15.2, 4.2.6, 5.3, 5.4, 6.1, 3.10, 3.11, 3.12, 4.2.7, 5.2.1, 5.2.3, 7.3.4, 9.2, 9.3, 6.3, 7.3.1, 8.3, 9.5.1, 9.7, 10.2.5, 10.3, 12.2.1, 12.2.2, 9.8, 9.9.1, 9.10.2, 9.10.3 12.2.4, **13.3**, 14, 15.4 Submittal Schedule Royalties, Patents and Copyrights 3.10.2, 3.12.5, 4.2.7 3.17 Subrogation, Waivers of Rules and Notices for Arbitration 6.1.1. **11.3** Substances, Hazardous 15.4.1 Safety of Persons and Property 10.3 **10.2**, 10.4 **Substantial Completion** 4.2.9, 8.1.1, 8.1.3, 8.2.3, 9.4.2, **9.8**, 9.9.1, 9.10.3, **Safety Precautions and Programs** 3.3.1, 4.2.2, 4.2.7, 5.3, **10.1**, 10.2, 10.4 12.2, 15.1.2 Samples, Definition of Substantial Completion, Definition of 3.12.3 9.8.1 Samples, Shop Drawings, Product Data and Substitution of Subcontractors 3.11, **3.12**, 4.2.7 5.2.3, 5.2.4 Samples at the Site, Documents and Substitutions of Materials 3.11 3.4.2, 3.5, 7.3.8 **Schedule of Values** Sub-subcontractor, Definition of **9.2**, 9.3.1 5.1.2 Schedules, Construction **Subsurface Conditions** 3.10, 3.12.1, 3.12.2, 6.1.3, 15.1.6.2 3.7.4 **Separate Contracts and Contractors Successors and Assigns** 1.1.4, 3.12.5, 3.14.2, 4.2.4, 4.2.7, 6, 8.3.1, 12.1.2 13.2 **Separate Contractors**, Definition of **Superintendent 3.9**, 10.2.6 6.1.1 Shop Drawings, Definition of **Supervision and Construction Procedures** 1.2.2, **3.3**, 3.4, 3.12.10, 4.2.2, 4.2.7, 6.1.3, 6.2.4, **Shop Drawings, Product Data and Samples** 7.1.3, 7.3.4, 8.2, 8.3.1, 9.4.2, 10, 12, 14, 15.1.4 3.11, 3.12, 4.2.7 **Suppliers** 1.5, 3.12.1, 4.2.4, 4.2.6, 5.2.1, 9.3, 9.4.2, 9.5.4, 9.6, Site, Use of **3.13**, 6.1.1, 6.2.1 9.10.5, 14.2.1 Site Inspections Surety 3.2.2, 3.3.3, 3.7.1, 3.7.4, 4.2, 9.9.2, 9.4.2, 9.10.1, 13.4 5.4.1.2, 9.6.8, 9.8.5, 9.10.2, 9.10.3, 11.1.2, 14.2.2, Site Visits, Architect's 15.2.7 3.7.4, 4.2.2, 4.2.9, 9.4.2, 9.5.1, 9.9.2, 9.10.1, 13.4 Surety, Consent of Special Inspections and Testing 9.8.5, 9.10.2, 9.10.3 4.2.6, 12.2.1, 13.4 Surveys

User Notes:

1.1.7, 2.3.4

Suspension by the Owner for Convenience 14.3

Suspension of the Work 3.7.5, 5.4.2, 14.3

Suspension or Termination of the Contract 5.4.1.1.14

Taxes

3.6, 3.8.2.1, 7.3.4.4

Termination by the Contractor

14.1, 15.1.7 **Termination by the Owner for Cause**

5.4.1.1, **14.2,** 15.1.7 **Termination by the Owner for Convenience**

Termination of the Contractor Employment 14.2.2

TERMINATION OR SUSPENSION OF THE **CONTRACT**

Tests and Inspections

3.1.3, 3.3.3, 3.7.1, 4.2.2, 4.2.6, 4.2.9, 9.4.2, 9.8.3, 9.9.2, 9.10.1, 10.3.2, 12.2.1, **13.4**

TIME

Time, Delays and Extensions of

3.2.4, 3.7.4, 5.2.3, 7.2.1, 7.3.1, 7.4, **8.3**, 9.5.1, 9.7, 10.3.2, 10.4, 14.3.2, 15.1.6, 15.2.5

Time Limits

2.1.2, 2.2, 2.5, 3.2.2, 3.10, 3.11, 3.12.5, 3.15.1, 4.2, 5.2, 5.3, 5.4, 6.2.4, 7.3, 7.4, 8.2, 9.2, 9.3.1, 9.3.3, 9.4.1, 9.5, 9.6, 9.7, 9.8, 9.9, 9.10, 12.2, 13.4, 14, 15.1.2, 15.1.3, 15.4

Time Limits on Claims

3.7.4, 10.2.8, 15.1.2, 15.1.3 Title to Work

9.3.2, 9.3.3

UNCOVERING AND CORRECTION OF WORK

12

Uncovering of Work

12.1

Unforeseen Conditions, Concealed or Unknown 3.7.4, 8.3.1, 10.3

Unit Prices

7.3.3.2, 9.1.2

Use of Documents

1.1.1, 1.5, 2.3.6, 3.12.6, 5.3

Use of Site

3.13, 6.1.1, 6.2.1

Values, Schedule of

9.2, 9.3.1

Waiver of Claims by the Architect 13.3.2

Waiver of Claims by the Contractor

9.10.5, 13.3.2, **15.1.7**

Waiver of Claims by the Owner

9.9.3, 9.10.3, 9.10.4, 12.2.2.1, 13.3.2, 14.2.4, **15.1.7**

Waiver of Consequential Damages

14.2.4, 15.1.7

Waiver of Liens

9.3, 9.10.2, 9.10.4

Waivers of Subrogation

6.1.1, 11.3

Warranty

3.5, 4.2.9, 9.3.3, 9.8.4, 9.9.1, 9.10.2, 9.10.4, 12.2.2,

15.1.2

Weather Delays

8.3, 15.1.6.2

Work, Definition of

1.1.3

Written Consent

1.5.2, 3.4.2, 3.7.4, 3.12.8, 3.14.2, 4.1.2, 9.3.2, 9.10.3,


13.2, 13.3.2, 15.4.4.2

Written Interpretations

4.2.11, 4.2.12

Written Orders

1.1.1, 2.4, 3.9, 7, 8.2.2, 12.1, 12.2, 13.4.2, 14.3.1



User Notes:

ARTICLE 1 GENERAL PROVISIONS

§ 1.1 Basic Definitions

§ 1.1.1 The Contract Documents

The Contract Documents are enumerated in the Agreement between the Owner and Contractor (hereinafter the Agreement) and consist of the Agreement, Conditions of the Contract (General, Supplementary and other Conditions), Drawings, Specifications, Addenda issued prior to execution of the Contract, other documents listed in the Agreement, and Modifications issued after execution of the Contract. A Modification is (1) a written amendment to the Contract signed by both parties, (2) a Change Order, (3) a Construction Change Directive, or (4) a written order for a minor change in the Work issued by the Owner. Unless specifically enumerated in the Agreement, the Contract Documents do not include the advertisement or invitation to bid, Instructions to Bidders, sample forms, other information furnished by the Owner in anticipation of receiving bids or proposals, the Contractor's bid or proposal, or portions of Addenda relating to bidding or proposal requirements.

§ 1.1.2 The Contract

The Contract Documents form the Contract for Construction. The Contract represents the entire and integrated agreement between the parties hereto and supersedes prior negotiations, representations, or agreements, either written or oral. The Contract may be amended or modified only by a Modification. The Contract Documents shall not be construed to create a contractual relationship of any kind (1) between the Contractor and the Architect or the Architect's consultants, (2) between the Owner and a Subcontractor or a Sub-subcontractor, (3) between the Owner and the Architect or the Architect's consultants, or (4) between any persons or entities other than the Owner and the Contractor. The Architect shall, however, be entitled to performance and enforcement of obligations under the Contract intended to facilitate performance of the Architect's duties.

§ 1.1.3 The Work

The term "Work" means the construction and services required by the Contract Documents, whether completed or partially completed, and includes all other labor, materials, equipment, and services provided or to be provided by the Contractor to fulfill the Contractor's obligations. The Work may constitute the whole or a part of the Project.

§ 1.1.4 The Project

The Project is the total construction of which the Work performed under the Contract Documents may be the whole or a part and which may include construction by the Owner and by Separate Contractors.

§ 1.1.5 The Drawings

The Drawings are the graphic and pictorial portions of the Contract Documents showing the design, location and dimensions of the Work, generally including plans, elevations, sections, details, schedules, and diagrams.

§ 1.1.6 The Specifications

The Specifications are that portion of the Contract Documents consisting of the written requirements for materials, equipment, systems, standards and workmanship for the Work, and performance of related services.

§ 1.1.7 Instruments of Service

Instruments of Service are representations, in any medium of expression now known or later developed, of the tangible and intangible creative work performed by the Architect and the Architect's consultants under their respective professional services agreements. Instruments of Service may include, without limitation, studies, surveys, models, sketches, drawings, specifications, and other similar materials.

§ 1.2 Correlation and Intent of the Contract Documents

§ 1.2.1 The intent of the Contract Documents is to include all items necessary for the proper execution and completion of the Work by the Contractor. The Contract Documents are complementary, and what is required by one shall be as binding as if required by all; performance by the Contractor shall be required only to the extent consistent with the Contract Documents and reasonably inferable from them as being necessary to produce the indicated results.

§ 1.2.1.1 The invalidity of any provision of the Contract Documents shall not invalidate the Contract or its remaining provisions. If it is determined that any provision of the Contract Documents violates any law, or is otherwise invalid or unenforceable, then that provision shall be revised to the extent necessary to make that provision legal and enforceable. In such case the Contract Documents shall be construed, to the fullest extent permitted by law, to give effect to the parties' intentions and purposes in executing the Contract.

- § 1.2.2 Organization of the Specifications into divisions, sections and articles, and arrangement of Drawings shall not control the Contractor in dividing the Work among Subcontractors or in establishing the extent of Work to be performed by any trade.
- § 1.2.3 Unless otherwise stated in the Contract Documents, words that have well-known technical or construction industry meanings are used in the Contract Documents in accordance with such recognized meanings.

§ 1.3 Capitalization

Terms capitalized in these General Conditions include those that are (1) specifically defined, (2) the titles of numbered articles, or (3) the titles of other documents published by the American Institute of Architects.

§ 1.4 Interpretation

In the interest of brevity the Contract Documents frequently omit modifying words such as "all" and "any" and articles such as "the" and "an," but the fact that a modifier or an article is absent from one statement and appears in another is not intended to affect the interpretation of either statement.

§ 1.5 Ownership and Use of Drawings, Specifications, and Other Instruments of Service

- § 1.5.1 The Architect and the Architect's consultants shall be deemed the authors and owners of their respective Instruments of Service, including the Drawings and Specifications, and retain all common law, statutory, and other reserved rights in their Instruments of Service, including copyrights. The Contractor, Subcontractors, Subsubcontractors, and suppliers shall not own or claim a copyright in the Instruments of Service. Submittal or distribution to meet official regulatory requirements or for other purposes in connection with the Project is not to be construed as publication in derogation of the Architect's or Architect's consultants' reserved rights.
- § 1.5.2 The Contractor, Subcontractors, Sub-subcontractors, and suppliers are authorized to use and reproduce the Instruments of Service provided to them, solely and exclusively for execution of the Work. All copies made under this authorization shall bear the copyright notice, if any, shown on the Instruments of Service. The Contractor, Subcontractors, Sub-subcontractors, and suppliers may not use the Instruments of Service on other projects or for additions to the Project outside the scope of the Work without the specific written consent of the Owner.

§ 1.6 Notice

- § 1.6.1 Except as otherwise provided in Section 1.6.2, where the Contract Documents require one party to notify or give notice to the other party, such notice shall be provided in writing to the designated representative of the party to whom the notice is addressed and shall be deemed to have been duly served if delivered in person, by mail, by courier, or by electronic transmission.
- § 1.6.2 Notice of Claims as provided in Section 15.1.3 shall be provided in writing and shall be deemed to have been duly served only if delivered to the designated representative of the party to whom the notice is addressed by certified or registered mail, or by courier providing proof of delivery.

§ 1.7 Digital Data Use and Transmission

If the parties intend to transmit Instruments of Service or any other information or documentation in digital form, they shall endeavor to establish necessary protocols governing such transmissions, unless otherwise already provided in the Agreement or the Contract Documents.

ARTICLE 2 OWNER

§ 2.1 General

- § 2.1.1 The Owner is the person or entity identified as such in the Agreement and is referred to throughout the Contract Documents as if singular in number. The Owner shall designate in writing a representative who shall have express authority to bind the Owner with respect to all matters requiring the Owner's approval or authorization. Except as otherwise provided in Section 4.2.1, the Architect does not have such authority. The term "Owner" means the Owner or the Owner's authorized representative.
- § 2.1.2 The Owner shall furnish to the Contractor, within fifteen days after receipt of a written request, information necessary and relevant for the Contractor to evaluate, give notice of, or enforce mechanic's lien rights. Such information shall include a correct statement of the record legal title to the property on which the Project is located, usually referred to as the site, and the Owner's interest therein.

§ 2.2 Evidence of the Owner's Financial Arrangements

§ 2.2.1 For the purposes of this Agreement the Owner has provided sufficient and adequate funding for this project. The Contractor may only request such evidence if (1) the Owner fails to make payments to the Contractor as the Contract Documents require; (2) a change in the Work materially changes the Contract Sum; or (3) the Contractor identifies in writing a reasonable concern regarding the Owner's ability to make payment when due. The Owner shall furnish such evidence as a condition precedent to commencement or continuation of the Work or the portion of the Work affected by a material change.

§ 2.3 Information and Services Required of the Owner

- § 2.3.1 Except for permits and fees that are the responsibility of the Contractor under the Contract Documents, including those required under Section 3.7.1, the Owner shall secure and pay for necessary approvals, easements, assessments and charges required for construction, use or occupancy of permanent structures or for permanent changes in existing facilities.
- § 2.3.2 The Owner may retain an architect lawfully licensed to practice architecture, or an entity lawfully practicing architecture, in the jurisdiction where the Project is located. That person or entity is identified as the Architect in the Agreement and is referred to throughout the Contract Documents as if singular in number.
- § 2.3.5 The Owner shall furnish surveys describing physical characteristics, legal limitations and utility locations for the site of the Project, and a legal description of the site. The Contractor shall be entitled to rely on the accuracy of information furnished by the Owner but shall exercise proper precautions relating to the safe performance of the Work.
- § 2.3.6 The Owner shall furnish information or services required of the Owner by the Contract Documents with reasonable promptness. The Owner shall also furnish any other information or services under the Owner's control and relevant to the Contractor's performance of the Work with reasonable promptness after receiving the Contractor's written request for such information or services.
- **§ 2.3.6** Unless otherwise provided in the Contract Documents, the Owner shall furnish to the Contractor one copy of the Contract Documents for purposes of making reproductions pursuant to Section 1.5.2.

§ 2.4 Owner's Right to Stop the Work

If the Contractor fails to correct Work that is not in accordance with the requirements of the Contract Documents as required by Section 12.2 or repeatedly fails to carry out Work in accordance with the Contract Documents, the Owner may issue a written order to the Contractor to stop the Work, or any portion thereof, until the cause for such order has been eliminated; however, the right of the Owner to stop the Work shall not give rise to a duty on the part of the Owner to exercise this right for the benefit of the Contractor or any other person or entity, except to the extent required by Section 6.1.3.

§ 2.5 Owner's Right to Carry Out the Work

If the Contractor defaults or neglects to carry out the Work in accordance with the Contract Documents and fails within a ten-day period after receipt of notice from the Owner to commence and continue correction of such default or neglect with diligence and promptness, the Owner may, without prejudice to other remedies the Owner may have, correct such default or neglect. In such case an appropriate Change Order shall be issued deducting from payments then or thereafter due the Contractor for the reasonable cost of correcting such deficiencies, including Owner's expenses and compensation for the additional professional design services made necessary by such default, neglect, or failure. If current and future payments are not sufficient to cover such amounts, the Contractor shall pay the difference to the Owner. If the Contractor disagrees with the actions of the Owner or the professional design services, or the amounts claimed as costs to the Owner, the Contractor may file a Claim pursuant to Article 15.

ARTICLE 3 CONTRACTOR

§ 3.1 General

User Notes:

§ 3.1.1 The Contractor is the person or entity identified as such in the Agreement and is referred to throughout the Contract Documents as if singular in number. The Contractor shall be lawfully licensed, if required in the jurisdiction where the Project is located. The Contractor shall designate in writing a representative who shall have express authority to bind the Contractor with respect to all matters under this Contract. The term "Contractor" means the Contractor or the Contractor's authorized representative.

- § 3.1.2 The Contractor shall perform the Work in accordance with the Contract Documents.
- § 3.1.3 The Contractor shall not be relieved of its obligations to perform the Work in accordance with the Contract Documents either by activities or duties of the Architect in the Owners's administration of the Contract, or by tests, inspections or approvals required or performed by persons or entities other than the Contractor.
- § 3.1.4 Progress Meetings. The Contractor shall schedule and conduct meetings with the Owner and as determined by the Owner with the Architect also present, to discuss such matters as procedures, progress, coordination, and the Final Project Schedules. The Contractor shall prepare, record, and promptly distribute minutes of each progress meeting to each attendee and identified stakeholders. The Contractor shall also provide a short-term look ahead schedule for presentation and review at each progress meeting. The short-term schedule shall be in sufficient detail to allow the Contractor and Owner to make any necessary schedule modifications to maintain the progress of the Work and for adherence to the time frames stipulated in the Agreement. The following shall also be included in the progress meeting agenda:
 - .1 Coordination of architectural, structural, mechanical, electrical, civil work or any other item associated with the Work.
 - .2 Measures to mitigate adverse effects of construction on the residents of the development during construction.
 - .3 Resolving issues with governing agencies.
 - .4 Status of submittals, RFI's, COR's and COR's.
 - .5 Site safety and associated issues.
 - .6 Segregated and comingled material recycling reports.
 - .7 Section 3 compliance and status.

§ 3.2 Review of Contract Documents and Field Conditions by Contractor

- § 3.2.1 Execution of the Contract by the Contractor is a representation that the Contractor has visited the site, become generally familiar with local conditions under which the Work is to be performed, and correlated personal observations with requirements of the Contract Documents.
- § 3.2.2 Because the Contract Documents are complementary, the Contractor shall, before starting each portion of the Work, carefully study and compare the various Contract Documents relative to that portion of the Work, as well as the information furnished by the Owner pursuant to Section 2.3.4, shall take field measurements of any existing conditions related to that portion of the Work, and shall observe any conditions at the site affecting it. These obligations are for the purpose of facilitating coordination and construction by the Contractor and are not for the purpose of discovering errors, omissions, or inconsistencies in the Contract Documents; however, the Contractor shall promptly report to the Owner any errors, inconsistencies or omissions discovered by or made known to the Contractor as a request for information in such form as the Owner may require. It is recognized that the Contractor's review is made in the Contractor's capacity as a contractor and not as a licensed design professional, unless otherwise specifically provided in the Contract Documents.
 - .1 If there is a discrepancy between Scope of Work, Specifications and/or Drawings, the Scope of Work shall take precedence followed by the Specifications and lastly the drawings.
- § 3.2.3 The Contractor is not required to ascertain that the Contract Documents are in accordance with applicable laws, statutes, ordinances, codes, rules and regulations, or lawful orders of public authorities, but the Contractor shall promptly report to the Owner any nonconformity discovered by or made known to the Contractor as a request for information in such form as the Owner may require.
- § 3.2.4 If the Contractor believes that additional cost or time is involved because of clarifications or instructions the Owner issues in response to the Contractor's notices or requests for information pursuant to Sections 3.2.2 or 3.2.3, the Contractor shall submit Claims as provided in Article 15. If the Contractor fails to perform the obligations of Sections 3.2.2 or 3.2.3, the Contractor shall pay such costs and damages to the Owner, subject to Section 15.1.7, as would have been avoided if the Contractor had performed such obligations. If the Contractor performs those obligations, the Contractor shall not be liable to the Owner for damages resulting from errors, inconsistencies or omissions in the Contract Documents, for differences between field measurements or conditions and the Contract Documents, or for nonconformities of the Contract Documents to applicable laws, statutes, ordinances, codes, rules and regulations, and lawful orders of public authorities.

§ 3.3 Supervision and Construction Procedures

- § 3.3.1 The Contractor shall supervise and direct the Work, using the Contractor's best skill and attention. The Contractor shall be solely responsible for, and have control over, construction means, methods, techniques, sequences, and procedures, and for coordinating all portions of the Work under the Contract. If the Contract Documents give specific instructions concerning construction means, methods, techniques, sequences, or procedures, the Contractor shall evaluate the jobsite safety thereof and shall be solely responsible for the jobsite safety of such means, methods, techniques, sequences, or procedures. If the Contractor determines that such means, methods, techniques, sequences or procedures may not be safe, the Contractor shall give timely notice to the Owner, and shall propose alternative means, methods, techniques, sequences, or procedures. The Owner shall evaluate the proposed alternative solely for conformance with the design intent for the completed construction. Unless the Owner objects to the Contractor's proposed alternative, the Contractor shall perform the Work using its alternative means, methods, techniques, sequences, or procedures and shall not proceed with that portion of the Work without further written instructions from the Owner. If the Contractor is then instructed to proceed with the required means, methods, techniques, sequences or procedures without acceptance of changes proposed by the Contractor, the Owner shall be solely responsible for any loss or damage arising solely from those Owner-required means, methods, techniques, sequences or procedures.
- § 3.3.2 The Contractor shall be responsible to the Owner for acts and omissions of the Contractor's employees, Subcontractors and their agents and employees, and other persons or entities performing portions of the Work for, or on behalf of, the Contractor or any of its Subcontractors.
- § 3.3.3 The Contractor shall be responsible for inspection of portions of Work already performed to determine that such portions are in proper condition to receive subsequent Work.

§ 3.4 Labor and Materials

- § 3.4.1 Unless otherwise provided in the Contract Documents, the Contractor shall provide and pay for labor, materials, equipment, tools, construction equipment and machinery, water, heat, utilities, transportation, and other facilities and services necessary for proper execution and completion of the Work, whether temporary or permanent and whether or not incorporated or to be incorporated in the Work.
- § 3.4.2 Except in the case of minor changes in the Work authorized by the Owner in accordance with Section 3.12.8, the Contractor may make substitutions only with the consent of the Owner, and in accordance with a Change Order or Construction Change Directive.
- § 3.4.3 The Contractor shall enforce strict discipline and good order among the Contractor's employees and other persons carrying out the Work. The Contractor shall not permit employment of unfit persons or persons not properly skilled in tasks assigned to them.

§ 3.5 Warranty

- § 3.5.1 The Contractor warrants to the Owner that materials and equipment furnished under the Contract will be of good quality, new and in conformance with the Contract Documents unless the Contract Documents require or permit otherwise. The Contractor further warrants that the Work will conform to the requirements of the Contract Documents and will be free from defects, except for those inherent in the quality of the Work-the Contract Documents require or permit. Work, materials, or equipment not conforming to these requirements may be considered defective. The Contractor's warranty excludes remedy for damage or defect caused by abuse, alterations to the Work not executed by the Contractor, improper or insufficient maintenance, improper operation, or normal wear and tear and normal usage. If required by the Owner, the Contractor shall furnish satisfactory evidence as to the kind and quality of materials and equipment.
- § 3.5.2 All material, equipment, or other special warranties required by the Contract Documents shall be issued in the name of the Owner, or shall be transferable to the Owner, and shall commence in accordance with Section 9.8.4.

§ 3.6 Taxes

User Notes:

The Contractor shall pay sales, consumer, use and similar taxes for the Work provided by the Contractor that are legally enacted when bids are received or negotiations concluded, whether or not yet effective or merely scheduled to go into effect.

§ 3.7 Permits, Fees, Notices and Compliance with Laws

- § 3.7.1 Unless otherwise provided in the Contract Documents, the Contractor shall secure and pay permits other than those acquired and paid by the Owners.
- § 3.7.2 The Contractor shall comply with and give notices required by applicable laws, statutes, ordinances, codes, rules and regulations, and lawful orders of public authorities applicable to performance of the Work.
- § 3.7.3 If the Contractoror performs Work knowing it to be contrary to applicable laws, statutes, ordinances, codes, rules and regulations, or lawful orders of public authorities, the Contractor shall assume appropriate responsibility for such Work and shall bear the costs attributable to correction. The Contract shall provide the required tenant notices as directed by the Owner.

§ 3.7.4 Concealed or Unknown Conditions

If the Contractor encounters conditions at the site that are (1) subsurface or otherwise concealed physical conditions that differ materially from those indicated in the Contract Documents or (2) unknown physical conditions of an unusual nature that differ materially from those ordinarily found to exist and generally recognized as inherent in construction activities of the character provided for in the Contract Documents, the Contractor shall promptly provide notice to the Owner before conditions are disturbed and in no event later than 14 days after first observance of the conditions. The Owner will promptly investigate such conditions and, if the Owner determines that they differ materially and cause an increase or decrease in the Contractor's cost of, or time required for, performance of any part of the Work, will recommend that an equitable adjustment be made in the Contract Sum or Contract Time, or both. If the Owner determines that the conditions at the site are not materially different from those indicated in the Contract Documents and that no change in the terms of the Contract is justified, the Owner shall promptly notify the Contractor in writing, stating the reasons.

§ 3.7.5 If, in the course of the Work, the Contractor encounters human remains or recognizes the existence of burial markers, archaeological sites or wetlands not indicated in the Contract Documents, the Contractor shall immediately suspend any operations that would affect them and shall notify the Owner. Upon receipt of such notice, the Owner shall promptly take any action necessary to obtain governmental authorization required to resume the operations. The Contractor shall continue to suspend such operations until otherwise instructed by the Owner but shall continue with all other operations that do not affect those remains or features. Requests for adjustments in the Contract Sum and Contract Time arising from the existence of such remains or features may be made as provided in Article 15.

§ 3.8 Allowances

§ 3.8.1 The Contractor shall include in the Contract Sum all allowances stated in the Contract Documents. Items covered by allowances shall be supplied for such amounts and by such persons or entities as the Owner may direct.

§ 3.8.2 Unless otherwise provided in the Contract Documents,

- allowances shall cover the cost to the Contractor of materials and equipment delivered at the site and all required taxes, less applicable trade discounts;
- .2 Contractor's costs for unloading and handling at the site, labor, installation costs, overhead, profit, and other expenses contemplated for stated allowance amounts shall be included in the shall be included in the allowances; and
- .3 whenever costs are more than or less than allowances, the Contract Sum shall be adjusted accordingly by Change Order. The amount of the Change Order shall reflect (1) the difference between actual costs and the allowances under Section 3.8.2.1 and (2) changes in Contractor's costs under Section 3.8.2.2.

§ 3.9 Superintendent

§ 3.9.1 The Contractor shall employ a competent superintendent and necessary assistants who shall be in attendance at the Project site during performance of the Work. The superintendent shall represent the Contractor, and communications given to the superintendent shall be as binding as if given to the Contractor.

§ 3.9.2 The Contractor, as soon as practicable after award of the Contract, shall confirm for the Owner of the name and qualifications of the superintendent as identified in the Bid Documents. Within 14 days of receipt of the information, the Owner may notify the Contractor, stating whether the Owner (1) has reasonable objection to the proposed superintendent or (2) requires additional time for review. Failure of the Owner to provide notice within the 14-day period shall constitute notice of no reasonable objection.

- § 3.9.3 The Contractor shall not employ a proposed superintendent to whom the Owner has made reasonable and timely objection. The Contractor shall not change the superintendent without the Owner's consent, which shall not unreasonably be withheld or delayed.
- § 3.9.4 The Contractor's Superintendent(s) shall be physically present at the jobsite from daily commencement of work to daily completion of work. The site shall be managed daily without interruption. Daily commencement and daily completion are defined as the actual hours of operation for the project.

§ 3.10 Contractor's Construction and Submittal Schedules

- § 3.10.1 The Contractor, promptly after being awarded the Contract, shall submit for the Owner's information a Contractor's construction schedule for the Work. The schedule shall contain detail appropriate for the Project, including (1) the date of commencement of the Work, interim schedule milestone dates, and the date of Substantial Completion; (2) an apportionment of the Work by construction activity; and (3) the time required for completion of each portion of the Work. The schedule shall provide for the orderly progression of the Work to completion and shall not exceed time limits current under the Contract Documents. The schedule shall be revised at appropriate intervals as required by the conditions of the Work and Project.
- § 3.10.2 The Contractor, promptly after being awarded the Contract and thereafter as necessary to maintain a current submittal schedule, shall submit a submittal schedule for the Owner's approval. The Owner's approval shall not be unreasonably delayed or withheld. The submittal schedule shall (1) be coordinated with the Contractor's construction schedule, and (2) allow the Owner reasonable time to review submittals. If the Contractor fails to submit a submittal schedule, or fails to provide submittals in accordance with the approved submittal schedule, the Contractor shall not be entitled to any increase in Contract Sum or extension of Contract Time based on the time required for review of submittals.
- § 3.10.3 The Contractor shall perform the Work in general accordance with the most recent schedules submitted to the Owner.

§ 3.11 Documents and Samples at the Site

The Contractor shall make available, at the Project site, the Contract Documents, including Change Orders, Construction Change Directives, and other Modifications, in good order and marked currently to indicate field changes and selections made during construction, and the approved Shop Drawings, Product Data, Samples, and similar required submittals. These shall be in electronic form or paper copy, available to the Owner, and delivered to the Owner upon completion of the Work as a record of the Work as constructed.

§ 3.12 Shop Drawings, Product Data and Samples

- § 3.12.1 Shop Drawings are drawings, diagrams, schedules, and other data specially prepared for the Work by the Contractor or a Subcontractor, Sub-subcontractor, manufacturer, supplier, or distributor to illustrate some portion of the Work.
- § 3.12.2 Product Data are illustrations, standard schedules, performance charts, instructions, brochures, diagrams, and other information furnished by the Contractor to illustrate materials or equipment for some portion of the Work.
- § 3.12.3 Samples are physical examples that illustrate materials, equipment, or workmanship, and establish standards by which the Work will be judged.
- § 3.12.4 Shop Drawings, Product Data, Samples, and similar submittals are not Contract Documents. Their purpose is to demonstrate how the Contractor proposes to conform to the information given and the design concept expressed in the Contract Documents for those portions of the Work for which the Contract Documents require submittals. Review by the Architect is subject to the limitations of Section 4.2.7. Informational submittals upon which the Architect is not expected to take responsive action may be so identified in the Contract Documents. Submittals that are not required by the Contract Documents may be returned by the Architect without action.
- § 3.12.5 The Contractor shall review for compliance with the Contract Documents, approve, and submit to the Owner, Shop Drawings, Product Data, Samples, and similar submittals required by the Contract Documents, in accordance with the submittal schedule approved by the Owner or, in the absence of an approved submittal

schedule, with reasonable promptness and in such sequence as to cause no delay in the Work or in the activities of the Owner or of Separate Contractors.

- § 3.12.6 By submitting Shop Drawings, Product Data, Samples, and similar submittals, the Contractor represents to the Owner that the Contractor has (1) reviewed and approved them, (2) determined and verified materials, field measurements and field construction criteria related thereto, or will do so, and (3) checked and coordinated the information contained within such submittals with the requirements of the Work and of the Contract Documents.
- § 3.12.7 The Contractor shall perform no portion of the Work for which the Contract Documents require submittal and review of Shop Drawings, Product Data, Samples, or similar submittals, until the respective submittal has been approved by the Owner.
- § 3.12.8 The Work shall be in accordance with approved submittals except that the Contractor shall not be relieved of responsibility for deviations from the requirements of the Contract Documents by the Owner's approval of Shop Drawings, Product Data, Samples, or similar submittals, unless the Contractor has specifically notified the Owner of such deviation at the time of submittal and (1) the Owner has given written approval to the specific deviation as a minor change in the Work, or (2) a Change Order or Construction Change Directive has been issued authorizing the deviation. The Contractor shall not be relieved of responsibility for errors or omissions in Shop Drawings, Product Data, Samples, or similar submittals, by the Owner's approval thereof.
- § 3.12.9 The Contractor shall direct specific attention, in writing or on resubmitted Shop Drawings, Product Data, Samples, or similar submittals, to revisions other than those requested by the Owner on previous submittals. In the absence of such notice, the Owner's approval of a resubmission shall not apply to such revisions.
- § 3.12.10 The Contractor shall not be required to provide professional services that constitute the practice of architecture or engineering unless such services are specifically required by the Contract Documents for a portion of the Work or unless the Contractor needs to provide such services in order to carry out the Contractor's responsibilities for construction means, methods, techniques, sequences, and procedures. The Contractor shall not be required to provide professional services in violation of applicable law.
- § 3.12.10.1 If professional design services or certifications by a design professional related to systems, materials, or equipment are specifically required of the Contractor by the Contract Documents, the Owner will specify all performance and design criteria that such services must satisfy. The Contractor shall be entitled to rely upon the adequacy and accuracy of the performance and design criteria provided in the Contract Documents. The Contractor shall cause such services or certifications to be provided by an appropriately licensed design professional, whose signature and seal shall appear on all drawings, calculations, specifications, certifications, Shop Drawings, and other submittals prepared by such professional. Shop Drawings, and other submittals related to the Work, designed or certified by such professional, if prepared by others, shall bear such professional's written approval when submitted to the Owner. The Owner shall be entitled to rely upon the adequacy and accuracy of the services, certifications, and approvals performed or provided by such design professionals, provided the Owner has specified to the Contractor the performance and design criteria that such services must satisfy. Pursuant to this Section 3.12.10, the Owner will review and approve or take other appropriate action on submittals only for the limited purpose of checking for conformance with information given and the design concept expressed in the Contract Documents.
- § 3.12.10.2 If the Contract Documents require the Contractor's design professional to certify that the Work has been performed in accordance with the design criteria, the Contractor shall furnish such certifications to the Architect at the time and in the form specified by the Architect.

§ 3.13 Use of Site

The Contractor shall confine operations at the site to areas permitted by applicable laws, statutes, ordinances, codes, rules and regulations, lawful orders of public authorities, and the Contract Documents and shall not unreasonably encumber the site with materials or equipment.

§ 3.14 Cutting and Patching

§ 3.14.1 The Contractor shall be responsible for cutting, fitting, or patching required to complete the Work or to make its parts fit together properly. All areas requiring cutting, fitting, or patching shall be restored to the condition existing prior to the cutting, fitting, or patching, unless otherwise required by the Contract Documents.

§ 3.14.2 The Contractor shall not damage or endanger a portion of the Work or fully or partially completed construction of the Owner or Separate Contractors by cutting, patching, or otherwise altering such construction, or by excavation. The Contractor shall not cut or otherwise alter construction by the Owner or a Separate Contractor except with written consent of the Owner and of the Separate Contractor. Consent shall not be unreasonably withheld. The Contractor shall not unreasonably withhold, from the Owner or a Separate Contractor, its consent to cutting or otherwise altering the Work.

§ 3.15 Cleaning Up

§ 3.15.1 The Contractor shall keep the premises and surrounding area free from accumulation of waste materials and rubbish caused by operations under the Contract. At completion of the Work, the Contractor shall remove waste materials, rubbish, the Contractor's tools, construction equipment, machinery, and surplus materials from and about the Project. Contractor to be in compliance with Section 6002 of the Solid Waste Disposal Act as amended by Resource Conservation & Recovery Act.

§ 3.15.2 If the Contractor fails to clean up as provided in the Contract Documents, the Owner may do so and the Owner shall be entitled to reimbursement from the Contractor.

§ 3.16 Access to Work

The Contractor shall provide the Owner and Architect with access to the Work in preparation and progress wherever located.

§ 3.17 Royalties, Patents and Copyrights

The Contractor shall pay all royalties and license fees. The Contractor shall defend suits or claims for infringement of copyrights and patent rights and shall hold the Owner harmless from loss on account thereof, but shall not be responsible for defense or loss when a particular design, process, or product of a particular manufacturer or manufacturers is required by the Contract Documents, or where the copyright violations are contained in Drawings, Specifications, or other documents prepared by the Owner. However, if an infringement of a copyright or patent is discovered by, or made known to, the Contractor, the Contractor shall be responsible for the loss unless the information is promptly furnished to the Owner. Contractor is to be in compliance with the Right of Inventions Act (37 CFR Part 401).

§ 3.18 Indemnification

§ 3.18.1 To the fullest extent permitted by law, the Contractor shall indemnify and hold harmless the Owner, Architect, Architect's consultants, and agents and employees of any of them from and against claims, damages, losses, and expenses, including but not limited to attorneys' fees, arising out of or resulting from performance of the Work, provided that such claim, damage, loss, or expense is attributable to bodily injury, sickness, disease or death, or to injury to or destruction of tangible property (other than the Work itself), but only to the extent caused by the negligent acts or omissions of the Contractor, a Subcontractor, anyone directly or indirectly employed by them, or anyone for whose acts they may be liable, regardless of whether or not such claim, damage, loss, or expense is caused in part by a party indemnified hereunder. Such obligation shall not be construed to negate, abridge, or reduce other rights or obligations of indemnity that would otherwise exist as to a party or person described in this Section 3.18.

§ 3.18.2 In claims against any person or entity indemnified under this Section 3.18 by an employee of the Contractor, a Subcontractor, anyone directly or indirectly employed by them, or anyone for whose acts they may be liable, the indemnification obligation under Section 3.18.1 shall not be limited by a limitation on amount or type of damages, compensation, or benefits payable by or for the Contractor or a Subcontractor under workers' compensation acts, disability benefit acts, or other employee benefit acts.

ARTICLE 4 ARCHITECT

§ 4.1 General

User Notes:

§ 4.1.1 The Architect is the person or entity retained by the Owner pursuant to Section 2.3.2 and identified as such in the Agreement.

§ 4.1.2 Duties, responsibilities, and limitations of authority of the Architect as set forth in the Contract Documents shall not be restricted, modified, or extended without written consent of the Owner, Contractor, and Architect. Consent shall not be unreasonably withheld.

§ 4.2 Administration of the Contract

- § 4.2.1 The Owner will provide administration of the Contract as described in the Contract Documents during construction until the date the Owner issues the final Certificate for Payment.
- § 4.2.2 The Owner will visit the site at intervals appropriate to the stage of construction to become generally familiar with the progress and quality of the portion of the Work completed, and to determine in general if the Work observed is being performed in a manner indicating that the Work, when fully completed, will be in accordance with the Contract Documents. However, the Owner will not be required to make exhaustive or continuous on-site inspections to check the quality or quantity of the Work. The Owner will not have control over, charge of, or responsibility for the construction means, methods, techniques, sequences or procedures, or for the safety precautions and programs in connection with the Work, since these are solely the Contractor's rights and responsibilities under the Contract Documents.
- § 4.2.3 On the basis of the site visits, the Owner will identify (1) known deviations from the Contract Documents, (2) known deviations from the most recent construction schedule submitted by the Contractor, and (3) defects and deficiencies observed in the Work. The Owner will not be responsible for the Contractor's failure to perform the Work in accordance with the requirements of the Contract Documents. The Owner will not have control over or charge of, and will not be responsible for acts or omissions of, the Contractor, Subcontractors, or their agents or employees, or any other persons or entities performing portions of the Work.
- § 4.2.4 The Owner will conduct a mandatory pre-construction meeting with the Contractor. The meeting will include but is not limited to a review of the scope of work, project schedules, general requirements for construction work, jobsite security, staging and storage areas, material recycling and salvage, jobsite cleanup, and tests, samples and construction observation. The meeting will also include a review of the submittal process for applications for payment, the change order process, the process for progress payments, the final application for payment, and release of retention. A review of the Certified Payroll process will also be conducted. A separate Certified Payroll training session will be conducted by the Owner with the Contractor and with each subcontractor.
- § 4.2.5 A separate meeting will be also be conducted to review the Section 3 plan submitted by the Contractor and to review of the Section 3 reporting procedures.
- § 4.2.6 The Contractor shall contact the local jurisdiction to conduct a pre-construction conference with building officials and other local agencies as applicable for the project.

§ 4.2.4 Communications

Except as otherwise provided in the Contract Documents or when direct communications have been specially authorized, the Owner and Contractor shall endeavor to communicate with each other directly about matters arising out of or relating to the Contract. Communications by and with the Architect's consultants shall be through the Owner. Communications by and with Subcontractors and suppliers shall be through the Contractor. Communications by and with Separate Contractors shall be through the Owner. The Contract Documents may specify other communication protocols.

- § 4.2.5 Based on the Owner's evaluations of the Contractor's Applications for Payment, the Owner will review and certify the amounts due the Contractor and will issue Certificates for Payment in such amounts.
- § 4.2.6 The Owner has authority to reject Work that does not conform to the Contract Documents. Whenever the Owner considers it necessary or advisable, the Owner will have authority to require inspection or testing of the Work in accordance with Sections 13.4.2 and 13.4.3, whether or not the Work is fabricated, installed or completed. However, neither this authority of the Owner nor a decision made in good faith either to exercise or not to exercise such authority shall give rise to a duty or responsibility of the Owner to the Contractor, Subcontractors, suppliers, their agents or employees, or other persons or entities performing portions of the Work.
- § 4.2.7 The Owner and/or Architect will review and approve, or take other appropriate action upon, the Contractor's submittals such as Shop Drawings, Product Data, and Samples, but only for the limited purpose of checking for conformance with information given and the design concept expressed in the Contract Documents. The Owner and/or Architect's action will be taken in accordance with the submittal schedule approved by the Owner or, in the absence of an approved submittal schedule, with reasonable promptness while allowing sufficient time in the Owner's professional judgment to permit adequate review. Review of such submittals is not conducted for the

purpose of determining the accuracy and completeness of other details such as dimensions and quantities, or for substantiating instructions for installation or performance of equipment or systems, all of which remain the responsibility of the Contractor as required by the Contract Documents. The Owner's review of the Contractor's submittals shall not relieve the Contractor of the obligations under Sections 3.3, 3.5, and 3.12. The Owner and/or Architect's review shall not constitute approval of safety precautions or of any construction means, methods, techniques, sequences, or procedures. The Owner's and/or Architect's approval of a specific item shall not indicate approval of an assembly of which the item is a component.

- § 4.2.8 The Owner will prepare Change Orders and Construction Change Directives, and may order minor changes in the Work as provided in Section 7.4. The Owner will investigate and make determinations and recommendations regarding concealed and unknown conditions as provided in Section 3.7.4.
- § 4.2.9 The Owner will conduct inspections to determine the date or dates of Substantial Completion and the date of final completion; issue Certificates of Substantial Completion pursuant to Section 9.8; written warranties and related documents required by the Contract and assembled by the Contractor pursuant to Section 9.10; and issue a final Certificate for Payment pursuant to Section 9.10.
- § 4.2.11 The Owner will interpret and decide matters concerning performance under, and requirements of, the Contract Documents. The Owner's response to such requests will be made in writing within any time limits agreed upon or otherwise with reasonable promptness.
- § 4.2.12 Interpretations and decisions of the Owner will be consistent with the intent of, and reasonably inferable from, the Contract Documents and will be in writing or in the form of drawings..
- § 4.2.13 The Owner's decisions on matters relating to aesthetic effect will be final if consistent with the intent expressed in the Contract Documents.
- § 4.2.14 The Owner will review and respond to requests for information about the Contract Documents. The Owner's response to such requests will be made in writing within any time limits agreed upon or otherwise with reasonable promptness. If appropriate, the Architect will assist the Owner and respond to Requests For Information (RFI's) as directed by the Owner and will prepare and issue supplemental Drawings and Specifications in response to the Requests For Information.

ARTICLE 5 SUBCONTRACTORS

§ 5.1 Definitions

- § 5.1.1 A Subcontractor is a person or entity who has a direct contract with the Contractor to perform a portion of the Work at the site. The term "Subcontractor" is referred to throughout the Contract Documents as if singular in number and means a Subcontractor or an authorized representative of the Subcontractor. The term "Subcontractor" does not include a Separate Contractor or the subcontractors of a Separate Contractor.
- § 5.1.2 A Sub-subcontractor is a person or entity who has a direct or indirect contract with a Subcontractor to perform a portion of the Work at the site. The term "Sub-subcontractor" is referred to throughout the Contract Documents as if singular in number and means a Sub-subcontractor or an authorized representative of the Sub-subcontractor.

§ 5.2 Award of Subcontracts and Other Contracts for Portions of the Work

- § 5.2.1 Unless otherwise stated in the Contract Documents, the Contractor, as soon as practicable after award of the Contract, shall confirm for the Owner of the persons or entities for each principal portion of the Work, including those who are to furnish materials or equipment fabricated to a special design as identified in the Bid Documents. Within 14 days of receipt of the information, the Owner may notify the Contractor whether the Owner (1) has reasonable objection to any such proposed person or entity or (2) requires additional time for review. Failure of the Owner to provide notice within the 14-day period shall constitute notice of no reasonable objection.
- § 5.2.2 The Contractor shall not contract with a proposed person or entity to whom the Owner has made reasonable and timely objection. The Contractor shall not be required to contract with anyone to whom the Contractor has made reasonable objection. The Contractor shall ensure that all and any Subcontractor(s) are not on any Debarment Lists and are Not Excluded from performing work on Federally Funded Projects. The Contractor shall provide written evidence of such to the Owner prior to the commencement of work.

User Notes:

§ 5.2.3 If the Owner has reasonable objection to a person or entity proposed by the Contractor, the Contractor shall propose another to whom the Owner has no reasonable objection. If the proposed but rejected Subcontractor was reasonably capable of performing the Work, the Contract Sum and Contract Time shall be increased or decreased by the difference, if any, occasioned by such change, and an appropriate Change Order shall be issued before commencement of the substitute Subcontractor's Work. However, no increase in the Contract Sum or Contract Time shall be allowed for such change unless the Contractor has acted promptly and responsively in submitting names as required.

§ 5.2.4 The Contractor shall not substitute a Subcontractor, person, or entity for one previously selected if the Owner makes reasonable objection to such substitution.

§ 5.3 Subcontractual Relations

By appropriate written agreement, the Contractor shall require each Subcontractor, to the extent of the Work to be performed by the Subcontractor, to be bound to the Contractor by terms of the Contract Documents, and to assume toward the Contractor all the obligations and responsibilities, including the responsibility for safety of the Subcontractor's Work that the Contractor, by these Contract Documents, assumes toward the Owner and Architect. Each subcontract agreement shall preserve and protect the rights of the Owner and Architect under the Contract Documents with respect to the Work to be performed by the Subcontractor so that subcontracting thereof will not prejudice such rights, and shall allow to the Subcontractor, unless specifically provided otherwise in the subcontract agreement, the benefit of all rights, remedies, and redress against the Contractor that the Contractor, by the Contract Documents, has against the Owner. Where appropriate, the Contractor shall require each Subcontractor to enter into similar agreements with Sub-subcontractors. The Contractor shall make available to each proposed Subcontractor, prior to the execution of the subcontract agreement, copies of the Contract Documents to which the Subcontractor will be bound, and, upon written request of the Subcontractor, identify to the Subcontractor terms and conditions of the proposed subcontract agreement that may be at variance with the Contract Documents. Subcontractors will similarly make copies of applicable portions of such documents available to their respective proposed Subsubcontractors.

§ 5.4 Contingent Assignment of Subcontracts

§ 5.4.1 Each subcontract agreement for a portion of the Work is assigned by the Contractor to the Owner, provided that

- .1 assignment is effective only after termination of the Contract by the Owner for cause pursuant to Section 14.2 and only for those subcontract agreements that the Owner accepts by notifying the Subcontractor and Contractor; and
- .2 assignment is subject to the prior rights of the surety, if any, obligated under bond relating to the Contract.

When the Owner accepts the assignment of a subcontract agreement, the Owner assumes the Contractor's rights and obligations under the subcontract.

- § 5.4.2 Upon such assignment, if the Work has been suspended for more than 30 days, the Subcontractor's compensation shall be equitably adjusted for increases in cost resulting from the suspension.
- § 5.4.3 Upon assignment to the Owner under this Section 5.4, the Owner may further assign the subcontract to a successor contractor or other entity. If the Owner assigns the subcontract to a successor contractor or other entity, the Owner shall nevertheless remain legally responsible for all of the successor contractor's obligations under the subcontract.

ARTICLE 6 CONSTRUCTION BY OWNER OR BY SEPARATE CONTRACTORS § 6.1 Owner's Right to Perform Construction and to Award Separate Contracts

§ 6.1.1 The term "Separate Contractor(s)" shall mean other contractors retained by the Owner under separate agreements. The Owner reserves the right to perform construction or operations related to the Project with the Owner's own forces, and with Separate Contractors retained under Conditions of the Contract substantially similar to those of this Contract, including those provisions of the Conditions of the Contract related to insurance and waiver of subrogation.

User Notes:

- § 6.1.2 When separate contracts are awarded for different portions of the Project or other construction or operations on the site, the term "Contractor" in the Contract Documents in each case shall mean the Contractor who executes each separate Owner-Contractor Agreement.
- § 6.1.3 The Owner shall provide for coordination of the activities of the Owner's own forces and of each Separate Contractor with the Work of the Contractor, who shall cooperate with them. The Contractor shall participate with any Separate Contractors and the Owner in reviewing their construction schedules. The Contractor shall make any revisions to its construction schedule deemed necessary after a joint review and mutual agreement. The construction schedules shall then constitute the schedules to be used by the Contractor, Separate Contractors, and the Owner until subsequently revised.
- § 6.1.4 Unless otherwise provided in the Contract Documents, when the Owner performs construction or operations related to the Project with the Owner's own forces or with Separate Contractors, the Owner or its Separate Contractors shall have the same obligations and rights that the Contractor has under the Conditions of the Contract, including, without excluding others, those stated in Article 3, this Article 6, and Articles 10, 11, and 12.

§ 6.2 Mutual Responsibility

- § 6.2.1 The Contractor shall afford the Owner and Separate Contractors reasonable opportunity for introduction and storage of their materials and equipment and performance of their activities, and shall connect and coordinate the Contractor's construction and operations with theirs as required by the Contract Documents.
- § 6.2.2 If part of the Contractor's Work depends for proper execution or results upon construction or operations by the Owner or a Separate Contractor, the Contractor shall, prior to proceeding with that portion of the Work, promptly notify the Owner of apparent discrepancies or defects in the construction or operations by the Owner or Separate Contractor that would render it unsuitable for proper execution and results of the Contractor's Work. Failure of the Contractor to notify the Owner of apparent discrepancies or defects prior to proceeding with the Work shall constitute an acknowledgment that the Owner's or Separate Contractor's completed or partially completed construction is fit and proper to receive the Contractor's Work. The Contractor shall not be responsible for discrepancies or defects in the construction or operations by the Owner or Separate Contractor that are not apparent.
- § 6.2.3 The Contractor shall reimburse the Owner for costs the Owner incurs that are payable to a Separate Contractor because of the Contractor's delays, improperly timed activities or defective construction. The Owner shall be responsible to the Contractor for costs the Contractor incurs because of a Separate Contractor's delays, improperly timed activities, damage to the Work or defective construction.
- § 6.2.4 The Contractor shall promptly remedy damage that the Contractor wrongfully causes to completed or partially completed construction or to property of the Owner or Separate Contractor as provided in Section 10.2.5.
- § 6.2.5 The Owner and each Separate Contractor shall have the same responsibilities for cutting and patching as are described for the Contractor in Section 3.14.
- § 6.2.6 The Contractor is obligated to comply with all Davis-Bacon and/or State Prevailing regulations if applicable, and shall inform all Subcontractors of this mandatory requirement. Strict compliance of the provisions of certified payrolls and monitoring of that compliance is a direct responsibility of the Contractor for each Subcontractor. Failure of the Contractor to monitor Davis-Bacon requirements including certified payroll compliance by Subcontractors, as evidenced by the Owner's review and written correction notices provided to the Contractor of non-compliance, will result in delay of progress payments to the Contractor by the Owner.

§ 6.3 Owner's Right to Clean Up

If a dispute arises among the Contractor, Separate Contractors, and the Owner as to the responsibility under their respective contracts for maintaining the premises and surrounding area free from waste materials and rubbish, the Owner may clean up and the Owner will allocate the cost among those responsible.

CHANGES IN THE WORK ARTICLE 7 § 7.1 General § 7.1.1

The Owner anticipates that it will desire the Contractor to accomplish Work that was not able to .1 be reasonably defined in sufficient detail during the solicitation for Bids for this Project. The

User Notes:

- Contractor agrees to perform such Owner Directed Work in accordance with the Contract Documents.
- .2 A fixed sum has been determined by the Owner for each individual and separate Owner Directed Work Item. The total Contract Amount includes the lump sum total of all combined Owner Directed Work Items. It is at the Sole Discretion and Decision of the Owner to Authorize the Contractor to proceed with each individual Owner Directed Work Item. If any or all Owner Directed Work Items are determined to be excluded from the Work, the Owner will provide a Change Order to the Contractor to deduct those amounts from the Contract.
- .3 If any or all Owner Directed Work Items are authorized by the Owner to be completed. The Owner will issue an Owner Directed Work Order to the Contractor for that Work Item.
- .4 For each Owner Directed Work Order issued to the Owner, the Contractor shall provide a complete and detailed cost estimate for that item to the Owner. The Contractor's estimate shall be approved by the Owner, prior to the commencement of any Owner Directed Work. Adjustments to the Contract may be made as an additive or deductive Change Order as determined by the difference between the Owner Directed Work Item Allowance, the Final Approved Estimated Cost as submitted by the Contractor, and the final Analysis of the Cost as conducted by the Owner.
- .5 The Contractor shall provide a complete and accurate time and material account and reconciliation report to the Owner for each issued work authorization for each Owner Directed Work Item.
- Owner Directed Work Items are defined in the Contract Documents. .6
- § 7.1.1 Changes in the Work may be accomplished after execution of the Contract, and without invalidating the Contract, by Change Order, Construction Change Directive or order for a minor change in the Work, subject to the limitations stated in this Article 7 and elsewhere in the Contract Documents. All changes in the Work shall be completed for a Fixed Fee.
 - Overhead, Profit, and General Conditions
 - (a.) The allowed markup shall cover all indirect project costs, including but not limited to: project Overhead, Profit, and General Conditions
 - (b.) The Contractor shall be allowed a maximum of 14% Overhead, Profit, and General Conditions, on the cost of craft labor, equipment, small tools and materials for self-performed Change Order work.
 - (c.) The Contractor shall be allowed a maximum of 8% Overhead, Profit, and General Conditions on the cost of craft labor, equipment, small tools and materials for Subcontractor Change Order work. The Contractor is not allowed to take a profit on the profit of the Subcontractor, as stated in form HUD-5370, section 29.
 - (d.) A Subcontractor shall be allowed a maximum of 14% of the cost of craft labor, equipment, materials, and small tools for Overhead, Profit, and General Conditions, for performing selfperformed Change Order work.
 - (e.) A Lower Tier Subcontractor shall be allowed a maximum of 14% of the cost of craft labor, equipment, materials, and small tools for Overhead, Profit, and General Conditions, for performing Change Order work.
- § 7.1.2 A Change Order shall be based upon agreement among the Owner and Contractor. A Construction Change Directive requires agreement by the Owner and may or may not be agreed to by the Contractor. An order for a minor change in the Work may be issued by the Owner.
- § 7.1.3 Changes in the Work shall be performed under applicable provisions of the Contract Documents. The Contractor shall proceed promptly with changes in the Work, unless otherwise provided in the Change Order, Construction Change Directive, or order for a minor change in the Work.

§ 7.2 Change Orders

- § 7.2.1 A Change Order is a written instrument prepared by the Owner and signed by the Owner and Contractor stating their agreement upon all of the following:
 - .1 The change in the Work;
 - .2 The amount of the adjustment, if any, in the Contract Sum; and
 - .3 The extent of the adjustment, if any, in the Contract Time.

§ 7.3 Construction Change Directives § 7.3.1

{426/612.052/02533547-2}

User Notes:

distribution of this AIA® Document, or any portion of it, may result in severe civil and criminal penalties, and will be prosecuted to the maximum extent possible under the law. This draft was produced by AIA software at 18:17:19 on 06/29/2018 under Order No.5266129296 which xpires on 06/07/2019, and is not for resale.

A Construction Change Directive shall be provided as stipulated by the Owner and in accordance with the King County Housing Authority Change Order Request documents (COR) per Exhibit as designated in Document A101-2017, Article 9.1.7.2. The COR is a written order prepared by the Owner and signed by the Owner and upon Owner's request, by the Architect, directing a change in the Work prior to agreement on adjustment, if any, in the Contract Sum or Contract Time, or both. The Owner may by Construction Change Directive, without invalidating the Contract, order changes in the Work within the general scope of the Contract consisting of additions, deletions or other revisions, the Contract Sum and Contract Time being adjusted accordingly.

§ 7.3.2 A Construction Change Directive shall be used in the absence of total agreement on the terms of a Change Order. The Owner's Change Order Request / Change Order Approval Form (COR/COA) per Exhibit as designated in Contract Document A101-2017, Article 9.1.7.2, including the General Contractor Breakdown Summary (GC-COR) Exhibit, and the Subcontractor Breakdown Summary (SC-COR) Exhibit, shall be used by the Contractor for all construction change directives.

§ 7.3.3 If the Construction Change Directive provides for an adjustment to the Contract Sum, the adjustment shall be based on one of the following methods:

- .1 Mutual acceptance of a lump sum properly itemized and supported by sufficient substantiating data to permit evaluation;
- .2 Unit prices stated in the Contract Documents or subsequently agreed upon;
- .3 Cost to be determined in a manner agreed upon by the parties and a mutually acceptable fixed or percentage fee; or
- **.4** As provided in Section 7.3.4.

§ 7.3.4 If the Contractor does not respond promptly or disagrees with the method for adjustment in the Contract Sum, the Owner shall determine the adjustment on the basis of reasonable expenditures and savings of those performing the Work attributable to the change, including, in case of an increase in the Contract Sum, an amount for overhead and profit as set forth in the Agreement, or if no such amount is set forth in the Agreement, a reasonable amount. In such case, and also under Section 7.3.3.3, the Contractor shall keep and present, in such form as the Owner may prescribe, an itemized accounting together with appropriate supporting data. Unless otherwise provided in the Contract Documents, costs for the purposes of this Section 7.3.4 shall be limited to the following:

- .1 Costs of labor, including applicable payroll taxes, fringe benefits required by agreement or custom, workers' compensation insurance, and other employee costs approved by the Owner;
- .2 Costs of materials, supplies, and equipment, including cost of transportation, whether incorporated or consumed;
- **.3** Rental costs of machinery and equipment, exclusive of hand tools, whether rented from the Contractor or others;
- .4 Costs of premiums for all bonds and insurance, permit fees, and sales, use, or similar taxes, directly related to the change; and
- .5 Costs of supervision and field office personnel directly attributable to the change.

§ 7.3.5 If the Contractor disagrees with the adjustment in the Contract Time, the Contractor may make a Claim in accordance with applicable provisions of Article 15.

§ 7.3.6 Upon receipt of a Construction Change Directive, the Contractor shall promptly proceed with the change in the Work involved and advise the Owner of the Contractor's agreement or disagreement with the method, if any, provided in the Construction Change Directive for determining the proposed adjustment in the Contract Sum or Contract Time.

§ 7.3.7 A Construction Change Directive signed by the Contractor indicates the Contractor's agreement therewith, including adjustment in Contract Sum and Contract Time or the method for determining them. Such agreement shall be effective immediately and shall be recorded as a Change Order.

§ 7.3.8 The amount of credit to be allowed by the Contractor to the Owner for a deletion or change that results in a net decrease in the Contract Sum shall be actual net cost as confirmed by the Owner. When both additions and credits covering related Work or substitutions are involved in a change, the allowance for overhead and profit shall be figured on the basis of net increase, if any, with respect to that change.

- § 7.3.9 Pending final determination of the total cost of a Construction Change Directive to the Owner, the Contractor may request payment for Work completed under the Construction Change Directive in Applications for Payment. The Owner will make an interim determination for purposes of monthly certification for payment for those costs and certify for payment the amount that the Owner determines to be reasonably justified. The Owner's interim determination of cost shall adjust the Contract Sum on the same basis as a Change Order, subject to the right of either party to disagree and assert a Claim in accordance with Article 15.
- § 7.3.10 When the Owner and Contractor agree with a determination made concerning the adjustments in the Contract Sum and Contract Time, or otherwise reach agreement upon the adjustments, such agreement shall be effective immediately and the Owner will prepare a Change Order. Change Orders may be issued for all or any part of a Construction Change Directive.

§ 7.4 Minor Changes in the Work

The Architect may order minor changes in the Work that are consistent with the intent of the Contract Documents and do not involve an adjustment in the Contract Sum or an extension of the Contract Time. The Architect's order for minor changes shall be in writing. If the Contractor believes that the proposed minor change in the Work will affect the Contract Sum or Contract Time, the Contractor shall notify the Architect and shall not proceed to implement the change in the Work. If the Contractor performs the Work set forth in the Architect's order for a minor change without prior notice to the Architect that such change will affect the Contract Sum or Contract Time, the Contractor waives any adjustment to the Contract Sum or extension of the Contract Time.

ARTICLE 8 TIME

§ 8.1 Definitions

- **§ 8.1.1** Unless otherwise provided, Contract Time is the period of time, including authorized adjustments, allotted in the Contract Documents for Substantial Completion of the Work.
- § 8.1.2 The date of commencement of the Work is the date established in the Agreement.
- § 8.1.3 The date of Substantial Completion is the date certified by the Owner in accordance with Section 9.8.
- § 8.1.4 The term "day" as used in the Contract Documents shall mean calendar day unless otherwise specifically defined.

§ 8.2 Progress and Completion

- § 8.2.1 Time limits stated in the Contract Documents are of the essence of the Contract. By executing the Agreement, the Contractor confirms that the Contract Time is a reasonable period for performing the Work.
- § 8.2.2 The Contractor shall not knowingly, except by agreement or instruction of the Owner in writing, commence the Work prior to the effective date of insurance required to be furnished by the Contractor and Owner.
- § 8.2.3 The Contractor shall proceed expeditiously with adequate forces and shall achieve Substantial Completion within the Contract Time.

§ 8.3 Delays and Extensions of Time

- § 8.3.1 If the Contractor is delayed at any time in the commencement or progress of the Work by (1) an act or neglect of the Owner or Architect, of an employee of either, or of a Separate Contractor; (2) by changes ordered in the Work; (3) by labor disputes, fire, unusual delay in deliveries, unavoidable casualties, adverse weather conditions documented in accordance with Section 15.1.6.2, or other causes beyond the Contractor's control; (4) by delay authorized by the Owner pending mediation and binding dispute resolution; or (5) by other causes that the Contractor asserts, and the Owner determines, justify delay, then the Contract Time shall be extended for such reasonable time as the Owner may determine.
- § 8.3.2 Claims relating to time shall be made in accordance with applicable provisions of Article 15.
- **§ 8.3.3** This Section 8.3 does not preclude recovery of damages for delay by either party under other provisions of the Contract Documents.

User Notes:

ARTICLE 9 PAYMENTS AND COMPLETION

§ 9.1 Contract Sum

- § 9.1.1 The Contract Sum is stated in the Agreement and, including authorized adjustments, is the total amount payable by the Owner to the Contractor for performance of the Work under the Contract Documents.
- § 9.1.2 If unit prices are stated in the Contract Documents or subsequently agreed upon, and if quantities originally contemplated are materially changed so that application of such unit prices to the actual quantities causes substantial inequity to the Owner or Contractor, the applicable unit prices shall be equitably adjusted.

§ 9.2 Schedule of Values

Where the Contract is based on a stipulated sum or Guaranteed Maximum Price, the Contractor shall submit a schedule of values to the Owner before the first Application for Payment, allocating the entire Contract Sum to the various portions of the Work. The schedule of values shall be prepared in the form, and supported by the data to substantiate its accuracy, required by the Owner. This schedule shall be used as a basis for reviewing the Contractor's Applications for Payment. Any changes to the schedule of values shall be submitted to the Owner and supported by such data to substantiate its accuracy as the Owner may require, and unless objected to by the Owner, shall be used as a basis for reviewing the Contractor's subsequent Applications for Payment.

§ 9.3 Applications for Payment

- § 9.3.1 At least ten days before the date established for each progress payment, the Contractor shall submit to the Owner an itemized Application for Payment using AIA Form G701 and AIA Form G702 and in accordance with Article 5 of A101-2017 prepared in accordance with the schedule of values, if required under Section 9.2, for completed portions of the Work. The application shall be notarized, if required, and supported by all data substantiating the Contractor's right to payment that the Owner require, such as copies of requisitions, and releases and waivers of liens from Subcontractors and suppliers, and shall reflect retainage if provided for in the Contract Documents.
- § 9.3.1.1 As provided in Section 7.3.9, such applications may include requests for payment on account of changes in the Work that have been properly authorized by Construction Change Directives.
- § 9.3.1.2 Applications for Payment shall not include requests for payment for portions of the Work for which the Contractor does not intend to pay a Subcontractor or supplier, unless such Work has been performed by others whom the Contractor intends to pay.
- § 9.3.2 Unless otherwise provided in the Contract Documents, payments shall be made on account of materials and equipment delivered and suitably stored at the site for subsequent incorporation in the Work. If approved in advance by the Owner, payment may similarly be made for materials and equipment suitably stored off the site at a location agreed upon in writing. Payment for materials and equipment stored on or off the site shall be conditioned upon compliance by the Contractor with procedures satisfactory to the Owner to establish the Owner's title to such materials and equipment or otherwise protect the Owner's interest, and shall include the costs of applicable insurance, storage, and transportation to the site, for such materials and equipment stored off the site.
- § 9.3.3 The Contractor warrants that title to all Work covered by an Application for Payment will pass to the Owner no later than the time of payment. The Contractor further warrants that upon submittal of an Application for Payment all Work for which Certificates for Payment have been previously issued and payments received from the Owner shall, to the best of the Contractor's knowledge, information, and belief, be free and clear of liens, claims, security interests, or encumbrances, in favor of the Contractor, Subcontractors, suppliers, or other persons or entities that provided labor, materials, and equipment relating to the Work.

§ 9.4 Certificates for Payment

§ 9.4.1 The Architect will, within seven days after receipt of the Contractor's Application for Payment, either (1) issue to the Owner a Certificate for Payment in the full amount of the Application for Payment, with a copy to the Contractor; or (2) issue to the Owner a Certificate for Payment for such amount as the Architect determines is properly due, and notify the Contractor and Owner of the Architect's reasons for withholding certification in part as provided in Section 9.5.1; or (3) withhold certification of the entire Application for Payment, and notify the Contractor and Owner of the Architect's reason for withholding certification in whole as provided in Section 9.5.1.

§ 9.4.2 The issuance of a Certificate for Payment will constitute a representation by the Owner, based on the Owner's evaluation of the Work and the data in the Application for Payment, that, to the best of the Owner's knowledge, information, and belief, the Work has progressed to the point indicated, the quality of the Work is in accordance with the Contract Documents, and that the Contractor is entitled to payment in the amount certified. The foregoing representations are subject to an evaluation of the Work for conformance with the Contract Documents upon Substantial Completion, to results of subsequent tests and inspections, to correction of minor deviations from the Contract Documents prior to completion, and to specific qualifications expressed by the Owner. However, the issuance of a Certificate for Payment will not be a representation that the Owner has (1) made exhaustive or continuous on-site inspections to check the quality or quantity of the Work; (2) reviewed construction means, methods, techniques, sequences, or procedures; (3) reviewed copies of requisitions received from Subcontractors and suppliers and other data requested by the Owner to substantiate the Contractor's right to payment; or (4) made examination to ascertain how or for what purpose the Contractor has used money previously paid on account of the Contract Sum.

§ 9.5 Decisions to Withhold Certification

§ 9.5.1 The Owner may withhold Payment in whole or in part, to the extent reasonably necessary to protect the Owner, if in the Owner's opinion the representations to the Owner required by Section 9.4.2 cannot be made. If the Owner is unable to certify payment in the amount of the Application, the Owner will notify the Contractor as provided in Section 9.4.1. If the Contractor and Owner cannot agree on a revised amount, the Owner will promptly release Payment for the amount for which the Owner is able to make such representations. The Owner may also withhold a Certificate for Payment or, because of subsequently discovered evidence, may nullify the whole or a part of a Payment previously issued, to such extent as may be necessary in the Owner's opinion to protect the Owner from loss for which the Contractor is responsible, including loss resulting from acts and omissions described in Section 3.3.2, because of

- .1 defective Work not remedied:
- .2 third party claims filed or reasonable evidence indicating probable filing of such claims, unless security acceptable to the Owner is provided by the Contractor;
- .3 failure of the Contractor to make payments properly to Subcontractors or suppliers for labor, materials or equipment;
- .4 reasonable evidence that the Work cannot be completed for the unpaid balance of the Contract Sum;
- .5 damage to the Owner or a Separate Contractor;
- reasonable evidence that the Work will not be completed within the Contract Time, and that the unpaid balance would not be adequate to cover actual or liquidated damages for the anticipated delay; or
- .7 repeated failure to carry out the Work in accordance with the Contract Documents.
- § 9.5.2 When either party disputes the Architect's decision regarding a Certificate for Payment under Section 9.5.1, in whole or in part, that party may submit a Claim in accordance with Article 15.
- § 9.5.3 When the reasons for withholding certification are removed, approval will be made for amounts previously withheld.
- § 9.5.4 If the Owner withholds payment under Section 9.5.1.3, the Owner may, at its sole option, issue joint checks to the Contractor and to any Subcontractor or supplier to whom the Contractor failed to make payment for Work properly performed or material or equipment suitably delivered. If the Owner makes payments by joint check, the Owner shall notify and the Contractor shall reflect such payment on its next Application for Payment.

§ 9.6 Progress Payments

- § 9.6.1 After the Owner has issued an Application for Payment, the Owner shall make payment in the manner and within the time provided in the Contract Documents.
- § 9.6.2 The Contractor shall pay each Subcontractor, no later than seven days after receipt of payment from the Owner, the amount to which the Subcontractor is entitled, reflecting percentages actually retained from payments to the Contractor on account of the Subcontractor's portion of the Work. The Contractor shall, by appropriate agreement with each Subcontractor, require each Subcontractor to make payments to Sub-subcontractors in a similar manner.

- § 9.6.3 The Owner will, on request, furnish to a Subcontractor, if practicable, information regarding percentages of completion or amounts applied for by the Contractor and action taken thereon by the Owner on account of portions of the Work done by such Subcontractor.
- § 9.6.4 The Owner has the right to request written evidence from the Contractor that the Contractor has properly paid Subcontractors and suppliers amounts paid by the Owner to the Contractor for subcontracted Work. If the Contractor fails to furnish such evidence within seven days, the Owner shall have the right to contact Subcontractors and suppliers to ascertain whether they have been properly paid. The Owner shall have an obligation to pay, or to see to the payment of money to, a Subcontractor or supplier, except as may otherwise be required by law.
- § 9.6.5 The Contractor's payments to suppliers shall be treated in a manner similar to that provided in Sections 9.6.2, 9.6.3 and 9.6.4.
- § 9.6.6 A Certificate for Payment, a progress payment, or partial or entire use or occupancy of the Project by the Owner shall not constitute acceptance of Work not in accordance with the Contract Documents.
- § 9.6.7 Unless the Contractor provides the Owner with a payment bond in the full penal sum of the Contract Sum, payments received by the Contractor for Work properly performed by Subcontractors or provided by suppliers shall be held by the Contractor for those Subcontractors or suppliers who performed Work or furnished materials, or both, under contract with the Contractor for which payment was made by the Owner. Nothing contained herein shall require money to be placed in a separate account and not commingled with money of the Contractor, create any fiduciary liability or tort liability on the part of the Contractor for breach of trust, or entitle any person or entity to an award of punitive damages against the Contractor for breach of the requirements of this provision.
- § 9.6.8 Provided the Owner has fulfilled its payment obligations under the Contract Documents, the Contractor shall defend and indemnify the Owner from all loss, liability, damage or expense, including reasonable attorney's fees and litigation expenses, arising out of any lien claim or other claim for payment by any Subcontractor or supplier of any tier. Upon receipt of notice of a lien claim or other claim for payment, the Owner shall notify the Contractor. If approved by the applicable court, when required, the Contractor may substitute a surety bond for the property against which the lien or other claim for payment has been asserted.

§ 9.7 Failure of Payment

If the Owner does not issue a Certificate for Payment, through no fault of the Contractor, within seven days after receipt of the Contractor's Application for Payment, or if the Owner does not pay the Contractor within seven days after the date established in the Contract Documents, the amount certified by the Owner or awarded by binding dispute resolution, then the Contractor may, upon seven additional days' notice to the Owner, stop the Work until payment of the amount owing has been received. The Contract Time shall be extended appropriately and the Contract Sum shall be increased by the amount of the Contractor's reasonable costs of shutdown, delay and start-up, plus interest as provided for in the Contract Documents.

§ 9.8 Substantial Completion

- § 9.8.1 Substantial Completion is the stage in the progress of the Work when the Work or designated portion thereof is sufficiently complete in accordance with the Contract Documents so that the Owner can occupy or utilize the Work for its intended use.
- § 9.8.2 When the Contractor considers that the Work, or a portion thereof which the Owner agrees to accept separately, is substantially complete, the Contractor shall prepare and submit to the Owner a comprehensive list of items to be completed or corrected prior to final payment. Failure to include an item on such list does not alter the responsibility of the Contractor to complete all Work in accordance with the Contract Documents.
- § 9.8.3 Upon receipt of the Contractor's list, the Owner will make an inspection to determine whether the Work or designated portion thereof is substantially complete. If the Owner's inspection discloses any item, whether or not included on the Contractor's list, which is not sufficiently complete in accordance with the Contract Documents so that the Owner can occupy or utilize the Work or designated portion thereof for its intended use, the Contractor shall, before issuance of the Certificate of Substantial Completion, complete or correct such item upon notification by the Owner. In such case, the Contractor shall then submit a request for another inspection by the Owner to determine Substantial Completion.

- § 9.8.4 When the Work or designated portion thereof is substantially complete, the Owner will prepare a Certificate of Substantial Completion that shall establish the date of Substantial Completion; establish responsibilities of the Owner and Contractor for security, maintenance, heat, utilities, damage to the Work and insurance; and fix the time within which the Contractor shall finish all items on the list accompanying the Certificate. Warranties required by the Contract Documents shall commence on the date of Substantial Completion of the Work or designated portion thereof unless otherwise provided in the Certificate of Substantial Completion.
- § 9.8.5 The Certificate of Substantial Completion shall be submitted to the Contractor for written acceptance of responsibilities assigned in the Certificate. Upon such acceptance, and consent of surety if any, the Owner shall make payment of retainage applying to the Work or designated portion thereof. Such payment shall be adjusted for Work that is incomplete or not in accordance with the requirements of the Contract Documents.

§ 9.9 Partial Occupancy or Use

- § 9.9.1 The Owner may occupy or use any completed or partially completed portion of the Work at any stage when such portion is designated by separate agreement with the Contractor, provided such occupancy or use is consented to by the insurer and authorized by public authorities having jurisdiction over the Project. Such partial occupancy or use may commence whether or not the portion is substantially complete, provided the Owner and Contractor have accepted in writing the responsibilities assigned to each of them for payments, retainage, if any, security, maintenance, heat, utilities, damage to the Work and insurance, and have agreed in writing concerning the period for correction of the Work and commencement of warranties required by the Contract Documents. When the Contractor considers a portion substantially complete, the Contractor shall prepare and submit a list to the Owner as provided under Section 9.8.2. Consent of the Contractor to partial occupancy or use shall not be unreasonably withheld. The stage of the progress of the Work shall be determined by written agreement between the Owner and Contractor.
- § 9.9.2 Immediately prior to such partial occupancy or use, the Owner and Contractor shall jointly inspect the area to be occupied or portion of the Work to be used in order to determine and record the condition of the Work.
- § 9.9.3 Unless otherwise agreed upon, partial occupancy or use of a portion or portions of the Work shall not constitute acceptance of Work not complying with the requirements of the Contract Documents.

§ 9.10 Final Completion and Final Payment

- § 9.10.1 Upon receipt of the Contractor's notice that the Work is ready for final inspection and acceptance and upon receipt of a final Application for Payment, the Owner will promptly make such inspection. When the Owner finds the Work acceptable under the Contract Documents and the Contract fully performed, the Owner will promptly notify the Contractor that to the best of the Owner's knowledge, information and belief, and on the basis of the Owner's on-site visits and inspections, the Work has been completed in accordance with the Contract Documents and that the entire balance found to be due the Contractor and noted in the final Application for Payment is due and payable. The Owner's acceptance will constitute a further representation that conditions listed in Section 9.10.2 as precedent to the Contractor's being entitled to final payment have been fulfilled.
- § 9.10.2 Neither final payment nor any remaining retained percentage shall become due until the Contractor submits to the Owner (1) an affidavit that payrolls, bills for materials and equipment, and other indebtedness connected with the Work for which the Owner or the Owner's property might be responsible or encumbered (less amounts withheld by Owner) have been paid or otherwise satisfied, (2) a certificate evidencing that insurance required by the Contract Documents to remain in force after final payment is currently in effect, (3) a written statement that the Contractor knows of no reason that the insurance will not be renewable to cover the period required by the Contract Documents, (4) consent of surety, if any, to final payment, (5) documentation of any special warranties, such as manufacturers' warranties or specific Subcontractor warranties, and (6) if required by the Owner, other data establishing payment or satisfaction of obligations, such as receipts and releases and waivers of liens, claims, security interests, or encumbrances arising out of the Contract, to the extent and in such form as may be designated by the Owner. If a Subcontractor refuses to furnish a release or waiver required by the Owner, the Contractor may furnish a bond satisfactory to the Owner to indemnify the Owner against such lien, claim, security interest, or encumbrance. If a lien, claim, security interest, or encumbrance remains unsatisfied after payments are made, the Contractor shall refund to the Owner all money that the Owner may be compelled to pay in discharging the lien, claim, security interest, or encumbrance, including all costs and reasonable attorneys' fees.
- § 9.10.3 If, after Substantial Completion of the Work, final completion thereof is materially delayed through no fault of the Contractor or by issuance of Change Orders affecting final completion, the Owner shall, upon application by

the Contractor and certification by the Owner, and without terminating the Contract, make payment of the balance due for that portion of the Work fully completed, corrected, and accepted. If the remaining balance for Work not fully completed or corrected is less than retainage stipulated in the Contract Documents, and if bonds have been furnished, the written consent of the surety to payment of the balance due for that portion of the Work fully completed and accepted shall be submitted by the Contractor to the Owner prior to certification of such payment. Such payment shall be made under terms and conditions governing final payment, except that it shall not constitute a waiver of Claims.

- § 9.10.4 The making of final payment shall constitute a waiver of Claims by the Owner except those arising from
 - .1 liens, Claims, security interests, or encumbrances arising out of the Contract and unsettled;
 - .2 failure of the Work to comply with the requirements of the Contract Documents;
 - .3 terms of special warranties required by the Contract Documents; or
 - .4 audits performed by the Owner, if permitted by the Contract Documents, after final payment.
- § 9.10.5 Acceptance of final payment by the Contractor, a Subcontractor, or a supplier, shall constitute a waiver of claims by that payee except those previously made in writing and identified by that payee as unsettled at the time of final Application for Payment.

ARTICLE 10 PROTECTION OF PERSONS AND PROPERTY

§ 10.1 Safety Precautions and Programs

The Contractor shall be responsible for initiating, maintaining, and supervising all safety precautions and programs in connection with the performance of the Contract.

§ 10.2 Safety of Persons and Property

- § 10.2.1 The Contractor shall take reasonable precautions for safety of, and shall provide reasonable protection to prevent damage, injury, or loss to
 - .1 employees on the Work and other persons who may be affected thereby;
 - .2 the Work and materials and equipment to be incorporated therein, whether in storage on or off the site, under care, custody, or control of the Contractor, a Subcontractor, or a Sub-subcontractor; and
 - .3 other property at the site or adjacent thereto, such as trees, shrubs, lawns, walks, pavements, roadways, structures, and utilities not designated for removal, relocation, or replacement in the course of construction.
- § 10.2.2 The Contractor shall comply with, and give notices required by applicable laws, statutes, ordinances, codes, rules and regulations, and lawful orders of public authorities, bearing on safety of persons or property or their protection from damage, injury, or loss.
- § 10.2.3 The Contractor shall implement, erect, and maintain, as required by existing conditions and performance of the Contract, reasonable safeguards for safety and protection, including posting danger signs and other warnings against hazards; promulgating safety regulations; and notifying the owners and users of adjacent sites and utilities of the safeguards.
- § 10.2.4 When use or storage of explosives or other hazardous materials or equipment, or unusual methods are necessary for execution of the Work, the Contractor shall exercise utmost care and carry on such activities under supervision of properly qualified personnel.
- § 10.2.5 The Contractor shall promptly remedy damage and loss (other than damage or loss insured under property insurance required by the Contract Documents) to property referred to in Sections 10.2.1.2 and 10.2.1.3 caused in whole or in part by the Contractor, a Subcontractor, a Sub-subcontractor, or anyone directly or indirectly employed by any of them, or by anyone for whose acts they may be liable and for which the Contractor is responsible under Sections 10.2.1.2 and 10.2.1.3. The Contractor may make a Claim for the cost to remedy the damage or loss to the extent such damage or loss is attributable to acts or omissions of the Owner or Architect or anyone directly or indirectly employed by either of them, or by anyone for whose acts either of them may be liable, and not attributable to the fault or negligence of the Contractor. The foregoing obligations of the Contractor are in addition to the Contractor's obligations under Section 3.18.

- § 10.2.6 The Contractor shall designate a responsible member of the Contractor's organization at the site whose duty shall be the prevention of accidents. This person shall be the Contractor's superintendent unless otherwise designated by the Contractor in writing to the Owner.
- § 10.2.7 The Contractor shall not permit any part of the construction or site to be loaded so as to cause damage or create an unsafe condition.

§ 10.2.8 Injury or Damage to Person or Property

If either party suffers injury or damage to person or property because of an act or omission of the other party, or of others for whose acts such party is legally responsible, notice of the injury or damage, whether or not insured, shall be given to the other party within a reasonable time not exceeding 21 days after discovery. The notice shall provide sufficient detail to enable the other party to investigate the matter.

§ 10.3 Hazardous Materials and Substances

- § 10.3.1 The Contractor is responsible for compliance with any requirements included in the Contract Documents regarding hazardous materials or substances. If the Contractor encounters a hazardous material or substance not addressed in the Contract Documents and if reasonable precautions will be inadequate to prevent foreseeable bodily injury or death to persons resulting from a material or substance, including but not limited to asbestos or polychlorinated biphenyl (PCB), encountered on the site by the Contractor, the Contractor shall, upon recognizing the condition, immediately stop Work in the affected area and notify the Owner of the condition.
- § 10.3.2 Upon receipt of the Contractor's notice, the Owner shall obtain the services of a licensed laboratory to verify the presence or absence of the material or substance reported by the Contractor and, in the event such material or substance is found to be present, to cause it to be rendered harmless. Unless otherwise required by the Contract Documents, the Owner shall furnish in writing to the Contractor the names and qualifications of persons or entities who are to perform tests verifying the presence or absence of the material or substance or who are to perform the task of removal or safe containment of the material or substance. The Contractor will promptly reply to the Owner in writing stating whether or not there is reasonable objection to the persons or entities proposed by the Owner. If the Contractor has an objection to a person or entity proposed by the Owner, the Owner shall propose another to whom the Contractor has no reasonable objection. When the material or substance has been rendered harmless, Work in the affected area shall resume upon written agreement of the Owner and Contractor. By Change Order, the Contract Time shall be extended appropriately and the Contract Sum shall be increased by the amount of the Contractor's reasonable additional costs of shutdown, delay, and start-up.
- § 10.3.3 To the fullest extent permitted by law, the Owner shall indemnify and hold harmless the Contractor, Subcontractors, Architect, Architect's consultants, and agents and employees of any of them from and against claims, damages, losses, and expenses, including but not limited to attorneys' fees, arising out of or resulting from performance of the Work in the affected area if in fact the material or substance presents the risk of bodily injury or death as described in Section 10.3.1 and has not been rendered harmless, provided that such claim, damage, loss, or expense is attributable to bodily injury, sickness, disease or death, or to injury to or destruction of tangible property (other than the Work itself), except to the extent that such damage, loss, or expense is due to the fault or negligence of the party seeking indemnity.
- § 10.3.4 The Owner shall not be responsible under this Section 10.3 for hazardous materials or substances the Contractor brings to the site unless such materials or substances are required by the Contract Documents. The Owner shall be responsible for hazardous materials or substances required by the Contract Documents, except to the extent of the Contractor's fault or negligence in the use and handling of such materials or substances.
- § 10.3.5 The Contractor shall reimburse the Owner for the cost and expense the Owner incurs (1) for remediation of hazardous materials or substances the Contractor brings to the site and negligently handles, or (2) where the Contractor fails to perform its obligations under Section 10.3.1, except to the extent that the cost and expense are due to the Owner's fault or negligence.
- § 10.3.6 If, without negligence on the part of the Contractor, the Contractor is held liable by a government agency for the cost of remediation of a hazardous material or substance solely by reason of performing Work as required by the Contract Documents, the Owner shall reimburse the Contractor for all cost and expense thereby incurred.

§ 10.4 Emergencies

In an emergency affecting safety of persons or property, the Contractor shall act, at the Contractor's discretion, to prevent threatened damage, injury, or loss. Additional compensation or extension of time claimed by the Contractor on account of an emergency shall be determined as provided in Article 15 and Article 7.

ARTICLE 11 INSURANCE AND BONDS

§ 11.1 Contractor's Insurance and Bonds

- § 11.1.1 The Contractor shall purchase and maintain insurance of the types and limits of liability, containing the endorsements, and subject to the terms and conditions, as described in the Agreement or elsewhere in the Contract Documents. The Contractor shall purchase and maintain the required insurance from an insurance company or insurance companies lawfully authorized to issue insurance in the jurisdiction where the Project is located. The Owner, Architect, and Architect's consultants shall be named as additional insureds under the Contractor's commercial general liability policy or as otherwise described in the Contract Documents.
- § 11.1.2 The Contractor shall provide surety bonds of the types, for such penal sums, and subject to such terms and conditions as required by the Contract Documents. The Contractor shall purchase and maintain the required bonds from a company or companies lawfully authorized to issue surety bonds in the jurisdiction where the Project is located.
- § 11.1.3 Upon the request of any person or entity appearing to be a potential beneficiary of bonds covering payment of obligations arising under the Contract, the Contractor shall promptly furnish a copy of the bonds or shall authorize a copy to be furnished.
- § 11.1.4 Notice of Cancellation or Expiration of Contractor's Required Insurance. Within three (3) business days of the date the Contractor becomes aware of an impending or actual cancellation or expiration of any insurance required by the Contract Documents, the Contractor shall provide notice to the Owner of such impending or actual cancellation or expiration. Upon receipt of notice from the Contractor, the Owner shall, unless the lapse in coverage arises from an act or omission of the Owner, have the right to stop the Work until the lapse in coverage has been cured by the procurement of replacement coverage by the Contractor. The furnishing of notice by the Contractor shall not relieve the Contractor of any contractual obligation to provide any required coverage.

§ 11.2 Owner's Insurance

- § 11.2.1 The Owner shall purchase and maintain insurance of the types and limits of liability, containing the endorsements, and subject to the terms and conditions, as described in the Agreement or elsewhere in the Contract Documents. The Owner shall purchase and maintain the required insurance from an insurance company or insurance companies lawfully authorized to issue insurance in the jurisdiction where the Project is located.
- § 11.2.2 Failure to Purchase Required Property Insurance. If the Owner fails to purchase and maintain the required property insurance, with all of the coverages and in the amounts described in the Agreement or elsewhere in the Contract Documents, the Owner shall inform the Contractor in writing prior to commencement of the Work, Upon receipt of notice from the Owner, the Contractor may delay commencement of the Work and may obtain insurance that will protect the interests of the Contractor, Subcontractors, and Sub-Subcontractors in the Work. When the failure to provide coverage has been cured or resolved, the Contract Sum and Contract Time shall be equitably adjusted. In the event the Owner fails to procure coverage, the Owner waives all rights against the Contractor, Subcontractors, and Sub-subcontractors to the extent the loss to the Owner would have been covered by the insurance to have been procured by the Owner. The cost of the insurance shall be charged to the Owner by a Change Order. If the Owner does not provide written notice, and the Contractor is damaged by the failure or neglect of the Owner to purchase or maintain the required insurance, the Owner shall reimburse the Contractor for all reasonable costs and damages attributable thereto.
- § 11.2.3 Notice of Cancellation or Expiration of Owner's Required Property Insurance. Within three (3) business days of the date the Owner becomes aware of an impending or actual cancellation or expiration of any property insurance required by the Contract Documents, the Owner shall provide notice to the Contractor of such impending or actual cancellation or expiration. Unless the lapse in coverage arises from an act or omission of the Contractor: (1) the Contractor, upon receipt of notice from the Owner, shall have the right to stop the Work until the lapse in coverage has been cured by the procurement of replacement coverage by either the Owner or the Contractor; (2) the Contract Time and Contract Sum shall be equitably adjusted; and (3) the Owner waives all rights against the Contractor, Subcontractors, and Sub-subcontractors to the extent any loss to the Owner would have been covered by the insurance had it not expired or been cancelled. If the Contractor purchases replacement coverage, the cost of the

insurance shall be charged to the Owner by an appropriate Change Order. The furnishing of notice by the Owner shall not relieve the Owner of any contractual obligation to provide required insurance.

§ 11.3 Waivers of Subrogation

§ 11.3.1 The Owner and Contractor waive all rights against (1) each other and any of their subcontractors, subsubcontractors, agents, and employees, each of the other; (2) the Architect and Architect's consultants; and (3) Separate Contractors, if any, and any of their subcontractors, sub-subcontractors, agents, and employees, for damages caused by fire, or other causes of loss, to the extent those losses are covered by property insurance required by the Agreement or other property insurance applicable to the Project, except such rights as they have to proceeds of such insurance. The Owner or Contractor, as appropriate, shall require similar written waivers in favor of the individuals and entities identified above from the Architect, Architect's consultants, Separate Contractors, subcontractors, and sub-subcontractors. The policies of insurance purchased and maintained by each person or entity agreeing to waive claims pursuant to this section 11.3.1 shall not prohibit this waiver of subrogation. This waiver of subrogation shall be effective as to a person or entity (1) even though that person or entity would otherwise have a duty of indemnification, contractual or otherwise, (2) even though that person or entity did not pay the insurance premium directly or indirectly, or (3) whether or not the person or entity had an insurable interest in the damaged property.

§ 11.3.2 If during the Project construction period the Owner insures properties, real or personal or both, at or adjacent to the site by property insurance under policies separate from those insuring the Project, or if after final payment property insurance is to be provided on the completed Project through a policy or policies other than those insuring the Project during the construction period, to the extent permissible by such policies, the Owner waives all rights in accordance with the terms of Section 11.3.1 for damages caused by fire or other causes of loss covered by this separate property insurance.

§ 11.4 Loss of Use, Business Interruption, and Delay in Completion Insurance

The Owner, at the Owner's option, may purchase and maintain insurance that will protect the Owner against loss of use of the Owner's property, or the inability to conduct normal operations, due to fire or other causes of loss. The Owner waives all rights of action against the Contractor and Architect for loss of use of the Owner's property, due to fire or other hazards however caused.

§11.5 Adjustment and Settlement of Insured Loss

§ 11.5.1 A loss insured under the property insurance required by the Agreement shall be adjusted by the Owner as fiduciary and made payable to the Owner as fiduciary for the insureds, as their interests may appear, subject to requirements of any applicable mortgagee clause and of Section 11.5.2. The Owner shall pay the Architect and Contractor their just shares of insurance proceeds received by the Owner, and by appropriate agreements the Architect and Contractor shall make payments to their consultants and Subcontractors in similar manner.

§ 11.5.2 Prior to settlement of an insured loss, the Owner shall notify the Contractor of the terms of the proposed settlement as well as the proposed allocation of the insurance proceeds. The Contractor shall have 14 days from receipt of notice to object to the proposed settlement or allocation of the proceeds. If the Contractor does not object, the Owner shall settle the loss and the Contractor shall be bound by the settlement and allocation. Upon receipt, the Owner shall deposit the insurance proceeds in a separate account and make the appropriate distributions. Thereafter, if no other agreement is made or the Owner does not terminate the Contract for convenience, the Owner and Contractor shall execute a Change Order for reconstruction of the damaged or destroyed Work in the amount allocated for that purpose. If the Contractor timely objects to either the terms of the proposed settlement or the allocation of the proceeds, the Owner may proceed to settle the insured loss, and any dispute between the Owner and Contractor arising out of the settlement or allocation of the proceeds shall be resolved pursuant to Article 15. Pending resolution of any dispute, the Owner may issue a Construction Change Directive for the reconstruction of the damaged or destroyed Work.

ARTICLE 12 UNCOVERING AND CORRECTION OF WORK

§ 12.1 Uncovering of Work

§ 12.1.1 If a portion of the Work is covered contrary to the Owner's request or to requirements specifically expressed in the Contract Documents, it must, if requested in writing by the Owner, be uncovered for the Owner's examination and be replaced at the Contractor's expense without change in the Contract Time.

§ 12.1.2 If a portion of the Work has been covered that the Owner has not specifically requested to examine prior to its being covered, the Owner may request to see such Work and it shall be uncovered by the Contractor. If such Work is in accordance with the Contract Documents, the Contractor shall be entitled to an equitable adjustment to the Contract Sum and Contract Time as may be appropriate. If such Work is not in accordance with the Contract Documents, the costs of uncovering the Work, and the cost of correction, shall be at the Contractor's expense.

§ 12.2 Correction of Work

§ 12.2.1 Before Substantial Completion

The Contractor shall promptly correct Work rejected by the Owner or failing to conform to the requirements of the Contract Documents, discovered before Substantial Completion and whether or not fabricated, installed or completed. Costs of correcting such rejected Work, including additional testing and inspections, the cost of uncovering and replacement, and compensation for the Owner's services and expenses made necessary thereby, shall be at the Contractor's expense.

§ 12.2.2 After Substantial Completion

- § 12.2.2.1 In addition to the Contractor's obligations under Section 3.5, if, within one year after the date of Substantial Completion of the Work or designated portion thereof or after the date for commencement of warranties established under Section 9.9.1, or by terms of any applicable special warranty required by the Contract Documents, any of the Work is found to be not in accordance with the requirements of the Contract Documents, the Contractor shall correct it promptly after receipt of notice from the Owner to do so, unless the Owner has previously given the Contractor a written acceptance of such condition. The Owner shall give such notice promptly after discovery of the condition. During the one-year period for correction of Work, if the Owner fails to notify the Contractor and give the Contractor an opportunity to make the correction, the Owner waives the rights to require correction by the Contractor and to make a claim for breach of warranty. If the Contractor fails to correct nonconforming Work within a reasonable time during that period after receipt of notice from the Owner, the Owner may correct it in accordance with Section 2.5.
- § 12.2.2.2 The one-year period for correction of Work shall be extended with respect to portions of Work first performed after Substantial Completion by the period of time between Substantial Completion and the actual completion of that portion of the Work.
- § 12.2.2.3 The one-year period for correction of Work shall not be extended by corrective Work performed by the Contractor pursuant to this Section 12.2.
- § 12.2.3 The Contractor shall remove from the site portions of the Work that are not in accordance with the requirements of the Contract Documents and are neither corrected by the Contractor nor accepted by the Owner.
- § 12.2.4 The Contractor shall bear the cost of correcting destroyed or damaged construction of the Owner or Separate Contractors, whether completed or partially completed, caused by the Contractor's correction or removal of Work that is not in accordance with the requirements of the Contract Documents.
- § 12.2.5 Nothing contained in this Section 12.2 shall be construed to establish a period of limitation with respect to other obligations the Contractor has under the Contract Documents. Establishment of the one-year period for correction of Work as described in Section 12.2.2 relates only to the specific obligation of the Contractor to correct the Work, and has no relationship to the time within which the obligation to comply with the Contract Documents may be sought to be enforced, nor to the time within which proceedings may be commenced to establish the Contractor's liability with respect to the Contractor's obligations other than specifically to correct the Work.

§ 12.3 Acceptance of Nonconforming Work

If the Owner prefers to accept Work that is not in accordance with the requirements of the Contract Documents, the Owner may do so instead of requiring its removal and correction, in which case the Contract Sum will be reduced as appropriate and equitable. Such adjustment shall be effected whether or not final payment has been made.

ARTICLE 13 MISCELLANEOUS PROVISIONS § 13.1 Governing Law

The Contract shall be governed by the law of the place where the Project is located, excluding that jurisdiction's choice of law rules. If the parties have selected arbitration as the method of binding dispute resolution, the Federal Arbitration Act shall govern Section 15.4.

§ 13.2 Successors and Assigns

§ 13.2.1 The Owner and Contractor respectively bind themselves, their partners, successors, assigns, and legal representatives to covenants, agreements, and obligations contained in the Contract Documents. Except as provided in Section 13.2.2, neither party to the Contract shall assign the Contract as a whole without written consent of the other. If either party attempts to make an assignment without such consent, that party shall nevertheless remain legally responsible for all obligations under the Contract.

§ 13.2.2 The Owner may, without consent of the Contractor, assign the Contract to a lender providing construction financing for the Project, if the lender assumes the Owner's rights and obligations under the Contract Documents. The Contractor shall execute all consents reasonably required to facilitate the assignment.

§ 13.3 Rights and Remedies

§ 13.3.1 Duties and obligations imposed by the Contract Documents and rights and remedies available thereunder shall be in addition to and not a limitation of duties, obligations, rights, and remedies otherwise imposed or available by law.

§ 13.3.2 No action or failure to act by the Owner, or Contractor shall constitute a waiver of a right or duty afforded them under the Contract, nor shall such action or failure to act constitute approval of or acquiescence in a breach thereunder, except as may be specifically agreed upon in writing.

§ 13.4 Tests and Inspections

§ 13.4.1 Tests, inspections, and approvals of portions of the Work shall be made as required by the Contract Documents and by applicable laws, statutes, ordinances, codes, rules, and regulations or lawful orders of public authorities. Unless otherwise provided, the Contractor shall make arrangements for such tests, inspections, and approvals with an independent testing laboratory or entity acceptable to the Owner, or with the appropriate public authority, and shall bear all related costs of tests, inspections, and approvals. The Contractor shall give the Owner timely notice of when and where tests and inspections are to be made so that the Owner may be present for such procedures. The Owner shall bear costs of tests, inspections, or approvals that do not become requirements until after bids are received or negotiations concluded. The Owner shall directly arrange and pay for tests, inspections, or approvals where building codes or applicable laws or regulations so require.

§ 13.4.2 If the Owner, or public authorities having jurisdiction determine that portions of the Work require additional testing, inspection, or approval not included under Section 13.4.1, the Owner will instruct the Contractor to make arrangements for such additional testing, inspection, or approval, by an entity acceptable to the Owner, and the Contractor shall give timely notice to the Owner of when and where tests and inspections are to be made so that the Owner may be present for such procedures. Such costs, except as provided in Section 13.4.3, shall be at the Owner's expense.

§ 13.4.3 If procedures for testing, inspection, or approval under Sections 13.4.1 and 13.4.2 reveal failure of the portions of the Work to comply with requirements established by the Contract Documents, all costs made necessary by such failure, including those of repeated procedures and compensation for the Owner's services and expenses, shall be at the Contractor's expense.

§ 13.4.4 Required certificates of testing, inspection, or approval shall, unless otherwise required by the Contract Documents, be secured by the Contractor and promptly delivered to the Owner.

§ 13.4.5 If the Owner is to observe tests, inspections, or approvals required by the Contract Documents, the Owner will do so promptly and, where practicable, at the normal place of testing.

§ 13.4.6 Tests or inspections conducted pursuant to the Contract Documents shall be made promptly to avoid unreasonable delay in the Work.

§ 13.5 Interest

Payments due and unpaid under the Contract Documents shall bear interest from the date payment is due at the rate the parties agree upon in writing or, in the absence thereof, at the legal rate prevailing from time to time at the place where the Project is located.

ARTICLE 14 TERMINATION OR SUSPENSION OF THE CONTRACT

§ 14.1 Termination by the Contractor

- § 14.1.1 The Contractor may terminate the Contract if the Work is stopped for a period of 30 consecutive days through no act or fault of the Contractor, a Sub-contractor, a Sub-subcontractor, their agents or employees, or any other persons or entities performing portions of the Work, for any of the following reasons:
 - Issuance of an order of a court or other public authority having jurisdiction that requires all Work to be stopped;
 - .2 An act of government, such as a declaration of national emergency, that requires all Work to be stopped;
 - .3 Because the Owner has not issued a Certificate for Payment and has not notified the Contractor of the reason for withholding certification as provided in Section 9.4.1, or because the Owner has not made payment on a Certificate for Payment within the time stated in the Contract Documents; or
 - .4 The Owner has failed to furnish to the Contractor reasonable evidence as required by Section 2.2.
- § 14.1.2 The Contractor may terminate the Contract if, through no act or fault of the Contractor, a Subcontractor, a Sub-subcontractor, their agents or employees, or any other persons or entities performing portions of the Work under direct or indirect contract with the Contractor, repeated suspensions, delays, or interruptions of the entire Work by the Owner as described in Section 14.3, constitute in the aggregate more than 100 percent of the total number of days scheduled for completion, or 120 days in any 365-day period, whichever is less.
- § 14.1.3 If one of the reasons described in Section 14.1.1 or 14.1.2 exists, the Contractor may, upon seven days' notice to the Owner, terminate the Contract and recover from the Owner payment for Work executed, as well as reasonable overhead and profit on Work not executed, and costs incurred by reason of such termination.
- § 14.1.4 If the Work is stopped for a period of 60 consecutive days through no act or fault of the Contractor, a Subcontractor, a Sub-subcontractor, or their agents or employees or any other persons or entities performing portions of the Work because the Owner has repeatedly failed to fulfill the Owner's obligations under the Contract Documents with respect to matters important to the progress of the Work, the Contractor may, upon seven additional days' notice to the Owner, terminate the Contract and recover from the Owner as provided in Section 14.1.3.

§ 14.2 Termination by the Owner for Cause

- § 14.2.1 The Owner may terminate the Contract if the Contractor
 - repeatedly refuses or fails to supply enough properly skilled workers or proper materials;
 - .2 fails to make payment to Subcontractors or suppliers in accordance with the respective agreements between the Contractor and the Subcontractors or suppliers;
 - repeatedly disregards applicable laws, statutes, ordinances, codes, rules and regulations, or lawful .3 orders of a public authority; or
 - .4 otherwise is guilty of substantial breach of a provision of the Contract Documents.
- § 14.2.2 When any of the reasons described in Section 14.2.1 exist, the Owner may, without prejudice to any other rights or remedies of the Owner and after giving the Contractor and the Contractor's surety, if any, seven days' notice, terminate employment of the Contractor and may, subject to any prior rights of the surety:
 - Exclude the Contractor from the site and take possession of all materials, equipment, tools, and .1 construction equipment and machinery thereon owned by the Contractor;
 - .2 Accept assignment of subcontracts pursuant to Section 5.4; and
 - .3 Finish the Work by whatever reasonable method the Owner may deem expedient. Upon written request of the Contractor, the Owner shall furnish to the Contractor a detailed accounting of the costs incurred by the Owner in finishing the Work.
- § 14.2.3 When the Owner terminates the Contract for one of the reasons stated in Section 14.2.1, the Contractor shall not be entitled to receive further payment until the Work is finished.
- § 14.2.4 If the unpaid balance of the Contract Sum exceeds costs of finishing the Work, including compensation for the Architect's services and expenses made necessary thereby, and other damages incurred by the Owner and not expressly waived, such excess shall be paid to the Contractor. If such costs and damages exceed the unpaid balance, the Contractor shall pay the difference to the Owner. The amount to be paid to the Contractor or Owner, as the case may be, upon application, and this obligation for payment shall survive termination of the Contract.

§ 14.3 Suspension by the Owner for Convenience

- § 14.3.1 The Owner may, without cause, order the Contractor in writing to suspend, delay or interrupt the Work, in whole or in part for such period of time as the Owner may determine.
- § 14.3.2 The Contract Sum and Contract Time shall be adjusted for increases in the cost and time caused by suspension, delay, or interruption under Section 14.3.1. Adjustment of the Contract Sum shall include profit. No adjustment shall be made to the extent
 - .1 that performance is, was, or would have been, so suspended, delayed, or interrupted, by another cause for which the Contractor is responsible; or
 - .2 that an equitable adjustment is made or denied under another provision of the Contract.

§ 14.4 Termination by the Owner for Convenience

- § 14.4.1 The Owner may, at any time, terminate the Contract for the Owner's convenience and without cause.
- § 14.4.2 Upon receipt of notice from the Owner of such termination for the Owner's convenience, the Contractor shall
 - .1 cease operations as directed by the Owner in the notice;
 - .2 take actions necessary, or that the Owner may direct, for the protection and preservation of the Work; and
 - **.3** except for Work directed to be performed prior to the effective date of termination stated in the notice, terminate all existing subcontracts and purchase orders and enter into no further subcontracts and purchase orders.
- § 14.4.3 In case of such termination for the Owner's convenience, the Owner shall pay the Contractor for Work properly executed; costs incurred by reason of the termination, including costs attributable to termination of Subcontracts; and the termination fee, if any, set forth in the Agreement.

ARTICLE 15 CLAIMS AND DISPUTES

§ 15.1 Claims

§ 15.1.1 Definition

A Claim is a demand or assertion by one of the parties seeking, as a matter of right, payment of money, a change in the Contract Time, or other relief with respect to the terms of the Contract. The term "Claim" also includes other disputes and matters in question between the Owner and Contractor arising out of or relating to the Contract. The responsibility to substantiate Claims shall rest with the party making the Claim.

§ 15.1.2 Time Limits on Claims

The Owner and Contractor shall commence all Claims and causes of action against the other and arising out of or related to the Contract, whether in contract, tort, breach of warranty or otherwise, in accordance with the requirements of the binding dispute resolution method selected in the Agreement and within the period specified by applicable law, but in any case not more than 10 years after the date of Substantial Completion of the Work. The Owner and Contractor waive all Claims and causes of action not commenced in accordance with this Section 15.1.2.

§ 15.1.3 Notice of Claims

- § 15.1.3.1 Claims by either the Owner or Contractor, where the condition giving rise to the Claim is first discovered prior to expiration of the period for correction of the Work set forth in Section 12.2.2, shall be initiated by notice to the other party. Claims by either party under this Section 15.1.3.1 shall be initiated within 21 days after occurrence of the event giving rise to such Claim or within 21 days after the claimant first recognizes the condition giving rise to the Claim, whichever is later.
- § 15.1.3.2 Claims by either the Owner or Contractor, where the condition giving rise to the Claim is first discovered after expiration of the period for correction of the Work set forth in Section 12.2.2, shall be initiated by notice to the other party.

§ 15.1.4 Continuing Contract Performance

§ 15.1.4.1 Pending final resolution of a Claim, except as otherwise agreed in writing or as provided in Section 9.7 and Article 14, the Contractor shall proceed diligently with performance of the Contract and the Owner shall continue to make payments in accordance with the Contract Documents.

§ 15.1.4.2 The Contract Sum and Contract Time shall be adjusted in accordance with the Initial Decision Maker's decision, subject to the right of either party to proceed in accordance with this Article 15. The Architect will issue Certificates for Payment in accordance with the decision of the Initial Decision Maker.

§ 15.1.5 Claims for Additional Cost

If the Contractor wishes to make a Claim for an increase in the Contract Sum, notice as provided in Section 15.1.3 shall be given before proceeding to execute the portion of the Work that is the subject of the Claim. Prior notice is not required for Claims relating to an emergency endangering life or property arising under Section 10.4.

§ 15.1.6 Claims for Additional Time

§ 15.1.6.1 If the Contractor wishes to make a Claim for an increase in the Contract Time, notice as provided in Section 15.1.3 shall be given. The Contractor's Claim shall include an estimate of cost and of probable effect of delay on progress of the Work. In the case of a continuing delay, only one Claim is necessary.

§ 15.1.6.2 If adverse weather conditions are the basis for a Claim for additional time, such Claim shall be documented by data substantiating that weather conditions were abnormal for the period of time, could not have been reasonably anticipated, and had an adverse effect on the scheduled construction.

§ 15.1.7 Waiver of Claims for Consequential Damages

The Contractor and Owner waive Claims against each other for consequential damages arising out of or relating to this Contract. This mutual waiver includes

- damages incurred by the Owner for rental expenses, for losses of use, income, profit, financing, business and reputation, and for loss of management or employee productivity or of the services of such persons; and
- .2 damages incurred by the Contractor for principal office expenses including the compensation of personnel stationed there, for losses of financing, business and reputation, and for loss of profit, except anticipated profit arising directly from the Work.

This mutual waiver is applicable, without limitation, to all consequential damages due to either party's termination in accordance with Article 14. Nothing contained in this Section 15.1.7 shall be deemed to preclude assessment of liquidated damages, when applicable, in accordance with the requirements of the Contract Documents.

§ 15.2 Initial Decision

§ 15.2.1 Claims, excluding those where the condition giving rise to the Claim is first discovered after expiration of the period for correction of the Work set forth in Section 12.2.2 or arising under Sections 10.3, 10.4, and 11.5, shall be referred to the Initial Decision Maker for initial decision. The Architect will serve as the Initial Decision Maker, unless otherwise indicated in the Agreement. Except for those Claims excluded by this Section 15.2.1, an initial decision shall be required as a condition precedent to mediation of any Claim. If an initial decision has not been rendered within 30 days after the Claim has been referred to the Initial Decision Maker, the party asserting the Claim may demand mediation and binding dispute resolution without a decision having been rendered. Unless the Initial Decision Maker and all affected parties agree, the Initial Decision Maker will not decide disputes between the Contractor and persons or entities other than the Owner.

§ 15.2.2 The Initial Decision Maker will review Claims and within ten days of the receipt of a Claim take one or more of the following actions: (1) request additional supporting data from the claimant or a response with supporting data from the other party, (2) reject the Claim in whole or in part, (3) approve the Claim, (4) suggest a compromise, or (5) advise the parties that the Initial Decision Maker is unable to resolve the Claim if the Initial Decision Maker lacks sufficient information to evaluate the merits of the Claim or if the Initial Decision Maker concludes that, in the Initial Decision Maker's sole discretion, it would be inappropriate for the Initial Decision Maker to resolve the Claim.

§ 15.2.3 In evaluating Claims, the Initial Decision Maker may, but shall not be obligated to, consult with or seek information from either party or from persons with special knowledge or expertise who may assist the Initial Decision Maker in rendering a decision. The Initial Decision Maker may request the Owner to authorize retention of such persons at the Owner's expense.

§ 15.2.4 If the Initial Decision Maker requests a party to provide a response to a Claim or to furnish additional supporting data, such party shall respond, within ten days after receipt of the request, and shall either (1) provide a response on the requested supporting data, (2) advise the Initial Decision Maker when the response or supporting data will be furnished, or (3) advise the Initial Decision Maker that no supporting data will be furnished. Upon receipt of the response or supporting data, if any, the Initial Decision Maker will either reject or approve the Claim in whole or in part.

§ 15.2.5 The Initial Decision Maker will render an initial decision approving or rejecting the Claim, or indicating that the Initial Decision Maker is unable to resolve the Claim. This initial decision shall (1) be in writing; (2) state the reasons therefor; and (3) notify the parties and the Architect, if the Architect is not serving as the Initial Decision Maker, of any change in the Contract Sum or Contract Time or both. The initial decision shall be final and binding on the parties but subject to mediation and, if the parties fail to resolve their dispute through mediation, to binding dispute resolution.

§ 15.2.6 Either party may file for mediation of an initial decision at any time, subject to the terms of Section 15.2.6.1.

§ 15.2.6.1 Either party may, within 30 days from the date of receipt of an initial decision, demand in writing that the other party file for mediation. If such a demand is made and the party receiving the demand fails to file for mediation within 30 days after receipt thereof, then both parties waive their rights to mediate or pursue binding dispute resolution proceedings with respect to the initial decision.

§ 15.2.7 In the event of a Claim against the Contractor, the Owner may, but is not obligated to, notify the surety, if any, of the nature and amount of the Claim. If the Claim relates to a possibility of a Contractor's default, the Owner may, but is not obligated to, notify the surety and request the surety's assistance in resolving the controversy.

§ 15.2.8 If a Claim relates to or is the subject of a mechanic's lien, the party asserting such Claim may proceed in accordance with applicable law to comply with the lien notice or filing deadlines.

§ 15.3 Mediation

§ 15.3.1 Claims, disputes, or other matters in controversy arising out of or related to the Contract, except those waived as provided for in Sections 9.10.4, 9.10.5, and 15.1.7, shall be subject to mediation as a condition precedent to binding dispute resolution.

§ 15.3.2 The parties shall endeavor to resolve their Claims by mediation which, unless the parties mutually agree otherwise, shall be administered by the American Arbitration Association in accordance with its Construction Industry Mediation Procedures in effect on the date of the Agreement. A request for mediation shall be made in writing, delivered to the other party to the Contract, and filed with the person or entity administering the mediation. The request may be made concurrently with the filing of binding dispute resolution proceedings but, in such event, mediation shall proceed in advance of binding dispute resolution proceedings, which shall be stayed pending mediation for a period of 60 days from the date of filing, unless stayed for a longer period by agreement of the parties or court order. If an arbitration is stayed pursuant to this Section 15.3.2, the parties may nonetheless proceed to the selection of the arbitrator(s) and agree upon a schedule for later proceedings.

§ 15.3.3 Either party may, within 30 days from the date that mediation has been concluded without resolution of the dispute or 60 days after mediation has been demanded without resolution of the dispute, demand in writing that the other party file for binding dispute resolution. If such a demand is made and the party receiving the demand fails to file for binding dispute resolution within 60 days after receipt thereof, then both parties waive their rights to binding dispute resolution proceedings with respect to the initial decision.

§ 15.3.4 The parties shall share the mediator's fee and any filing fees equally. The mediation shall be held in the place where the Project is located, unless another location is mutually agreed upon. Agreements reached in mediation shall be enforceable as settlement agreements in any court having jurisdiction thereof.

§ 15.4 Arbitration

§ 15.4.1 If the parties have selected arbitration as the method for binding dispute resolution in the Agreement, any Claim subject to, but not resolved by, mediation shall be subject to arbitration which, unless the parties mutually agree otherwise, shall be administered by the American Arbitration Association in accordance with its Construction Industry Arbitration Rules in effect on the date of the Agreement. The Arbitration shall be conducted in the place where the Project is located, unless another location is mutually agreed upon. A demand for arbitration shall be

made in writing, delivered to the other party to the Contract, and filed with the person or entity administering the arbitration. The party filing a notice of demand for arbitration must assert in the demand all Claims then known to that party on which arbitration is permitted to be demanded.

- § 15.4.1.1 A demand for arbitration shall be made no earlier than concurrently with the filing of a request for mediation, but in no event shall it be made after the date when the institution of legal or equitable proceedings based on the Claim would be barred by the applicable statute of limitations. For statute of limitations purposes, receipt of a written demand for arbitration by the person or entity administering the arbitration shall constitute the institution of legal or equitable proceedings based on the Claim.
- § 15.4.2 The award rendered by the arbitrator or arbitrators shall be final, and judgment may be entered upon it in accordance with applicable law in any court having jurisdiction thereof.
- § 15.4.3 The foregoing agreement to arbitrate and other agreements to arbitrate with an additional person or entity duly consented to by parties to the Agreement, shall be specifically enforceable under applicable law in any court having jurisdiction thereof.

§ 15.4.4 Consolidation or Joinder

- § 15.4.4.1 Subject to the rules of the American Arbitration Association or other applicable arbitration rules, either party may consolidate an arbitration conducted under this Agreement with any other arbitration to which it is a party provided that (1) the arbitration agreement governing the other arbitration permits consolidation, (2) the arbitrations to be consolidated substantially involve common questions of law or fact, and (3) the arbitrations employ materially similar procedural rules and methods for selecting arbitrator(s).
- § 15.4.4.2 Subject to the rules of the American Arbitration Association or other applicable arbitration rules, either party may include by joinder persons or entities substantially involved in a common question of law or fact whose presence is required if complete relief is to be accorded in arbitration, provided that the party sought to be joined consents in writing to such joinder. Consent to arbitration involving an additional person or entity shall not constitute consent to arbitration of any claim, dispute or other matter in question not described in the written consent.
- § 15.4.4.3 The Owner and Contractor grant to any person or entity made a party to an arbitration conducted under this Section 15.4, whether by joinder or consolidation, the same rights of joinder and consolidation as those of the Owner and Contractor under this Agreement.

ARTICLE 16 Federal Provisions

§ 16.1 Prohibition Against the Use of Lead Based Paint

The Contractor shall comply with the prohibition against the use of lead based paint contained in the Lead Based Paint Poisoning Act (42 USC 4821-4846) as implemented by 24 CFR Part 35.

§ 16.2 Federal Health, Safety, and Accident Prevention

The Contractor shall ensure that no laborer or mechanic shall be required to work in surroundings or under working conditions which are unsanitary, hazardous, or dangerous to his/her health and/or safety as determined under the construction safety and health standards promulgated by the Secretary of Labor by regulation. The Contractor shall comply with §5.07 and with the regulations and standards issued by the Secretary of Labor at 29 CFR Parts 1904 and 1926 Failure to comply may result in imposition of sanctions pursuant to the Contract Work Hours and Safety Standards Act (Public Law 9154, 83 Stat. 96), 40 USC 3701 to 3708 et seq.

§ 16.3 Clean Air and Water Applicable to Contracts in Excess Of \$150,000

The Contractor shall comply with all requirements of the United States Environmental Protection Agency (EPA) 40 CFR Part 15, 42 USC 7401, 33 USC 1251 et seq., the Federal Water Pollution Control Act 33 USC 1281 et seq., and Executive Order 11738.

§ 16.4 Energy Efficiency

The Contractor shall comply with all standards and policies relating to energy efficiency which are contained in the energy conservation plan issued in compliance with the Energy Policy and Conservation Act (Pub. L. 94-163) in Washington State and the Federal Energy Policy and Conservation Act (42 USC 6201).

User Notes:

(1936282232)

§ 16.5 Labor Standards; Davis-Bacon and Related Acts, if Applicable

The Contractor shall comply with all provisions of the Davis-Bacon Act and Related Acts such as the Housing Act of 1937, the National Housing Act, the Housing and Community Development Act of 1974, the National Affordable Housing Act of 1990, Equal Employment Opportunity 41 CFR Part 60 or similar related Acts for Federal Labor Standards for this Contract. The Contractor is responsible for the full compliance of all employers, including the Contractor, Subcontractors, and all the Lower-Tier Subcontractors with the Labor Standards Provisions applicable to this Project.

§ 16.6 Interest of Member of Congress

No member of or delegate to the Congress of the United States of America shall be admitted to any share or part of this Contract or to any benefit to arise therefrom, but this provision shall not be construed to extend to this Contract if made with a corporation for its general benefit. Copeland Anti-Kickback Act 40 USC 3145.

§ 16.7 Interest of Members, Officers, Commissioners and Employees, or Former Members, Officers and Employees

No member, officer, or employee of King County Housing Authority, no member of the Governing body of the locality in which the project is situated, no member of the governing body in which the Owner was activated, and no other public official or such who exercises any functions or responsibilities with respect to the project, shall, during his or her tenure, or for one year thereafter, have any interest, direct or indirect, in this contract or the proceeds thereof.

§ 16.8 Organization Conflicts of Interest

- 1 The Contractor warrants that to the best of its knowledge and belief and except as otherwise disclosed, it does not have any organizational conflict of interest which is defined as a situation in which the nature of the work under this Contract and the Contractor's organizational, financial, contractual or other interests are such as:
 - .a Award of the Contract may result in an unfair competitive advantage; or
 - **.b** The Contractor's objectivity in performing the Contract Work may be impaired.
- .2 The Contractor agrees that if after award they discover an organizational conflict of interest with respect to this Contract, they shall make an immediate and full disclosure in writing to the Contracting Officer, which shall include a description of the action, which the Contractor has taken or intend to take to eliminate or neutralize the conflict. The Owner may, however, terminate the Contract if it deems the action to be in the best interest of the Owner.
- .3 In the event the Contractor was aware of an organizational conflict of interest before the award of this Contract and intentionally did not disclose the conflict to the Contracting Officer, the Owner may terminate the Contract for default.
- .4 In the event the Contractor was aware of an organizational conflict of interest before the award of this Contract and intentionally did not disclose the conflict to the Contracting Officer, the Owner may terminate the Contract for default.

§ 16.9 Lobbying

Contractor shall be in compliance with the Byrd Anti-Lobbying Amendment 31 USC 3145.

§ 17 Audits and Inspections

The records and documents with respect to all matters covered by this Contract shall be subject at all times to inspection, review or audit by the Owner or any other government agency so authorized by law during the performance of this Contract. The Owner shall have the right to an annual audit of the Contractor's financial statement and condition.

- 1 The Contractor shall maintain accounts and records in accordance with State Auditor's procedures, including personnel, property, financial and programmatic records which sufficiently and properly reflect all direct and indirect costs of any nature expended and services performed in the performance of this Contract and other such records as may be deemed necessary by the Owner to ensure proper accounting for all funds contributed by the Owner to the performance of this Contract and compliance with this Contract.
- The Owner shall maintain these records for a period of six (6) years after termination hereof unless permission to destroy them in granted by the office of the archivist in accordance with RCW Chapter 40.14

§ 18 Section 3 – Instructions, Requirements and Income Guidelines, if Applicable

Contractor shall comply with all requirements of the Section 3 Program for economic opportunities providing to the greatest extent possible, job training employment and contract opportunities for low or very low income residents including persons who are recipients of HUD assistance for housing, with preference for both targeted workers living in the service area or neighborhood of the Development and YouthBuild participants, as defined at 24 CFR Part 75 ("Section 3 Regulations") per the Exhibit, as designated in AIA Contract Document A101-2007, Section 8.6.1.

- § 18.1 The work to be performed under this contract is subject to the requirements of the Section 3 Regulations. The purpose of Section 3 is to ensure that employment and other economic opportunities generated by HUD assistance or HUD-assisted projects covered by Section 3, shall, to the greatest extent feasible, be directed to low- and very lowincome persons, including persons who are recipients of HUD assistance for housing, with preference for both targeted workers living in the service area or neighborhood of the Development and YouthBuild participants.
- § 18.2 The parties to this contract agree to comply with HUD's Section 3 Regulations. As evidenced by their execution of this contract, the parties to this contract certify that they are under no contractual or other impediment that would prevent them from complying with the Section 3 Regulations.
- § 18.3 The Contractor agrees to send to each labor organization or representative of workers with which the Contractor has a collective bargaining agreement or other understanding, if any, a notice advising the labor organization or workers' representative of the Contractor's commitments under this Section 3 clause, and will post copies of the notice in conspicuous places at the work site where both employees and applicants for training and employment positions can see the notice. The notice shall describe the Section 3 preference, shall set forth minimum number and job titles subject to hire, availability of apprenticeship and training positions, the qualifications for each; and the name and location of the person(s) taking applications for each of the positions; and the anticipated date the work shall begin.
- § 18.4 The Contractor agrees to include this Section 3 clause in every subcontract subject to compliance with Section 3 Regulations, and agrees to take appropriate action, as provided in an applicable provision of the subcontract or in this Section 3 clause, upon a finding that the subcontractor is in violation of the Section 3 Regulations. The Contractor will not subcontract with any subcontractor where the Contractor has notice or knowledge that the subcontractor has been found in violation of the Section 3 Regulations.
- § 18.5 The Contractor will certify that any vacant employment positions, including training positions, that are filled (1) after the Contractor is selected but before the contract is executed, and (2) with persons other than those to whom Section 3 Regulations require employment opportunities to be directed, were not filled to circumvent the Contractor's obligations under Section 3 Regulations.
- § 18.6 Noncompliance with Section 3 Regulations may result in sanctions, termination of this contract for default, and debarment or suspension from future HUD assisted contracts.
- § 18.7 The Contractor shall submit to the Owner a Section 3 Work Plan, including hiring and subcontracting activities, and an Individual Certification Form for each person that is assigned to the project, prior to the contract execution. The Contractor will submit to the Owner with each Application for Payment the Section 3 Labor Hours Benchmark Status Report and any Individual Certification Form(s) for persons not initially assigned to the project prior to the contract execution. Noncompliance, incorrect, or missing documents will result in progress payments being withheld until all issues are resolved to the satisfaction of the Owner.
- § 18.8 Section 3 Employment and Training. Without limiting Contractor's obligation to comply with Section 3 Regulations, Contractor specifically agrees to use best efforts to provide employment and training opportunities to Section 3 workers in the following order of priority:
 - .1 To residents of the KCHA development where the work is being performed;
 - .2 To residents of other KCHA developments or for residents of Section 8-assisted housing managed by KCHA:
 - .3 To participants in YouthBuild programs; and
 - .4 To low- and very low-income persons residing within the Puget Sound Area.
- § 18.8 Section 3 Contracting. Without limiting Contractor's obligation to comply with Section 3 Regulations,

Contractor specifically agrees to use best efforts to award contracts and subcontracts to business concerns that provide economic opportunities to Section 3 workers in the following order of priority:

- .1 To Section 3 business concerns that provide economic opportunities for KCHA residents of the development where the work is being performed;
- .2 To Section 3 business concerns that provide economic opportunities for KCHA residents of other KCHA developments or Section-8 assisted housing managed by KCHA;
- .3 To YouthBuild programs; and
- To Section 3 business concerns that provide economic opportunities to Section 3 workers residing within the Puget Sound Area.

§ 19 OTHER INFORMATIVE INFORMATION

§ 19.1 Certificate of Endorsement, Final Project Schedule, Subcontractor List, Performance and Payment Bond and Section 3 Plan must be received and approved by the Owner prior to the issuance of the Notice to Proceed.





PERFORMANCE AND PAYMENT BOND INSTRUCTIONS

DIRECTIONS FOR PREPARATION OF PERFORMANCE AND PAYMENT BOND

- 1. Individual sureties, partnerships, or corporations not in the surety business will not be acceptable.
- 2. The name of the Principal shall be shown exactly as it appears in the Contract.
- 3. The penal sum shall not be less than required by the Specifications.
- 4. If the Principals are partners or joint venturers, each member shall execute the bond as an individual and state is place of residence.
- 5. If the principal is a corporation, the bond shall be executed under its corporate seal. If the corporation has no corporate seal, it shall so state and affix a scroll or adhesive seal following the corporate name.
- 6. The official character and authority of the person(s) executing the bond for the Principal, if a corporation, shall be certified by the Secretary or Assistant Secretary thereof under the corporate seal, or copies attached to such records of the corporation as will evidence the official character and authority of the officer signing, duly certified by the Secretary or Assistant Secretary, under the corporate seal, to be true copies.
- 7. The current power-of-attorney of the person signing for the surety company must be attached to the bond.
- 8. The date of the bond must not be prior to the date of the Contract.
- 9. The following information must be placed on the bond by the surety company:
 - a. The Rate of premium in dollars per thousand; and
 - b. The total dollar amount of premium charged
- 10. The signature of a witness shall appear in the appropriate place attending to the signature of each party of the bond.
- 11. Type or print the name underneath each signature appearing on the bond
- 12. An executed copy of the bond must be attached to each copy of the Contract (original counterpart) intended for signing.



KCHA – PEPPER TREE ENVELOPE CAPITAL CONSTRUCTION DEPARTMENT

as PRINCIPAL, and		_ as
SURETY are held and bound unto the KING hereinafter called the Public Housing Authority	COUNTY HOUSING AUTHORITY of Seattle	
\$	•	_ and No/100
	ful money of the United States, for the payment of which sum will and truly be made, we bind oursel jointly and severally, firmly by these presents.	
WHEREAS the Principal has entered into	a certain Contract with the Public Housing A	uthority dated
	of which is hereto attached and made a part hereof.	
all claims arising out of the prosecution of the Wo Authority for all expenses which it may incur by a and if the Principal shall make full payment to al prosecution of the Work under the contract, in a hereupon, and if the Principal shall pay or cause to of the Contract as well as payment of gasoline an all motor vehicle fees required for commercial mot	which the Contract provides, and if the Principal shaper with under the contract and shall fully indemnify the Freason of such claims, including its attorney's fees at all persons supplying labor, services, materials, or equive default of which such persons shall have a direct abe paid all sales and use taxes payable as a result of the dispecial motor fuels taxes in the performance of the or vehicles used in connection with the performance of	Public Housing and court costs, uipment in the right of action are performance to Contract and of the Contract,
or extension of the term thereof, nor any forbeara release the Principal or the Surety from liability he or forbearance is hereby waived. IN WITNESS WHEREOF, the aforesaid Principal or extension of the term thereof, nor any forbearance is hereby waived.	ance on the part of the Public Housing Authority, shereunder. Notice to the Surety of any such modificate that and Surety have executed this instrument and affirm	all in any way ion, extension,
or extension of the term thereof, nor any forbeara release the Principal or the Surety from liability he or forbearance is hereby waived. IN WITNESS WHEREOF, the aforesaid Principhereto, this day of	ance on the part of the Public Housing Authority, shereunder. Notice to the Surety of any such modificate that and Surety have executed this instrument and affirm	all in any way ion, extension,
or extension of the term thereof, nor any forbeara release the Principal or the Surety from liability he or forbearance is hereby waived. IN WITNESS WHEREOF, the aforesaid Principal or extension of the term thereof, nor any forbearance is hereby waived.	ance on the part of the Public Housing Authority, shereunder. Notice to the Surety of any such modificate that and Surety have executed this instrument and affirm	all in any way ion, extension, extension, xed their seals
or extension of the term thereof, nor any forbeara release the Principal or the Surety from liability he or forbearance is hereby waived. IN WITNESS WHEREOF, the aforesaid Principhereto, this day of	ance on the part of the Public Housing Authority, shereunder. Notice to the Surety of any such modificat the pal and Surety have executed this instrument and affirm 20 (Individual Principal) (Business Address)	all in any way ion, extension,
or extension of the term thereof, nor any forbeara release the Principal or the Surety from liability he or forbearance is hereby waived. IN WITNESS WHEREOF, the aforesaid Principhereto, this day of	ence on the part of the Public Housing Authority, shereunder. Notice to the Surety of any such modificat oal and Surety have executed this instrument and affi	all in any way ion, extension, extension, xed their seals
or extension of the term thereof, nor any forbeara release the Principal or the Surety from liability he or forbearance is hereby waived. IN WITNESS WHEREOF, the aforesaid Principhereto, this day of	ance on the part of the Public Housing Authority, shereunder. Notice to the Surety of any such modificate to all and Surety have executed this instrument and affit 20 (Individual Principal) (Business Address) (Business Address)	all in any way ion, extension, extension, extension (Seal)
release the Principal or the Surety from liability he or forbearance is hereby waived. IN WITNESS WHEREOF, the aforesaid Principhereto, this day of WITNESS:	ence on the part of the Public Housing Authority, shereunder. Notice to the Surety of any such modificat oal and Surety have executed this instrument and affi 20 (Individual Principal) (Business Address) (Individual Principal)	all in any way ion, extension, extension, extension (Seal)
or extension of the term thereof, nor any forbeara release the Principal or the Surety from liability he or forbearance is hereby waived. IN WITNESS WHEREOF, the aforesaid Principhereto, this day of	cance on the part of the Public Housing Authority, shereunder. Notice to the Surety of any such modificate to the Surety o	all in any way ion, extension, ex
or extension of the term thereof, nor any forbeara release the Principal or the Surety from liability he or forbearance is hereby waived. IN WITNESS WHEREOF, the aforesaid Principhereto, this day of	Ince on the part of the Public Housing Authority, shereunder. Notice to the Surety of any such modificate to all and Surety have executed this instrument and affirm 20 [Individual Principal] (Business Address) (Corporate Principal) (Business Address)	all in any way ion, extension, extension, extension (Seal)
or extension of the term thereof, nor any forbeara release the Principal or the Surety from liability he or forbearance is hereby waived. IN WITNESS WHEREOF, the aforesaid Principhereto, this day of	Individual Principal) (Business Address) (Corporate Principal) (Business Address) (Business Address) (Corporate Principal) (Business Address)	all in any way ion, extension, ex
or extension of the term thereof, nor any forbeara release the Principal or the Surety from liability he or forbearance is hereby waived. IN WITNESS WHEREOF, the aforesaid Principhereto, this day of WITNESS: ATTEST:	Ince on the part of the Public Housing Authority, shereunder. Notice to the Surety of any such modificate to all and Surety have executed this instrument and affit 20 (Individual Principal) (Business Address) (Individual Principal) (Business Address) (Corporate Principal) (Business Address) (By)	all in any way ion, extension, ex
or extension of the term thereof, nor any forbeara release the Principal or the Surety from liability he or forbearance is hereby waived. IN WITNESS WHEREOF, the aforesaid Principhereto, this day of WITNESS: ATTEST:	Ince on the part of the Public Housing Authority, shereunder. Notice to the Surety of any such modificate and and Surety have executed this instrument and affit 20 [Individual Principal] (Business Address) (Corporate Principal) (Business Address) (Business Address) (Corporate Principal) (Business Address) (Business Address) (Corporate Principal) (Corporate Principal) (Corporate Principal) (Corporate Principal) (Corporate Principal)	all in any way ion, extension, xed their seals (Seal) (Seal)
or extension of the term thereof, nor any forbeara release the Principal or the Surety from liability he or forbearance is hereby waived. IN WITNESS WHEREOF, the aforesaid Principhereto, this day of WITNESS: ATTEST:	Ince on the part of the Public Housing Authority, shereunder. Notice to the Surety of any such modificate to all and Surety have executed this instrument and affirm 20 [Individual Principal] [Business Address] [Corporate Principal] [Business Address] [Business Address] [Corporate Principal] [Business Address] [Corporate Principal] [Business Address]	all in any way ion, extension, ex



CERTIFICATE AS TO CORPORATE PRINCIPAL

CERTIFICATE AS TO CORPORATE PRINCIPAL

I,	certify that I am the
President / Vice President / Secretary /	of the Entity: Corporation
/LLC /	, named as the Principal in the aforegoing bond. The authorized
Official of the named bonding agent w	ho signed the said bond on behalf of the Principal, hereby certifies
that said bond was fully signed, sealed	d and attested for and in behalf of said Entity by authority of its
Governing body.	
Named Bonding Agent:	
Affix Corporate Seal / Authorized Sign	ature:



KING COUNTY HOUSING AUTHORITY INSURANCE REQUIREMENTS

INSTRUCTIONS / ENDORSEMENT INFORMATION FOR COMPLETING, EXECUTING, AND SUBMITTING EVIDENCE OF INSURANCE

A. INSURED CONTRACTOR:

- 1. In order to reduce problems and time delays in providing evidence of insurance to the King County Housing Authority you are requested to give your insurance agent or broker a copy of the Insurance Requirements Sheet along with the Instructions/Endorsement Form(s) for Completing, Executing, and Submitting Evidence of Insurance.
- 2. If the agreement requires Workers' Compensation coverage and you have been authorized by the State to self-insure Workers' Compensation, then a copy of the certificate from the State authorizing self-insurance for Workers' Compensation shall meet the requirements for Workers' Compensation insurance covering activities within the State.
- 3. All questions relating to insurance should be directed to the department or office responsible for your contract, lease, permit, or other agreement.

B. INSURANCE AGENT OR BROKER:

- 1. The appropriate Endorsement Form shall include:
 - a. King County Housing Authority as Additional Insured
 - b. State that the Contractor's Insurance Is Primary
 - c. State King County Housing Authority's Insurance Is Non-Contributory In Claims Settlement Funding

PLEASE NOTE: King County Housing Authority WILL NOT ACCEPT Certificates of Insurance Alone.

- 2. More than one insurance policy may be required to comply with the insurance requirements. Endorsement forms appropriate to your insured's agreement, contract, lease or permit are included. In each instance, King County Housing Authority shall be named as additionally insured on the appropriate endorsement forms.
- 3. You shall have an authorized representative of the insurance company forward the completed endorsement forms with his/her phone number noted at the bottom of the page, to King County Housing Authority.
- 4. The name of the Insurance Company underwriting the coverage and its address shall be noted on the endorsement form.
- 5. The "General description of agreement(s) and/or activity(s) insured" shall include reference to the activity and/or to either the specific King County Housing Authority's:
 - a. Project or Site Name
 - b. Contract Number
 - c. Lease Number
 - d. Permit Number
 - e. Construction Approval Number



- 6. The Coverage and limits for each type of insurance are specified on the insurance requirements sheet. When coverage is on a scheduled basis, then a separate sheet is to be attached to the endorsement listing such scheduled locations, vehicles, etc. so covered.
- 7. Endorsements to excess policies will be required when primary insurance is insufficient in complying with King County Housing Authority's requirements.
- 8. If there is insufficient space on the form to note pertinent information, such as inclusions, exclusions or specific provisions, etc., a separate sheet may be attached.
- 9. When additional sheets are attached, change the number of pages at the bottom of the form to so indicate.
- 10. Completed Endorsement(s) including cancellation notices and questions relating to the required insurance are to be directed to:

KING COUNTY HOUSING AUTHORITY ATTN: CAPITAL CONSTRUCTION DEPARTMENT 700 ANDOVER PARK WEST, SUITE C TUKWILA, WA 98188

- 11. Improperly Completed Endorsements will be returned to your insured for correction by an authorized representative of the insurance company.
- 12. For extensions or renewals on insurance policies which have King County Housing Authority Endorsement Form(s) attached, the Housing Authority will accept a copy of the endorsement to extend the period of coverage as evidence of continued coverage.

C. MINIMUM LIMITS:

1. REFER TO "Insurance Requirements" attached.



INSURANCE REQUIREMENTS FOR BUILDING TRADE CONTRACTORS (with Construction Risks)

The Awarded Contractor shall comply as follows:

Contractor shall procure and maintain, at their expense, for the duration of the contract insurance against claims for injuries to persons or damages to property, which may arise from or in connection with the performance of the work hereunder by the Contractor, his agents, representatives, employees or subcontractors.

THE KING COUNTY HOUSING AUTHORITY (AUTHORITY) SHALL BE NAMED AS ADDITIONALLY INSURED ON THE APPROPRIATE ENDORSEMENT FORMS.

MINIMUM SCOPE OF INSURANCE:

Coverage shall be at least as broad as:

- 1. Insurance Services Office Commercial General Liability coverage including Products / Completed Operations.
- 2. Insurance Services Office covering any Owned, Leased, Hired and Non-owned, and Automobile Liability.
- 3. Workers' Compensation insurance as required by State law and Employers Liability coverage.
- 4. Builders Risk (Property / Course of Construction insurance covering for all risks of loss for all projects in excess of \$250,000.)
- 5. Professional Liability / Errors and Omission (when applicable).

MINIMUM LIMITS OF INSURANCE:

Contractor shall maintain limits no less than:

- 1. General Liability: \$1,000,000 per occurrence, \$2,000,000 general aggregate, including \$1,000,000 Products / Completed Operations for bodily injury, personal injury and property damage. If Commercial General Liability Insurance or other form with a general aggregate limit is used, either the general aggregate limit shall apply separately to this project / location or the general aggregate limit shall be twice the required occurrence limit.
- 2. Automobile Liability: \$1,000,000 per accident for bodily injury / property damage.
- 3. Employer's Liability / Washington Stop Gap: \$1,000,000 per accident for bodily injury, sickness or disease.
- 4. Builder Risk (Property) / Course of Construction: Completed value of the project.
- 5. Professional Liability / Errors and Omissions: \$1,000,000 per claim; \$2,000,000 aggregate (when applicable).

DEDUCTIBLES AND SELF-INSURED RETENTIONS:

Any deductibles or self-insured retentions must be declared to and approved by the Authority. At the option of the Authority, either: the insurer shall reduce or eliminate such deductibles or self-insured retentions as respects the Authority, its successors and assigns, director, officers, officials, employees, agents, partners and volunteers; or the Contractor shall provide a financial guarantee satisfactory to the Authority guaranteeing payment of losses and related investigations, claim administration and defense expenses.



NOTE: If this contract deals with hazardous materials or activities (i.e. lead based paint, asbestos, armed security guards) additional provisions covering those exposures must be included in order to protect the Authority's interests.

OTHER INSURANCE PROVISIONS:

General Liability and Automobile Liability Policies are to contain, or be endorsed to contain, the following provisions:

- 1. The Authority, its successors and assigns, director, officers, officials, employees, agents, partners, and volunteers are to be covered as additional insureds with respect to (i) general liability arising out of work done or operations performed by or on behalf of the contractor, including materials, parts or equipment furnished in respect to such work or operations. The endorsement(s) effectuating the foregoing additional insured coverage shall be ISO form CG 20 10 11 85, or CG 20 10 10 01 issued concurrently with CG 20 37 10 01, or their equivalent as long as it provides additional insured coverage, and not limited to the minimum acceptable as required herein, for completed operations; (ii) automobile liability arising out of vehicles owned, leased, hired, or borrowed by or on behalf of the Contractor; (iii) any insurance written on a claims made basis, shall have a retroactive date that coincides with, or precedes, the commencement of any work under this contract. Evidence of such coverage shall be maintained for a minimum of six (6) years beyond the expiration of the project and if a Claims Made policy is not renewed or replaced, then evidence of an extended reporting period of six (6) years shall be provided.
- 2. For any claims related to this project, the Contractor's insurance coverage shall be primary insurance as respects the Authority, its successors and assigns, director, officers, officials, employees, agents, partners and volunteers. Any insurance or self-insurance maintained or expired by the Authority, its officers, officials, employees, or volunteers shall be excess of the Contractor's insurance and shall not contribute with it.
- 3. The Contractor on behalf of itself and its liability insurance carriers release and waive any claims and subrogation rights against The Authority, its successors and assigns, director, officers, officials, employees, agents, partners, and volunteers. The Contractor agrees that they will cause its insurance carriers to include in its policies such a clause or endorsement. If extra cost shall be charged therefore, the Contractor shall pay the same.
- 4. Each insurance policy required by this clause shall be endorsed to state that coverage shall not be canceled or materially changed, except after thirty (30) days / (ten (10) days for non-payment of premium) without prior written notice given to the Authority through certified mail, with return receipt requested.
- 5. Maintenance of the proper insurance for the duration of the contract is a material element of the contract. Material changes in the required coverage or cancellation of the coverage shall constitute a material breach of the contract.

Builders Risk / Course of Construction Policies shall contain the following provisions:

- 1. The Authority and its insurers shall be named as loss payees.
- 2. The insurer shall waive all rights of subrogation against the Authority, its successors and assigns, director, officers, officials, employees, agents, partners and volunteers.

Bidder's Insurance Requirements Contract Documents C.4

¹ "Equivalent" means that any endorsements provided must have the equivalent coverage of the listed endorsements. NOTE: This may cost the Contract extra money to get this coverage.



ACCEPTABILITY OF INSURERS:

Insurance is to be placed with insurers with a current A.M. Best's rating of no less than **A-:VII**. Contractors must provide written verification of their insurer's rating.

VERIFICATION OF COVERAGE:

Contractor shall furnish the Authority with **original certificates** and **amendatory endorsements** affecting coverage required by this clause. The endorsements should be on forms provided by the Authority or on other than the Authority's forms, provided those endorsements conform fully to the requirements. All certificates and endorsements are to be received and approved by the Authority before work commences in sufficient time to permit Contractor to remedy any deficiencies. The Authority reserves the right to require complete, certified copies of all required insurance policies, or pertinent parts thereof, including endorsements affecting the coverage required by these specifications at any time.

SUBCONTRACTORS:

- 1. Subcontractor shall include the Contractor as additional insured under their policies. All coverages for subcontractors shall be subject to all of the requirements stated herein.
- 2. Contractor shall be responsible for the adequacy of required coverages for subcontractors, and compile related certificates of insurance and endorsements evidencing subcontractors' compliance.

INDEMNIFICATION AND HOLD HARMLESS:

- 1. To the fullest extent permitted by law the Contractor hereby agrees to indemnify and hold harmless the KCHA, its successors and assigns, directors, officials, officers and employees, volunteers, partners and agents (all foregoing singly and collectively "Indemnitees"), from and against any and all claims losses, harm, costs, liabilities, damages and expenses including, but not limited to, reasonable attorneys' fees arising or resulting from the performance of the Work, or the acts or omissions of the Contractor its successors and assigns, employees, subcontractors or anyone acting on the Contractor's behalf in connection with this Contract or its performance; PROVIDED, however, that the Contractor shall not be required to so indemnify any such Indemnitees against liability for damages caused by or resulting from the sole negligence of Indemnitees; PROVIDED FURTHER that if such damages are caused by or result from the concurrent negligence of the Indemnitees and the Contractor or anyone acting on the Contractor's behalf, then the Contractor's indemnity hereunder shall be limited to the extent of the negligence of the Contractor, its successors and assigns, et al.
- 2. The foregoing indemnity is specifically and expressly intended to constitute waiver of the Contractor's immunity under Washington's Industrial Act, RCW Title 51, and that this waiver has been specifically negotiated and agreed upon by the parties.
- 3. The Contractor hereby agrees to require all its subcontractors or anyone acting under its direction or control or on its behalf in connection with or incidental to the performance of this Contract to execute an indemnity clause identical to the preceding clause, specifically naming KCHA as Indemnitee, and failure to do so shall constitute a material breach of this Contract by the Contractor.



SITE SPECIFIC SAFETY PLAN REQUIREMENTS

Following is a list of the elements that are typically addressed in a construction site specific safety plan. A site specific safety plan will be one of the required post-selection documents be submitted by the contractor selected through this bid solicitation.

NOTE: In addition to the typical elements of a construction safety plan that addresses the contractor, KCHA requires that if a/the employee(s) of the Contractor or any sub-contractor is asked to put on a mask by either a resident or property manager when they are in a building or resident's unit, the employee(s) will do so; the Contractor should reflect this in their safety plan.

The selected contractor with responsible for obtaining similar plans from all subcontractors and for the supervision and enforcement of safety requirements on the site. The contractor's Site-Specific Safety Plan will be submitted to KCHA before any work can begin. The Plan will need to address the following:

- 1. An initial job/job-site safety orientation and a schedule of weekly safety meetings that show employees and subcontractors what they need to know to perform their job assignments safely.
- 2. Details how and when to report on-the-job injuries.
- 3. Identifies on-site available 1st Aid / CPR trained personnel, readily accessible first-aid on the job site and/or access to the nearest clinic or hospital from the job site.
- 4. Identifies what to do in an emergency, including how to exit the workplace.
- 5. Lists the required personal protective equipment (PPE) and describes the proper use and care of the PPE.
- 6. Details the on-site Haz-Com Program that identifies hazardous materials (Asbestos, Lead) or chemicals including instruction about the safe use and storage.
- 7. Designates an on-site representative responsible for job-site Safety.
- 8. Designates who is responsible for performing and recording regular periodic site reviews, and inspections for your employees and subcontractors.
- 9. Describes programs related to housekeeping and jobsite safety.
- 10. Outlines the job-site specific fall protection plan.
- 11. Describes electrical and/or power generation controls on-site.
- 12. Has provisions for trenching /excavations and/or confined space entry.
- 13. Has provisions for "masking-up"



SUB-CONTRACTOR VERIFICATION FORM

It is the responsibility of the General Contractor to obtain and verify the Subcontractor's Information described below. For compliance, the General Contractor must submit a copy of the Subcontractor Verification form prior to the sub starting work. A copy of the Affidavit of Intent form must accompany the applicable Certified Payroll. Without these forms, the Pay Application maybe withheld.

KCHA will review subcontractors' qualifications, safety record, and the history of compliance (including subcontractor's principals working under another company name) with labor and other state and federal laws. Based on this review, KCHA reserves the right at its sole discretion to reject subcontractors and require the selected General Contractor to replace or substitute a subcontractor with one acceptable to KCHA.

Name of Company:	
Physical Address:	
Contact Name and Title	
Email Address:	Phone No.:
WA State Contractor's License:	UBI Number:
Employment Security Number:	L&I's Workers' Comp. Acct. ID:
Federal Tax ID Number:	DUNS Number:
SUB-CONTRACTOR IS A(N): Individe	ual Partnership* Corporation** – in state of
* If Partnership, prov	vide Full Name(s) and Address(es) of all parties
** If your company is "also kno	own as (AKA)" or "doing business as (DBA) list all names
	FICATION RATE (EMR): 2020; 2021; 2022; of EMR stated, showing complete worksheet calculations).
Sub-Contractor is not presently debarred, suspen excluded from covered transactions by any feder	nded, proposed for debarment, declared ineligible, or voluntarily ral department or agency:
NOTE: The penalty for making false statement	in offer is prescribed in 18 U.S.C. 1001.
SUBMITTED ON : Day of	, 20
Signature of General Contractor	Name of General Contractor (Print)
Title of General Contractor (Print)	Date

Certification of Payments to Influence Federal Transactions

U.S. Department of Housing and Urban Development Office of Public and Indian Housing

CONTRACT DOCUMENTS C.7

Public reporting burden for this information collection is estimated to average 30 minutes. This includes the time for collecting, reviewing, and reporting data. The information requested is required to obtain a benefit. This form is used to ensure federal funds are not used to influence members of Congress. There are no assurances of confidentiality. HUD may not conduct or sponsor, and an applicant is not required to respond to a collection of information unless it displays a currently valid OMB control number.

HUD may not conduct or sponsor, and an applicant is not required to respond to a colle	ction of infori	nation unless it displays a currently valid OMB control number.
Applicant Name		
Program/Activity Receiving Federal Grant Funding		
. Togianin, earny . toooning . ocolai olaini aliang		
The undersigned certifies, to the best of his or her knowledge and b	elief that:	
The undersigned certifies, to the best of his of her knowledge and b	ciici, mat.	
(1) No Federal appropriated funds have been paid or will be paid, by or on behalf of the undersigned, to any person for influencing or attempting to influence an officer or employee of an agency, a Member of Congress, an officer or employee of Congress, or an employee of a Member of Congress in connection with the awarding of any Federal contract, the making of any Federal grant, the making of any Federal loan, the entering into of any cooperative agreement, and the extension, continuation, renewal, amendment, or modification of any Federal contract, grant, loan, or cooperative agreement. (2) If any funds other than Federal appropriated funds have been paid or will be paid to any person for influencing or attempting to influence an officer or employee of an agency, a Member of Congress, an officer or employee of Congress, or an employee of a Member of Congress in connection with this Federal contract, grant, loan, or cooperative agreement, the undersigned shall complete and submit Standard Form-LLL, Disclosure Form to Report Lobbying, in accordance with its instructions.	certifica at all t under g sub reci This ce reliance into. Su or enter 31, U.S certifica	the undersigned shall require that the language of this attion be included in the award documents for all subawards iters (including subcontracts, subgrants, and contracts grants, loans, and cooperative agreements) and that all pients shall certify and disclose accordingly. Trification is a material representation of fact upon which was placed when this transaction was made or entered abmission of this certification is a prerequisite for making ing into this transaction imposed by Section 1352, Title S. Code. Any person who fails to file the required attion shall be subject to a civil penalty of not less than and not more than \$100,000 for each such failure.
I hereby certify that all the information stated herein, as well as any inf Warning: HUD will prosecute false claims and statements. Conviction 1012; 31 U.S.C. 3729, 3802)		
Name of Authorized Official	Title	
Signature		Date (mm/dd/yyyy)

Previous edition is obsolete form HUD 50071 (01/14)

DISCLOSURE OF LOBBYING ACTIVITIES

Complete this form to disclose lobbying activities pursuant to 31 U.S.C.1352

Approved by OMB 4040-0013

1. * Type of Federal Action:	2. * Status of Federal Action:	3. * Report Type:
a. contract	a. bid/offer/application	a. initial filing
b. grant	b. initial award	b. material change
c. cooperative agreement	c. post-award	
d. loan		
e. loan guarantee f. loan insurance		
	Fusik	
4. Name and Address of Reporting	Entity:	
Prime SubAwardee		
* Name		
* Street 1	Street 2	
* City	State	Zip
Congressional District, if known:		
5. If Reporting Entity in No.4 is Subay	wardee, Enter Name and Address of Pri	me:
6. * Federal Department/Agency:	7. * Federal Prog	ram Name/Description:
or reactar permitted and the second	- Contracting to the contracting	
	CFDA Number, if applical	ble:
8. Federal Action Number, if known:	9. Award Amoun	t, if known:
,	\$	·
10. a. Name and Address of Lobbying	Registrant:	
Prefix * First Name	Middle Name	
* Last Name	Suffix	
* Street 1	Street 2	
* City	State	Zip
b. Individual Performing Services (incli		
Prefix * First Name	Middle Name	
* Last Name	Suffix	
* Street 1	Street 2	
* City	State	Zin
59	Sidle	Zip
	by title 31 U.S.C. section 1352. This disclosure of lobbying act action was made or entered into. This disclosure is required pur	
the Congress semi-annually and will be available for	public inspection. Any person who fails to file the required disclo	
\$10,000 and not more than \$100,000 for each such fa * Signature:	illure.	
S.g.iaturo.		
*Name: Prefix * First Nam	e Middle Na	me
* Last Name	Suffi	ix
Title:	Telephone No.:	Date:
Federal Use Only:		Authorized for Local Reproduction Standard Form - LLL (Rev. 7-97)



CERTIFICATION OF COMPLIANCE WITH WASHINGTON STATE WAGE PAYMENT STATUTES

· ·		ree year period immediately preceding the bid solicitation date of
		I" violator, as defined in RCW 49.48.082, of any provision of chapters
	•	final and binding citation and notice of assessment issued by the WA
State Department of La	bor & Industries of through	n a civil judgement entered by a court of limited or general jurisdiction.
I certify under penalty	of perjury under the laws o	of the State of Washington that the forgoing is true and correct.
Bidder		
Signature of Authorized	I Official*	
Printed name		
Title		
Date	City	State
Check one:		
Individual Partners	ship Joint Venture	Corporation
State of Incorporation,	or if not a corporation, Stat	te where business entity was formed:
If a co-partnership, give	company name under wh	ich business is transacted:

^{*}If a corporation, this Certification must be executed in the corporate name by the president or vice president (Or any other coporate officer accompanied by evidence of authority to sign). If a co-partnership, Certification must be executed by a partner.



Vendor Set-up Form (Alternative W-9)

FOR KCHA USE ONLY Subm	itted by:		Vendor Number:		Date:		
Name (as shown on your income tax return):							
Business name/disregard en	itity name, if different f	rom above:					
Check appropriate box for F	ederal tax classification	(required):					
☐ Individual	\square S Corporation		Trust/Estate	Other	(see instructions)		
☐ C Corporation	Partnership		Exempt Payee				
Limited Liability Compar P=Partnerships)	ny (LLC). Enter the tax cl	assification (C=C	corporation, S=S Cor	poratio	on, >>		
1099 Address (number, stre	eet, and apt. or suite no.	.): City	, State, and Zip Code:		Telephone:		
Remit to address (if differen	t from above):	City	, State, and Zip Code:		Email:		
Taxpayer Identification Num	nber (TIN)			Τ	PROVIDE ONE ONLY		
Enter your TIN in the appropria	te box. The TIN provided r			SSN:			
the "Name" line to avoid backu (SSN). For other entities, it is yo			ocial security number	EIN:			
Terms of Payment	Net 30		f Manth				
Terms or rayment		∐ Net 10th o					
	☐ Net 10	Due upon					
*Section-3: O Yes O No *	Questions can be direct	ted to KCHA Sec	tion 3 Coordinator 20	6-826-5	5335		
WMBE:	OWNED (MBE OR	O WOMEN O	OWNED (WBE)	○ No	ot Applicable		
☐ 1. White An	nerican	4. Hispanio	American		ONE OF THE ABOVE (NEC)		
🗌 2. Black Am	erican	☐ 5. Asian Pa	acific American	☐ Ot	her		
☐ 3. Native Ar	merican	6. Hasidic	Jew				
Certification							
Under the penalties of perjury, I certi	-						
ا ـ	form is my correct taxpayer ide						
· ·	-		- '		ied by the Internal Revenue Service (IRS) that I am hat I am no longer subject to backup withholding, and		
3. I am a U.S. citizen or other U	•	Jort all litterest of div	idenas, or cy the ins has not	neu me u	nat i ani no longer subject to backup withholding, and		
		eve been notified by t	he IRS that you are currently	subject to	o backup withholding because you have failed to		
					paid, acquisition of abandonment of secured property, est and dividends, you are not required to sign the		
certification, but you must provide yo	our correct TIN.						
The IRS doe not require your consent	to any provision of this docum	ent other than the ce	rtification required to avoid	backup w	vithholding.		
	of U.S. Person:				Date:		
Return completed form to		• •					
See instructions below or re	efer to the IRS instruction	ons at <u>www.irs.g</u>	ov for details on comp	oleting	this form.		
I					ral requirements to request a taxpayer identification quirements for vendor establishment.		
Complete form if: 1. You	u are a U.S. person (including a	resident alien);					
_	u are a vendor that provides go		HA; AND				
] 3. You	u will receive payment from KCI	HA					



SECTION 3 – INDIVIDUAL CERTIFICATION FORM

Section 3 of the Housing and Urban Development (HUD) Act of 1968, as amended, requires that Housing Authorities and agencies receiving HUD funding, to the greatest extent feasible, provide economic opportunities to low-income persons. **Information provided on this form shall remain confidential and be used for reporting purposes only.** *Print all information*

NAME:						_
ADDRESS:						
EMAIL ADDRESS:		PHONE	NUMBER:			
HIRE DATE:		POSITI	ON TITLE:		_	
EMPLOYER / COMPANY N.	AME:					
1. I am a resident in a KCH.	A Property.		_	Yes	s No)
Property Name:						
2. I am currently in KCHA'					s No)
3. I am currently a participa	nt in a HUD Yo	outhBuild Prograi	n	Ye	s No)
 a. I live in KITSAP COUMY TOTAL income fo Below or Equal to b. I live in KING or SNO 	s the past 12 mo \$61,000	C		box) \$61,000		
My TOTAL income for			appropriate	box)		
Below or Equal to	\$70,650	(Greater than	\$70,650		
c. I live in PIERCE COU My TOTAL income fo		onths was: (check	appropriate	box)		
Below or Equal to	\$60,200	(Greater than	\$60,200		
d. I live in SKAGIT COU My TOTAL income fo		onths was: (check	appropriate	box)		
Below or Equal to	\$51,050	(Greater than	\$51,050		
e. I live in THURSTON My TOTAL income for		onths was: (check	appropriate	box)		
Below or Equal to	\$57,400	(Greater than	\$57,400		





f	. I live in		COUNTY and			
	My TOTAL inc	ome for the past	12 months was: \$		<u> </u>	
5.	Section 8 assisted	housing managed rojects or Secti	a resident of public d by KCHA; a residence on 8 assisted how	lent of other	Yes	No
I herel	by certify under the p	enalty of perju	ry that the informati	on above is true and	correct.	
Signat	ure					

If submitting for a new hire, attach completed forms to Labor Hours Benchmark Status Report and submit to project manager. If submitting for Section 3 business qualification, attach to Section 3 Business Certification Form. For questions, please contact KCHA by email at section3@kcha.org.



SECTION 3 – INDIVIDUAL CERTIFICATION FORM FAQ's

Question: What is this form?

Answer: This form is a Section 3 Certification Form that will be used to determine if an individual

is a Section 3 worker as defined by HUD 24 CFR 75 and the KCHA.

Question: Who fills out this form?

Answer: Any individual who is paid in full or part with HUD funds. (If unsure if position is HUD

funded, please contact Contract administrator.)

Question: What will this form be used for?

Answer: This form will be used for the purpose of determining Section 3 eligibility and for statistical

purposes.

Question: Who collects this form and where does it go?

Answer: Any employer or contractor that has a contract with the KCHA that is HUD funded will

collect this data from any employee who was employed within the last five years. Once the

data is collected the original copy will come to KCHA.

Question: Who is a KCHA Resident?

Answer: Someone who lives in a KCHA Housing Development whose name is listed on a current

lease.

Question: How long should I go back to calculate my income?

Answer: Individuals should calculate back 12 months from their date of hire.

Question: What if I don't live in King County?

Answer: Individuals who do not reside in King County may still be eligible to be certified by KCHA

as a Section 3 resident.

If you have more specific questions, please contact KCHA at section3@kcha.org.



SECTION 3 – LABOR HOURS BENCHMARK REPORT - INSTRUCTIONS

Complete the Labor Hours Benchmark Status Report as indicated below and return the completed form along with the pay application(s) for the same period.

Return the Labor Hours Benchmark Status Report and pay application to:

	la, WA 98188	
Attn:		
Email:		

REPORT LINES:

- 1) Name of the project as it appears on the Contract
- 2) Company Name

King County Housing Authority

700 Andover Park West

- 3) Name of the person filling out the Labor Hours Benchmark Status Report
- 4) Phone number of the person filling out the Labor Hours Benchmark Status Report
- 5) Email address of the person filling out the Labor Hours Benchmark Status Report
- 6) Contract number as it appears on the Contract
- 7) Contract Award date (date of Letter of Award)
- 8) Reporting Period should be the same as the pay application period
- 9) Total hours worked by all workers on the project this will be everyone that is listed on the certified payrolls during Reporting Period.
- 10) Total hours worked on the project by Section 3 workers during the Reporting Period.

A Section 3 worker is identified as:

- a. The worker's income for the previous or annualized calendar year is below the income limit established by HUD; or
- b. Is employed by a Section 3 business concern; or
- c. Is a YouthBuild participant.

These will be the workers identified as Section 3 employees upon the submittal of their Section 3 Individual Certification Form at the beginning of the project OR when they were brought onto the project. A copy of these forms should be available from your company's payroll office. Copies can also be obtained by submitting a request to section3@kcha.org. Please include your company's name, project name and contact information.

11) Total hours worked on the project by Targeted Section 3 workers during the Reporting Period.

A Targeted Section 3 worker is identified as:

- a. Employed by a Section 3 business concern; or
- b. Is a resident of public housing or Section 8 assisted housing; or
- c. Resides within one mile of the project site.

These workers will be identified as Targeted Section 3 employees upon the submittal of their Section 3 Individual Certification Form at the beginning of the project OR when they were brought onto the project. A copy of these forms should be available from your company's payroll office. Copies can also be obtained by submitting a request to section3@kcha.org. Please include your company's name, project name and contact information.

See sample scenarios on pgs. 3 & 4



SECTION 3 – LABOR HOURS BENCHMARK REPORT

		GENERAL INFORMATION				
1)	PROJECT NAME:					
2)	COMPANY NAME:					
3)	CONTACT PERSON:					
4)	CONTACT PHONE NO.:					
5)	CONTACT EMAIL ADDRESS:					
6)	CONTRACT NO.:	7) CONTRACT AWARD DATE:				
	SECTION	3 LABOR HOUR BENCHMARKS				
8)	REPORTING PERIOD: FROM:	TO:				
9)	The totals below are for YOUR COMPANY ONLY and JUST THOSE WORKERS WORKING ON THE PROJECT SITE. TOTAL I AROR HOURS FOR ALL WORKERS ON THE PROJECT DURING THE					
I ce	rtify that the information in this report	is true and correct to the best of my knowledge:				
SIGN	NATURE	TITLE				
PRIN	IT NAME	DATE				
TKI	TIVINIE	DITTE				
То	To be completed by KCHA Staff RECEIVED BY:					
SIGN	NATURE	TITLE				
PRIN	NT NAME	DATE				



SCENARIO 1:

A crew of 5 <u>none</u> of whom self-certified as a Section 3 worker.

Reporting period is from June 1 to June 30, 2022.

The total hours that the crew worked on the project site during the reporting period totaled 1,000.

CE	CTI	ON	3 T	AROR	HOUR	RENCH	Λ	DKC

8)						
	REPORTING PERIOD: FROM: 6-1-22 TO: 6-30-22					
The totals below are for YOUR COMPANY ONLY and JUST THOSE WORKERS WORKING ON THE PROJECT TOTAL LABOR HOURS FOR ALL WORKERS ON THE PROJECT DURING THE REPORTING PERIOD (onsite work crew):						
10)	TOTAL LABOR HOURS FOR ALL SECTION 3 WORKERS ON THE PROJECT DURING THE REPORTING PERIOD (onsite work crew who self-certified as Section 3 Workers):	0				
11)	TOTAL LABOR HOURS FOR ALL <u>TARGETED</u> SECTION 3 WORKERS ON THE PROJECT DURING THE REPORTING PERIOD (onsite work crew who self-certified as Targeted Section 3 Workers):	0				
SCENARIO 2: A crew of 5, two of whom self-certified as Section 3 workers. Reporting period is from June 1 to June 30, 2022. The total hours that the <u>crew</u> worked on the project site during the reporting period totaled 1,000. The total hours of the two that self-certified as Section 3 workers during the reporting period totaled 80. SECTION 3 LABOR HOUR BENCHMARKS						
i ne u	otal hours of the two that self-certified as Section 3 workers during the reporting period totaled 80).				
8)).				
8)	otal hours of the two that self-certified as Section 3 workers during the reporting period totaled 80 SECTION 3 LABOR HOUR BENCHMARKS					
8) Th	otal hours of the two that self-certified as Section 3 workers during the reporting period totaled 80 SECTION 3 LABOR HOUR BENCHMARKS REPORTING PERIOD: FROM: 6-1-22 TO: 6-30-22 Totals below are for YOUR COMPANY ONLY and JUST THOSE WORKERS WORKING ON THE PROJECT TOTAL LABOR HOURS FOR ALL WORKERS ON THE PROJECT DURING THE	CCT SITE.				



SCENARIO 3:

A crew of 5, <u>one</u> of whom self-certified as a Section 3 worker and the other as a Targeted Section 3 worker. Reporting period is from June 1 to June 30.

The total hours that the <u>crew</u> worked on the project site during the reporting period totaled 1,000.

The total hours of the <u>one that self-certified as a Section 3 worker</u> during the reporting period totaled 40.

The total hours of the one that self-certified as a Targeted Section 3 worker during the reporting period totaled 40.

SECTION 3 LABOR HOUR BENCHMARKS								
8)	REPORTING PERIOD: FRO	0M: <u>6-</u>	1-22	TO: <u>6-30-22</u>				
	The totals below are for YOUR COMPANY ONLY and JUST THOSE WORKERS WORKING ON THE PROJECT SITE. TOTAL LABOR HOURS FOR ALL WORKERS ON THE PROJECT DURING THE							
9)	REPORTING PERIOD (onsite wo	rk crew):			1000			
10)	TOTAL LABOR HOURS FOR DURING THE REPORTING PI			ORKERS ON THE PROJECT who self-certified as Section 3 Workers):	_40			
11)	TOTAL LABOR HOURS FOR ALL <u>TARGETED</u> SECTION 3 WORKERS ON THE PROJECT DURING THE REPORTING PERIOD (onsite work crew who self-certified as Targeted Section 3 Workers):			40				
	Section 5 workers).				40			
Reporting period is from June 1 to June 30, 2022. The total hours that the <u>crew</u> worked on the project during the reporting period totaled <u>ZERO</u> . SECTION 3 LABOR HOUR BENCHMARKS								
8)	REPORTING PERIOD: FRO	OM: 6-	1-22	TO: <u>6-30-22</u>				
The totals below are for YOUR COMPANY ONLY and JUST THOSE WORKERS WORKING ON THE PROJECT SITE. TOTAL LABOR HOURS FOR ALL WORKERS ON THE PROJECT DURING THE								
9)	REPORTING PERIOD (onsite wo		ORTELIA OTT	THE TROUBET BORING THE	0			
10)	TOTAL LABOR HOURS FOR DURING THE REPORTING PR			ORKERS ON THE PROJECT who self-certified as Section 3 Workers):	0			
11)				ECTION 3 WORKERS ON THE te work crew who self-certified as Targeted	0			

YES, A LABOR HOUR BENCH MARK FORM HAS TO BE SUBMITTED EVEN IF NO WORK IS PERFORMED **BUT** THE GC/SUB (ALL TIERS) HAVE NOT FINISHED THE PROJECT.



D - **SECTION**

THIRD PARTY REPORTS

There are no reports for this project.



E - SECTION

DRAWINGS & SPECIFICATIONS

- **E.1** Scope of Work and Technical Specifications
- E.2 Drawings (if not included see attached)



SCOPE OF WORK & TECHNICAL SPECIFICATIONS

SCOPE OF WORK

DIVISION 01 - GENERAL REQUIREMENTS

01 1000	SUMMARY
01 2600	CONTRACT MODIFICATION PROCEDURES
01 2900	PAYMENT PROCEDURES
01 3100	PROJECT MANAGEMENT AND COORDINATION
01 3200	CONSTRUCTION PROGRESS DOCUMENTATION
01 3300	SUBMITTAL PROCEDURES
01 4000	QUALITY REQUIREMENTS
01 5000	TEMPORARY FACILITIES AND CONTROLS
01 6000	PRODUCT REQUIREMENTS
01 7300	EXECUTION
01 7329	CUTTING AND PATCHING
01 7419	CONSTRUCTION WASTE MANAGEMENT AND DISPOSAL
01 7700	CLOSEOUT PROCEDURES
01 7823	OPERATION AND MAINTENANCE DATA
01 7839	PROJECT RECORD DOCUMENTS
*****	SUBSTITUTION REQUEST FORM-KCHA

DIVISION 02 - EXISTING CONDITIONS

024100 DEMOLITION

DIVISION 06 - WOOD, PLASTICS, AND COMPOSITES

061000	ROUGH CARPENTRY
062000	FINISH CARPENTRY

068220 FIBERGLASS REINFORCED PLASTIC RAILINGS

DIVISION 07 - THERMAL AND MOISTURE PROTECTION

072100	THERMAL INSULATION
072500	WEATHER BARRIERS
074646	FIBER-CEMENT SIDING
076200	SHEET METAL FLASHING AND TRIM
079200	JOINT SEALANTS

DIVISION 08 - OPENINGS

081613 FIBERGLASS DOORS





085313 VINYL WINDOWS 087100 DOOR HARDWARE

089100 LOUVERS

DIVISION 09 - FINISHES

092116 GYPSUM BOARD ASSEMBLIES
 096700 FLUID-APPLIED COATING
 099113 EXTERIOR PAINTING
 099123 INTERIOR PAINTING

DIVISION 12 - FURNISHINGS

122116 LOUVER BLINDS

DIVISION 26 - ELECTRICAL

265600

260005 ELECTRICAL - EXISTING SYSTEM
260519 WIRES AND CABLES
260526 GROUNDING
260532 OUTLET AND PULL BOXES
260533 RACEWAY

EXTERIOR LIGHTING



LIST OF DRAWINGS

A0.0	COVER SHEET
A1.0	SITE PLAN
AD2.0	DEMO PLANS
AD2.1	DEMO ELEVATIONS
A2.0	FLOOR PLANS
A2.1	EXTERIOR ELEVATIONS
A2.2	DECKS - PLANS AND ELEVATIONS
A8.0	WALL ASSEMBLY AND EXTERIOR DETAILS
A8.1	EXTERIOR BALCONY DETAILS
A8.2	DOOR DETAILS
A8.3	WINDOW DETAILS
S0.1	GENERAL NOTES
S0.2	GENERAL NOTES
\$2.0	FIRST/SECOND FLOOR PLAN
\$2.1	FHIRD FLOOR/ROOF PLAN
\$3.0	DETAILS

TABLE OF CONTENTS - SCOPE OF WORK

1.0	Project Sun	ımarv

2.0 Project Administration Requirements

- A. Pre-construction
- **B.** Construction Administration
- C. Closeout

3.0 General Requirements

- A. Acknowledgement
- **B.** Staffing and Experience
- C. Quality Assurance and Quality Control
- D. Inspection of Work

E. Site Requirements

- 1. Work Hours
- 2. Restrictions
- 3. Contractor Responsibilities

F. Project Phasing

4.0 Safety, Protection and Restoration

- A. Safety
- **B.** Protection
- C. Restoration
- D. Hazardous Material

5.0 Divisions (See Specification Sections for complete details)

Division 1 General Conditions

- A. Site Staging and Deliveries
- B. Temporary Facilities

Division 2 Site Construction

A.	Selective Demolition	(Section 02 41 00)
B.	Existing Utilities	(Section 02 41 00)

C. Debris and Waste Removal

Division 6 Wood and Plastics

A.	Rough Carpentry	(Section	06 10 00)
B.	Finish Carpentry	(Section	06 20 00)
C.	Fiberglass Railing System	(Section	06 81 00)

Rev Date: 06-06-23 Page 1 of 20

Division 7 Thermal and Moisture Protection

A.	Thermal Insulation	(Section 07 21 00)
B.	Weather Resistant Barriers	(Section 07 25 00)
C.	Fiber Cement Siding	(Section 07 46 46)
D.	Sheet Metal Flashing and Trim	(Section 07 62 00)
E.	Joint Sealants	(Section 07 92 00)

Division 8 Doors and Windows

A.	Fiberglass Doors	(Section 08 16 13)
B.	Vinyl Windows	(Section 08 53 13)
C.	Door Hardware	(Section 08 71 00)
D.	Louvers	(Section 08 91 00)

Division 9 Finishes

A.	Gypsum Wall Board Assemblie	s (Section 09 21 16
B.	Fluid Applied Coating	(Section 09 67 00)
C.	Exterior Painting	(Section 09 91 13)
D.	Interior Painting	(Section 09 91 23)

Division 12 Furnishings

A. V	Window Coverings	(Section 12 21 16)
------	------------------	--------------------

Division 26 Electrical

A.	Electrical- Existing Systems	(Section 26 00 05)
B.	Wires and Cables	(Section 26 05 19)
C.	Grounding	(Section 26 05 26)
D.	Outlet and Pull Boxes	(Section 26 05 32)
E.	Raceway	(Section 26 05 33)
F.	Exterior Lighting	(Section 26 56 00)

Rev Date: 06-06-23

SECTION 001010 SCOPE OF WORK

1.0 PROJECT SUMMARY

Pepper Tree Apartments is located in the City of Shoreline, built in 1985, and consists of a three (3) story multifamily building which houses 30 individual residential units. The resident population is a diverse community of families with children and the elderly. The existing structure consist of 2x framing, batt insulation, GWB, weather resistant barrier and fiber cement siding; all of which will be removed down to the existing framing and re-insulated with new batt insulation between the stud bays, ½" fire-retardant wall sheathing (Section 06100), 1" Mineral fiber board insulation, 1x4 furring strips (refer to A8.0), Tyvek drain wrap and fiber cement siding and trim. Wall insulation assembly varies as noted per plans.

The existing roof, barge boards, fascia and soffits will remain in place. The soffits, fascia board, and barge boards will be repainted Benjamin Moore Calm OC-22.

Exterior work will include:

- Installation of structural floor-to-floor hold-downs to the upper roof section per structural drawings and details.
- Locations of hold-down assembly are noted in S2.0 and S2.1. The work will be performed from the exterior of the building. The Contractor will be responsible for all structural hardware, blocking, nailing, and drilling of the existing structure to complete a total installation per the details noted in S3.0.
- Contractor will repair any damage incurred to the interior drywall, stud framing, and batt insulation.
- Demo and framing of existing deck walls and reconstruction to incorporate new fiberglass railings. Refer to detail 1/A8.1.
- Demo of existing deck surface application. This removal will include grinding to remove any adhesion, patching, or floating to ensure proper application of new fluid applied deck coating. Refer to detail 1/A8.1 and specification section 096700.
- Removal of windows (balcony sliders Type C will be removed and re-installed), patio doors, patio storage doors, and mechanical & electrical room doors. Building Entry doors at the east and west elevations will remain in place. Refer to wall assembly detail 8/A8.0.
- NOTE: ****All removal and installation of windows will be performed by a <u>Glazier</u> Refer to Non Routine Maintenance Rates included in bid book.
- The Contractor is responsible to field verify all window and door openings prior to pricing and ordering materials. The Contractor will provide complete window and door systems including all shimming, flashings, proper fitting thresholds, air sealing, door painting, trims, new interior sills, drywall repairs and interior painting. Contractor will install each window and door on the same day as removal.
- Electrical Panel block out and trim at selective elevations, blocking installation at hose bibs, light fixture, GFI outlets, and building signs.
- The Contractor will add an electrical extension box as required to accommodate the new wall
 assembly and added blocking for both front and back unit light fixtures as well as for new GFI
 outlets on back patios.
- Existing hose bibs be removed, extended, and reinstalled to incorporate new wall assembly.
- All building lights and fire alarm apparatuses will be removed and reinstalled to incorporate the new building assembly.
- Sand, prep, and paint all existing metal handrails at the east elevation and west elevation entrance area to the building including the exterior walkway handrail along the west sidewalk.

Rev Date: 06-06-23 Page 3 of 20

The Owner is informing the Contractor that the drawings are showing "typical" details and conditions on site. The drawings are intended to show the basis of design and do not depict every feature, layout or condition on site. The basic building styles were chosen to demonstrate the intent of the project and "typical" details. Contractor to verify all site conditions prior to bid. This includes all door and window sizing, and whether if tempered or obscured glass is required. The Contractor is responsible to carry a contingency or risk factor that will allow the Contractor to pick up small variations or conditions that happen in this type of work. Above is only the general scope of work. The Contractor is responsible to review the entire scope of work, the specifications, and drawings for a complete understanding of all work items for this project.

2.0 PROJECT ADMINISTRATION REQUIREMENTS

A. Pre-Construction Administration

BEFORE commencement of work begins on-site the Contractor will provide the Owner the following items:

1. Project Master Schedule

- a. Completed in Microsoft Project, Primavera or similar.
- b. Must be cost loaded to reflect Schedule of Values items.
- c. Project phasing shall be integrated into master schedule.
- d. Shall include the following project milestones:

1)	Contract start date (CS)	TBD
2)	Notice to Proceed (NTP)	TBD
3)	Construction Duration (CD) Start Date/Stop Date	TBD - TBD
4)	Substantial Completion (SC)	TBD
5)	Physical Completion (PC) and Warranty Start Date of Entire Project	TBD
6)	Contract Completion (CC) of Entire Project	TBD

*The dates listed above are estimated milestone dates, provided to the Contractor for incorporation and inclusion in the negotiated final project Critical Path Method (CPM) schedule. These estimated dates may change. Such changes, if any, shall not result in an automatic extension of the Final Completion date. The Contractor shall make reasonable flexibility in the schedule to accommodate any such date changes in order to accomplish the interim milestone dates (NTP, CD Start/Stop, SC, PC and CC).

2. Schedule of Values (SOV)

- a. Each item must correlate to the project schedule.
- b. Schedule of Values to contain a two and one-half (2.5%) percent line item for the closeout documents
- c. Schedule of Values to reflect detailed tasks by labor and material.
- d. Contractor to include a separate line item for each item listed below:
 - 1) Overhead and Profit.
 - 2) General Conditions.
 - 3) Material and Labor for each task or based on subcontracted work. This will allow KCHA to pay for materials purchased at the beginning of the project or during the course of construction (once KCHA has established that the Contractor has ordered, has been invoiced, and has a suitable location to store materials. See Contract documents for requirements.)
 - 4) Mobilization.

3. Submittal Schedule

All submittals to King County Housing Authority (KCHA) prior to start of related work.

Rev Date: 06-06-23 Page 4 of 20

- a. The Contractor shall provide and manage a schedule of all submittals required on the project as listed in each specification section.
- b. Submittals will be processed with enough time for the Owner to reasonably provide feedback fourteen (14) calendar days prior to materials being delivered to the site.
- c. Any material submitted that is not listed in the project specifications will need to be submitted with a Substitution Request Form for review.
- **4. Site Specific Safety Plan**: The Site Specific Plan should be submitted for review then kept on site during construction. Verify regular safety meetings are being held per proposed plan.

Contractor's employees and all sub-contractors' employees will be required to wear a mask if they are asked to do so by a resident or property manager while in a building or a resident's unit.

- **5. Phasing and Coordination Plan** including the following (See section 3 item I, regarding Phasing):
 - a. Resident access plan for entry and exiting of apartment units.
 - b. Resident parking plan for proposed parking lot closings and openings.
- **6.** Subcontractor List with the names all subcontractors including contact information.

*NOTE: All items stated above must be submitted and approved BEFORE Contractor commences work.

B. Construction Administration

- 1. Master Schedule: The Contractor shall maintain (update and track) the provided project master schedule using CPM for the project. This work will progress and be reflected with the project SOV. Project phasing shall be reflected in the master schedule. The Contractor is responsible for all scheduling and coordination between all trades and any other subcontractors working for the Contractor.
- 2. Two (2) Week Look-Ahead: The Contractor will provide weekly a two (2) week "look-ahead" schedule updating the relationship of this report with master project schedule. This shall be provided for review and be a topic of discussion during weekly site meetings. This schedule will be specific to the individual tasks as well as to identify work requiring site notifications and coordination.
- **3. Daily Reports:** Contractor to provide copies of daily site reports on a weekly basis. The daily report will describe daily man power, weather conditions, work in progress, delays and issues. Daily report format shall be submitted (during pre-construction phase) to Owner for review.
- **4. Meeting Minutes:** Contractor to manage and provide copies of meeting minutes/notes for all pre-construction, coordination, safety and weekly Owner/Architect/Contractor (OAC) meetings. Meeting minutes format to be submitted (during pre-construction phase) to Owner for review.
- **5. Notices:** It is the Contractor's responsibility to plan, coordinate and inform KCHA of work which shall require notice. Failure to provide adequate notice that results in a delay will be fully on the Contractor.
 - a. Unit Entry: The Contractor must coordinate unit entry with the Owner such that all required Notices-to-Tenants can be posted forty-eight (48) business hours PRIOR to Entry.
 - b. Shut Downs: Contractor will provide proper notification (minimum of seventy-two (72) business hours to the Owner and (minimum of forty-eight (48) business hours to the tenants.
 - c. General Notices: The Contractor shall provide notice to Owner related to project start, potential impacts on tenants' accessibility and moving if items which could interfere with construction progress.
- **6. As-Builts:** The Contractor will be responsible to assess and record the existing conditions of any damaged or non-working items, such as existing electrical and mechanical equipment, pipe, utilities, concrete, asphalt etc., and prior to removal of work. Contractor is responsible to

Rev Date: 06-06-23 Page 5 of 20

restore or replace all finishes that become damaged as a result of work being performed. Contractor is not responsible for repairs of existing damage. As-Built drawings shall be current-to-date and will be reviewed on-site prior to each pay application.

- **7. Certified Payrolls:** All Contractor employees and all sub-contractor employees will need to know their trade classification and pay rate.
 - a. Owner will be conducting on-site wage interviews verifying job classification and wage rate.
 - b. **HUD Non-Routine Maintenance Wage** Rates apply to this project and must be posted on-site at all times.
- 8. Punch List: When the Contractor has deemed the project as substantially complete, meaning all base bid work is complete and conforms to requirements of the specifications and quality standards established through the mockups and as stated in the contract documents, the Contractor and a KCHA representative shall thoroughly inspect and list work that is non-conforming that the Contractor must complete prior to final payment. The work may include incomplete or incorrect installations or incidental damage to existing finishes, material, and structures. The list shall be provided to the Owner for their review and approval. All punch list items are expected to be finished and accepted by the physical completion date.

C. Closeout Administration

- 1. O&M Manuals: One (1) hard copy and one (1) electronic copy of the Operation and Maintenance (O&M) manual for all major materials and equipment shall be supplied by the Contractor to the Owner upon Project completion and prior to request for final payment.
 - a. Electronic copy to be submitted for approval prior to submitting hard copy.
 - b. O&M manual will include all warranties associated with the Work.
 - c. O&M manual will include relevant data associated with warranties and works such as
 - 1) Name of installer with all contact information.
 - 2) Name of manufacturer and location material was purchased with all contact information.
 - d. All O&M manuals are subject to Owner approval
- **2. Final As-Built Drawings:** Upon substantial completion of the Project, the marked-up set of site documents shall be converted into as-built drawings and submitted to the Owner for review and approval.
- **3. Permits Finals:** Upon physical completion of the Project, all completed permits and permit drawings to be submitted to Owner and City of Shoreline with final sign offs.
- **4. Master Keys and Access Cards:** Upon physical completion of the Project, Contractor shall return all master keys and access cards, signing off a Key Return Form.
- **5. Punch List(s):** Upon physical completion of the Project, all lists shall be completed and signed off by the Owner.

3.0 GENERAL REQUIREMENTS

A. Acknowledgements

- 1. By signing the contract, the Contractor acknowledges that they have reviewed and can fully implement all administrative and physical aspects of the work as described in the project scope of work, specifications and drawings. The Contractor also acknowledges that they have completed an extensive site walk of the site and accepts the site conditions.
- 2. The Contractor will be responsible to assess and record the existing conditions of any damaged items, such as interior, sills, drywall, and window coverings, existing pipe, and utilities, prior to removal of work. KCHA's assumption is that all items are in good working order. Contractor is responsible to restore or replace all finishes that become damaged as a result of work being performed. Contractor is not responsible for repairs of existing damage.

Rev Date: 06-06-23 Page 6 of 20

- 3. The Contractor will provide all materials, fasteners, shoring, staging, labor, equipment, and expertise necessary to provide a quality "Turnkey" project, complete with all elements of the work, safely, on time, and within budget.
- 4. The Owner does not foresee any change orders for work resulting in site conditions that were clearly visible and present during the Mandatory Pre-bid Site Visit. By submitting a bid the Contractor acknowledges any labor, material and equipment required for a "Turnkey" project not specifically covered in the plans and specifications has been included in their base bid.
- 5. The Contractor's Superintendent or Foreman will be assigned a construction master key and will be held responsible for all costs related to the re-keying should the key be lost or stolen. If the master key is lost or stolen the Contractor will be responsible for re-keying all related locksets to a new keying system by the **end of the day** the issue is reported.
- 6. The Contactor has and will continue to field verify all visible existing site conditions, adjacent conditions/components and quantities. If there is a discrepancy between Scope of Work, Specifications and/or Drawings, the Scope of Work shall take precedence followed by the Specifications and lastly the Drawings.
- 7. Any questions occurring during bidding or construction shall be resolved by <u>direction in writing</u> from Owner. Any issues not so resolved or any conflicts between the scope of work, specifications and plans, shall result with the Contractor bidding, furnishing and installing the most stringent condition. No exceptions. Contractor must submit an RFI if a conflict exists between the scope of work, specifications and plans.
- 8. It is incumbent on the Contractor to inform the Owner of any conflicts between manufacturers' requirements and the provided plans and specifications through the RFI process and prior to submitting a bid.
- 9. Contractor must demonstrate a comprehensive understanding that all work described in the project documents is all-inclusive and results in a complete system. Contractor to provide all materials, unless stated otherwise. All tasks must be complete with uniform fit, function, form, style and type.
- 10. Permits: The Owner will obtain the building permit; all other permits (including city of jurisdiction permits or agency of jurisdiction permits) are the Contractor's responsibility. Contractor shall keep permits posted and onsite at all times
- 11. Plans & Specifications: The Contractor shall keep all associated permits and the approved permit plan set on site at all times. The Contractor will keep and maintain, on-site, a separate but complete set of construction drawings and specifications for markups and daily use.
- 12. Any damage caused by construction related activities (i.e. demolition, laydown areas) to existing physical assets to remain will be the Contractor's responsibility to correct at no cost to the Owner.

B. Staffing and Experience Requirements

- 1. The Contractor is expected to be on-site working each consecutive weekday unless directed otherwise by Owner.
- 2. A qualified and experienced full time site Superintendent or Foreman will be on site at all times.
- 3. The Contractor shall employ a sufficient number of workers and equipment to perform the Work in a diligent and expeditious manner. KCHA expects the Contractor to adequately staff the project to maintain the schedule, including reallocating and increasing staffing as needed to correct any slippage in the schedule.
- 4. Contractor and sub-contractor employees shall perform all work in a professional manner. All tasks must be complete with uniform fit, function, form, style and type.
- 5. All trades are to have a minimum of three (3) years of experience in their given trade.

Rev Date: 06-06-23 Page 7 of 20

- 6. Tradesmen must have the proper certification to perform work or to operate specific equipment that requires certifications and/or licenses.
- 7. The Contractor shall immediately remove from the site any of its employees or its subcontractors' employees, as the Owner shall deem incompetent, careless, insubordinate or otherwise disruptive to the progression of the project.

C. Quality Assurance / Quality Control

- 1. All Work shall be performed using new materials, installed plumb, level, true to the line, free of defects, and completed in a professional workmanlike manner to provide a complete, safe, and operable "Turnkey" installation.
- 2. The Contractor will follow all manufacturers' requirements and recommendations for the installation of all products to maintain the integrity of all manufacturer's warranties.
- 3. Mockups: The Contractor will provide all mockups, within his base scope, required for the project as listed in each specification section. Mockups and color samples will be produced with enough time for the Owner to reasonably provide feedback one (1) week prior to these components being staged and implemented on site. Mockups will set expectations of quality expected for the project.
- 4. Quality Assurance/ Quality Control: The Contactor will provide ongoing QA/QC at each step of work and take corrective measures prior to the next element of work being performed. This will include, but is not limited to, sequencing partial punches and substantial completions throughout the project.
- 5. Contractor responsible for subcontractor's quality of workmanship and materials, completion of scope, and scheduling on site.
- 6. It is incumbent on the Contractor to inform the Owner of any conflicts between manufacturers' requirements and the provided plans and specifications through the RFI process and prior to submitting a bid.

D. Inspection of Work

- 1. Code Compliance: All work will be code compliant and without defect for all materials and applications at time of KCHA punch inspection.
- 2. Owner Progress Inspections: All work is subject to Owner inspection and approval and is the responsibility of the Contractor until it is turned over to Owner.
- 3. Jurisdiction Inspections (as required per permit): The Contractor is required to attend all inspections, and inform KCHA representative within 48 hours prior to such scheduled inspections. Contractor is responsible for any costs associated with re-inspections for work not approved by the Authority Having Jurisdiction.

E. Site Requirements

- 1. All communication and coordination will be with Owner representatives only.
- 2. On-site tenant support services (i.e. laundry, common space, maintenance facilities and storage) must be fully accessible and operational at all times.
- 3. Work shall be coordinated not to interrupt services (i.e. garbage, mail, EMS, etc.).
- 4. Emergency and tenant access must be maintained at all times.
- 5. The Contractor is required to maintain the cleanliness of the work-site; there will be daily inspections by the Owner to verify cleanliness, safety and tenant access. The Contractor will be responsible for cleanup and housekeeping of work limits, staging areas, and Contractor's parking areas by the end of each business day. Contractor to secure all equipment, materials, and tools, ensure that unfinished work areas are protected and secure prior to leaving for the weekend.

Rev Date: 06-06-23 Page 8 of 20

- 6. No noise prior to 8:00am but layout and work setup can begin at 7:30am unless permission is granted by the Owner's Representative.
- 7. All interior work in each unit to be completed within 5 consecutive days. See Section 2 Project Administration Requirements; subsection B Construction Administration Notices.
- 8. If Unit access is required, Contractor will not enter units before 8:00AM, once proper notification has been posted by KCHA.
- 9. The Contractor is responsible for providing sanitary services, potable water and field office spaces for their agents. No public bathroom, drinkable water or office space is available onsite, for the Contractor or its agents.
- 10. The Contractor must read and comply with all safety requirements as stated in Section 4 A.
- 11. The Contractor is responsible for all necessary locates (both private and public).
- 12. See Division 1 related to staging and deliveries.

F. General Restrictions

- 1. No parking in fire lanes. Fire lanes will be uninhibited at all times for first responder and tenant service access, unless otherwise approved by Fire Marshal.
- 2. No smoking on site by any Contractor or any of the Contractor's representatives (i.e. subcontractors, suppliers, consultants, etc.).
- 3. No washing out of any materials on site will be allowed. All contaminated or silt laden water must be contained and responsibly disposed of offsite.
- 4. No loud or offensive music is permitted.
- 5. No dumping on site. Contractor will not be allowed to use Owner's waste facilities.

G. Work Hours

- 1. Work to be performed during normal hours of operation from 8:00am to 4:30 pm. There will be no work on weekends (unless prior approval has been granted by Owner). Owner does not pay overtime.
- 2. There will be no work on Owner holidays. Contractor to verify with Owner's Representative if there are any Owner holidays occurring during the duration of the project.

H. Contractor's Responsibilities

- 1. Contractor will be responsible to provide power for all work described. Contractor will not be allowed to use any on-site power unless prior approval has been granted by the Owner.
- 2. Water use available with previous approval from Owner. Contractor must obtain approval of Owner for water usage forty-eight (48) hours prior to use.
- 3. The Contractor is responsible for City of Shoreline hauling route, plans, and street use permits.

I. Project Phasing

- 1. This project will directly impact thirty (30) residential dwelling units. The Owner's expectation is to have the building protected from the elements at the end of each work day. Each window and door replacement to be swapped out on the same day.
- 2. Owner anticipates multiple sequencing sections in the envelope replacement of these buildings. The Owner's expectation is not to open up "Vast" areas of the project for prolong periods of time or shutting down public areas to accommodate staging, stock piling, mobilization or for convenience of construction. Contractor must realize and accept that this project is being conducted in a fully occupied housing development and all that it encompasses (families, elderly, children out of school, daily traffic from families coming and going at all times during the day). The Owner is not only concerned about scope, schedule and budget, but the impact on its residents. The Contractor must take these considerations in to their phasing and

Rev Date: 06-06-23 Page 9 of 20

sequencing accordingly. The Contractor must review their risk factors to accommodate these considerations in their bid.

4.0 SAFETY, PROTECTION & RESTORATION

A. Safety

- 1. Contractor shall provide and have on site at all times a site specific safety plan.
- 2. Contractor's employees and all sub-contractors' employees will be required to wear a mask if they are asked to do so by a resident or property manager while in a building or a resident's unit.
- 3. Comply with all safety and health codes within Local, State and Federal jurisdictions.
- 4. All work must operate within OSHA and State-equivalent (WISHA) standards and requirements.
- 5. The Contractor shall conduct weekly safety meetings; the minutes from these meeting are to be available to the Owner upon request. A schedule for safety meetings will be provided with the Contractor's submittal of the Safety Plan. Confirmation that the weekly safety meeting did take place and the topic of the safety meeting will be stated in the weekly site meeting minutes.
- 6. All workers on-site will wear high visibility vests or apparel with company logo or name that clearly identifies the workers.
- 7. All workers must be equipped with proper personal protective equipment (PPE) and be wearing it when appropriate or required while they are on-site (i.e. hardhat, safety glasses, ear plugs and fall arrest etc.).
- 8. Contractor to keep walkways free of debris, materials, tools and equipment at all times. Access must be maintained for residents at all times. If access is blocked or limited, the Contractor must ensure that a safe, alternative route can be maintained and accessed by residents.
- 9. The Contractor will be diligent in ensuring that all safety measures are performed at all times for all aspects of work being performed.
- 10. Work Areas shall be cordoned off with safety fencing and/or caution tape while work is in progress.
- 11. Contractor is responsible for safety and security of work areas affected by work and will provide temporary guardrails, temporary cover and/or locks for openings. Contractor's main focus is the safety of his work force and the safety of KCHA's residents and staff.
- 12. The Contractor is responsible to secure all materials and equipment to prevent damage and to also take precautions to prevent theft of their personal items.

B. Protection

- 1. Protect existing roofing, concrete walkways, paving, landscaping and all other finished surfaces which are to remain.
- 2. Contractor will provide protection at landscape areas where material laydown, storage, construction trailers or equipment are stored.
- 3. Contractor is responsible to protect and maintain all areas within the project work limits including, but not limited to, landscaping, hardscapes, exterior amenities, existing improvements, and adjacent/abutting finishes to remain (roofing, soffits, selective doors, etc. If necessary, Contractor shall coordinate with Owner for removal / relocation of tenant property on back patios.
- 4. See individual scope item related to protection Dust and debris control Best Management Practices (BMPs) will be applied daily in all work areas
- 5. All construction activities, including staging and traffic area, shall be prohibited within five (5') feet of drip lines of protected trees.

Rev Date: 06-06-23 Page 10 of 20

C. Restoration

- 1. Contractor responsible for restoration of any damage due to construction related activities. Contractor is advised to do a pre-construction walk and do an assessment with KCHA site personal prior to construction to note and document existing conditions.
- 2. Contractor will restore all landscape impacted by construction to existing pre-construction conditions.
 - a. Grass areas that are identified for replacement or are damaged from construction activities are to be conditioned with new 3-way topsoil mix to a depth of (4") inches and tilled in to existing soils.
 - b. The Contractor shall roll to consolidate topsoil for areas to be sodded leaving surface smooth, uniform, firm against deep foot printing, and with a fine loose texture.
- 3. Planted areas that are damaged are to be conditioned with new wood chip mulch:
 - a. Will be free from deleterious materials and suitable as a top dressing.
 - b. Loosen subgrade of planting beds to a minimum of 4 inches. Remove stones larger than 1" and sticks, roots, rubbish and other extraneous matter and legally dispose. Mulch shall contain minimal nutrient content.
 - c. Areas shall be conditioned with new top soil, tilled in to a depth of two (2") inches, and then two (2") inches of mulch placed throughout the affected area. Mulch should be a minimal nutrient, non-growth promoting mulch (non-die/stain/colored, wood chip/mulch, mulch that does not promote growth) spread around the affected area and section of planting bed/box/defined area. Contractor should work with KCHA to determine limits of mulch required for the project.

D. Hazardous Materials

1. There are no findings of lead based paint or asbestos materials found on the construction of this building.

5.0 DIVISIONS

DIVISION 1 GENERAL CONDITIONS

A. Site Staging and Deliveries

- 1. Contractor will coordinate bulk material deliveries with Owner forty-eight (48) hours prior to delivers where potential for parking access will be temporarily blocked no more than fifteen (15) minutes.
- 2. Contractor and subcontractors will only be allowed to off load and load up tools no more than fifteen (15) minutes. Heavy equipment used specifically for construction will not block emergency access. Construction activities will not block parking areas not scheduled for work.
- 3. Contractor to use existing parking on site to stage materials in areas approved by the property manager. Property manager to designate parking spaces that will be fenced off around the perimeter and locked, to store materials for current phases of work. KCHA will work with property manager to designate areas around the building for additional material storage. No trash and debris will be stored, and must be removed from the site on a daily basis. Contractor must perform daily cleanup around staging site to ensure dust and debris does not build up in the parking lot.

B. Temporary Facilities

- 1. Use of onsite restroom facilities will not be permitted. Contractor is responsible for portable toilets; Contractor to consult with Owner for placement.
- 2. Contractor is not permitted to use tenant or building power without KCHA approval. For bidding purposes, Contractor is to provide power for this project.

Rev Date: 06-06-23 Page 11 of 20

3. Contractor to provide all dumpsters, job shacks, con-x boxes, fencing etc. Locations to be negotiated and approved by Owner.

DIVISION 2 SITE CONSTRUCTION

A. Demolition

Refer to Specification Section 024100 Selective Demolition.

- 1. The Contractor shall remove and legally dispose of all materials as required by the contract documents to allow for the installation of all new specified materials. Materials included to be removed and disposed of are as follow (but non-inclusive): gutters, downspouts, siding, foam board, exterior drywall, fasteners, exterior trim, windows, exterior doors, door hardware, window coverings, hose bibs, exterior lighting fixtures, and all related envelope assembly components from structure per scope of work, drawings and specifications.
- 2. Contractor shall salvage and/or protect all materials as necessary until they are to be reinstalled, (i.e. select hardware, sliding glass doors, communication boxes, fire alarm components, exterior lighting, pipe penetrations, etc.). This list is not all inclusive and the Contractor must verify which items are to be salvaged per the contract documents and in coordination with the Owner prior to demolition activities.
- 3. Install temporary barriers as necessary to protect tenants and staff during demolition. Take precautionary measures to close off access to the decks from the units, but ensure that the measures taken can be easily breached by first responders in case of emergency. It is the Contractor's responsibility to notify the Fire Marshal that work is being done on the decks and landings and that the ingress and egress from the units have been temporarily modified.
- 4. Recycling efforts will be performed to the fullest extents possible as specified in the contract documents. Contractor to comply with recycling measures and reporting per Specification section 01 74 19 Construction Waste Management and Disposal.

B. Existing Utilities

- 1. The Contractor is responsible to locate all public and private utilities which may impact the work.
- Contractor to verify any existing equipment, devices, fixtures, cabling, wires and conduit is in
 operational order prior to moving, relocating, replacing or rerouting. KCHA makes the
 assumption that equipment was working prior to Contractor's arrival on site and should
 continue to work at the end of the project.
- 3. Contractor to include in bid all necessary modifications, labor and parts necessary to run/reroute all existing cabling and exposed conduit. All costs associated with work noted will be Contractor's responsibility.
- 4. The Contractor will coordinate the decommissioning of electrical, plumbing, fire and HVAC elements with the Owner and respective service providers.
- 5. Contractor responsible for repairing all wires, cables, communication boxes etc. damaged by construction activities on same day incident occurs.
- 6. Contractor responsible to pull utility boxes (cable, phone and electrical meters) away from building surface to allow installation of insulation and siding assembly per manufacturer's instructions. It is the Owner's expectation that the Contractor will not be required to shut power off to the building or unit to install siding. These conditions must be approved by both Contractor and Owner prior to demolition.
- 7. Contractor is responsible to air seal and /or fire seal all penetrations, vents and appurtenances.
- 8. Contractor is responsible to carefully remove and protect all utility and communication services (including fire components) on structure to be reinstalled. Services shall be maintained and

Rev Date: 06-06-23 Page 12 of 20

operational for duration of project unless otherwise scheduled disruption is required to perform work.

9. Terminations and caps will be clearly marked on site and recorded in the project record drawings (i.e. red line drawings or as-builts) with clear and accurate dimensions.

C. Landscaping

- 1. Prior to start of work, the Contractor and Owner shall walk the site identifying the condition of all trees, plants, and landscaping. Any trees, plants, grass etc. damaged due to construction activities must be replaced by the Contractor with like vegetation at Contractor's expense.
- 2. Restore all landscape impacted by construction to existing pre-construction conditions. Grass areas to be restored with sod. See requirements above in Section 4, Subsection C.

D. Locating And Utilities

- 1. Contractor responsible to locate all public and private utilities that may be impacted by construction work.
- 2. Contractor to be responsible to repair and or replace all utilities and building components damaged by construction work.

DIVISION 6 WOOD & PLASTICS

A. Rough Carpentry

Refer to Specification Section 061000.

- 1. Contractor is responsible for all additional blocking, framing, and specified hardware to incorporate seismic upgrades as noted on structural pages S.01, S.02, S2.0, S2.1, and S3.0.
- 2. Contractor to install ½" fire rated wall sheathing as noted on wall assembly and exterior details per plan page A8.0.
- 3. Contractor to make all modifications to existing decks once walls are removed to incorporate new fiberglass railing system. Refer to exterior details noted on A8.1.
- 4. Contractor is responsible to shim, modify and repair minor irregularities in the assemblies in order to produce a finished product that is consistent in plane prior to cover. The Contractor will be responsible to ensure that all new components provide the necessary structural support for new elements to be installed as well as plane out with existing surfaces.
- 5. Contractor will be responsible for 100% blocking required for all GWB patching.
- 6. The Owner anticipates that there may be some compromised structural members and these will be addressed on a Time and Material basis. Contractor must receive KCHA approval prior to any additional work being performed outside the contract scope of work. KCHA must also document damage prior to the Contractor removing compromised components. Failure to do this may result in the Contractor burdening the cost of replacement.

B. Finish Carpentry

Refer to Specification (Section 062000)

- 1. Use lengths of material that when installed provide minimal amount of splicing. All splices are to be weather cut in the correct direction and all ends sealed.
- Contractor to provide labor and materials to complete interior finish carpentry inclusive of the modification, removal of interior trim items such as door and window casings, interior blinds and drywall repair.
- 3. Interior base shall be modified as necessary for the proper installation of doors and casing. Base shall match existing.
- 4. Interior side of storage closets on decks will be trimmed with flat stock MDF to cover the gap between the new door jamb and existing GWB.

Rev Date: 06-06-23 Page 13 of 20

- 5. The Contractor shall be responsible for the repair of any damage to interior GWB that is incurred from the modification, removal and replacement of the interior finishes (i.e. interior door and window casing) GWB, texture and paint repairs shall be required at areas where new trim does not cover the caulk line of the old trim.
- 6. For all GWB repairs, labor and materials will be included to patch, texture and paint to match existing adjacent surfaces. Match texture to blend in with existing texture and paint corner to corner, top to bottom.

C. Fiberglass Railing System

Refer to Specification Section 068100

- 1. General Contractor to provide labor and materials to install fiber glass railing system at locations identified per plan.
- 2. Provide all necessary blocking to meet manufacturer's requirements. Refer for plans and specifications for location and quantity.
- 3. Contractor shall field verify and measure prior to fabrication of installation.
- 4. Contractor shall submit shop drawings prior to fabrication.

DIVISION 7 THERMAL AND MOISTURE PROTECTION

A. Thermal Insulation

Refer to Specification Section 072100

- 1. Contractor to install 1" exterior Mineral Wool Block and Board insulation at locations noted per plan. Refer to detail 16/A8.0 for wall assembly.
- 2. Contractor to install batt insulation in exterior wall where there are gaps or missing insulation.
- 3. Trim insulation neatly to fit in spaces.
- 4. Insulating foam sealant for filling perimeter window and door shim spaces and crevices in exterior wall and roof.

B. Weather Barriers

Refer to Specification Section 072500

- 1. Prior to mass production, the Contractor will provide a mockup of the WRB and associate flashing at openings and penetrations to demonstrate the method of installation incorporating interior and exterior corners, windows, and exterior doors that demonstrates quality and performance. The <u>Contractor shall coordinate inspection and approval of mockup with manufacturer's</u> and Owner's representatives prior to commencing with siding installation.
- 2. Weather resistant barrier to be DuPont Drain Wrap or approved equal. Contractor to use same source for all WRB accessories, (Seam Tape, Wrap Caps, etc.).
- 3. Upon completion of any corrective work to structure or plane, and by sequence, install all uniform weather resistant barrier, flashing, wrap and sealants prior to installation of new vinyl windows, pre-hung fiberglass door units to meet new finish dimensions. All corners and penetrations will be sealed per manufacturer's requirements for installation.

C. Fiber Cement Siding

Refer to Specification Section 074646

- 1. The Contractor to provide all labor and materials for the installation of a complete siding system, inclusive of all siding, trim (i.e. inside and outside corners, window and door casings, mounting blocks for lighting, fixtures, hose bibs), all necessary caulking and fasteners. Refer to specifications for dimensions of various sizes and depth of siding materials.
- 2. Contractor is responsible to correct any substandard structural, level and plumb framing components prior to cover. The Contractor will be responsible to ensure that all existing

Rev Date: 06-06-23 Page 14 of 20

- components provide the necessary structural support for new elements to be installed, as well as flush out with existing adjacent surfaces.
- 3. Contractor is to provide qualified and experienced caulker for all sealant work. Caulk all nail holes and gaps less than 1/4" with high quality paintable latex caulk. Gaps greater than 1/4" will not be accepted. No over application, smears or ruts will be accepted. Contractor to provide a caulking mock-up. Once approved by the Owner, the Contractor will be required to apply caulking for the entire project per quality of excepted mock-up. Prior to paint application, the owner will inspect siding, trim and caulking for uniform fit and finish. Only after Owner approval may Contractor proceed to exterior painting.
- 4. Provide <u>weather cuts</u> at all vertical trim and corner boards, and prime all cuts. All end cuts will be sealed and painted prior to installation.
- 5. All exterior trim shall be shimmed, planed and back cut as necessary to provide a smooth and even surface at joints.

D. Sheet Metal Flashings and Trim

Refer to Specification Section 076200

- 1. The Contractor shall provide labor and materials to install metal flashings and counterflashings, at perimeter edge, window and door heads, fixture blocking, as required for weathertight installation.
- 2. All windows head flashings shall not have any penetrations and shall have appropriate end dams formed to prevent water penetration (i.e. hemmed edges, soldered corners, plastic cement, etc.). All related finishes shall be pre-painted however, where necessary, these surfaces must be rust-proof, primed and/or can accept exterior paint without blemish.
- 3. Contractor will be responsible to extend all existing duct work to beyond newly installed wall assembly.
- 4. Flashing Material: Fabricate from pre-finished G90 galvanized sheet steel, 24 gauge, Kynar 500 (PVDF) finish. Color as selected by Owner from standard color chart.
- 5. Contractor to provide and install site-rolled (5") inch aluminum 20 gauge K-Style gutters and (2x3) downspouts. The gutter and downspout metals shall be Kynar 500 (PVFD) finish, color selected by Owner from standard color chart.
- 6. Contractor shall provide new PVC down spout adapter cap and where applicable, reducer and vertical run of pipe to new downspout connection.
 - a. All gutters will be installed with Gutter Debris Protection per specification.
 - b. All gutters and downspouts to be installed plumb and parallel to adjacent building lines.

E. Joint Sealants

Refer to Specification Section 079200.

- 1. Provide joint sealants, joint fillers and accessory joint material from a single manufacturer for each different product required to ensure compatibility.
- 2. Coordinate as required with other trades to assure proper and adequate provision in the work of those trades for interface with the work.
- 3. Clean and remove loose materials and foreign matter which might impair adhesion.
- 4. Sealant to be high quality and paintable. See specifications for acceptable products.
- 5. If sealant flashes once painted, contractor will be responsible to sand and repaint until corrected.
- 6. Contractor is responsible for fire caulking all joints and penetrations at fire-resistance-rated and smoke-resistant assemblies. Contractor to comply with manufacturer requirements and all applicable codes per jurisdiction.

Rev Date: 06-06-23 Page 15 of 20

DIVISION 8 OPENINGS

A. Fiberglass Doors

Refer to Specification Section 081613

- 1. Contractor is responsible to field verify all door openings prior to pricing and ordering materials. The Contractor will provide complete door systems including all shimming, flashings, proper fitting thresholds, air sealing, door painting, trims, drywall repairs and interior painting.
- 2. Exterior door removal and replacement noted patio and storage doors per door schedule A8.2.
- 3. The Contractor shall provide and install new pre-finished fiberglass doors, *composite jambs*, *bored*, *mortised and machined to fit the hardware specified per the door hardware schedule*.
- 4. All doors will be installed true, level and plumb with square and consistent reveals and close (and latch) firmly with the single push of a hand (i.e. entry closers, bomber hinges, etc.) and provide a proper seal and not allow daylight to be seen on from either side of door.
- 5. Provide and install transition strips between existing flooring and new threshold at interior of front door, storage door and patio door. This condition occurs where there is a difference between the existing door threshold and new door threshold. Provide extended metal threshold or metal trim to cover gap between new door threshold and existing carpet.
- 6. Thresholds shall be installed on a firm foundation and supported to prevent bow or bend when pressure is applied to threshold. Where applicable thresholds will be secured with pressure treated materials or with non-shrink grout between threshold and concrete slab. Contractor shall us shims, adhesive, or other approved materials that will prevent threshold from bow or bending when pressure is applied.
- 7. Removal and replacement of any trim or base molding on the interior of the entry doors and sliding glass doors will be part of the scope of work. These locations may require additional fill pieces to create a flush smooth surface and are to be included in Contractor's bid price
- 8. Contractor to protect all doors prior and during installation. KCHA will not accept doors damaged during transport or installation.
- 9. All doors and frames to be removed and replaced within the same day.

B. Vinyl Windows

Refer to Specification Section 085313

- 1. Contractor to provide and install all new Milgard Tuscany white vinyl windows per window schedule noted on plan page A8.3.
- 2. Contractor will be responsible for repairs of damage screens until punch walk is complete.
- 3. **All windows to have fresh air ventilation systems**. Vents to be vinyl construction which match color of new windows.
- 4. Remove all windows' blind treatments, and associated hardware, patch walls where existing brackets/hardware are removed. *Contractor to provide temporary window coverings or maintain existing blinds until new are installed.*
- 5. Contractor will be responsible to mask off area of work and clean area of work inside of residential units at the end of each work day at a minimum. This includes floors, walls, and tenant belongings.
- 6. Contractor will have five (5) consecutive working days to complete <u>all</u> interior work per unit.
- 7. Contractor to clean all newly installed windows inside and out. Remove all stickers.
- 8. Mock-ups will be required for KCHA approval demonstrating flashing and weather resistant barrier (WRB) applications are consistent with manufacturer's recommendations. **The**

Rev Date: 06-06-23 Page 16 of 20

Contractor shall coordinate inspection and approval of mockup with manufacturer's representative and KCHA prior to window installation.

C. Door Hardware

Refer to Specification Section 087100

- 1. Contractor to provide a complete finish hardware and suitable fastenings for the Project in accordance with Drawings, Specifications and Schedules.
- 2. Contractor to coordinate keying with Owner prior to ordering. New patio door, and storage doors will be keyed to match existing front unit door schedule.
- 3. New exterior electrical/maintenance storage doors will be keyed to match KCHA master key.
- 4. Contractor to provide KCHA with a Master Keying Biting Schedule of all new cores.
- 5. Contractor to salvage all existing door hardware and return to KCHA.
- 6. Contractor to coordinate key exchange with Property Manager five (5) business days prior to new lock installation.
- 7. Property Manager will distribute keys to residents.

DIVISION 9 FINISHES

A. Gypsum Board Assemblies

Refer to Specification Section 092116

- 1. Contractor will patch any interior wall damage incurred during construction. All GWB patches to have 100% blocking at all 4 sides. 2x material and ³/₄" plywood is acceptable for backing. All work for existing finishes to be performed in accordance with safe work practices.
- 2. For all GWB repairs labor and materials will be included to, patch, texture and paint to match existing adjacent surfaces. Match texture to blend in with existing texture and paint corner to corner, top to bottom.
- 3. Contractor will protect all resident possessions and finished surfaces from dust, joint compound, tape, texture or overspray.

B. Fluid Applied Coating

Refer to Specification Section 096700

- 1. Contractor will remove subfloor ridges and bumps, including any adhesive or existing flooring material. Fill low spots, cracks, joints, holes, and other defects with subfloor filler.
- 2. Apply, trowel, and float filler to achieve smooth, flat, hard surface. Grind irregularities above the surface level. Prohibit traffic until filler is cured.
- 3. Vacuum clean substrate.
- 4. Apply primer to surfaces required by flooring manufacturer.
- 5. Finish to small level surface.
- 6. Extend into door openings and extend into storage closet as noted on drawings.

C. Exterior Painting

Refer to Specification Section 099113

- 1. Contractor will provide labor and materials to paint exterior fascia boards, barge boards, soffits, siding, trim, exposed blocking, doors, jambs and all other surfaces to be painted per scope of work, drawings and specifications.
- 2. Contractor will prep, sand and prime existing metal handrails located at East and West building entry and handrail along west elevation sidewalk.
- 3. Contractor will use metal paint application to assure proper adhesion.
- 4. Contractor to submit all paint drawdowns for Owner approval prior to paint applications.

Rev Date: 06-06-23 Page 17 of 20

- 5. Contractor will provide all necessary prep work including caulking, sanding and priming to prepare all finishes for a complete uniform paint application.
- 6. Caulking shall be neat and consistent applied by an experience applicator. Contractor to include caulking as part of the siding and trim mock-up to establish quality expectations.
- 7. All caulking and putty will be allowed to cure per manufacturer's instruction prior to paint touch up. (Refer to Section 079200 Joint Sealants). Caulk to be high quality paintable latex caulk. Caulk and/or putty all joints, seams and nail holes using approved materials and methods as specified and per manufacturer's instructions. All caulking and putty to be applied in a smooth and uniform fashion without defect, gaps, seams, or smears to plane and seamlessly integrate with abutting surfaces (this includes interior trim work).
- 8. Touchup shall be allowed for interior walls unless there is otherwise noticeable variation of the new versus the existing paint color/texture. Interior walls shall be painted from corner to corner, top to bottom.
- 9. All doors and jambs to be pre-painted (all six [6] sides) prior to installation.
- 10. Primer is NOT considered a pre-painted finish for the top and bottom of door.
- 11. Any metal work should be coated with metal self-etching primer prior to painting.
- 12. Contractor will be responsible for full protection of door finish (up to substantial completion) and will be responsible for repair and repaint of all doors top to bottom.

Touch up paint will not be accepted by KCHA. Full door will be painted

D. Interior Painting

Refer to Specification Section 099123

- 1. Contractor will protect all resident possessions and finished surfaces from dust, mud, texture or overspray and clean and/or replace any items not to receive paints and coatings.
- 2. This work shall be inclusive labor and materials to perform surface preparation, fill, sanding and prime and paint.
- 3. Interior trim will be pre-painted prior to install. Nail holes will be filled and wiped clean and touch up paint included.
- 4. Hand paint all surfaces necessary to provide a uniform and aesthetic paint application per plan.
- 5. All caulking and putty will be allowed to cure per manufacturer's instruction prior to paint touch up. (Refer to Section 079200 Joint Sealants). Caulk to be high quality paintable latex caulk. Caulk and/or putty all joints, seams and nail holes using approved materials and methods as specified and per manufacturer's instructions. All caulking and putty to be applied in a smooth and uniform fashion without defect, gaps, seams, or smears to plane and seamlessly integrate with abutting surfaces.
- 6. Contractor will patch, texture and paint to match any existing interior or exterior wall or siding damage incurred during demolition or installation.
- 7. Interior walls will be painted from corner to corner, top to bottom. Contractor may not feather in unless prior approval is given by Owner.
- 8. Interior doors and jambs will be painted a separate color from the exterior. Doors to be painted on all sides. Contractor to coordinate with Owner's representative in regards to color, placement and line breaks.
- 9. Contractor will supply all interior paint to match existing and leave 1 gallon of each color and type in location designated by building staff.

Rev Date: 06-06-23 Page 18 of 20

DIVISION 12 FURNISHINGS

A. General

Refer to Specification Section 122116

- 1. The Contractor is responsible for removing existing horizontal and vertical blinds. Provide and install new window blinds with matching valances included, to match existing color and operation. Verify all measurements prior to placing new order due to window installation modifications, allow no more than ½" gap either side of jamb. All openings must be verified.
- 2. Slider lift cord lengths will be modified to be twelve (12") inches above floor. Window lift cord lengths will be modified to be twelve (12") above sills.
- 3. Contractor to consider how scribe molding will impact installation of window blinds. Contractor will be responsible for making all adjustments for proper fit.
- 4. All window blind components (blinds, brackets, control rods, hooks, pull chords) will be defect and blemish free and adjusted, cleaned, and protected prior to final acceptance.

DIVISION 22 PLUMBING

A. General

Refer to detail 15/A8.0

- 1. Contractor shall schedule and coordinate water shut offs forty-eight (48) hours in advance, work shall be inclusive of all labor and materials necessary to complete installation.
- 2. Existing hose bibs to be removed, extended and reinstalled to allow new blocking and siding assembly.
- 3. Hose bibs shall be mounted to a fiber cement block consistent in size and with even 2" reveals on all four sides. Extend supply piping as required to install new hose bib. Extend water heater overflow pipes to accommodate new siding profile.
- 4. Hose bibs and blocks shall be pre-drilled and fastened securely with stainless steel screws. Blocks shall be installed over appropriate flashing panel (as specified in Section 072500 Weather Barriers) and be flush, level and cleanly caulked. Coordinate with siding contractor for all blocking and head flashing prior to installation.
 - a. Installation of necessary blocking from the exterior wall to assure stable and sturdy install.
 - b. Install all blocking and flashing as noted per plan 15/A8.0.
 - c. Provide and install new extension piping for all hose bibs and water heater drain pipes as a result of mounting block application and wall thickness changes.

DIVISION 26 ELECTRICAL

A. General

Refer to Specification Section 260005, 260519,260526, 260532, 260533 265600

- 1. Contractor to provide removal and disposal of selected lighting and removal and reinstallation of other selected lighting as noted per plan.
- 2. Exterior lighting will be in operation by end of each work day. Temporary lighting must be provided and operational if necessary.
- 3. Contractor to install new patio exterior lights per Contractor verified quantities.
 - a. Install all light mounting blocks and head flashing per plan.
 - b. See Lighting Specifications Section 265100 2.01 new LED Lighting fixtures.
 - 1) Fixtures to be Luminaire LED Swoop series.
 - c. The Contractor will provide and install junction boxes which are missing or damaged. Extend junction boxes as required to fit all mounting blocks or new materials. The

Rev Date: 06-06-23 Page 19 of 20

Contractor should carry a small budget for the material and labor associated with cutting and installation of junction boxes.

- d. All lights to be new and in working condition.
- 4. Contractor to verify all existing equipment, devices, fixtures, cabling, wires and conduit is operational prior to relocating, replacing or rerouting. Contractor assumes final responsibility that such accessories are operational at final project acceptance.
- 5. Contractor to include in bid all necessary modifications, labor and parts necessary to run/re-route all existing cabling, exposed conduit and wires behind new siding where possible. Provide new exterior PVC latching surface cable raceway painted to match adjacent surfaces.
- 6. Contractor to remove and dispose of abandoned wires and cable prior to installation of new siding.
- 7. Contractor to remove exterior GFI outlets and replace with new exterior GFI outlets with waterproof cover. Include all electrical extension boxes and wiring as needed. Coordinate with siding contractor for mounting blocks and head flashing prior to installation.
- 8. Contractor to provide parts and fittings to re-mount all card access readers, door activators, fire alarm devices, lockboxes on fiber cement blocks. Extend wiring as required to fit new blocks.
- 9. Contractor is responsible to air and fire seal all penetrations, vents and appurtenances.
- 10. Contractor to have rough in inspections performed and approval to cover from authority having jurisdiction prior to cover.
- 11. Contractor shall have a lock out/ tag out procedure in place while performing any electrical service work.
- 12. Reattach all pre-existing utility and communication services so that components are installed plumb and parallel to adjacent building lines.

END OF SECTION

Rev Date: 06-06-23 Page 20 of 20

SECTION 01 1000 SUMMARY

PART 1	GENERAL	
1.1	RELATED DOCUMENTS	
A.	Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 01 Specification Sections, apply to this Section.	
1.2	SUMMARY	
A.	 This Section includes the following: Work covered by the Contract Documents. Phased construction. Work under other contracts. Owner-furnished products. Owner's occupancy requirements. Applicable Codes. Reference standards. Use of premises and work restrictions. Specification formats and conventions. Execution, correlation and intent – Contract Documents. 	
1.3	WORK COVERED BY CONTRACT DOCUMENTS	
A.	Project Identification: 1. Project Name: 2. Project Location: PEPPER TREE ENVELOPE 19926 Ballinger Way NE, Shoreline, WA 98155	
В.	Owner/Developer: King County Housing Authority 1. Owner's Representative: 2. Contact Phone: 206-574-1283	
C.	Architects / Engineer: 1. Representative: SHKS 2. Contact Phone: 206-675-9151	
D.	Reference Section A of the Bid Documents for scope of work.	

A. Construction shall be phased to accommodate Owner's desired schedule as noted in the bid documents and/or drawings, if applicable. Final Project Schedule shall include

PHASED CONSTRUCTION

1.4

phasing schedule to be prepared by the Contractor, and reviewed and approved by the Owner.

- B. Contractor shall prepare a phasing plan to maintain access to residential units during construction. Plan to be reviewed and approved by Owner prior to Work commencing.
- C. Before commencing Work of each phase of construction, submit an updated copy of Contractor's Final Project Schedule showing the sequence, commencement and completion dates, and move-out and -in dates of residents for all phases of the Work.

1.5 WORK UNDER OTHER CONTRACTS

A. General: Cooperate fully with separate contractors so work on those contracts may be carried out smoothly, without interfering with or delaying work under this Contract. Coordinate the Work of this Contract with work performed under separate contracts.

1.6 OWNER-FURNISHED PRODUCTS

- A. Owner will furnish products as indicated. This section includes receiving, unloading, handling, storing, protecting, and installing Owner-furnished products.
- B. Owner-Furnished Products:
 - 1. Products and materials as noted on drawings or otherwise indicated for re-use.
 - 2. Products and materials as noted on drawings or otherwise indicated to be supplied by Owner.

1.7 OWNER'S OCCUPANCY REQUIREMENTS

- A. Owner Occupancy of Completed Areas of Construction: Owner reserves the right to occupy and to place and install equipment in completed areas of the building before Substantial Completion. Such placement of equipment and partial occupancy shall not constitute acceptance of the total Work. PRIOR to partial Owner Occupancy:
 - 1. Owner will prepare a Certificate of Substantial Completion for each specific portion of the Work to be occupied.
 - 2. Contractor is responsible for obtaining a Certificate of Occupancy from authorities having jurisdiction before Owner occupancy.
 - 3. The mechanical and electrical systems shall be fully operational; all required tests and inspections shall be successfully completed for areas to be occupied. On occupancy, Owner will operate and maintain mechanical and electrical systems serving the occupied portions of building.
 - 4. On occupancy, Owner will assume responsibility for maintenance and custodial service for the occupied portions of building.
 - 5. Coordinate insurance requirements with Owner prior to Owner occupancy of completed areas of the building.
- 1.8 CUTTING & PATCHING Refer to Section 01 7329 Cutting and Patching.

1.9 APPLICABLE CODES

A. Perform all Work in accordance with the current code requirements of the city holding jurisdiction over the site where Work is to be completed.

B. Certification of Code Compliance: All materials, methods and equipment shall comply with requirements of applicable codes and the Contract Documents, including requirements of all incorporated standards. The Contractor shall furnish, as a part of the Contract, certification of such compliance if requested by the Architect or the Code Enforcing Agency. Such certification shall be submitted in the form of test results or other data from a recognized independent testing laboratory. Contractor shall coordinate and provide all required submittals to the Code Enforcing Agency in a timely manner so as to not delay progress of the Project.

1.10 USE OF PREMISES AND WORK RESTRICTIONS

- A. General: Contractor shall have full use of premises for construction operations subject to phased construction requirements as specified in this Section and as indicated on Drawings by the Contract limits.
 - 1. Security Procedures: Refer to the Scope of Work Division 1, Section 4 Safety, Protection & Restoration and 01 5000 Temporary Facilities and Controls, for required security procedures to be followed while working at this building.
 - 2. Contractor Identification: All Contractors on site shall be easily identifiable and must wear clothing, name badges, hardhats, safety vests, or other visible identification or identifying article (approved by Owner) with employee's, laborer or staff member's company logo or company name.
- B. Use of Site: Limit use of premises to areas within the Contract limits indicated. Do not disturb portions of Project site beyond areas in which the Work is indicated.
 - 1. Limits: Confine construction operations to areas as indicated on drawings.
- C. Use of Parking Lot: Limited.
- D. Work Restrictions, General: Comply with restrictions on construction operations.
 - 1. Comply with limitations on use of public streets and with other requirements of authorities having jurisdiction.
- E. On-Site Work Hours: Work in the existing occupied buildings will start no earlier than 8:00am, and will be completed by 4:30pm. Hours for work performed outside of the building will be at the discretion of Owner's Representative.
 - 1. Early Morning Hours: As approved by Owner's representative.
 - 2. Hours for Utility Shutdowns: Notify Owner and all affected utility companies seventy-two (72) hours in advance of proposed shutdown.
 - 3. Contractor to notify residents of Work a minimum of forty-eight (48) hours prior to start of Work.
 - a. If Work progress or new work affects additional or a new set of residents, the Contractor must give a new notice of work to all affected residences a minimum of forty-eight (48) hours prior to start of Work.
 - 4. Hours for Core Drilling and other loud activities must comply with city of jurisdiction's noise codes.
- F. Nonsmoking Properties. All of King County Housing Authority properties are nonsmoking.

- G. Controlled Substances: Use of tobacco products and other controlled substances on Project site is not permitted.
- H. Employee Screening: Comply with Owner's requirements for drug and background screening of Contractor personnel working on Project site.
 - 1. Maintain list of approved screened personnel with Owner's representative.

1.11 SPECIFICATION FORMATS AND CONVENTIONS

- A. Specification Format: The Specifications are organized into Divisions and Sections using the 33-division format and CSI/CSC's "2010 Master Format" numbering system.
 - 1. Division 01: Sections in Division 01 govern the execution of the Work of all Sections in the Specifications.
- B. Specification Content: The Specifications use certain conventions for the style of language and the intended meaning of certain terms, words and phrases when used in particular situations. These conventions are as follows:
 - 1. Abbreviated Language: Language used in the Specifications and other Contract Documents is abbreviated. Words and meanings shall be interpreted as appropriate. Words implied, but not stated, shall be inferred as the sense requires. Singular words shall be interpreted as plural and plural words shall be interpreted as singular, where applicable, as the context of the Contract Documents indicates.
 - 2. Imperative mood and streamlined language are generally used in the Specifications. Requirements expressed in the imperative mood are to be performed by Contractor. Occasionally, the indicative or subjunctive mood may be used in the Section Text for clarity to describe responsibilities that must be fulfilled indirectly by Contractor or by others when so noted.
 - a. The words "shall," "shall be," or "shall comply with," depending on the context, are implied where a colon (:) is used within a sentence or phrase.

1.12 EXECUTION, CORRELATION AND INTENT – CONTRACT DOCUMENTS

- A. General: If there is a discrepancy between Scope of Work, Specifications and/or Drawings, the Scope of Work shall take precedence followed by the Specifications and lastly the drawings. Contact Owner immediately for clarification of conflicts, corrections and clarifications.
- PART 2 PRODUCTS (Not Used)
- PART 3 EXECUTION (Not Used)

END OF SECTION 01 1000

SECTION 01 2600 CONTRACT MODIFICATION PROCEDURES

PART 1 GENERAL

1.1 RELATED DOCUMENTS

A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. Section includes administrative and procedural requirements for handling and processing Contract Modifications.
- B. Related Sections:
 - 1. Division 01 Section "Product Requirements" for administrative procedures for handling requests for substitutions made after Contract award.

1.3 MINOR CHANGES IN THE WORK

A. Reference Article 7 in the General Conditions.

1.4 PROPOSAL REQUESTS

- A. The Contractor will have ten (10) calendar days from first notification to supply Owner with the information outlined in this section.
- B. Owner-Initiated Change Order Requests (COR): Contractor will issue a detailed description of:
 - 1. Proposed changes in the Work that may require adjustment to the Contract Sum or the Contract Time. If necessary, the description will include supplemental or revised Drawings and Specifications.
 - 2. Change Order Requests (COR) and Construction Change Directives (CCD) shall be initiated by the Owner, dated and sequentially numbered on Owner provided forms
 - 3. CORs are not instructions either to stop Work in progress or to execute the proposed change.
 - 4. After receipt of COR, submit a quotation estimating cost adjustments to the Contract Sum and the Contract Time necessary to execute the change.
 - a. Provide a cost breakdown, including overhead and profit as a separate line item, and time extension request as provided for in Article 7 of The General Conditions.
 - b. Provide all necessary product information, specifications, etc. required to justify any Contractor requested changes.
 - 5. The allowed markup shall cover all indirect project costs, including but not limited to, the project Overhead, Profit and General Conditions
 - a. The Contractor shall be allowed a maximum of fourteen (14%) percent Overhead, Profit, and General Conditions, on the cost of craft labor,

- equipment, small tools and materials for self-performed Change Order work.
- b. The Contractor shall be allowed a maximum of eight (8%) percent Overhead, Profit and General Conditions on the cost of craft labor, equipment, small tools and materials for Subcontractor Change Order work. The Contractor is not allowed to take profit on the profit of the Subcontractor as stated in form HUD-5370, section 29.
- c. A Subcontractor shall be allowed a maximum of fourteen (14%) percent of the cost of craft labor, equipment, materials and small tools for Overhead, Profit and General Conditions, for self-performed Change Order work.
- d. A Lower-Tier Subcontractor shall be allowed a maximum of fourteen (14%) percent of the cost of craft labor, equipment, materials and small tools for Overhead, Profit and General Conditions, for self-performed Change Order work.
- 6. Include a list of quantities of products required (or eliminated) their unit costs and a total amount of purchases and credits to be made. If requested, furnish survey data to substantiate quantities.
- 7. Indicate applicable taxes, delivery charges, equipment rental and amounts of trade discounts.
- 8. Include costs of labor and supervision directly attributable to the change.
- 9. Include an updated Contractor's Final Project Schedule that indicates the effect of the change, including but not limited to, changes in activity duration, start and finish times, and activity relationship. Use available total float before requesting an extension of the Contract Time.
 - a. Time extension requests must demonstrate the impact on the project Critical Path Schedule. See the General Conditions Article 15 and Section 01 3200 -Construction Progress Documentation.
- 10. Review all pricing provided by subcontractors and suppliers for accuracy and completeness. Verify that their scope of work is consistent with the requested change. Verify math is correct and that markup rates complies with the General Conditions.
- 11. After signing the Change Order Request or CCD, the Contractor shall return it to the Owner.
- 12. Quotation Form: Use forms acceptable to Owner.
- 13. After review of the Contractor's price, cost breakdown and requested time extension, if any, the Owner will submit for estimation and do one of the following:
 - a. Sign and route for approval.
 - b. Reject and resubmit to the Contractor for pricing correction.
 - c. Revise the Change Order Request or CCD and submit to the Contractor for repricing.
- 14. Prior to the Owner's acceptance of Change Order Requests, appropriate personnel shall also review the change requests.
- C. Contractor-Initiated Proposals: If latent or changed conditions require modifications to the Contract, Contractor may initiate a claim by submitting a request for a change to Owner.
 - 1. Include a statement outlining reasons for the change and the effect of the change on the Work. Provide a complete description of the proposed change. Indicate the effect of the proposed change on the Contract Sum and the Contract Time.

- 2. Provide a cost breakdown, including overhead and profit as a separate line item, and time extension request as provided for in Article 7 of the General Conditions.
- 3. Provide all necessary product information, specifications, etc. required to justify any Contractor requested changes.
- 4. Allowances for direct supervision, safety, small tools, overhead and profit are limited by the General Conditions, Article 7.1.1.
- 5. Include a list of quantities of products required (or eliminated), their unit costs and total amount of purchases and credits to be made. If requested, furnish survey data to substantiate quantities.
- 6. Indicate applicable taxes, delivery charges, equipment rental and amounts of trade discounts.
- 7. Include costs of labor and supervision directly attributable to the change.
- 8. Include an updated Contractor's Final Project Schedule that indicates the effect of the change, including but not limited to, changes in activity duration, start and finish times, and activity relationship. Use available total float before requesting an extension of the Contract Time.
 - a. Time extension requests must demonstrate the impact on the project Critical Path Schedule. See the General Conditions, and Section 01 3200-Construction Progress Documentation.
- 9. Comply with requirements in Division 01 Section "Product Requirements" if the proposed change requires substitution of one product or system for product or system specified.
- 10. Proposal Request Form: Use form acceptable to Owner.
- 11. After review of the Contractor's price, cost breakdown and requested time extension, if any, the Owner will submit for estimation and do one of the following:
 - a. Sign and send on for approval.
 - b. Reject and resubmit to the Contractor for pricing correction.
 - c. Revise the Change Order Request or CCD and submit to the Contractor for repricing.
- 12. Prior to the Owner's acceptance of Change Order Requests, appropriate personnel shall also review the change requests.

1.5 CONSTRUCTION CHANGE DIRECTIVE (CCD)

- A. The Contractor will have ten (10) calendar days from first notification to supply Owner with the information outlined in this section.
- B. Construction Change Directive: The Owner may issue a Field Authorization in accordance with provisions in Article 7, General Conditions. Construction Change Directive instructs Contractor to proceed with a change in the Work, for subsequent inclusion in a Change Order.
- C. Documentation: Maintain detailed records on a time and material basis of Work required by the CCD, with supporting documentation as required by CORs.
 - 1. After completion of change, submit an itemized account and supporting data necessary to substantiate cost and time adjustments to the Contract, consistent with Article 7 of the General Conditions of the Contract.

1.6 CHANGE ORDER PROCEDURES

- A. The Contractor will have ten (10) calendar days from first notification to supply Owner with the information outlined in this section.
- B. When approved and signed by the Owner, the Construction Change Directive will either be included in a Change Order Request (COR) to be charged against the Contract Allowance, or will be included in a formal Change Order, which will modify the Contract amount.
- PART 2 PRODUCTS (Not Used)
- PART 3 EXECUTION (Not Used)

END OF SECTION 01 2600

SECTION 01 2900 PAYMENT PROCEDURES

PART 1 GENERAL

1.1 RELATED DOCUMENTS

A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

A. This Section specifies administrative and procedural requirements necessary to prepare and process Applications for Payment.

1.3 DEFINITIONS

A. Schedule of Values: A statement furnished by Contractor allocating portions of the Contract Sum to various portions of the Work and used as the basis for reviewing Contractor's Applications for Payment.

1.4 SCHEDULE OF VALUES

- A. Coordination: Coordinate preparation of the Schedule of Values with preparation of Contractor's Master Project Schedule.
 - 1. Correlate line items in the Schedule of Values with other required administrative forms and schedules, including the following:
 - a. Application for Payment forms with Continuation Sheets.
 - b. Submittal Schedule.
 - 2. Submit the Schedule of Values to Owner at earliest possible date but no later than fourteen (14) calendar days after the date of bid opening.
 - 3. Sub-schedules: Where the Work is separated into phases requiring separately phased payments, provide sub-schedules showing values correlated with each phase of payment.
- B. Format and Content: Use the Project Documents as a guide to establish line items for the Schedule of Values. Lines items are based on Scope of Work and sequencing.
 - 1. Identification: Include the following Project identification on the Schedule of Values:
 - a. Project name and location.
 - b. Name of Owner.
 - c. Owner's contract number.
 - d. Contractor's name and address.
 - e. Date of submittal.
 - 2. Arrange the Schedule of Values in tabular form with separate columns to indicate the following for each item listed:

- a. Item #, including separate line for an Allowance (if applicable).
- b. Description of the Work.
- c. Total Dollar Value.
- d. Previous Application Amount.
- e. Dollar Amount Charged on Current Pay Application.
- f. Stored Materials.
- g. Total Complete and Stored.
 - Percentage of the Contract Sum to nearest onehundredth percent, adjusted to total one hundred (100%) percent.
- h. Balance to Finish
- i. Retainage
- 3. Provide a breakdown of the Contract Sum in enough detail to facilitate continued evaluation of Applications for Payment and progress reports. Coordinate with the Project Documents. Provide several line items for principal subcontract amounts, where appropriate.
- 4. Round amounts to nearest one (1) cent; total shall equal the Contract Sum
- 5. Provide a separate line item in the Schedule of Values for each part of the Work where Applications for Payment may include materials or equipment purchased or fabricated and stored, but not yet installed.
 - Differentiate between items stored on-site and items stored offsite. Include evidence of insurance or bonded warehousing per Article 9.3.2 AIA A201-2017 General Conditions.
- 6. Provide separate line items in the Schedule of Values for initial cost of materials, for each subsequent stage of completion, and for total installed value of that part of the Work.
- 7. Each item in the Schedule of Values and Applications for Payment shall be complete. Include total cost and proportionate share of general overhead and profit for each item.
 - a. Temporary facilities and other major cost items that are not direct cost of actual work-in-place may be shown either as separate line items in the Schedule of Values or distributed as general overhead expense, at Contractor's option.
- 8. Schedule Updating: Update and resubmit the Schedule of Values before the next Applications for Payment when Change Orders result in a change in the Contract Sum.

1.5 APPLICATIONS FOR PAYMENT

- A. Each Application for Payment shall be consistent with previous applications and payments as certified by Owner and paid for by Owner.
- B. Payment Application Times:
 - 1. The date for each progress payment is indicated in the Contract between Owner and Contractor.
 - 2. The period of construction Work covered by each Application for Payment is the period indicated in the Contract.
- C. Payment Application Forms:

- 1. Use Payment Application forms as provided by Owner for Applications for Payment.
- D. Application Preparation: Complete every entry on form. Notarize and execute by a person authorized to sign legal documents on behalf of Contractor. Owner will return incomplete applications without action.
 - 1. Entries shall match data on the Schedule of Values and Contractor's Final Project Schedule. Use updated schedules if revisions were made.
 - 2. Include amounts of Change Orders and Construction Change Directives issued before last day of construction period covered by application.
 - 3. Provide current Subcontractor List with each Application for Payment.
- E. Transmittal: Submit one (1) signed and notarized original Application for Payment to Owner by a method ensuring receipt within forty-eight (48) hours. The Application for Payment shall include intent to pay prevailing wages and a running spreadsheet that itemizes both the intent and affidavit of wages paid to date for each subcontractor.
 - 1. Transmit Application for Payment with a transmittal form listing attachments and recording appropriate information about the application.
- F. General Contractor Certification Upon Application For Payment: Refer to attached Exhibits in Contract.
- G. Initial Application for Payment: Administrative actions and submittals that must precede the first Application for Payment include the following:
 - 1. List of subcontractors. (Required at pre-construction conference.)
 - 2. Schedule of Values.
 - 3. Contractor's Final Project Schedule to be created in MS Project or equivalent format. (Required at pre-construction conference.)
 - 4. Certificates of insurance and insurance policies. (Required prior to contract award.)
 - 5. Performance and payment bonds. (Required prior to contract award.)
 - 6. Section 3 Work Plan, for projects whose contract value is five hundred thousand dollars (\$500,000) or higher.
 - 7. Intent to Pay Prevailing Wages must be filed with L&I.
 - 8. Contractor to provide Owner with initial Cash Flow Projections. Cash Flow Projection needs to reflect Work as detailed in Final Project Schedule.
- H. **All** Application for Payments will be reviewed for completion and correctness, including reasons outlined in A201-2017 General Conditions.
- I. Application for Payment at Substantial Completion: After Owner issues the Certificate of Substantial Completion, submit an Application for Payment showing one hundred (100%) percent completion for portion of the Work claimed as substantially complete.
 - 1. Include documentation supporting claim that the Work is substantially complete and a statement showing an accounting of changes to the Contract Sum.

- 2. This application shall reflect Certificates of Partial Substantial Completion issued previously for Owner occupancy of designated portions of the Work.
- J. Final Payment Application: Administrative actions and submittals that must precede or coincide with submittal of the final Application for Payment include the following (refer to Article 9.10 in AIA A201-2017 General Conditions:
 - 1. Completion of Project closeout requirements.
 - 2. Completion of Items specified.
 - 3. Ensure that unsettled claims will be settled.
 - 4. Ensure that incomplete Work is not accepted and will be completed without undue delay.
 - 5. Transmittal of required Project construction records to the Owner.
 - 6. Proof that fees and similar obligations were paid.
 - 7. Removal of temporary facilities and services.
 - 8. Removal of surplus materials, rubbish and similar elements.
 - 9. Operations and Maintenance Manuals
 - 10. Record Drawings (i.e. As-built drawings, redline drawings)
 - 11. Final Affidavits of Wages Paid filed with L&I.
- 1.6 SPECIAL PAYMENT REQUIREMENTS (Not Used)
- PART 2 PRODUCTS (Not Used)
- PART 3 EXECUTION (Not Used)

END OF SECTION 01 2900

SECTION 01 3100 PROJECT MANAGEMENT AND COORDINATION

PART 1 GENERAL

1.1 RELATED DOCUMENTS

A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes administrative provisions for coordinating construction operations on Project including, but not limited to, the following:
 - 1. General project coordination procedures.
 - 2. Coordination Drawings.
 - 3. Project meetings.
 - 4. Requests for Information (RFIs).
- B. See Division 01 Section "Execution" for procedures for coordinating general installation and field-engineering services, including establishment of benchmarks and control points.

1.3 DEFINITIONS

A. RFI: Request from Contractor seeking interpretation or clarification of the Contract Document.

1.4 COORDINATION

- A. Coordination: Contractor's Responsibility to coordinate construction operations included in different Sections of the Specifications to ensure efficient and orderly installation of each part of the Work. Coordinate construction operations, included in different Sections that depend on each other for proper installation, connection and operation.
 - 1. Schedule construction operations in sequence required to obtain the best results where installation of one part of the Work depends on installation of other components, before or after its own installation.
 - 2. Coordinate installation of different components with other contractors to ensure maximum accessibility for required maintenance, service and repair.
 - 3. Make adequate provisions to accommodate items scheduled for later installation.
- B. Administrative Procedures: Coordinate scheduling and timing of required administrative procedures with other construction activities and activities of other contractors to avoid conflicts and to ensure orderly progress of the Work. Such administrative activities include, but are not limited to, the following:
 - 1. Preparation of Contractor's Final Project Schedule.
 - 2. Preparation of the Schedule of Values.
 - 3. Installation and removal of temporary facilities and controls.
 - 4. Delivery and processing of submittals.
 - 5. Progress meetings.

- 6. Pre-installation conferences.
- 7. Project closeout activities.

1.5 PROJECT MEETINGS

- A. General: Contractor is responsible for scheduling and conducting meetings and conferences at Project site, unless otherwise indicated.
 - 1. Attendees: Inform participants, others who are involved and individuals whose presence is required, of date and time of each meeting. Notify Owner of scheduled meeting dates and times.
 - 2. Agenda: Prepare the meeting agenda. Distribute the agenda to all invited attendees.
 - 3. Minutes: Record significant discussions and agreements achieved. Distribute the meeting minutes to everyone concerned; send the electronic version of the meeting minutes to the Project Manager and the Project Engineer, within three (3) business days of the meeting.
- B. Pre-construction Conference: A pre-construction conference shall be scheduled before starting construction. Owner to hold the conference at Project site or another convenient location. Conduct the meeting to review responsibilities and personnel assignments.
 - 1. Attendees: Authorized representatives of Owner, Architect, and their consultants; Contractor and its superintendent; major subcontractors; suppliers; and other concerned parties shall attend the conference.
 - 2. Agenda: Owner to discuss items of significance that could affect progress, including the following:
 - a. Scope of Work.
 - b. Contract Start and End Dates.
 - c. Authority of Owner's Personnel.
 - d. Davis Bacon/Prevailing Wage Certified Payroll Reports/Labor Relations and Section 3.
 - e. Insurance Certificate, Endorsement and Performance and Payment Bonds.
 - f. General Requirements/Special Conditions.
 - g. Final Project Schedule, including Phasing.
 - h. Easements, Permits, Lines & Grades.
 - i. Contractor's Superintendent.
 - j. Subcontractor List.
 - k. Safety Plan (see attachment at end of this section).
 - 1. Tests, Samples and Observations.
 - m. Progress Meetings and Reports.
 - n. Applications and Certificates of Payment, and Retention.
 - o. Progress Payments.
 - p. Change Orders.
 - q. Warranty Requirements.
 - r. Submittals.
 - s. Temporary and Storage Facilities, Staging Areas and Jobsite Security.
 - t. Clean-up and Trash Removal.
 - u. Salvage of Materials and Spare Materials.
 - v. Record Drawings.
 - w. Substantial Completion, Final Payment and Retainage.
 - x. Recycling and Energy Conservation.

- y. Minutes: The Owner will record and distribute Pre-construction meeting minutes via email.
- C. Progress Meetings: The Contractor will conduct progress meetings at weekly intervals. (refer to Article 3.1.4 of General Conditions).
 - 1. Attendees: In addition to representatives of Owner and the Contractor, each subcontractor, supplier and other entity concerned with current progress or involved in planning, coordination, or performance of future activities shall be represented at these meetings. All participants at the conference shall be familiar with Project and authorized to conclude matters relating to the Work.
 - 2. Agenda: Review and correct or approve minutes of previous progress meeting. Review other items of significance that could affect progress. Include topics for discussion as appropriate to status of Project.
 - a. Contractor's Final Project Schedule: Review progress since the last meeting. Determine whether each activity is on time, ahead of schedule, or behind schedule, in relation to Contractor's Final Project Schedule. Determine how construction behind schedule will be expedited; secure commitments from parties involved to do so. Discuss whether schedule revisions are required to ensure that current and subsequent activities will be completed within the Contract Time.
 - 1) Contractor shall provide a short term look-ahead schedule for presentation and review at each progress meeting.
 - b. Review present and future needs of each entity present, including the following:
 - 1) Interface requirements.
 - 2) Sequence of operations.
 - 3) Status of submittals.
 - 4) Deliveries.
 - 5) Off-site fabrication.
 - 6) Access.
 - 7) Site utilization.
 - 8) Temporary facilities and controls.
 - 9) Work hours.
 - 10) Hazards and risks.
 - 11) Progress cleaning.
 - 12) Quality and work standards.
 - 13) Status of correction of deficient items.
 - 14) Field observations.
 - 15) RFIs.
 - 16) Status of proposal requests.
 - 17) Pending changes.
 - 18) Status of Change Orders.
 - 19) Pending claims and disputes.
 - 20) Documentation of information for payment requests.
 - 21) Safety
 - 22) Section 3 compliance and status
 - 3. Minutes: Contractor will record the meeting minutes.
 - 4. Reporting: Contractor will email the minutes to all concerned prior to the meeting and will distribute written copies of the minutes of the meeting to each party present and to parties who should have been present.
 - a. Schedule Updating: Revise Contractor's Two (2)-Week Look Ahead Schedule after each progress meeting. This schedule will be discussed in

- each progress meeting. Issue revised schedule concurrently with the report of each meeting.
- b. Contractor's weekly reports will consist of five (5) daily reports, each reflecting the preceding five (5) days. These reports will be sent electronically to the Owner on a schedule that will be determined at the Pre-Construction Meeting or at each progress meeting.

1.6 REQUESTS FOR INFORMATION (RFIs)

- A. Procedure: Immediately on discovery of the need for interpretation of the Contract Documents, and if not possible to request interpretation at Project meeting, prepare and submit an RFI in the form specified.
 - 1. RFIs generated from subcontractor or supplier of the Contractor must be routed through the General Contractor.
 - 2. Coordinate and submit RFIs in a prompt manner so as to avoid delays in Contractor's work or work of subcontractors.
 - 3. If a suggestion can be determined or derived at by the initiator of the RFI, it is required the suggestion be supplied with the submitted RFI. If no suggestion is given where one is possible, the RFI will be returned as incomplete.
- B. Content of the RFI: Include a detailed, legible description of item needing interpretation and the following:
 - 1. Project name and number.
 - 2. RFI Subject.
 - 3. Date.
 - 4. Name of Contractor.
 - 5. Name of Architect.
 - 6. RFI number, numbered sequentially.
 - 7. Specification Section number and title and related paragraphs, as appropriate.
 - 8. Drawing number and detail references, as appropriate.
 - 9. Field dimensions and conditions, as appropriate.
 - 10. Contractor's suggested solution(s). If Contractor's solution(s) impact the Contract Time or the Contract Sum, Contractor shall state impact in the RFI.
 - 11. Contractor's signature.
 - 12. Attachments: Include drawings, descriptions, measurements, photos, product data, shop drawings and other information necessary to fully describe items needing interpretation.
- C. Hard-Copy RFIs: Form established by Contractor's Project Management system.
 - 1. Identify each page of attachments with the RFI number and sequential page number.
- D. Owner's Action: Owner will review each RFI, determine action required and return it. Allow five (5) working days for Owner's acknowledgement of each RFI.
 - 1. The following RFIs will be returned without action:
 - a. Requests for approval of submittals.
 - b. Requests for approval of substitutions.
 - c. Requests for coordination information already indicated in the Contract Documents.
 - d. Requests for adjustments in the Contract Time or the Contract Sum.
 - e. Requests for interpretation of Owner's actions on submittals.
 - f. Incomplete RFIs or RFIs with numerous errors.

- 2. Owner's action may include a request for additional information, in which case Owner's time for response will start again.
- 3. Owner's action may include architect and/or engineer recommendation or approval of proposed solution.
- 4. Owner's action on RFIs that may result in a change to the Contract Time or the Contract Sum may be eligible for Contractor to submit Change Order Request according to General Conditions.
 - a. If Contractor believes the RFI response warrants change in the Contract Time or the Contract Sum, notify Owner in writing within five (5) days of receipt of the RFI response.
- E. On receipt of Owner's action, update the RFI log and immediately distribute the RFI response to affected parties. Review response and notify Owner within three (3) days if Contractor disagrees with response.
- F. Contractor RFI Log: Prepare, maintain and submit a tabular log of RFIs organized by the RFI number. Submit log weekly. Include the following:
 - 1. Project name.
 - 2. Name and address of Contractor.
 - 3. Name and address of Architect.
 - 4. RFI number including RFIs that were dropped and not submitted.
 - 5. RFI description.
 - 6. Date the RFI was submitted.
 - 7. Date Architect's response was received.
 - 8. Identification of related Minor Change in the Work, Construction Change Directive and Change Order Request, as appropriate.
- PART 2 PRODUCTS (Not Used)
- PART 3 EXECUTION (Not Used)

GENERAL CONTRACTOR SITE SAFETY PLAN CHECKLIST

Instructions: Please indicate whether or not your Site Safety Plan contains the following provisions.

Contractors: Site Safety Plan Evaluation

Yes	No	N/A		
[]	[]	[]	1.	Will your company have a written, established, supervised and enforced site
				safety plan for the project? (The site safety plan must be presented before
				starting work)
[]	[]	[]	2.	Does the site safety plan include an orientation and weekly safety meetings
				that show your employees and other subcontractors what they need to know to perform their job assignments safely?
[]	[]	[]	3.	Does the site safety plan describe how and when to report on-the-job injuries?
[]	[]	[]	4.	Door the site sefety plan identify on site available 1st Aid / CDD trained
				Does the site safety plan identify on-site available 1st Aid / CPR trained personnel, readily accessible first-aid and and/or access to the nearest clinic
				or hospital on job site?
<u> </u>	Г٦	ГТ	5.	Does the site safety plan identify what to do in an emergency, including how to
LJ	LJ	LJ	٥.	exit the workplace?
	[]	[]	6.	Does the site safety plan explain how employees and other subcontractors
LJ	LJ	LJ	0.	report unsafe conditions and practices?
[]	[]	ſ 1	7.	Does the site safety plan describe the required personal protective equipment
				(PPE) and the proper use and care of the PPE?
[]	[]	[]	8.	Is there an on-site Haz-com Program that identifies hazardous materials
				(Asbestos, Lead) or chemicals including instruction about the safe use and
				storage?
[]	[]	[]	9.	Does the site safety plan identify the designated representative responsible for
				job-site Safety?
[]	[]	[]	10.	Does the site safety plan describe who is responsible for performing and
				recording regular periodic site reviews, and inspections for your employees
				and subcontractors?
[]	[]	[]	11.	Does the site safety plan describe programs related to housekeeping and jobsite
			10	safety?
l J	l J	[]	12.	Does the site safety plan include a job-site specific written fall protection plan
			10	covering potential falls hazards and protections?
	<u> []</u>	_ []	13.	Does the site safety plan describe electrical and or power generation controls?
LJ		[]	14.	Does the site safety plan have provisions for trenching /excavations and/or
				confined space?

Notes:

SECTION 01 3200 CONSTRUCTION PROGRESS DOCUMENTATION

PART 1 GENERAL

1.1 RELATED DOCUMENTS

A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes administrative and procedural requirements for documenting the progress of construction during performance of the Work, including the following:
 - 1. Contractor's Final Project Schedule.
 - 2. Submittals Schedule (refer to Article 3.10.2 in General Conditions AIA A201-2017).
 - 3. Daily construction reports.

1.3 DEFINITIONS

- A. Activity: A discrete part of a project that can be identified for planning, scheduling, monitoring and controlling the construction project. Activities included in a Final Project Schedule consume time and resources.
 - 1. Critical activities are activities on the critical path. They must start and finish on the planned early start and finish times.
 - 2. Predecessor Activity: An activity that precedes another activity in the network.
 - 3. Successor Activity: An activity that follows another activity in the network.
- B. CPM: Critical Path Method, which is a method of planning and scheduling a construction project where activities are arranged based on activity relationships. Network calculations determine when activities can be performed and the critical path of Project.
- C. Critical Path: The longest connected chain of interdependent activities through the network schedule that establishes the minimum overall Project duration and contains no float.
- D. Float: The measure of leeway in starting and completing an activity.
 - 1. Float time is not for the exclusive use or benefit of either Owner or Contractor, but is a jointly owned, expiring Project resource available to both parties as needed to meet schedule milestones and Contract completion date.
- E. Fragnet: A partial or fragmentary network that breaks down activities into smaller activities for greater detail.
- F. Major Area: A story of construction, a separate building or a similar significant construction element.

1.4 SUBMITTALS

- A. Submittals Schedule: Submit one (1) electronic copy of schedule to the Owner. Arrange the following information in a tabular format
 - 1. Scheduled date for first submittal.
 - 2. Specification Section number and title.
 - 3. Submittal category (action or informational).
 - 4. Name of subcontractor (if applicable).
 - 5. Description of the Work covered.
 - 6. Scheduled date for Architect's final release or approval.
- B. Contractor's Final Project Schedule: Submit one (1) electronic copy and one (1) hard copy of initial schedule to the Owner. The hard copy should be large enough to show entire schedule for entire construction period.

1.5 COORDINATION

- A. Coordinate preparation and processing of schedules and reports with performance of construction activities and with scheduling and reporting of separate contractors.
- B. Coordinate Contractor's Final Project Schedule with the Schedule of Values, list of subcontracts, Submittals Schedule, progress reports, payment requests, and other required schedules and reports.
 - 1. Secure time commitments for performing critical elements of the Work from parties involved.
 - 2. Coordinate each construction activity in the network with other activities and schedule them in proper sequence.

PART 2 PRODUCTS

2.1 SUBMITTALS SCHEDULE

- A. Preparation: Submit a schedule of submittals to the Owner, arranged in chronological order by dates required by Final Project Schedule. Include time required for review, resubmittal, ordering, manufacturing, fabrication and delivery when establishing dates.
 - 1. Coordinate Submittals Schedule with list of subcontracts, the Schedule of Values, and Contractor's Final Project Schedule.
 - 2. Submit concurrently with the first complete submittal of Contractor's Final Project Schedule.
- 2.2 CONTRACTOR'S FINAL PROJECT SCHEDULE, GENERAL (refer to Article 3.10.1in the General Conditions AIA A201)
 - A. Contractor to provide a baseline, cost-loaded schedule in MS Project or Primavera to the Owner's Representative one (1) day **prior** to the weekly project meeting. Contractor is to update the schedule weekly.
 - B. Time Frame: Extend schedule from date established for commencement of the Work to date of Substantial Completion as set by the date of Notice to Proceed.

- 1. Contract completion date shall not be changed by submission of a schedule that shows an early completion date, unless specifically authorized by Change Order.
- C. Activities: Treat each story or separate area as a separate numbered activity for each principal element of the Work. Comply with the following:
 - 1. Activity Duration.
 - 2. Procurement Activities: Include procurement process activities for long lead items and major items as separate activities in schedule.
 - a. Procurement cycle activities include, but are not limited to, submittals, approvals, purchasing, fabrication and delivery.
 - 3. Submittal Review Time: Include review and resubmittal times indicated in Division 01 Section "Submittal Procedures" in schedule. Coordinate submittal review times in Contractor's Final Project Schedule with Submittals Schedule.
 - 4. Startup and Testing Time: Include not less than ten (10) days for startup and testing.
 - 5. Substantial Completion: Indicate completion in advance of date established for Substantial Completion, and allow time for Architect's administrative procedures necessary for certification of Substantial Completion.
- D. Constraints: Include constraints and work restrictions indicated in the Contract Documents and as follows in Final Project Schedule, and show how the sequence of the Work is affected.
 - 1. Phasing: Arrange list of activities on schedule by phase.
 - 2. Work by Owner: Include a separate activity for each portion of the Work performed by Owner.
 - 3. Work Restrictions: Show the effect of the following items on the Final Project Schedule:
 - a. Coordination with existing construction.
 - b. Limitations of continued occupancies.
 - c. Uninterruptible services.
 - d. Partial occupancy before Substantial Completion.
 - e. Use of premises restrictions.
 - f. Provisions for future construction.
 - g. Seasonal variations.
 - h. Environmental control.
 - 4. Work Stages: Indicate important stages of construction for each major portion of the Work.
- E. Milestones: Include milestones indicated in the Contract Documents in Final Project Schedule, including, but not limited to, the Notice to Proceed, Substantial Completion and Final Completion.
- F. Contract Modifications: For each proposed contract modification and concurrent with its submission, prepare a time-impact analysis using fragnets to demonstrate the effect of the proposed change on the overall project schedule.

2.3 CONTRACTOR'S FINAL PROJECT SCHEDULE (GANTT CHART)

- A. Gantt-Chart Schedule: Submit to the Owner a comprehensive, fully developed, horizontal Gantt-chart-type, Contractor's Final Project Schedule within fourteen (14) calendar days of date after Letter of Award. Base schedule on the Preliminary Construction Schedule and whatever updating and feedback was received since the start of Project. The Gantt-Chart Final Project Schedule can be either in MS Project or equivalent format.
- B. Preparation: Indicate each significant construction activity separately. Identify first workday of each week with a continuous vertical line.
 - 1. For construction activities that require three (3) months or longer to complete, indicate an estimated completion percentage in ten (10%) percent increments within time bar.

PART 3 EXECUTION

3.1 CONTRACTOR'S FINAL PROJECT SCHEDULE

- A. Contractor's Final Project Schedule Updating: At two (2) week intervals, update schedule to reflect actual construction progress and activities. Issue schedule three (3) days before each regularly scheduled progress meeting.
 - 1. Revise schedule immediately after each meeting or other activity where revisions have been recognized or made. Issue updated schedule concurrently with the report of each such meeting.
 - 2. Include a report with updated schedule that indicates every change, including, but not limited to, changes in logic, durations, actual starts and finishes, and activity durations.
 - 3. As the Work progresses, indicate Actual Completion percentage for each activity.
- B. Distribution: Distribute electronic copies of approved schedule to Owner, separate contractors, testing and inspecting agencies, and other parties identified by Contractor with a need-to-know schedule responsibility.
 - 1. Post copies in Project meeting rooms and temporary field offices.
 - 2. When revisions are made, distribute updated schedules to the same parties and post in the same locations. Delete parties from distribution when they have completed their assigned portion of the Work and are no longer involved in performance of construction activities.

END OF SECTION 01 3200

SECTION 01 3300 SUBMITTAL PROCEDURES

PART 1 GENERAL

1.1 RELATED DOCUMENTS

A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

A. This Section includes administrative and procedural requirements for submitting Shop Drawings, Product Data, Samples and other submittals.

B. Related Sections:

- 1. See Division 01 40 00 Section "Quality Requirements" for submitting test and inspection reports and for mockup requirements.
- 2. See Division 01 77 00 Section "Closeout Procedures" for submitting warranties.
- 3. See Division 01 78 39 Section "Project Record Documents" for submitting Record Drawings, Record Specifications, and Record Product Data.
- 4. See Division 01 78 23 Section "Operation and Maintenance Data" for submitting operation and maintenance manuals.

1.3 DEFINITIONS

- A. Action Submittals: Written and graphic information that requires Owner's responsive action.
- B. Informational Submittals: Written information that does not require Owner's responsive action. Submittals may be rejected for not complying with requirements.

PART 2 PRODUCTS

2.1 SUBMITTAL PROCEDURES

- A. General Submittal Procedure Requirements:
 - 1. Submit electronic submittals to Owner via email as PDF electronic files.
 - a. Owner will return annotated file. Annotate and retain one (1) copy of file as an electronic Project record document file.
- B. Coordination: Coordinate preparation and processing of submittals with performance of construction activities.
 - 1. Coordinate each submittal with fabrication, purchasing, testing, delivery, other submittals and related activities that require sequential activity.
 - 2. Coordinate transmittal of different types of submittals for related parts of the Work so processing will not be delayed because of need to review submittals concurrently for coordination.
 - a. Owner reserves the right to withhold action on a submittal requiring coordination with other submittals until related submittals are received.

- C. Processing Time: Allow enough time for submittal review, including time for resubmittals, as follows:
 - 1. Time for review shall commence on Owner's receipt of submittal. No extension of the Contract Time will be authorized because of failure to transmit submittals enough in advance of the Work to permit processing, including resubmittals.
 - 2. Initial Review: Allow five (5) working days for initial review of each submittal. Allow additional time if coordination with subsequent submittals is required. Owner will advise Contractor when a submittal being processed must be delayed for coordination.
 - 3. Intermediate Review: If intermediate submittal is necessary, process it in same manner as initial submittal.
 - 4. Resubmittal Review: Allow seven (7) working days for review of each resubmittal.
- D. Identification: Place a permanent label or title block on each submittal for identification.
 - 1. Indicate name of firm or entity that prepared each submittal on label or title block.
 - 2. Provide a space approximately **4 by 5 inches** on label or beside title block to record Contractor's review and approval markings and action taken by Owner.
 - 3. Include the following information on label for processing and recording action taken:
 - a. Project name.
 - b. Date.
 - c. Name and address of Architect (if applicable).
 - d. Name and address of Contractor.
 - e. Name and address of subcontractor.
 - f. Name and address of supplier.
 - g. Name of manufacturer.
 - h. Submittal number or other unique identifier, including revision identifier.
 - 1) Submittal number shall use consecutively numbered submittals (001, 002, etc), followed by the Specification Section number, followed by a sequential number indicating version (e.g., 001-13 3300-0).
 - 2) Example: $001 01 \ 1300 0$
 - a) 001: Consecutively numbered submittals
 - b) 01 1300: Specification Section
 - c) 0: Version of submittal (0 = original submittal; 1 = first resubmittal; 2 = 2nd resubmittal; etc.)
 - i. Number and title of appropriate Specification Section.
 - j. Drawing number and detail references, as appropriate.
 - k. Location(s) where product is to be installed, as appropriate.
 - 1. Other necessary identification.
- E. Deviations: Highlight, encircle or otherwise specifically identify deviations from the Contract Documents on submittals.
 - 1. Substitution Requests.

- F. Additional Copies: Unless additional copies are required for final submittal, and unless Owner observes noncompliance with provisions in the Contract Documents, initial submittal may serve as final submittal.
 - 1. Additional copies submitted for maintenance manuals will not be marked with action taken and will be returned.
- G. Transmittal: Package each submittal individually and appropriately for transmittal and handling. Transmit each submittal using a transmittal form. Owner will return submittals, without review, received from sources other than Contractor.
 - 1. Include Contractor's certification stating that information submitted complies with requirements of the Contract Documents.
- H. Resubmittals: Make resubmittals in same form and number of copies as initial submittal.
 - 1. Note date and content of previous submittal.
 - 2. Note date and content of revision in label or title block and clearly indicate extent of revision.
 - 3. Resubmit submittals until they are marked "Make Corrections Noted" or "No Exceptions Taken".
- I. Distribution: Furnish copies of final submittals to manufacturers, subcontractors, suppliers, fabricators, installers and others as necessary for performance of construction activities. Show distribution on transmittal forms.
 - 1. Use for Construction: Use only final submittals with mark indicating "Make Corrections Noted" or "No Exceptions Taken".

2.2 CONTRACTOR'S USE OF ARCHITECT'S CAD FILES

- A. General: At Contractor's written request, copies of Architect's CAD files will be provided to Contractor for Contractor's use in connection with Project, subject to the following conditions:
 - 1. Release of CADD information will be restricted to the following categories:
 - a. Architectural floor plans.
 - b. Site plan.
 - c. Reflected ceiling plans.
 - d. Exterior elevations.
 - e. Stair sections.
 - 2. The CADD database will contain only the background information; the sheet numbers, sheet titles, room names and numbers, reference symbols, and other similar data will not be included.
 - 3. The CADD database will be generated on PC hardware with Autodesk AutoCAD software. Architect has the capability to develop CADD output to meet capabilities of all major platforms and major media types.
 - 4. When requesting CADD databases, specify the output form required.

PART 3 PRODUCTS

3.1 ACTION SUBMITTALS

A. General: Prepare and submit to Owner, Action Submittals required by individual Specification Sections.

- B. Electronic Submittals: Identify and incorporate information in each electronic submittal file as follows:
 - 1. Assemble complete submittal package into a single indexed file incorporating submittal requirements of a single Specification Section and transmittal form with links enabling navigation to each item.
 - 2. Name file with submittal number or other unique identifier, including revision identifier.
 - a. File name shall use project identifier and Specification Section number followed by a decimal point and then a sequential number (e.g., LNHS-061000.01). Resubmittals shall include an alphabetic suffix after another decimal point (e.g., LNHS-061000.01.A).
 - 3. Provide means for insertion to permanently record Contractor's review and approval markings and action taken by Owner.
 - 4. Transmittal Form for Electronic Submittals: Use electronic form acceptable to Owner, containing the following information:
 - a. Project name.
 - b. Date.
 - c. Name and address of Architect.
 - d. Name of Construction Manager.
 - e. Name of Contractor.
 - f. Name of firm or entity that prepared submittal.
 - g. Names of subcontractor, manufacturer, and supplier.
 - h. Category and type of submittal.
 - i. Submittal purpose and description.
 - j. Specification Section number and title.
 - k. Specification paragraph number or drawing designation and generic name for each of multiple items.
 - 1. Drawing number and detail references, as appropriate.
 - m. Location(s) where product is to be installed, as appropriate.
 - n. Related physical samples submitted directly.
 - o. Indication of full or partial submittal.
 - p. Transmittal number, numbered consecutively.
 - q. Submittal and transmittal distribution record.
 - r. Other necessary identification.
 - s. Remarks.
 - 5. Metadata: Include the following information as keywords in the electronic submittal file metadata:
 - a. Project name.
 - b. Number and title of appropriate Specification Section.
 - c. Manufacturer name.
 - d. Product name.
- C. Product Data: Collect information into a single submittal for each element of construction and type of product or equipment.
 - 1. If information must be specially prepared for submittal because standard printed data are not suitable for use, submit as Shop Drawings, not as Product Data.
 - 2. Mark each copy of each submittal to show which products and options are applicable.
 - 3. Include the following information, as applicable:
 - a. Manufacturer's written recommendations.
 - b. Manufacturer's product specifications.

- c. Manufacturer's installation instructions.
- d. Manufacturer's catalog cuts.
- e. Wiring diagrams showing factory-installed wiring.
- f. Printed performance curves.
- g. Operational range diagrams.
- h. Compliance with specified referenced standards.
- i. Testing by recognized testing agency.
- 4. Number of Copies: Submit to Owner, four (4) copies of Product Data, unless otherwise indicated. Owner will return two (2) copies. Mark up and retain one (1) returned copy as a Project Record Document.
- D. Shop Drawings: Prepare Project-specific information, drawn accurately to scale. Do not base Shop Drawings on reproductions of the Contract Documents or standard printed data, unless submittal of Architect's CAD Drawings is otherwise permitted.
 - 1. Preparation: Fully illustrate requirements in the Contract Documents. Include the following information, as applicable:
 - a. Dimensions.
 - b. Identification of products.
 - c. Fabrication and installation drawings.
 - d. Roughing-in and setting diagrams.
 - e. Wiring diagrams showing field-installed wiring, including power, signal, and control wiring.
 - f. Shop-work manufacturing instructions.
 - g. Templates and patterns.
 - h. Schedules.
 - i. Notation of coordination requirements.
 - j. Notation of dimensions established by field measurement.
 - k. Relationship to adjoining construction clearly indicated.
 - 1. Seal and signature of professional engineer if specified.
 - m. Wiring Diagrams: Differentiate between manufacturer-installed and field-installed wiring.
 - 2. Sheet Size: Except for templates, patterns and similar full-size drawings, submit to Owner, Shop Drawings on sheets at least 8-1/2 by 11 inches but no larger than 36 by 48 inches.
 - 3. Number of Copies: Submit to Owner, a minimum of three (3) opaque (bond) copies of each submittal. Submit additional copies as required for each consultant. Owner will return two (2) copies. At the sole discretion of the Owner electronic copies may be acceptable.
- E. Samples: Submit to Owner, Samples for review of kind, color, pattern, and texture for a check of these characteristics with other elements and for a comparison of these characteristics between submittal and actual component as delivered and installed.
 - 1. Transmit Samples that contain multiple, related components such as accessories together in one submittal package.
 - 2. Identification: Attach label on unexposed side of Samples that includes the following:
 - a. Generic description of Sample.
 - b. Product name and name of manufacturer.
 - c. Sample source.
 - d. Number and title of appropriate Specification Section.

- 3. Disposition: Maintain sets of approved Samples at Project site, available for quality control comparisons throughout the course of construction activity. Sample sets may be used to determine final acceptance of construction associated with each set.
- 4. Samples for Initial Selection: Submit manufacturer's color charts consisting of units or sections of units showing the full range of colors, textures and patterns available.
 - a. Number of Samples: Submit one (1) full set of available choices where color, pattern, texture or similar characteristics are required to be selected from manufacturer's product line. Owner will return submittal with options selected.
- 5. Samples for Verification: Submit full-size units or Samples of size indicated, prepared from same material to be used for the Work, cured and finished in manner specified, and physically identical with material or product proposed for use, and that show full range of color and texture variations expected. Samples include, but are not limited to, the following: partial sections of manufactured or fabricated components; small cuts or containers of materials; complete units of repetitively used materials; swatches showing color, texture and pattern; color range sets; and components used for independent testing and inspection.
 - a. Number of Samples: Submit three (3) sets of Samples. Owner will retain two (2) Sample sets; remainder will be returned.
- F. Product Schedule or List: As required in individual Specification Sections, prepare a written summary indicating types of products required for the Work and their intended location.
 - 1. Number of Copies: Submit a minimum of three (3) copies of product schedule or list, unless otherwise indicated. Submit additional copies for each consultant required to review the submittal. Owner will return two (2) copies.
- G. Submittals Schedule: Comply with requirements specified in the General Conditions of the Contract and Owner-Contractor Contract.
- H. Application for Payment: Comply with requirements specified in the Owner-Contractor Contract.
- I. Schedule of Values: Comply with requirements specified in the Owner-Contractor Contract. If needed, combine subcontract list in paragraph below with product list above. Subcontract list is required by General Conditions to be submitted as soon as practical after award of the Contract.
- J. Subcontract List: Prepare a written summary identifying individuals or firms proposed for each portion of the Work, including those who are to furnish products or equipment fabricated to a special design.
 - 1. Number of Copies: Submit electronically to Owner, one (1) copy of subcontractor list, unless otherwise indicated.

3.2 INFORMATIONAL SUBMITTALS

A. General: Prepare and submit Informational Submittals required by other Specification Sections.

- 1. Number of Copies: Submit to Owner, two (2) copies of each submittal, unless otherwise indicated. Owner will not return copies.
- 2. Certificates and Certifications: Provide a notarized statement that includes signature of entity responsible for preparing certification. Certificates and certifications shall be signed by an officer or other individual authorized to sign documents on behalf of that entity.
- 3. Test and Inspection Reports: Comply with requirements specified in Division 01 40 Section "Quality Requirements."
- B. Coordination Drawings: Comply with requirements specified in Division 01 31 00 Section "Project Management and Coordination."
- C. Contractor's Final Project Schedule: Comply with requirements specified in the General Conditions of the Contract, and Owner-Contractor Contract.
- D. Qualification Data: Prepare written information that demonstrates capabilities and experience of firm or person. Include lists of completed projects with project names and addresses, names and addresses of architects and Owners, and other information specified.
- E. Welding Certificates: Prepare written certification that welding procedures and personnel comply with requirements in the Contract Documents. Submit record of Welding Procedure Specification (WPS) and Procedure Qualification Record (PQR) on AWS forms. Include names of firms and personnel certified.
- F. Installer Certificates: Prepare written statements on manufacturer's letterhead certifying that Installer complies with requirements in the Contract Documents and, where required, is authorized by manufacturer for this specific Project.
- G. Manufacturer Certificates: Prepare written statements on manufacturer's letterhead certifying that manufacturer complies with requirements in the Contract Documents. Include evidence of manufacturing experience where required.
- H. Product Certificates: Prepare written statements on manufacturer's letterhead certifying that product complies with requirements in the Contract Documents.
- I. Material Certificates: Prepare written statements on manufacturer's letterhead certifying that material complies with requirements in the Contract Documents.
- J. Material Test Reports: Prepare reports written by a qualified testing agency, on testing agency's standard form, indicating and interpreting test results of material for compliance with requirements in the Contract Documents.
- K. Product Test Reports: Prepare written reports indicating current product produced by manufacturer complies with requirements in the Contract Documents. Base reports on evaluation of tests performed by manufacturer and witnessed by a qualified testing agency, or on comprehensive tests performed by a qualified testing agency.
- L. Research/Evaluation Reports: Prepare written evidence, from a model code organization acceptable to authorities having jurisdiction, that product complies with building code in effect for Project.

- M. Pre-construction Test Reports: Prepare reports written by a qualified testing agency, on testing agency's standard form, indicating and interpreting results of tests performed before installation of product, for compliance with performance requirements in the Contract Documents.
- N. Compatibility Test Reports: Prepare reports written by a qualified testing agency, on testing agency's standard form, indicating and interpreting results of compatibility tests performed before installation of product. Include written recommendations for primers and substrate preparation needed for adhesion.
- O. Field Test Reports: Prepare reports written by a qualified testing agency, on testing agency's standard form, indicating and interpreting results of field tests performed either during installation of product or after product is installed in its final location, for compliance with requirements in the Contract Documents.
- P. Maintenance Data: Prepare written and graphic instructions and procedures for operation and normal maintenance of products and equipment. Comply with requirements specified in Division 01 78 23 Section "Operation and Maintenance Data."
- Q. Design Data: Prepare written and graphic information, including, but not limited to, performance and design criteria, list of applicable codes and regulations, and calculations. Include list of assumptions and other performance and design criteria and a summary of loads. Include load diagrams if applicable. Provide name and version of software, if any, used for calculations. Include page numbers.
- R. Manufacturer's Instructions: Prepare written or published information that documents manufacturer's recommendations, guidelines, and procedures for installing or operating a product or equipment. Include name of product and name, address and telephone number of manufacturer.
- S. Manufacturer's Field Reports: Prepare written information documenting factoryauthorized service representative's tests and inspections. Include the following, as applicable:
 - 1. Statement on condition of substrates and their acceptability for installation of product.
 - 2. Summary of installation procedures being followed, whether they comply with requirements and, if not, what corrective action was taken.
 - 3. Results of operational and other tests and a statement of whether observed performance complies with requirements.
- T. Insurance Certificates and Bonds: Prepare written information indicating current status of insurance or bonding coverage. Include name of entity covered by insurance or bond, limits of coverage, amounts of deductibles, if any, and term of the coverage.
- U. Material Safety Data Sheets (MSDSs): Submit information directly to Owner.
 - 1. Architect will not review submittals that include MSDSs and will return them for resubmittal.

3.3 DELEGATED DESIGN

- A. Performance and Design Criteria: Where professional design services or certifications by a design professional are specifically required of Contractor by the Contract Documents, provide products and systems complying with specific performance and design criteria indicated.
 - 1. If criteria indicated are not sufficient to perform services or certification required, submit a written request for additional information to Owner.
- B. Delegated-Design Submittal: In addition to Shop Drawings, Product Data, and other required submittals, electronically submit three (3) copies of a statement, signed and sealed by the responsible design professional, for each product and system specifically assigned to Contractor to be designed or certified by a design professional.
 - 1. Indicate that products and systems comply with performance and design criteria in the Contract Documents. Include list of codes, loads, and other factors used in performing these services.
 - 2. If submittal has a wet stamp, then send three (3) hard copies, with the wet stamp to Owner for approval. Owner will return one (1) copy to Contractor.

PART 4 EXECUTION

4.1 CONTRACTOR'S REVIEW

A. Review each submittal and check for coordination with other Work of the Contract and for compliance with the Contract Documents. Note corrections and field dimensions.

4.2 OWNER'S ACTION

- A. Action Submittals: Owner will review each submittal, make marks to indicate corrections or modifications required, and return it. Owner will stamp each submittal with an action stamp and will mark stamp appropriately to indicate action taken.
- B. Informational Submittals: Owner will review each submittal and will not return it, or will return it if it does not comply with requirements. Owner will forward each submittal to appropriate party.
- C. Partial submittals are not acceptable, will be considered nonresponsive, and will be returned without review.
- D. Submittals not required by the Contract Documents may not be reviewed and may be discarded.

END OF SECTION 01 3300

SECTION 01 4000 QUALITY REQUIREMENTS

PART 1 GENERAL

1.1 RELATED DOCUMENTS

A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes administrative and procedural requirements for quality assurance and quality control.
- B. Testing and inspecting services are required to verify compliance with requirements specified or indicated. These services do not relieve Contractor of responsibility for compliance with the Contract Document requirements.
 - 1. Specified tests, inspections and related actions do not limit Contractor's other quality assurance and quality-control procedures that facilitate compliance with the Contract Document requirements.
 - 2. Requirements for Contractor to provide quality-assurance and quality-control services required by Architect, Owner, or authorities having jurisdiction are not limited by provisions of this Section.
- C. See Divisions 02 through 33 Sections for specific test and inspection requirements, if applicable. Not all Divisions will be used.

1.3 DEFINITIONS

- A. Quality-Assurance Services: Activities, actions and procedures performed before and during execution of the Work to guard against defects and deficiencies and substantiate that proposed construction will comply with requirements.
- B. Quality-Control Services: Tests, inspections, procedures and related actions during and after execution of the Work to evaluate that actual products incorporated into the Work and completed construction comply with requirements. Services do not include contract enforcement activities performed by Owner.
- C. Mockups: Full-size, physical assemblies that are constructed on-site. Mockups are used to verify selections made under sample submittals, to demonstrate aesthetic effects and, where indicated, qualities of materials and execution, and to review construction, coordination, testing or operation; they are not Samples. Approved mockups establish the standard by which the Work will be judged.
- D. Pre-construction Testing: Tests and inspections that are performed specifically for the Project before products and materials are incorporated into the Work to verify performance or compliance with specified criteria.

- E. Product Testing: Tests and inspections that are performed by an NRTL, an NVLAP, or a testing agency qualified to conduct product testing and acceptable to authorities having jurisdiction, to establish product performance and compliance with industry standards.
- F. Source Quality-Control Testing: Tests and inspections that are performed at the source, i.e., plant, mill, factory or shop.
- G. Field Quality-Control Testing: Tests and inspections that are performed on-site for installation of the Work and for completed Work.
- H. Testing Agency: An entity engaged to perform specific tests, inspections or both. Testing laboratory shall mean the same as testing agency.
- I. Installer/Applicator/Erector: Contractor or another entity engaged by Contractor as an employee, Subcontractor, or Lower Tier Subcontractor, to perform a particular construction operation, including installation, erection, application and similar operations.
 - 1. Using a term such as "carpentry" does not imply that certain construction activities must be performed by accredited or unionized individuals of a corresponding generic name, such as "carpenter." It also does not imply that requirements specified apply exclusively to tradespeople of the corresponding generic name.
- J. Experienced: When used with an entity, "experienced" means having successfully completed a minimum of two (2) previous projects similar in size and scope to this Project; being familiar with special requirements indicated; and having complied with requirements of authorities having jurisdiction.

1.4 CONFLICTING REQUIREMENTS

- A. General: If compliance with two (2) or more standards is specified and the standards establish different or conflicting requirements for minimum quantities or quality levels, comply with the most stringent requirement. Refer uncertainties and requirements that are different, but apparently equal, to Owner for a decision before proceeding.
- B. Minimum Quantity or Quality Levels: The quantity or quality level shown or specified shall be the minimum provided or performed. The actual installation may comply exactly with the minimum quantity or quality specified, or it may exceed the minimum within reasonable limits. To comply with these requirements, indicated numeric values are minimum or maximum, as appropriate, for the context of requirements. Refer uncertainties to Owner for a decision before proceeding.

1.5 TESTING SUBMITTALS

- A. Qualification Data: For testing agencies, as prescribed by Contract, but not provided by Owner shall demonstrate their capabilities and experience. Include proof of qualifications in the form of a recent report on the inspection of the testing agency by a recognized authority.
- B. Reports: Prepare and electronically submit to the Owner certified written reports that include the following:
 - 1. Date of issue.

- 2. Project title and number.
- 3. Name, address and telephone number of testing agency.
- 4. Dates and locations of samples and tests or inspections.
- 5. Names of individuals making tests and inspections.
- 6. Description of the Work and test and inspection method.
- 7. Identification of product and Specification Section.
- 8. Complete test or inspection data.
- 9. Test and inspection results and an interpretation of test results.
- 10. Record of temperature and weather conditions at time of sample taking and testing and inspecting.
- 11. Comments or professional opinion on whether tested or inspected Work complies with the Contract Document requirements.
- 12. Name and signature of laboratory inspector.
- 13. Recommendations on re-testing and re-inspecting.
- C. Permits, Licenses and Certificates: For Owner's records, submit copies of permits, licenses, certifications, inspection reports, releases, jurisdictional settlements, notices, receipts for fee payments, judgments, correspondence, records and similar documents, established for compliance with standards and regulations bearing on performance of the Work.

1.6 QUALITY ASSURANCE

- A. General: Qualifications paragraphs in this Article establish the minimum qualification levels required; individual Specification Sections specify additional requirements.
- B. Installer Qualifications: A firm or individual experienced in installing, erecting, or assembling work similar in material, design and extent to that indicated for this Project, whose work has resulted in construction with a record of successful in-service performance.
- C. Manufacturer Qualifications: A firm experienced in manufacturing products or systems similar to those indicated for this Project and with a record of successful in-service performance, as well as sufficient production capacity to produce required units.
- D. Fabricator Qualifications: A firm experienced in producing products similar to those indicated for this Project and with a record of successful in-service performance, as well as sufficient production capacity to produce required units.
- E. Professional Engineer Qualifications: A professional engineer who is legally qualified to practice in jurisdiction where Project is located and who is experienced in providing engineering services of the kind indicated. Engineering services are defined as those performed for installations of the system, assembly or product that is similar to those indicated for this Project in material, design and extent.
- F. Specialists: Certain sections of the Specifications require that specific construction activities shall be performed by entities who are recognized experts in those operations. Specialists shall satisfy qualification requirements indicated and shall be engaged for the activities indicated.
 - 1. Requirement for specialists shall not supersede building codes and regulations governing the Work.

- G. Testing Agency Qualifications: An NRTL, an NVLAP, or an independent agency with the experience and capability to conduct testing and inspecting indicated, as documented according to ASTM E 548; and with additional qualifications specified in individual Sections; and where required by authorities having jurisdiction, that is acceptable to authorities.
 - 1. NRTL: A nationally recognized testing laboratory according to 29 CFR 1910.7.
 - 2. NVLAP: A testing agency accredited according to NIST's National Voluntary Laboratory Accreditation Program.
- H. Factory-Authorized Service Representative Qualifications: An authorized representative of manufacturer who is trained and approved by manufacturer to inspect installation of manufacturer's products that are similar in material, design and extent to those indicated for this Project.
- I. Mockups: Before installing portions of the Work requiring mockups, build mockups for each form of construction and finish required to comply with the following requirements, using materials indicated for the completed Work:
 - 1. Build mockups in location and of size indicated or, if not indicated, as directed by Owner.
 - 2. Notify Owner seven (7) calendar days in advance of dates and times when mockups will be constructed.
 - 3. Demonstrate the proposed range of aesthetic effects and workmanship.
 - 4. Obtain Owner's approval of mockups before starting work, fabrication or construction.
 - 5. Maintain mockups during construction in an undisturbed condition as a standard for judging the completed Work.
 - 6. Demolish and remove mockups when directed, unless otherwise indicated.
- J. Laboratory Mockups: Comply with requirements of pre-construction testing and those specified in individual Sections in Divisions 02 through 33.

1.7 QUALITY CONTROL

- A. Owner Responsibilities: Where quality-control services are indicated as Owner's responsibility, Owner will engage a qualified testing agency to perform these services.
 - 1. Owner will furnish Contractor with names, addresses and telephone numbers of testing agencies engaged and a description of types of testing and inspecting they are engaged to perform.
 - 2. Costs for retesting and re-inspecting construction that replaces or is necessitated by work that failed to comply with the Contract Documents will be charged to Contractor.
- B. Tests and inspections not explicitly assigned to Owner are Contractor's responsibility. Unless otherwise indicated, provide quality-control services specified and those required by authorities having jurisdiction. Perform quality-control services required of Contractor by authorities having jurisdiction, whether specified or not.
 - 1. Where services are indicated as Contractor's responsibility, engage a qualified testing agency to perform these quality-control services.
 - a. Contractor shall not employ same entity engaged by Owner, unless agreed to in writing by Owner.

- 2. Notify testing agencies at least twenty-four 24 hours in advance of time when Work that requires testing or inspecting will be performed.
- 3. Where quality-control services are indicated as Contractor's responsibility, electronically submit a certified written report, in duplicate, of each quality-control service to the Owner.
- 4. Testing and inspecting requested by Contractor and not required by the Contract Documents are Contractor's responsibility.
- 5. Submit additional copies of each written report directly to authorities having jurisdiction, when they so direct.
- C. Manufacturer's Field Services: Where indicated, engage a factory-authorized service representative to inspect field-assembled components and equipment installation, including service connections. Report results in writing as specified in Division 01 33 00 Section "Submittal Procedures."
- D. Re-testing/Re-inspecting: Regardless of whether original tests or inspections were Contractor's responsibility, provide quality-control services, including re-testing and reinspecting, for construction that replaced Work that failed to comply with the Contract Documents.
- E. Testing Agency Responsibilities: Cooperate with Owner and Contractor in performance of duties. Provide qualified personnel to perform required tests and inspections.
 - 1. Notify Owner and Contractor promptly of irregularities or deficiencies observed in the Work during performance of its services.
 - 2. Determine the location from which test samples will be taken and in which onsite tests will be conducted.
 - 3. Conduct and interpret tests and inspections and state in each report whether tested and inspected work complies with or deviates from requirements.
 - 4. Electronically submit to the Owner a certified written report, in duplicate, of each test, inspection and similar quality-control service through Contractor.
 - 5. Do not release, revoke, alter, or increase the Contract Document requirements or approve or accept any portion of the Work.
 - 6. Do not perform any duties of Contractor.
- F. Associated Services: Cooperate with agencies performing required tests, inspections and similar quality-control services, and provide reasonable auxiliary services as requested. Notify agency sufficiently in advance of operations to permit assignment of personnel. Provide the following:
 - 1. Access to the Work.
 - 2. Incidental labor and facilities necessary to facilitate tests and inspections.
 - 3. Adequate quantities of representative samples of materials that require testing and inspecting. Assist agency in obtaining samples.
 - 4. Facilities for storage and field curing of test samples.
 - 5. Delivery of samples to testing agencies.
 - 6. Preliminary design mix proposed for use for material mixes that require control by testing agency.
 - 7. Security and protection for samples and for testing and inspecting equipment at Project site.

- G. Coordination: Coordinate sequence of activities to accommodate required quality-assurance and quality-control services with a minimum of delay and to avoid necessity of removing and replacing construction to accommodate testing and inspecting.
 - 1. Schedule times for tests, inspections, obtaining samples and similar activities.

1.8 SPECIAL TESTS AND INSPECTIONS

- A. Special Tests and Inspections: Owner will engage a qualified special inspector to conduct special tests and inspections required by authorities having jurisdiction as the responsibility of Owner, and as follows:
 - 1. Verifying that manufacturer maintains detailed fabrication and quality-control procedures and reviewing the completeness and adequacy of those procedures to perform the Work.
 - 2. Notifying Owner and Contractor promptly of irregularities and deficiencies observed in the Work during performance of its services.
 - 3. Submitting a certified written report of each test, inspection, and similar quality-control service to Owner with copy to Contractor and to authorities having jurisdiction.
 - 4. Electronically submitting to the Owner a final report of special tests and inspections, which includes a list of unresolved deficiencies, at Substantial Completion.
 - 5. Interpreting tests and inspections and stating in each report whether tested and inspected work complies with or deviates from the Contract Documents.
 - 6. Re-testing and re-inspecting corrected work.

PART 2 PRODUCTS (Not Used)

PART 3 EXECUTION

3.1 REPAIR AND PROTECTION

- A. General: On completion of testing, inspecting, sample taking and similar services, repair damaged construction and restore substrates and finishes.
 - 1. Provide materials and comply with installation requirements specified in other Specification Sections. Restore patched areas and extend restoration into adjoining areas with durable seams that are as invisible as possible.
 - 2. Comply with the Contract Document requirements for Division 01 73 29 Section "Cutting and Patching."
- B. Protect construction exposed by or for quality-control service activities.
- C. Repair and protection are Contractor's responsibility, regardless of the assignment of responsibility for quality-control services.

END OF SECTION 01 4000

SECTION 01 5000 TEMPORARY FACILITIES AND CONTROLS

PART 1 GENERAL

1.1 RELATED DOCUMENTS

A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 01 73 00 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes requirements for temporary utilities, support facilities, and security and protection facilities.
- B. See Division 01 Section "Execution" for progress cleaning requirements.
- C. See Divisions 02 through 33 Sections for temporary heat, ventilation, and humidity requirements for products in those Sections. Not all Sections will be used

1.3 DEFINITIONS

A. Permanent Enclosure: As determined by Architect, permanent or temporary roofing is complete, insulated and weathertight; exterior walls are insulated and weathertight; and all openings are closed with permanent construction or substantial temporary closures.

1.4 USE CHARGES

- A. General: Cost or use charges for temporary facilities shall be included in the Contract Sum. Allow other entities to use temporary services and facilities without cost, including, but not limited to, Owner's construction forces, Architect, testing agencies and authorities having jurisdiction.
- B. Water Service from Existing System: Water from Owner's existing water system is available for use with approval of Owner's Representative. Provide connections and extensions of services as required for construction operations. Contractor must notify Owner forty-eight (48) hours before use of water service.
- C. Electric Power Service from Existing System: Contractor is responsible for supplying power service and distribution as required for construction operations, unless other arrangements are made with approval of Owner's Representative.

1.5 QUALITY ASSURANCE

A. Electric Service: Comply with NECA, NEMA, and UL standards and regulations for temporary electric service. Install service to comply with NFPA 70.

1.6 PROJECT CONDITIONS

- A. Temporary Use of Existing Permanent Facilities: Contractor shall assume responsibility for operation, maintenance and protection of each existing permanent service during its use as a construction facility before Owner's acceptance, regardless of previously assigned responsibilities.
- B. Conditions of Use: The following conditions apply to use of temporary services and existing facilities by all parties engaged in the Work:
 - 1. Keep temporary services and existing facilities clean and neat.
 - 2. Relocate temporary services as required by progress of the Work.
 - 3. Provide temporary keys and lock cores throughout duration of Contractor's occupancy of Owner's space. Contractor to provide Owner's Representative with temporary construction keys matching construction cores installed for access.
 - a. When Contractor is given keys to KCHA property, Contractor will claim responsibility for the keys by signing for keys acquired. If Contractor loses keys, Contractor is responsible for rekeying all locks associated with lost key. Contractor is responsible for returning keys back to Owner's Representative when Work is completed.

PART 2 PRODUCTS

2.1 TEMPORARY FACILITIES

- A. Field Offices, General: Prefabricated or mobile units with serviceable finishes, temperature controls and foundations adequate for normal loading.
- B. Storage and Fabrication Sheds: Provide sheds sized, furnished and equipped to accommodate materials and equipment for construction operations.
- C. Contractor is responsible for security of Temporary Facilities.

2.2 EQUIPMENT

- A. Fire Extinguishers: Portable, UL rated; with class and extinguishing agent as required by locations and classes of fire exposures.
- B. HVAC Equipment: Unless Owner authorizes use of permanent HVAC system, provide vented, self-contained, liquid-propane-gas or fuel-oil heaters with individual space thermostatic control.
 - 1. Use of gasoline-burning space heaters, open-flame heaters or salamander-type heating units is prohibited.
 - 2. Heating Units: Listed and labeled for type of fuel being consumed, by a testing agency acceptable to authorities having jurisdiction, and marked for intended use.
 - 3. Permanent HVAC System: If Owner authorizes use of permanent HVAC system for temporary use during construction, provide filter with MERV of 13 at each return air grille in system and remove and replace at end of construction.
- C. Self-Contained Toilet Units: Single-occupant units of chemical, aerated re-circulation, or combustion type; vented; fully-enclosed with a glass-fiber-reinforced polyester shell or similar nonabsorbent material.

- D. Drinking-Water Fixtures: Containerized, tap-dispenser, bottled-water, drinking-water units, including paper cup supply.
 - 1. Where power is accessible, provide electric water coolers to maintain dispensed water temperature at 45 to 55 degrees F.
- E. Electrical Outlets: Properly configured, NEMA-polarized outlets to prevent insertion of 110-to-120-V plugs into higher-voltage outlets; equipped with ground-fault circuit interrupters, reset button and pilot light.
- F. Power Distribution System Circuits: Where permitted, and overhead and exposed for surveillance, wiring circuits, not exceeding 125-V AC, 20-A rating, and lighting circuits may be nonmetallic sheathed cable.

PART 3 EXECUTION

3.1 INSTALLATION, GENERAL

- A. With Owner's approval, locate facilities where they will serve Project adequately and result in minimum interference with performance of the Work. Relocate and modify facilities as required by progress of the Work.
- B. Provide each facility ready for use when needed to avoid delay. Do not remove until facilities are no longer needed or are replaced by authorized use of completed permanent facilities.

3.2 TEMPORARY UTILITY INSTALLATION

- A. General: Install temporary service or connect to existing service.
 - 1. Arrange with utility company, Owner, and existing users for time when service can be interrupted, if necessary, to make connections for temporary services. Provide Owner with seventy-two (72) hour notice if disturbance is to occur to site staff or residents.
- B. Water Service: Connect to Owner's existing water service facilities. Clean and maintain water service facilities in a condition acceptable to Owner. At Substantial Completion, restore these facilities to condition existing before initial use.
- C. Sanitary Facilities: Provide temporary toilets, wash facilities and drinking water for use by construction personnel. Comply with requirements of authorities having jurisdiction for type, number, location, operation and maintenance of fixtures and facilities.
 - 1. Toilets: Use of Owner's existing toilet facilities will be permitted with Owner's approval, as long as facilities are cleaned and maintained daily. At Substantial Completion, restore these facilities to condition existing before initial use.
- D. Heating and Cooling: Provide temporary heating and cooling required by construction activities for curing or drying of completed installations or for protecting installed construction from adverse effects of low temperatures or high humidity. Select equipment that will not have a harmful effect on completed installations or elements being installed.

- 1. Maintain a minimum temperature of 50 degrees F in permanently enclosed portions of building for normal construction activities, and 65 degrees F for finishing activities and areas where finished Work has been installed.
- 2. Isolation of Work Areas in Occupied Facilities: Prevent dust, fumes and odors from entering occupied areas.
- E. Ventilation and Humidity Control: Provide temporary ventilation required by construction activities for curing or drying of completed installations or for protecting installed construction from adverse effects of high humidity. Select equipment that will not have a harmful effect on completed installations or elements being installed. Coordinate ventilation requirements to produce ambient condition required and minimize energy consumption.
- F. Electric Power Service: Provide electric power service and distribution system of sufficient size, capacity, and power characteristics required for construction operations.
 - 1. Connect temporary service to Owner's existing power source, as directed by Owner after receiving approval by Owner's Representative.
- G. Lighting: Provide temporary lighting with local switching that provides adequate illumination for construction operations, observations, inspections and traffic conditions.
 - 1. Install and operate temporary lighting that fulfills security and protection requirements without operating entire system.

3.3 SUPPORT FACILITIES INSTALLATION

- A. Waste Disposal Facilities: Provide waste-collection containers in sizes adequate to handle waste from construction operations. Comply with requirements of authorities having jurisdiction. Comply with Division 01 73 00 Section "Execution" for progress cleaning requirements. Contractor shall not use Owner's waste receptacles for any disposal.
- B. Parking: Use designated areas of Owner's existing parking areas for construction personnel upon Owner's approval.

3.4 SECURITY AND PROTECTION FACILITIES INSTALLATION

- A. Protection of Existing Facilities: Protect existing vegetation, equipment, structures, utilities and other improvements at Project site and on adjacent properties, except those indicated to be removed or altered. Repair damage to existing facilities.
- B. Environmental Protection: Provide protection, operate temporary facilities and conduct construction in ways and by methods that comply with environmental regulations and that minimize possible air, waterway and subsoil contamination or pollution or other undesirable effects.
- C. Security Enclosure and Lockup: Install substantial temporary enclosure around partially completed areas of construction. Provide lockable entrances to prevent unauthorized entrance, vandalism, theft and similar violations of security.
- D. Barricades, Warning Signs, and Lights: Comply with Owner's instructions for erecting structurally adequate barricades, including warning signs and lighting.

- E. Temporary Egress: Maintain temporary egress from existing occupied facilities as indicated and as required by Owner.
- F. Temporary Enclosures: Provide temporary enclosures for protection of construction, in progress and completed, from exposure, foul weather, other construction operations and similar activities. Provide temporary weathertight enclosure for building exterior.
 - 1. Where heating or cooling is needed and permanent enclosure is not complete, insulate temporary enclosures.
- G. Temporary Partitions: Provide floor-to-ceiling dustproof partitions to limit dust and dirt migration and to separate areas occupied by tenants from fumes and noise.
 - 1. Construct dustproof partitions with two (2) layers of 6-mil polyethylene sheet on each side. Overlap and tape full length of joints.
 - 2. Where fire-resistance-rated temporary partitions are indicated or are required by authorities having jurisdiction, construct partitions according to the rated assemblies.
 - 3. Seal joints and perimeter.
 - 4. Protect air-handling equipment.
 - 5. Provide walk-off mats at each entrance through temporary partition.
 - 6. Dust Control/Air handlers
- H. Temporary Fire Protection: Install and maintain temporary fire-protection facilities of types needed to protect against reasonably predictable and controllable fire losses. Comply with NFPA 241.
 - 1. Prohibit smoking on Owner's property.
 - 2. Supervise welding operations, combustion-type temporary heating units and similar sources of fire ignition according to requirements of authorities having jurisdiction.

3.5 OPERATION, TERMINATION AND REMOVAL

- A. Supervision: Enforce strict discipline in use of temporary facilities. To minimize waste and abuse, limit availability of temporary facilities to essential and intended uses.
- B. Maintenance: Maintain facilities in good operating condition until removal.
 - 1. Maintain operation of temporary enclosures, heating, cooling, humidity control, ventilation and similar facilities on a twenty-four (24) hour basis where required to achieve indicated results and to avoid possibility of damage.
- C. Temporary Facility Changeover: Do not change over from using temporary security and protection facilities to permanent facilities until Substantial Completion.
- D. Termination and Removal: Remove each temporary facility when need for its service has ended, when it has been replaced by authorized use of a permanent facility or no later than Substantial Completion. Complete or, if necessary, restore permanent construction that may have been delayed because of interference with temporary facility. Repair damaged Work, clean exposed surfaces and replace construction that cannot be satisfactorily repaired.
 - 1. Materials and facilities that constitute temporary facilities are property of Contractor. Owner reserves right to take possession of Project identification signs.

2. At Substantial Completion, clean and renovate permanent facilities used during construction period. Comply with final cleaning requirements specified in Division 01 77 00 Section "Closeout Procedures."

END OF SECTION 01 5000

SECTION 01 6000 PRODUCT REQUIREMENTS

PART 1 GENERAL

1.1 RELATED DOCUMENTS

A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes administrative and procedural requirements for selection of products for use in Project; product delivery, storage and handling; manufacturers' standard warranties on products; special warranties; product substitutions; and comparable products.
- B. See Division 01 77 00 Section "Closeout Procedures" for submitting warranties for Contract closeout.
- C. See Divisions 02 through 33 Sections for specific requirements for warranties on products and installations specified to be warranted. Not all Sections will be used.

1.3 DEFINITIONS

- A. Products: Items purchased for incorporating into the Work, whether purchased for Project or taken from previously purchased stock. The term "product" includes the terms "material," "equipment," "system," and terms of similar intent.
 - 1. Named Products: Items identified by manufacturer's product name, including make or model number or other designation shown or listed in manufacturer's published product literature that is current as of date of the Contract Documents.
 - 2. New Products: Items that have not previously been incorporated into another project or facility, except that products consisting of recycled-content materials are allowed, unless explicitly stated otherwise. Products salvaged or recycled from other projects are not considered new products.
 - 3. Comparable Product: Product that is demonstrated and approved through submittal process, or where indicated as a product substitution, to have the indicated qualities related to type, function, dimension, in-service performance, physical properties, appearance and other characteristics that equal or exceed those of specified product.
- B. Substitutions: Changes in products, materials, equipment and methods of construction from those required by the Contract Documents and proposed by Contractor.
- C. Basis-of-Design Product Specification: Where a specific manufacturer's product is named and accompanied by the words "basis of design," including make or model number or other designation, to establish the significant qualities related to type, function, dimension, in-service performance, physical properties, appearance and other characteristics for purposes of evaluating comparable products of other named manufacturers.

1.4 SUBMITTALS

- A. Substitution Requests: Electronically submit three (3) copies of each request for consideration to the Owner. Identify product or fabrication or installation method to be replaced. Include Specification Section number and title and Drawing numbers and titles.
 - 1. Documentation: Show compliance with requirements for substitutions and the following, as applicable:
 - Statement indicating why specified material or product cannot be provided.
 - b. Coordination information, including a list of changes or modifications needed to other parts of the Work and to construction performed by Owner and separate contractors, which will be necessary to accommodate proposed substitution.
 - c. Detailed comparison of significant qualities of proposed substitution with those of the Work specified. Significant qualities may include attributes such as performance, weight, size, durability, visual effect and specific features and requirements indicated.
 - d. Product Data, including drawings and descriptions of products and fabrication and installation procedures.
 - e. Samples, where applicable or requested.
 - f. List of similar installations for completed projects with project names and addresses and the names and addresses of Architects and Owners.
 - g. Material test reports from a qualified testing agency indicating and interpreting test results for compliance with requirements indicated.
 - h. Research/evaluation reports evidencing compliance with building code in effect for Project, from a model code organization acceptable to authorities having jurisdiction.
 - i. Detailed comparison of Contractor's Final Project Schedule using proposed substitution with products specified for the Work, including effect on the overall Contract Time. If specified product or method of construction cannot be provided within the Contract Time, include letter from manufacturer, on manufacturer's letterhead, stating lack of availability or delays in delivery.
 - j. Cost information, including a proposal of change, if any, in the Contract Sum.
 - k. Contractor's certification that proposed substitution complies with requirements in the Contract Documents and is appropriate for applications indicated.
 - 1. Contractor's waiver of rights to additional payment or time that may subsequently become necessary because of failure of proposed substitution to produce indicated results.
 - 2. Owner's Action: If necessary, the Owner will request additional information or documentation for evaluation within five (5) calendar days of receipt of a request for substitution. Owner will notify Contractor of acceptance or rejection of proposed substitution within ten (10) calendar days of receipt of request, or five (5) calendar days of receipt of additional information or documentation, whichever is later.
 - a. Form of Acceptance: Signed and Approved Substitution Request Form.

B. Basis-of-Design Product Specification Submittal: Comply with requirements in Division 01 Section "Submittal Procedures." Show compliance with requirements.

1.5 QUALITY ASSURANCE

A. Compatibility of Options: If Contractor is given option of selecting between two (2) or more products for use on Project, product selected shall be compatible with products previously selected, even if previously selected products were also options.

1.6 PRODUCT DELIVERY, STORAGE, AND HANDLING

A. Deliver, store and handle products using means and methods that will prevent damage, deterioration and loss, including theft. Comply with manufacturer's written instructions.

B. Delivery and Handling:

- 1. Schedule delivery to minimize long-term storage at Project site and to prevent overcrowding of construction spaces.
- 2. Coordinate delivery with installation time to ensure minimum holding time for items that are flammable, hazardous, easily damaged or sensitive to deterioration, theft and other losses.
- 3. Deliver products to Project site in an undamaged condition in manufacturer's original sealed container or other packaging system, complete with labels and instructions for handling, storing, unpacking, protecting and installing.
- 4. Inspect products on delivery to ensure compliance with the Contract Documents and to ensure that products are undamaged and properly protected.

C. Storage:

- 1. Store products to allow for inspection and measurement of quantity or counting of units.
- 2. Store materials in a manner that will not endanger Project structure.
- 3. Store products that are subject to damage by the elements, under cover in a weathertight enclosure above ground, with ventilation adequate to prevent condensation.
- 4. Store cementitious products and materials on elevated platforms.
- 5. Store foam plastic from exposure to sunlight, except to extent necessary for period of installation and concealment.
- 6. Comply with product manufacturer's written instructions for temperature, humidity, ventilation and weather-protection requirements for storage.
- 7. Protect stored products from damage and liquids from freezing.

1.7 PRODUCT WARRANTIES

- A. Warranties specified in other Sections shall be in addition to, and run concurrent with, other warranties required by the Contract Documents. Manufacturer's disclaimers and limitations on product warranties do not relieve Contractor of obligations under requirements of the Contract Documents.
 - 1. Manufacturer's Warranty: Pre-printed written warranty published by individual manufacturer for a particular product and specifically endorsed by manufacturer to Owner.

- 2. Special Warranty: Written warranty required by or incorporated into the Contract Documents, either to extend time limit provided by manufacturer's warranty or to provide more rights for Owner.
- B. Special Warranties: Prepare a written document that contains appropriate terms and identification, ready for execution. Electronically submit a draft for approval before final execution to the Owner.
 - 1. Manufacturer's Standard Form: Modified to include Project-specific information and properly executed.
 - 2. Specified Form: When specified forms are included with the Specifications, prepare a written document using appropriate form properly executed.
 - 3. Refer to Divisions 2 through 33 Sections for specific content requirements and particular requirements for submitting special warranties. Not all Sections will be used.
- C. Submittal Time: Comply with requirements in Division 01 Section "Closeout Procedures."

PART 2 PRODUCTS

2.1 PRODUCT SELECTION PROCEDURES

- A. General Product Requirements: Provide products that comply with the Contract Documents, that are undamaged and, unless otherwise indicated, that are new at time of installation.
 - 1. Provide products complete with accessories, trim, finish, fasteners and other items needed for a complete installation and indicated use and effect.
 - 2. Standard Products: If available, and unless custom products or nonstandard options are specified, provide standard products of types that have been produced and used successfully in similar situations on other projects.
 - 3. Owner reserves the right to limit selection to products with warranties not in conflict with requirements of the Contract Documents.
 - 4. Where products are accompanied by the term "as selected," Owner will make selection.
 - 5. Where products are accompanied by the term "match sample," sample to be matched is Owner's.
 - 6. Descriptive, performance and reference standard requirements in the Specifications establish "salient characteristics" of products.

B. Product Selection Procedures:

- 1. Products: Where Specifications include a list of names of both products and manufacturers, provide one (1) of the products listed or equal product that complies with requirements.
- 2. Manufacturers: Where Specifications include a list of manufacturers' names, provide a product by one (1) of the manufacturers listed or equal manufacturer that complies with requirements.
- 3. Available Products: Where Specifications include a list of names of both products and manufacturers, provide one (1) of the products listed, or a equal product. Comply with provisions in Part 2 "Product Substitutions" Article for consideration of an unnamed "or Equal" product.

- 4. Available Manufacturers: Where Specifications include a list of manufacturers, provide a product by one (1) of the manufacturers listed, or an unnamed manufacturer, that complies with requirements. Comply with provisions in Part 2 "Product Substitutions" Article for consideration of an unnamed manufacturer.
- 5. Product Options: Where Specifications indicate that sizes, profiles and dimensional requirements on Drawings are based on a specific product or system, provide the specified product or system. Comply with provisions in Part 2 "Product Substitutions" Article for consideration of an unnamed product or system.
- 6. Basis-of-Design Product: Where Specifications name a product and include a list of manufacturers, provide the specified product or a comparable product by one (1) of the other named manufacturers. Drawings and Specifications indicate sizes, profiles, dimensions and other characteristics that are based on the product named. Comply with provisions in Part 2 "Product Substitutions" Article for consideration of an unnamed product by the other named manufacturers.
- 7. Visual Matching Specification: Where Specifications require matching an established Sample, select a product that complies with requirements and matches Owner's sample. Owner's decision will be final on whether a proposed product matches.
 - a. If no product available within specified category matches and complies with other specified requirements, comply with provisions in Part 2 "Product Substitutions" Article for proposal of product.
- 8. Visual Selection Specification: Where Specifications include the phrase "as selected from manufacturer's colors, patterns and textures" or a similar phrase, select a product that complies with other specified requirements.
 - a. Standard Range: Where Specifications include the phrase "standard range of colors, patterns, textures" or similar phrase, Owner will select color, pattern, density or texture from manufacturer's product line that does not include premium items.
 - b. Full Range: Where Specifications include the phrase "full range of colors, patterns, textures" or similar phrase, Owner will select color, pattern, density or texture from manufacturer's product line that includes both standard and premium items.

2.2 PRODUCT SUBSTITUTIONS

- A. Timing: Owner will consider requests for substitutions if received within sixty (60) days after the Notice to Proceed. Requests received after that time may be considered or rejected at discretion of Owner.
- B. Conditions: Owner will consider Contractor's request for substitution when the following conditions are satisfied. If the following conditions are not satisfied, Owner will return requests without action, except to record noncompliance with these requirements:
 - 1. Requested substitution offers Owner a substantial advantage in cost, time, energy conservation, or other considerations, after deducting additional responsibilities Owner must assume. Owner's additional responsibilities may include compensation to Architect for redesign and evaluation services, increased cost of other construction by Owner and similar considerations.
 - 2. Requested substitution does not require extensive revisions to the Contract Documents.

- 3. Requested substitution is consistent with the Contract Documents and will produce indicated results.
- 4. Substitution request is fully documented and properly submitted.
- 5. Requested substitution will not adversely affect Contractor's Final Project Schedule.
- 6. Requested substitution has received necessary approvals of authorities having jurisdiction.
- 7. Requested substitution is compatible with other portions of the Work.
- 8. Requested substitution has been coordinated with other portions of the Work.
- 9. Requested substitution provides specified warranty.

PART 3 EXECUTION (Not Used)

END OF SECTION 01 6000

SECTION 01 7300 EXECUTION

PART 1 GENERAL

1.1 RELATED DOCUMENTS

A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes general procedural requirements governing execution of the Work including, but not limited to, the following:
 - 1. Construction layout.
 - 2. General installation of products.
 - 3. Progress cleaning.
 - 4. Starting and adjusting.
 - 5. Protection of installed construction.
 - 6. Correction of the Work.
- B. See Division 01 Section "Closeout Procedures" for submitting final property survey with Project Record Documents, recording of Owner-accepted deviations from indicated lines and levels, and final cleaning.

1.3 SUBMITTALS

A. Not Applicable

PART 2 PRODUCTS (Not Used)

PART 3 EXECUTION

3.1 EXAMINATION

- A. Existing Conditions: The existence and location of site improvements, utilities and other construction indicated as existing are not guaranteed. Before beginning work, investigate and verify the existence and location of mechanical and electrical systems and other construction affecting the Work. Notify Owner of any discrepancies between plans and actual conditions on site.
 - 1. Before construction, verify the location and points of connection of utility services.
- B. Acceptance of Conditions: Examine substrates, areas and conditions, with Installer or Applicator and Owner present where indicated, for compliance with requirements for installation tolerances and other conditions affecting performance. Record observations.
 - 1. Verify compatibility with and suitability of substrates, including compatibility with existing finishes or primers.

- 2. Examine roughing-in for mechanical and electrical systems to verify actual locations of connections before equipment and fixture installation.
- 3. Examine walls, floors and roofs for suitable conditions where products and systems are to be installed.
- 4. Proceed with installation only after unsatisfactory conditions have been corrected and approved by Owner. Proceeding with the Work indicates acceptance of surfaces and conditions.

3.2 PREPARATION

- A. Field Measurements: Take field measurements as required to fit the Work properly. Recheck measurements before installing each product. Where portions of the Work are indicated to fit to other construction, verify dimensions of other construction by field measurements before fabrication. Coordinate fabrication schedule with construction progress to avoid delaying the Work.
- B. Space Requirements: Verify space requirements and dimensions of items shown diagrammatically on Drawings.
- C. Review of Contract Documents and Field Conditions: Immediately on discovery of the need for clarification of the Contract Documents, submit a request for information to Owner, per Section 01 3100.
 - 1. It is the Contractor's responsibility to coordinate between the various Contract Documents, including the Drawings and Specifications, with neither superseding the other. In the event of conflicts or discrepancies among the Contract Documents, it is the Contractor's responsibility to seek clarification.
 - 2. Where conflicts and/or omissions have not been brought to the attention of the Owner, it is understood that the Contractor has made provisions in the bid for the most costly material or methods.

3.3 CONSTRUCTION LAYOUT

- A. Verification: Before proceeding to lay out the Work, verify layout information shown on Drawings, in relation to the property survey and existing benchmarks. If discrepancies are discovered, notify Owner promptly.
- B. General: Engage experienced layout engineers to lay out the Work using accepted surveying practices.
 - 1. Establish dimensions within tolerances indicated. Do not scale Drawings to obtain required dimensions.
 - 2. Inform installers of lines and levels to which they must comply.
 - 3. Check the location, level and plumb, of every major element as the Work progresses.
 - 4. Notify Owner when deviations from required lines and levels exceed allowable tolerances.

3.4 FIELD ENGINEERING

A. Reference Points: Locate existing permanent benchmarks, control points and similar reference points before beginning the Work. Preserve and protect permanent benchmarks and control points during construction operations.

3.5 INSTALLATION

- A. General: Locate the Work and components of the Work accurately, in correct alignment and elevation, as indicated.
 - 1. Make vertical work plumb and make horizontal work level.
 - 2. Where space is limited, install components to maximize space available for maintenance and ease of removal for replacement.
 - 3. Conceal pipes, ducts and wiring in finished areas unless otherwise indicated.
 - 4. Install materials in lengths that produce the minimum amount of joints.
- B. Comply with manufacturer's written instructions and recommendations for installing products in applications indicated.
- C. Install products at the time and under conditions that will ensure the best possible results. Maintain conditions required for product performance until Substantial Completion.
- D. Conduct construction operations so no part of the Work is subjected to damaging operations or loading in excess of that expected during normal conditions of occupancy.
- E. Tools and Equipment: Do not use tools or equipment that produces harmful noise and dust levels. Refer to Dust Control in the Scope of Work.
- F. Templates: Obtain and distribute to the parties involved templates for work specified to be factory prepared and field installed. Check Shop Drawings of other work to confirm that adequate provisions are made for locating and installing products to comply with indicated requirements.
- G. Attachments: Provide blocking and attachment plates, anchors and fasteners of adequate size and number to securely anchor each component in place, accurately located and aligned with other portions of the Work. Where size and type of attachments are not indicated, verify size and type required for load conditions.
 - 1. Mounting Heights: Where mounting heights are not indicated, mount components at heights directed by Owner.
 - 2. Allow for building movement, including thermal expansion and contraction.
 - 3. Coordinate installation of anchorages. Furnish setting drawings, templates and directions for installing anchorages, including sleeves, concrete inserts, anchor bolts, and items with integral anchors, that are to be embedded in concrete or masonry. Deliver such items to Project site in time for installation.
- H. Joints: Make joints of uniform width. Where joint locations in exposed work are not indicated, submit proposed joint layout, for Owner's approval. Fit exposed connections together to form hairline joints.
 - 1. Use weather cuts, miters, back caulk as needed. Use lengths that minimize joints.
- I. Hazardous Materials: Use products, cleaners, and installation materials that are not considered hazardous.
 - 1. If required, Contractor must submit MSDS for all products to be used onsite to Owner for approval. Owner shall have seven (7) calendar days to review and approve/disapprove of the product.

2. If required, Contractor must submit a weekly schedule detailing when and where approved products will be used on an hour-by-hour basis. This schedule must be submitted by 9:00 AM on Wednesday of the week prior to the scheduled work week

3.6 PROGRESS CLEANING

- A. General: Clean Project site and work areas daily, including common areas. Coordinate progress cleaning for joint-use areas where more than one installer has worked. Enforce requirements strictly. Dispose of materials lawfully in compliance with Section 01 7419 "Construction Waste Management and Disposal."
 - 1. Comply with requirements in NFPA 241 for removal of combustible waste materials and debris.
 - 2. Do not hold materials more than seven (7) calendar days during normal weather or three (3) calendar days if the temperature is expected to rise above 80 degrees F.
 - 3. Containerize hazardous and unsanitary waste materials separately from other waste. Mark containers appropriately and dispose of legally, according to regulations.
 - 4. Do not use Owner receptacles.
 - 5. Recycle as outlined in Waste Management Plan in Section 01 7419.
- B. Site: Maintain Project site free of waste materials and debris.
- C. Work Areas: Clean areas where work is in progress to the level of cleanliness necessary for proper execution of the Work.
 - 1. Remove liquid spills promptly.
 - 2. Where dust would impair proper execution of the Work, broom-clean or vacuum the entire work area, as appropriate.
- D. Installed Work: Keep installed work clean. Clean installed surfaces according to written instructions of manufacturer or fabricator of product installed, using only cleaning materials specifically recommended. If specific cleaning materials are not recommended, use cleaning materials that are not hazardous to health or property and that will not damage exposed surfaces.
- E. Concealed Spaces: Remove debris from concealed spaces before enclosing the space.
- F. Exposed Surfaces in Finished Areas: Clean exposed surfaces and protect as necessary to ensure freedom from damage and deterioration at time of Substantial Completion.
- G. Waste Disposal: Burying or burning waste materials on-site will not be permitted. Washing waste materials down sewers or into waterways will not be permitted.
- H. During handling and installation, clean and protect construction in progress and adjoining materials already in place. Apply protective covering where required to ensure protection from damage or deterioration at Substantial Completion.
- I. Clean and provide maintenance on completed construction as frequently as necessary through the remainder of the construction period. Adjust and lubricate operable components to ensure operability without damaging effects.

J. Limiting Exposures: Supervise construction operations to assure that no part of the construction, completed or in progress, is subject to harmful, dangerous, damaging or otherwise deleterious exposure during the construction period.

3.7 STARTING AND ADJUSTING

- A. Start equipment and operating components to confirm proper operation. Remove malfunctioning units, replace with new units and re-test.
- B. Adjust operating components for proper operation without binding. Adjust equipment for proper operation.
- C. Test each piece of equipment to verify proper operation. Test and adjust controls and safeties. Replace damaged and malfunctioning controls and equipment.
- D. Manufacturer's Field Service: If a factory-authorized service representative is required to inspect field-assembled components and equipment installation, comply with qualification requirements in Division 01 04 00 Section "Quality Requirements."

3.8 PROTECTION OF INSTALLED CONSTRUCTION

- A. Provide final protection and maintain conditions that ensure installed Work is without damage or deterioration at time of Substantial Completion.
- B. Comply with manufacturer's written instructions for temperature and relative humidity.

3.9 CORRECTION OF THE WORK

- A. Repair or remove and replace defective construction. Restore damaged substrates and finishes. Comply with requirements in Division 01 73 29 Section "Cutting and Patching."
 - 1. Repairing includes replacing defective parts, refinishing damaged surfaces, touching up with matching materials and properly adjusting operating equipment.
- B. Restore permanent facilities used during construction as well as landscapes and hardscapes to their original condition.
- C. Remove and replace damaged surfaces that are exposed to view if surfaces cannot be repaired without visible evidence of repair.
- D. Repair components that do not operate properly. Remove and replace operating components that cannot be repaired.
- E. Remove and replace chipped, scratched and broken glass or reflective surfaces.

END OF SECTION 01 7300

SECTION 01 7329 CUTTING AND PATCHING

PART 1 GENERAL

1.1 RELATED DOCUMENTS

A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes procedural requirements for cutting and patching.
- B. See Divisions 02 through 33 Sections for specific requirements and limitations applicable to cutting and patching individual parts of the Work. Not all Sections will be used.

1.3 QUALITY ASSURANCE

- A. Structural Elements: Do not cut and patch structural elements in a manner that could change their load-carrying capacity or load-deflection ratio.
- B. Operational Elements: Do not cut and patch operating elements and related components in a manner that results in reducing their capacity to perform as intended or that results in increased maintenance or decreased operational life or safety.
- C. Miscellaneous Elements: Do not cut and patch miscellaneous elements or related components in a manner that could change their load-carrying capacity, that results in reducing their capacity to perform as intended, or that results in increased maintenance or decreased operational life or safety.

D. Visual Requirements:

- 1. Unless indicated otherwise, patching, extending or matching shall be performed as necessary to make the Work complete, with all components matching and consistent.
- 2. Do not cut and patch construction in a manner that results in visual evidence of cutting and patching. Do not cut and patch construction exposed on the exterior or in occupied spaces in a manner that would, in Owner's opinion, reduce the building's aesthetic qualities. Remove and replace construction that has been cut and patched in a visually unsatisfactory manner.
- 3. Patching materials shall meet the requirements of the jurisdictional code authorities.
- 4. All patching procedures shall be reviewed with the Owner prior to proceeding.

1.4 WARRANTY

A. Existing Warranties: Remove, replace, patch and repair materials and surfaces cut or damaged during cutting and patching operations, by methods and with materials so as not to void existing warranties.

PART 2 PRODUCTS

2.1 MATERIALS

- A. General: Comply with requirements specified in other Sections.
- B. In-Place Materials: Use materials identical to in-place materials. For exposed surfaces, use materials that visually match in-place adjacent surfaces to the fullest extent possible.
 - 1. If identical materials are unavailable or cannot be used, use materials that, when installed, will match the visual and functional performance of in-place materials.

PART 3 EXECUTION

3.1 EXAMINATION

- A. Examine surfaces to be cut and patched and conditions under which cutting and patching are to be performed.
 - 1. Compatibility: Before patching, verify compatibility with and suitability of substrates, including compatibility with in-place finishes or primers.
 - 2. Proceed with installation only after unsafe or unsatisfactory conditions have been corrected.

3.2 PREPARATION

- A. Temporary Support: Provide temporary support of Work to be cut.
- B. Protection: Protect in-place construction during cutting and patching to prevent damage. Provide protection from adverse weather conditions for portions of Project that might be exposed during cutting and patching operations.
- C. Adjoining Areas: Avoid interference with use of adjoining areas or interruption of free passage to adjoining areas.
- D. Cut, move or remove items as necessary for access to alterations and renovations work; replace and restore at completion.
- E. Contact the Owner when unsuitable materials not marked for removal such as rotted wood, rusted metals and deteriorated concrete and masonry are discovered.
- F. Remove debris and abandoned items from area and from concealed spaces.
- G. Prepare surfaces and remove surface finishes to provide for proper installation of new work and new finishes.

3.3 PERFORMANCE

A. General: Employ skilled workers to perform cutting and patching. Proceed with cutting and patching at the earliest feasible time and complete without delay.

- B. Cutting: Cut in-place construction by sawing, drilling, breaking, chipping, grinding and similar operations, including excavation, using methods least likely to damage elements retained or adjoining construction. Provide appropriate dust control while cutting through surfaces. If possible, review proposed procedures with original Installer; comply with original Installer's written recommendations.
 - 1. In general, use hand or small power tools designed for sawing and grinding, not hammering and chopping. Cut holes and slots as small as possible, neatly to size required and with minimum disturbance of adjacent surfaces. Temporarily cover openings when not in use.
 - 2. Finished Surfaces: Cut or drill from the exposed or finished side into concealed surfaces.
 - 3. Concrete and Masonry: Cut using a cutting machine, such as an abrasive saw or a diamond-core drill.
 - 4. Excavating and Backfilling: Comply with requirements in applicable Division 31 and 33 Sections (Sections may not be used) where required by cutting and patching operations.
 - 5. Proceed with patching after construction operations requiring cutting are complete.
- C. Patching: Patch construction by filling, repairing, refinishing, closing up and similar operations following performance of other Work. Patch with durable seams that are as invisible as possible. Provide materials and comply with installation requirements specified in other Sections.
 - 1. Inspection: Where feasible, test and inspect patched areas after completion to demonstrate integrity of installation.
 - 2. Exposed Finishes: Restore exposed finishes of patched areas and extend finish restoration into retained adjoining construction in a manner that will eliminate evidence of patching and refinishing.
 - 3. Floors and Walls: Where walls or partitions that are removed extend one finished area into another, patch and repair floor and wall surfaces in the new space. Provide an even surface of uniform finish, color, texture and appearance. Remove in-place floor and wall coverings and replace with new materials, if necessary, to achieve uniform color and appearance.
 - 4. Ceilings: Patch, repair or rehang in-place ceilings as necessary to provide an even-plane surface of uniform appearance.
 - 5. Exterior Building Enclosure: Patch components in a manner that restores enclosure to a weathertight condition.
- D. Trim existing doors as necessary to clear new floor finishes; refinish trimmed areas.
- E. Where existing items are indicated as cut or reconfigured, cap and finish all exposed edges to match the existing construction to remain. Provide new or relocated supports spaced to be consistent with the installation.
- F. Cleaning: Clean areas and spaces where cutting and patching are performed. Completely remove paint, mortar, oils, putty and similar materials.

END OF SECTION 01 7329

SECTION 01 7419 CONSTRUCTION WASTE MANAGEMENT AND DISPOSAL

PART 1 GENERAL

1.1 RELATED DOCUMENTS

A. Drawings and general provisions of the Contract, including General and Supplementary Conditions, Project Documents, and other Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes administrative and procedural requirements for the following:
 - 1. Salvaging of non-hazardous demolition and construction waste.
 - 2. Recycling of non-hazardous demolition and construction waste.
 - 3. Disposing of non-hazardous demolition and construction waste.

1.3 DEFINITIONS

- A. Construction Waste: All non-hazardous building and site materials or other non-hazardous solid waste resulting from construction, remodeling, renovation, repair or land-clearing operations. Construction waste includes packaging and material that is recycled, reused, salvaged or disposed as garbage.
- B. Demolition Waste: All non-hazardous building and site materials or other non-hazardous solid waste resulting from demolition or selective demolition operations.
- C. Disposal: Removal off-site of demolition and construction waste and subsequent sale, recycling, reuse or deposit in landfill or incinerator acceptable to authorities having jurisdiction.
- D. Recycle: Recovery of demolition or construction waste for subsequent processing for the purpose of using the material in the manufacture of a new product.
 - 1. Source-Separated Recycling: The process of separating recyclable materials in separate containers as they are generated on the job-site. The separated materials are hauled directly to a recycling facility or transfer station.
 - 2. Co-mingled Recycling: The process of collecting mixed recyclable materials in one container on-site. The container is taken to a material recovery facility where materials are separated for recycling.
- E. Re-Use: Making use of a material without altering its form. Materials can be reused onsite or reused on other project off-site. Examples include, but are not limited to the following:
 - 1. Grinding of concrete for use as sub-base material.
 - 2. Chipping of land-clearing debris for use as mulch.

- F. Salvage: Recovery of demolition or construction waste and subsequent sale or re-use in another facility.
- G. Salvage and Re-use: Recovery of demolition or construction waste and subsequent incorporation into the Work.

1.4 PERFORMANCE GOALS

- A. General: Material from demolition projects shall be recycled or reused whenever practicable (RCW 39.04.135). Contractor to develop a waste management plan that results in end-of-Project rates for salvage/recycling of fifty (50%) percent by weight of total waste generated by the Work by one or a combination of the following:
 - 1. Salvage.
 - 2. Reuse.
 - 3. Source-separated Recycling.
 - 4. Co-mingled Recycling.
- B. Salvage/Recycle Goals: Owner's goal is to salvage and recycle as much non-hazardous demolition and construction waste as possible including the following materials:
 - 1. Cardboard.
 - 2. Clean dimensional wood.
 - 3. Metals: Material banding, stud trim, ductwork, piping, rebar, roofing, other trim, steel, iron, galvanized sheet steel, stainless steel, aluminum, copper, zinc, lead, brass, and bronze.
 - 4. Gypsum board.

1.5 SUBMITTALS

- A. Waste Management Plan: Submit three (3) copies of plan within seven (7) calendar days of date established for the Notice of Proceed.
- B. Waste Reduction Progress Reports: Electronically submit, concurrent with Final Application for Payment, the report to the Owner. Include separate reports for demolition and construction waste. Include the following information:
 - 1. Material category.
 - 2. Generation point of waste.
 - 3. Destination of waste.
 - 4. Total quantity of waste in tons.
 - 5. Quantity of waste salvaged, both estimated and actual in tons.
 - 6. Quantity of waste recycled, both estimated and actual in tons.
 - 7. Total quantity of waste recovered (salvaged plus recycled) in tons.
 - 8. Total quantity of waste recovered (salvaged plus recycled) as a percentage of total waste.
- C. Waste Reduction Calculations: Before request for Substantial Completion, electronically submit a copy of calculated end-of-Project rates for salvage, recycling, and disposal as a percentage of total waste generated by the Work to the Owner.
- D. Records of Donations: Indicate receipt and acceptance of salvageable waste donated to individuals and organizations. Indicate whether organization is tax exempt.

- E. Records of Sales: Indicate receipt and acceptance of salvageable waste sold to individuals and organizations. Indicate whether organization is tax exempt.
- F. Recycling and Processing Facility Records: Indicate receipt and acceptance of recyclable waste by recycling and processing facilities licensed to accept them. Include manifests, weight tickets, receipts and invoices. If waste is taken to a facility that landfills and recycles, include facility record of recycling rate for the period of construction.
- G. Landfill and Incinerator Disposal Records: Indicate receipt and acceptance of waste by landfills and incinerator facilities licensed to accept them. Include manifests, weight tickets, receipts and invoices.

1.6 QUALITY ASSURANCE

- A. Regulatory Requirements: Conduct construction waste management activities in accordance with State of Washington RCW 70.95.240, Seattle Municipal Code Chapter 21.36 and all other applicable laws and ordinances.
- B. Review of the following publications and programs (request copies by calling King County Solid Waste Division at 206-477-4466)
 - 1. Construction Recycling Directory for Seattle/ King County.
 - 2. Contractors Guide: Save money and resources through job-site recycling and waste prevention.
 - 3. King County Solid Waste Division Report of Co-mingled Recycling Facilities (available at www.metrokc.gov/dnrp/swd/construction-recycling/comingled.asp)

1.7 WASTE MANAGEMENT PLAN

- A. General: Develop a plan consisting of waste identification, waste reduction work plan and cost/revenue analysis. Include separate sections in plan for demolition and construction waste. Indicate quantities by weight or volume, but use same units of measure throughout waste management plan.
- B. Waste Identification: Indicate anticipated types and quantities of demolition and construction waste generated by the Work. Include estimated quantities and assumptions for estimates.
- C. Waste Reduction Work Plan: List each type of waste and whether it will be salvaged, recycled or disposed of in landfill or incinerator. Include points of waste generation, total quantity of each type of waste, quantity for each means of recovery and handling and transportation procedures.
 - 1. Salvaged Materials for Reuse: For materials that will be salvaged and reused in this Project, describe methods for preparing salvaged materials before incorporation into the Work.
 - 2. Salvaged Materials for Sale: For materials that will be sold to individuals and organizations, include list of their names, addresses and telephone numbers.
 - 3. Salvaged Materials for Donation: For materials that will be donated to individuals and organizations, include list of their names, addresses and telephone numbers.

- 4. Recycled Materials: Include list of local receivers and processors and type of recycled materials each will accept. Include names, addresses and telephone numbers
- 5. Disposed Materials: Indicate how and where materials will be disposed of. Include name, address and telephone number of each landfill and incinerator facility.
- 6. Handling and Transportation Procedures: Include method that will be used for separating recyclable waste including sizes of containers, container labeling and designated location on Project site where materials separation will be located.
- D. Cost/Revenue Analysis: Indicate total cost of waste disposal as if there was no waste management plan and net additional cost or net savings resulting from implementing waste management plan. Include the following:
 - 1. Total quantity of waste.
 - 2. Estimated cost of disposal (cost per unit). Include hauling and tipping fees and cost of collection containers for each type of waste.
 - 3. Total cost of disposal (with no waste management).
 - 4. Savings in hauling and tipping fees that are avoided.
 - 5. Handling and transportation costs. Include cost of collection containers for each type of waste.
 - 6. Net additional cost or net savings from waste management plan.

PART 2 PRODUCTS (Not Used)

PART 3 EXECUTION

3.1 PLAN IMPLEMENTATION

- A. General: Implement waste management plan as approved by Owner. Provide handling, containers, storage, signage, transportation and other items as required to implement waste management plan during the entire duration of the Contract.
- B. Waste Management Coordinator: Contractor shall be responsible for implementing, monitoring, and reporting status of waste management work plan.
- C. Training: Train workers, subcontractors and suppliers on proper waste management procedures, as appropriate for the Work occurring at Project site.
 - 1. Distribute waste management plan to everyone concerned within one (1) day of submittal return. A hard copy should remain on site. Send the plan electronically to the Owner.
 - 2. Distribute waste management plan to entities when they first begin work on-site. Review plan procedures and locations established for salvage, recycling and disposal.
 - 3. The General Contractor will ensure that the waste plan is communicated to the crews and subcontractors on site. They will be informed of:
 - a. How materials should be separated, and why.
 - b. Where materials should go.
 - c. How often the materials will be collected and delivered to the appropriate facilities.
 - d. The importance of recycling, and KCHA's recycling goals for the project.

- D. Site Access and Temporary Controls: Conduct waste management operations to ensure minimum interference with roads, streets, walks, walkways and other adjacent occupied and used facilities.
 - 1. Designate and label specific areas on Project site necessary for separating materials that are to be salvaged, recycled, reused, donated and sold.
 - 2. Comply with Division 01 50 00 Section "Temporary Facilities and Controls" for controlling dust and dirt, environmental protection and noise control.
 - 3. Clearly label the recycling bins and waste containers on site.
 - 4. Post lists of recyclable and non-recyclable materials in many locations, in different languages.
 - 5. The General Contractor will provide feedback to the crew and subcontractors on the results of their efforts
 - E. To the greatest extent possible, include in material purchasing agreements a waste reduction provision requesting that materials and equipment be delivered in packaging made of recyclable material, that they reduce the amount of packaging, that packaging be taken back for reuse or recycling, and to take back all unused product. Ensure that subcontractors require the same provisions in their purchase agreements.

3.2 SALVAGING DEMOLITION WASTE

- A. Salvaged Items for Reuse in the Work:
 - 1. Clean salvaged items.
 - 2. Pack or crate items after cleaning. Identify contents of containers.
 - 3. Store items in a secure area until installation.
 - 4. Protect items from damage during transport and storage.
 - 5. Install salvaged items to comply with installation requirements for new materials and equipment. Provide connections, supports and miscellaneous materials necessary to make items functional for use indicated.
- B. Salvaged Items for Sale and Donation: Not permitted on Project site.
- C. Salvaged Items for Owner's Use:
 - 1. Clean salvaged items.
 - 2. Pack or crate items after cleaning. Identify contents of containers.
 - 3. Store items in a secure area until delivery to Owner.
 - 4. Transport items to Owner's designated off-site storage area.
 - 5. Protect items from damage during transport and storage.

3.3 RECYCLING DEMOLITION AND CONSTRUCTION WASTE, GENERAL

- A. General: Recycle paper and beverage containers used by on-site workers.
- B. Recycling Receivers and Processors: The list below is provided for information only; available recycling receivers and processors include, but are not limited to, the following:
 - 1. Washington State Department of Ecology, Recycling, Northwest Region 425-649-7000.
 - 2. Industrial Materials Exchange (IMEX), Hazardous Waste Management Program, King County, Washington.

- 3. The "Recycling Plus Program Manual" published by the Washington State Clean Washington Center can be used to develop a job site reduction program. The manual includes a job-site recycling worksheet and form, tips on waste reduction, and other technical assistance. The manual also includes sample language for waste reduction requirements for subcontractors' agreements, as well as sample provision for a full-service recycling agreement.
- 4. LEED Reference Guide, Construction Waste Management section.
- 5. Recovery 1 is a resource recovery, recycling and research facility dedicated to developing sustainable waste management systems. www.recovery1.com or by phone at 800-949-5852.
- 6. Total Reclaim offers a wide variety of innovative environmental services for management of electronics and other hard to handle materials, including fluorescent lamps, refrigerant gases and appliances. www.totalreclaim.com or by phone 206-343-7443.
- 7. "Contractors' Guide for Preventing Waste and Recycling"

 https://kingcounty.gov/~/media/depts/dnrp/solid-waste/construction-recycling/documents/ConGuide.ashx?la=en
- 8. "Seattle/King County Construction Recycling Directory." https://kingcounty.gov/depts/dnrp/solid-waste/programs/green-building/county-green-building.aspx
- C. Recycling Incentives: Revenues, savings, rebates, tax credits and other incentives received for recycling waste materials shall accrue to Owner.
- D. Procedures: Separate recyclable waste from other waste materials, trash and debris. Separate recyclable waste by type at Project site to the maximum extent practical.
 - 1. Provide appropriately marked containers or bins for controlling recyclable waste until they are removed from Project site. Include list of acceptable and unacceptable materials at each container and bin.
 - a. Inspect containers and bins for contamination and remove contaminated materials if found.
 - 2. Stockpile processed materials on-site without intermixing with other materials. Place, grade and shape stockpiles to drain surface water. Cover to prevent windblown dust.
 - 3. Stockpile materials away from construction area. Do not store within drip line of remaining trees.
 - 4. Store components off the ground and protect from the weather.
 - 5. Remove recyclable waste off Owner's property and transport to recycling receiver or processor.

3.4 RECYCLING DEMOLITION WASTE

- A. Wood Materials: Sort and stack members according to size, type and length. Separate lumber, engineered wood products, panel products and treated wood materials.
- B. Metals: Separate metals by type.
 - 1. Structural Steel: Stack members according to size, type of member and length.
 - 2. Remove and dispose of bolts, nuts, washers and other rough hardware.
- C. Gypsum Board: Stack large clean pieces on wood pallets and store in a dry location. Remove edge trim and sort with other metals. Remove and dispose of fasteners.

- D. Equipment: Drain tanks, piping, and fixtures. Seal openings with caps or plugs. Protect equipment from exposure to weather.
- E. Plumbing Fixtures: Separate by type and size.
- F. Piping: Reduce piping to straight lengths and store by type and size. Separate supports, hangers, valves, sprinklers and other components by type and size.
- G. Lighting Fixtures: Separate lamps by type and protect from breakage.
- H. Electrical Devices: Separate switches, receptacles, switchgear, transformers, meters, panelboards, circuit breakers and other devices by type.
- I. Conduit: Reduce conduit to straight lengths and store by type and size.

3.5 RECYCLING CONSTRUCTION WASTE

A. Packaging:

- 1. Cardboard and Boxes: Break down packaging into flat sheets. Bundle and store in a dry location.
- 2. Polystyrene Packaging: Separate and bag materials.
- 3. Pallets: As much as possible, require deliveries using pallets to remove pallets from Project site. For pallets that remain on-site, break down pallets into component wood pieces and comply with requirements for recycling wood.
- 4. Crates: Break down crates into component wood pieces and comply with requirements for recycling wood.

B. Wood Materials:

- 1. Clean Cut-Offs of Lumber: Grind or chip into small pieces.
- 2. Clean Sawdust: Bag sawdust that does not contain painted or treated wood.
- C. Gypsum Board: Stack large clean pieces on wood pallets and store in a dry location.
 - 1. Clean Gypsum Board: Grind scraps of clean gypsum board using small mobile chipper or hammer mill. Screen out paper after grinding.

3.6 DISPOSAL OF WASTE

- A. General: Except for items or materials to be salvaged, recycled or otherwise reused, remove waste materials from Project site and legally dispose of them in a landfill or incinerator acceptable to authorities having jurisdiction.
 - 1. Except as otherwise specified, do not allow waste materials that are to be disposed of accumulate on-site.
 - 2. Remove and transport debris in a manner that will prevent spillage on adjacent surfaces and areas.
- B. Burning: Do not burn waste materials.
- C. Disposal: Transport waste materials off Owner's property and legally dispose of them.

END OF SECTION 01 7419

KING COUNTY HOUSING AUTHORITY PEPPER TREE ENVELOPE Waste Disposal and Recycling Data Form



The resource conservation program at KCHA tracks the disposal and recycling data for all KCHA activities. These includes all of the waste and recycling generated by residents, food composting, yard waste composting, unit-improvement waste, illegal dumping waste, and all waste created during the construction and demolition process.

Our goals for all of these areas are:

- 1. Track the diversion of our waste and improve when possible
- 2. Meet KCHA recycling goals.

Please provide estimates, to the best of your ability, about the projected waste being generated on this project as well as how much of that waste is being recycled vs disposed. If estimates aren't possible, then we will need this information at project close-out.

Project Name: PEPPER TREE ENVELOPE

Project Address: 19926 Ballinger Way NE, Shoreline, WA 98155

Work Order No.: 1322 Job No.: 101.9

DESCRIPTION	WEIGHT		QUANTITY Circle One	
Total Waste Generated**		Lbs.	CY	Tons
Waste Disposed		Lbs.	CY	Tons
Waste Recycled		Lbs.	CY	Tons
**Waste Disposed plus Waste Recycled should equal Total Waste Generated				
What % of the total waste do you estimate you will recycle?				

The following tables identify materials expected on this project, the quantities generated, whether they will be disposed or recycled, and what facility they will be disposed or recycled at.

DEMOLITION PHASE				
MATERIAL	QUANTITY Lbs./CY/Tons	DISPOSAL / RECYCLE? (CIRCLE ONE)		DISPOSAL OR RECYCLING FACILITY
		Disposal	Recycle	

Example: Roofing, 3 tons, Recycle, DTG Recycle

CONSTRUCTION PHASE				
MATERIAL	QUANTITY Lbs./CY/Tons	DISPOSAL / RECYCLE? (CIRCLE ONE)		DISPOSAL OR RECYCLING FACILITY
		Disposal	Recycle	

Example: Misc. Con. Mat., 30 cy, Recycle, Waste Management

SECTION 01 7700 CLOSEOUT PROCEDURES

PART 1 GENERAL

1.1 RELATED DOCUMENTS

A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes administrative and procedural requirements for contract closeout, including, but not limited to, the following:
 - 1. Inspection procedures.
 - 2. Warranties.
 - 3. Final cleaning.
- B. See the Owner-Contractor Contract for requirements for Applications for Payment for Substantial and Final Completion.
- C. See Division 01 7839 Section "Project Record Documents" for submitting Record Drawings, Record Specifications and Record Product Data.
- D. See Division 01 7823 Section "Operation and Maintenance Data" for operation and maintenance manual requirements.
- E. See Divisions 02 through 33 Sections for specific closeout and special cleaning requirements for the Work in those Sections. Not all Sections will be used.

1.3 SUBSTANTIAL COMPLETION (Refer to Article 9.8 AIA A201-2017)

- A. Preliminary Procedures: Before requesting inspection for determining date of Substantial Completion, complete the following. List items below that are incomplete in request.
 - 1. Prepare a list of items to be completed and corrected (punch list), the value of items on the list, and reasons why the Work is not complete.
 - 2. Advise Owner of pending insurance changeover requirements.
 - 3. Submit specific warranties, workmanship bonds, maintenance service agreements, final certifications and similar documents (to be included in O&M Manuals).
 - 4. Obtain and submit to Owner, the releases permitting Owner unrestricted use of the Work and access to services and utilities. Include occupancy permits, operating certificates, and similar releases.
 - 5. Prepare and submit Project Record Documents, operation and maintenance manuals, damage or settlement surveys, property surveys and similar final record information to the Owner.
 - 6. Deliver tools, spare parts, extra materials and similar items to location designated by Owner. Label with manufacturer's name and model number where applicable.
 - 7. Make final changeover of permanent locks and deliver keys to Owner. Advise Owner's personnel of changeover in security provisions.

- 8. Complete startup testing of systems.
- 9. Submit test/adjust/balance records to the Owner.
- 10. Terminate and remove temporary facilities from Project site, along with mockups, construction tools and similar elements.
- 11. Advise Owner of changeover in heat and other utilities.
- 12. Submit changeover information related to Owner's occupancy, use, operation and maintenance.
- 13. Complete final cleaning requirements, including touchup painting.
- 14. Touch up and otherwise repair and restore marred exposed finishes to eliminate visual defects.
- 15. Provide training on all newly installed systems by qualified personnel. Training will be presented to those that use the equipment, i.e. tenants site staff, facility users.
- B. Inspection: Submit a written request for inspection for Substantial Completion to the Owner. On receipt of request, Owner will either proceed with inspection or notify Contractor of unfulfilled requirements. Owner will prepare the Certificate of Substantial Completion after inspection or will notify Contractor of items, either on Contractor's list or additional items identified by Owner, that must be completed or corrected before certificate will be issued.
 - 1. Re-inspection: Request re-inspection when the Work identified in previous inspections as incomplete is completed or corrected.
 - 2. Results of completed inspection will form the basis of requirements for Final Completion.

1.4 CONTRACT COMPLETION (Refer to Article 9.10 in AIA A201-2017)

- A. Preliminary Procedures: Before requesting final inspection for determining date of Contract Completion, complete the following:
 - 1. Submit a final Application for Payment according to the Owner-Contractor Contract provisions to the Owner.
 - 2. Submit to the Owner, a certified copy of Owner's Substantial Completion inspection list of items to be completed or corrected (punch list), endorsed and dated by Owner. The certified copy of the list shall state that each item has been completed or otherwise resolved for acceptance.
 - 3. Submit evidence of final, continuing insurance coverage complying with insurance requirements to the Owner.
 - 4. Instruct Owner's personnel in operation, adjustment and maintenance of products, equipment and systems.
- B. Inspection: Submit a written request for final inspection for acceptance to the Owner. On receipt of request, Owner will either proceed with inspection or notify Contractor of unfulfilled requirements. Owner will notify Contractor of construction that must be completed or corrected before certificate will be issued.
 - 1. Re-inspection: Request re-inspection when the Work identified in previous inspections as incomplete is completed or corrected.

1.5 LIST OF INCOMPLETE ITEMS (PUNCH LIST)

A. Preparation: After Contractor has performed own Quality Control of the Work, Contractor will notify and schedule punch list inspection with Owner and other team

members. Owner will document items needing correction on Owner provided form listing area inspected and deficient item needing correction. Owner will provide Contractor with copy of punch list after inspection is completed. Owner has right to stop inspection due to quantity of repetitious items identified by Owner, or if Contractor has not performed own Quality Control of the Work

- 1. Organize list of spaces in sequential order.
- 2. Organize items applying to each space by major element, including categories for ceiling, individual walls, floors, equipment and building systems.

1.6 WARRANTIES (Refer to Article 3.5 in AIA A201-2017)

- A. Submittal Time: Submit written warranties on request of Owner for designated portions of the Work where commencement of warranties other than date of Substantial Completion is indicated.
- B. Organize warranty documents into an orderly sequence based on the table of contents of the Project Manual.
 - 1. Bind warranties and bonds in heavy-duty, 3-ring, vinyl-covered, loose-leaf binders, thickness as necessary to accommodate contents, and sized to receive 8-1/2-by-11-inch paper.
 - 2. Provide heavy paper dividers with plastic-covered tabs for each separate warranty. Mark tab to identify the product or installation. Provide a typed description of the product or installation, including the name of the product and the name, address and telephone number of Installer.
 - 3. Identify each binder on the front and spine with the typed or printed title "WARRANTIES," Project name and name of Contractor.
- C. Provide additional copies of each warranty to include in operation and maintenance manuals.

PART 2 PRODUCTS

2.1 MATERIALS

A. Cleaning Agents: Use cleaning materials and agents recommended by manufacturer or fabricator of the surface to be cleaned. Do not use cleaning agents that are potentially hazardous to health or property or that might damage finished surfaces.

PART 3 EXECUTION

3.1 FINAL CLEANING

- A. General: Provide final cleaning. Conduct cleaning and waste-removal operations to comply with local laws and ordinances and Federal and local environmental and antipollution regulations.
- B. Cleaning: Employ experienced workers or professional cleaners for final cleaning. Clean each surface or unit to condition expected in an average commercial building cleaning and maintenance program. Comply with manufacturer's written instructions.

- 1. Complete the following cleaning operations before requesting inspection for certification of Substantial Completion for entire Project or for a portion of Project:
 - a. Clean Project site, yard and grounds, in areas disturbed by construction activities, including landscape development areas, of rubbish, waste material, litter and other foreign substances.
 - b. Sweep paved areas broom clean. Remove petrochemical spills, stains and other foreign deposits.
 - c. Remove tools, construction equipment, machinery and surplus material from Project site.
 - d. Clean exposed exterior and interior hard-surfaced finishes to a dirt-free condition, free of stains, films and similar foreign substances. Avoid disturbing natural weathering of exterior surfaces. Restore reflective surfaces to their original condition.
 - e. Sweep concrete floors broom clean in unoccupied spaces.
 - f. Vacuum carpet and similar soft surfaces, removing debris and excess nap; shampoo if visible soil or stains remain.
 - g. Clean transparent materials, including mirrors and glass in doors and windows. Remove glazing compounds and other noticeable, vision-obscuring materials. Replace chipped or broken glass and other damaged transparent materials. Polish mirrors and glass, taking care not to scratch surfaces.
 - h. Remove labels that are not permanent.
 - i. Touch up and otherwise repair and restore marred, exposed finishes and surfaces. Replace finishes and surfaces that cannot be satisfactorily repaired or restored or that already show evidence of repair or restoration.
 - 1) Do not paint over "UL" and similar labels, including mechanical and electrical nameplates.
 - j. Wipe surfaces of mechanical and electrical equipment and similar equipment. Remove excess lubrication, paint and mortar droppings and other foreign substances.
 - k. Replace parts subject to unusual operating conditions.
 - 1. Clean plumbing fixtures to a sanitary condition, free of stains, including stains resulting from water exposure.
 - m. Replace disposable air filters and clean permanent air filters. Clean exposed surfaces of diffusers, registers and grills.
 - n. Clean light fixtures, lamps, globes and reflectors to function with full efficiency. Replace burned-out bulbs and those noticeably dimmed by hours of use, and defective or noisy starters in fluorescent and mercury vapor fixtures to comply with requirements for new fixtures.
 - o. Leave Project clean and ready for occupancy.
- C. Comply with safety standards for cleaning. Do not burn waste materials. Do not bury debris or excess materials on Owner's property. Do not discharge volatile, harmful or dangerous materials into drainage systems. Remove waste materials from Project site and dispose of lawfully.

END OF SECTION 01 7700

SECTION 01 7823 OPERATION AND MAINTENANCE DATA

PART 1 GENERAL

1.1 RELATED DOCUMENTS

A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes administrative and procedural requirements for preparing operation and maintenance manuals, including the following:
 - 1. Operation manuals for systems, subsystems, and equipment Maintenance manuals for the care and maintenance of products, materials, finishes, systems, and equipment.
- B. See Divisions 02 through 33 Sections for specific operation and maintenance manual requirements for the Work in those Sections. Every Division may not be used.

1.3 SUBMITTALS

- A. Manual: Submit one (1) electronic copy of each manual in final form at least fifteen (15) calendar days before final inspection. Owner will return copy with comments within fifteen (15) calendar days after final inspection.
 - 1. Correct or modify each manual to comply with Owner's comments. Submit two (2) hard copies and one (1) electronic copy on Compact Disk of each corrected manual within fifteen (15) calendar days of receipt of Owner's comments.

PART 2 - PRODUCTS

2.1 MANUALS- GENERAL

- A. Organization: Unless otherwise indicated, organize each manual into a separate section for each system and subsystem, and a separate section for each piece of equipment not part of a system. Each manual shall contain a title page, table of contents and manual contents.
- B. Title Page: Enclose title page in transparent plastic sleeve. Include the following information:
 - 1. Subject matter included in manual.
 - 2. Name and address of Project.
 - 3. Name and address of Owner.
 - 4. Date of submittal.
 - 5. Name, address and telephone number of Contractor.
 - 6. Name and address of Architect.
 - 7. Cross-reference to related systems in other operation and maintenance manuals.

- C. Table of Contents: List each product included in manual, identified by product name, indexed to the content of the volume, and cross-referenced to Specification Section number in Project Manual.
- D. Manual Contents: Organize into sets of manageable size. Arrange contents alphabetically by system, subsystem and equipment. If possible, assemble instructions for subsystems, equipment and components of one (1) system into a single binder.
 - 1. Binders: Heavy-duty, 3-ring, vinyl-covered, loose-leaf binders, in thickness necessary to accommodate contents, sized to hold 8-1/2-by-11-inch paper; with clear plastic sleeve on spine to hold label describing contents and with pockets inside covers to hold folded oversize sheets.
 - a. Identify each binder on front and spine, with printed title "OPERATION AND MAINTENANCE MANUAL," Project title or name, and subject matter of contents. Indicate volume number for multiple-volume sets.
 - 2. Dividers: Heavy-paper dividers with plastic-covered tabs for each section. Mark each tab to indicate contents. Include typed list of products and major components of equipment included in the section on each divider, cross-referenced to Specification Section number and title of Project Manual.
 - 3. Protective Plastic Sleeves: Transparent plastic sleeves designed to enclose diagnostic software diskettes for computerized electronic equipment.
 - 4. Drawings: Attach reinforced, punched binder tabs on drawings and bind with text.
 - a. If oversize drawings are necessary, fold drawings to same size as text pages and use as foldouts.
 - b. If drawings are too large to be used as foldouts, fold and place drawings in labeled envelopes and bind envelopes in rear of manual. At appropriate locations in manual, insert typewritten pages indicating drawing titles, descriptions of contents and drawing locations.

2.2 OPERATION MANUALS

- A. Content: In addition to requirements in this Section, include operation data required in individual Specification Sections and equipment descriptions, operating standards, operating procedures, operating logs, wiring and control diagrams, and license requirements.
- B. Descriptions: Include the following:
 - 1. Product name and model number.
 - 2. Manufacturer's name.
 - 3. Equipment identification with serial number of each component.
 - 4. Equipment function.
 - 5. Operating characteristics.
 - 6. Limiting conditions.
 - 7. Performance curves.
 - 8. Engineering data and tests.
 - 9. Complete nomenclature and number of replacement parts.
- C. Operating Procedures: Include start-up, break-in and control procedures; stopping and normal shutdown instructions; routine, normal, seasonal and weekend operating instructions; and required sequences for electric or electronic systems.

- D. Systems and Equipment Controls: Describe the sequence of operation and diagram controls as installed.
- E. Piped Systems: Diagram piping as installed and identify color-coding where required for identification.

2.3 PRODUCT MAINTENANCE MANUAL

- A. Content: Organize manual into a separate section for each product, material and finish. Include source information, product information, maintenance procedures, repair materials and sources, and warranties and bonds, as described below.
- B. Source Information: List each product included in manual; identify by product name and arrange to match manual's table of contents. For each product, list name, address and telephone number of Installer or supplier and maintenance service agent, and cross-reference Specification Section number and title in Project Manual.
- C. Product Information: Include the following, as applicable:
 - 1. Product name and model number.
 - 2. Manufacturer's name.
 - 3. Color, pattern and texture.
 - 4. Material and chemical composition.
 - 5. Re-ordering information for specially manufactured products.
- D. Maintenance Procedures: Include manufacturer's written recommendations and inspection procedures, types of cleaning agents, methods of cleaning, schedule for cleaning and maintenance, and repair instructions.
- E. Repair Materials and Sources: Include lists of materials and local sources of materials and related services.
- F. Warranties and Bonds: Include copies of warranties and bonds and lists of circumstances and conditions that would affect validity of warranties or bonds.

2.4 SYSTEMS AND EQUIPMENT MAINTENANCE MANUAL

- A. Content: For each system, subsystem and piece of equipment not part of a system, include source information, manufacturers' maintenance documentation, maintenance procedures, maintenance and service schedules, spare parts list and source information, maintenance service contracts, and warranty and bond information, as described below.
- B. Source Information: List each system, subsystem, and piece of equipment included in manual; identify by product name and arrange to match manual's table of contents. For each product, list name, address and telephone number of Installer or supplier and maintenance service agent, and cross-reference Specification Section number and title in Project Manual.
- C. Manufacturers' Maintenance Documentation: Manufacturers' maintenance documentation including maintenance instructions, drawings and diagrams for maintenance, nomenclature of parts and components, and recommended spare parts for each component part or piece of equipment.

- D. Maintenance Procedures: Include test and inspection instructions, troubleshooting guide, disassembly instructions, and adjusting instructions that detail essential maintenance procedures.
- E. Maintenance and Service Schedules: Include service and lubrication requirements, list of required lubricants for equipment, and separate schedules for preventive and routine maintenance and service with standard time allotment.
- F. Spare Parts List and Source Information: Include lists of replacement and repair parts, with parts identified and cross-referenced to manufacturers' maintenance documentation and local sources of maintenance materials and related services.
- G. Maintenance Service Contracts: Include copies of maintenance agreements with name and telephone number of service agent.
- H. Warranties and Bonds: Include copies of warranties and bonds and lists of circumstances and conditions that would affect validity of warranties or bonds.

PART 3 EXECUTION

3.1 MANUAL PREPARATION

- A. Product Maintenance Manual: Assemble a complete set of maintenance data indicating care and maintenance of each product, material and finish incorporated into the Work.
- B. Operation and Maintenance Manuals: Assemble a complete set of operation and maintenance data indicating operation and maintenance of each system, subsystem and piece of equipment not part of a system.
- C. Manufacturers' Data: Where manuals contain manufacturers' standard printed data, include only sheets pertinent to product or component installed. Mark each sheet to identify each product or component incorporated into the Work. If data includes more than one (1) item in a tabular format, identify each item using appropriate references from the Contract Documents. Identify data applicable to the Work and delete references to information not applicable.
- D. Drawings: Prepare drawings supplementing manufacturers' printed data to illustrate the relationship of component parts of equipment and systems and to illustrate control sequence and flow diagrams. Coordinate these drawings with information contained in Record Drawings to ensure correct illustration of completed installation.
 - 1. Do not use original Project Record Documents as part of operation and maintenance manuals.
- E. Comply with Division 01 7700 Section "Closeout Procedures" for schedule for submitting operation and maintenance documentation.

END OF SECTION 01 7823

SECTION 01 7839 PROJECT RECORD DOCUMENTS

PART 1 GENERAL

1.1 RELATED DOCUMENTS

A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes administrative and procedural requirements for Project Record Documents, including the following:
 - 1. Record Drawings.
 - 2. Record Specifications.
 - 3. Record Product Data.
- B. See Division 01 7823 Section "Operation and Maintenance Data" for operation and maintenance manual requirements.
- C. See Divisions 02 through 33 Sections for specific requirements for Project Record Documents of the Work in those Sections. Every Division may not be used.

1.3 CLOSEOUT SUBMITTALS

- A. Record Drawings: Submit to Owner PDF **and CAD** files of scanned record prints and three (3) sets of prints.
- B. Record Specifications: Submit annotated PDF electronic files of Project's Specifications, including addenda and contract modifications to the Owner.
- C. Record Product Data: Submit to the Owner, annotated PDF electronic files and directories of each submittal.
 - 1. Where record Product Data are required as part of operation and maintenance manuals, submit duplicate marked-up Product Data as a component of manual.
- D. Miscellaneous Record Submittals: See other Specification Sections for miscellaneous recordkeeping requirements and submittals in connection with various construction activities.
- E. Submit annotated PDF electronic files and directories of each submittal.

PART 2 PRODUCTS

2.1 RECORD DRAWINGS

A. Record Prints: Maintain one (1) set of black-line white prints of the Contract Drawings and Shop Drawings.

- 1. Preparation: Mark Record Prints to show the actual installation where installation varies from that shown originally. Require individual or entity who obtained record data, whether individual or entity is Installer, subcontractor or similar entity, to prepare the marked-up Record Prints.
 - a. Give particular attention to information on concealed elements that would be difficult to identify or measure and record later.
 - b. Record data as soon as possible after obtaining it. Record and check the markup before enclosing concealed installations.
- 2. Mark the Contract Drawings or Shop Drawings, whichever is most capable of showing actual physical conditions, completely and accurately. If Shop Drawings are marked, show cross-reference on the Contract Drawings.
- 3. Mark record sets with erasable, red-colored pencil. Use other colors to distinguish between changes for different categories of the Work at same location.
- 4. Note Field Authorization numbers, alternate numbers, Change Order numbers, and similar identification, where applicable.
- B. Format: Identify and date each Record Drawing; include the designation "PROJECT RECORD DRAWING" in a prominent location.
 - 1. Record Prints: Organize Record Prints and newly prepared Record Drawings into manageable sets. Bind each set with durable paper cover sheets. Include identification on cover sheets.
 - 2. Identification: As follows:
 - a. Project name.
 - b. Date.
 - c. Designation "PROJECT RECORD DRAWINGS."
 - d. Name of Architect.
 - e. Name of Contractor.

2.2 RECORD SPECIFICATIONS

- A. Preparation: Mark Specifications to indicate the actual product installation where installation varies from that indicated in Specifications, addenda and contract modifications.
 - 1. Give particular attention to information on concealed products and installations that cannot be readily identified and recorded later.
 - 2. Mark copy with the proprietary name and model number of products, materials, and equipment furnished, including substitutions and product options selected.
 - 3. Record the name of manufacturer, supplier, Installer and other information necessary to provide a record of selections made.
 - 4. Note related Change Orders, Record Product Data and Record Drawings where applicable.

2.3 RECORD PRODUCT DATA

- A. Preparation: Mark Product Data to indicate the actual product installation where installation varies substantially from that indicated in Product Data submittal.
 - 1. Give particular attention to information on concealed products and installations that cannot be readily identified and recorded later.
 - 2. Include significant changes in the product delivered to Project site and changes in manufacturer's written instructions for installation.

3. Note related Change Orders, Record Specifications and Record Drawings where applicable.

2.4 MISCELLANEOUS RECORD SUBMITTALS

A. Assemble miscellaneous records required by other Specification Sections for miscellaneous record keeping and submittal in connection with actual performance of the Work. Bind or file miscellaneous records and identify each, ready for continued use and reference.

PART 3 EXECUTION

3.1 RECORDING AND MAINTENANCE

- A. Recording: Maintain one (1) copy of each submittal during the construction period for Project Record Document purposes. Post changes and modifications to Project Record Documents as they occur; do not wait until the end of Project.
- B. Maintenance of Record Documents and Samples: Store Record Documents and Samples in the field office apart from the Contract Documents used for construction. Do not use Project Record Documents for construction purposes. Maintain Record Documents in good order and in a clean, dry, legible condition, protected from deterioration and loss. Provide access to Project Record Documents for Owner's reference during normal working hours.

END OF SECTION 01 7839

G703 - Continuation Sheet

SITE NAME - PROJECT NAME; Contract No. CCxxxxx65

 APPLICATION NO:
 06 FINAL

 APPLICATION DATE:
 04.19.21

 PERIOD FROM:
 04.01.21

PERIOD TO: 04.19.21 C G Α В D Ε F Η WORK COMPLETED **MATERIALS** TOTAL BALANCE TO RETAINAGE % PRESENTLY ITEM **SCHEDULED** FROM PREVIOUS COMPLETED & DESCRIPTION OF WORK **FINISH** (AGGREGATE STORED STORED TO DATE NO. VALUE APPLICATION(S) THIS PERIOD $(G \div C)$ TO DATE) (C - G) (D + E + F)(NOT IN D OR E) (G) Allowance & Contingencies 29,000.00 18,851.74 10,148.26 0.00 29,000.00 100.00% 0.00 1,450.00 Close out 13,523.33 6,761.00 6,762.33 0.00 13,523.33 100.00% 0.00 676.17 Bond & Insurance 24,050.00 24,050.00 0.00 0.00 24,050.00 100.00% 0.00 1,202.50 Mobilization 17,500.00 17,500.00 0.00 0.00 17,500.00 100.00% 0.00 875.00 Demo Siding and Windows 30,000.00 30,000.00 0.00 0.00 30,000.00 100.00% 0.00 1,500.00 Frame & GWB F/P, Door, Storage 19.000.00 19.000.00 0.00 0.00 19.000.00 100.00% 0.00 950.00 Deck Coatings 15.500.00 15.500.00 0.00 0.00 15.500.00 100.00% 0.00 775.00 Deck Railings 23,500.00 21,150.00 0.00 23,500.00 100.00% 0.00 1,175.00 2,350.00 Roofing incl Ladders and Hatches 57,300.00 28,650.00 28,650.00 0.00 57,300.00 100.00% 0.00 2,865.00 Roof Framing/Backing/Blocking 11.600.00 10.600.00 1.000.00 0.00 11.600.00 100.00% 0.00 580.00 Siding and Flashing Materials 43,000.00 43,000.00 0.00 0.00 43,000.00 100.00% 0.00 2,150.00 Siding Labor 47,000.00 45,000.00 2,000.00 0.00 47,000.00 100.00% 0.00 2,350.00 Window Materials 0.00 100.00% 800.00 16.000.00 16.000.00 0.00 16.000.00 0.00 15,000.00 15,000.00 0.00 0.00 15,000.00 100.00% 0.00 750.00 Window Labor Patio Door Materials 9,600.00 9,600.00 0.00 0.00 9,600.00 100.00% 0.00 480.00 0.00 490.00 Patio Door Labor 9.800.00 9,800.00 0.00 9.800.00 100.00% 0.00 Exterior Doors & Hardware Materials 13,500.00 13,500.00 0.00 0.00 13,500.00 100.00% 0.00 675.00 Exterior Door Labor 10,625.00 10,625.00 0.00 0.00 10,625.00 100.00% 0.00 531.25 **Door Hardware Materials** 2,200.00 2,200.00 0.00 0.00 2,200.00 100.00% 0.00 110.00 Gutters 4.200.00 0.00 4.200.00 0.00 4.200.00 100.00% 0.00 210.00 Flameblock Labor 15,000.00 15,000.00 0.00 0.00 15,000.00 100.00% 0.00 750.00 14,000.00 Flameblock Materials 14,000.00 0.00 0.00 14.000.00 100.00% 0.00 700.00 Blinds 8.500.00 8.500.00 0.00 0.00 8.500.00 100.00% 0.00 425.00 **Electrical & Lighting Fixtures** 12,800.00 0.00 12,800.00 12,800.00 0.00 100.00% 0.00 640.00 900.00 **Exterior Painting** 18,000.00 17,000.00 1,000.00 0.00 18,000.00 100.00% 0.00 Indirect Costs/Overhead/Profit 103.569.63 90.210.00 13,359.63 0.00 103.569.63 100.00% 0.00 5,178.48 CO 1 - Contingency (8.218.97) (8,218.97)0.00 (8,218.97)100.00% (410.95)0.00 0.00 TOTALS 575,548.99 514,297.74 61,251.25 0.00 575,548.99 100.00% 0.00 28,777.45 5% RETAINAGE 28.777.45 25,714.89 3,062.56 0.00 28.777.45 **TOTALS LESS RETAINAGE** 546,771.54 488,582.85 58,188.69 0.00 546,771.54 0.00 28,777.45 TOTAL BALANCE TO FINISH (H+I) 28,777.45 1

NET CHANGE ORDERS THIS PERIOD:(8,218.97)CHANGE ORDERS APPROVED THIS PERIOD (LIST C/O #s)NET C/O ADDITIONS (THIS PERIOD):0.00NET C/O DEDUCTIONS (THIS PERIOD):(8,218.97)TOTAL CHANGE ORDERS TO DATE:(8,218.97)

Form G702

Application and Certificate for Payment

		•	•					
TO OWNER:	King County Housing Authori	ty PROJECT	SITE NAME		APPLICATION NO:	06 FINAL	Distribution to:	
	Attn: Capital Construction Dept.	NAME / SCOPE			PERIOD TO:	04.19.21	OWNER: X	
	700 Andover Park W. Suite C	OF WORK:	PRO	JECT NAME	CONTRACT NO:	CCxxxxx65	ARCHITECT:	
	Tukwila, WA 98188				CONTRACT DATE:	11/16/2020	CONTRACTOR:	
FROM	CONTRACTOR NAME	VIA	ARC		NTP DATE:	11/16/2020	FIELD:	
CONTRACTOR:	CONTRACTOR ADDRESS	ARCHITECT:	119 S. MAIN ST		PROJECT NO:	215.1B	:	
	CITY, STATE, ZIP		SEATTLE, WA	98104-2579	WORK ORDER NO:	1243		
CONTRACTO	DIC ADDI ICATION FOR D	AVMENT		The undersioned Contractor	certifies that to the ho	est of the Contractor'	s knowledge, information and	
CONTRACTO	R'S APPLICATION FOR P	ATWENT		•			pleted in accordance with the	
Application is made	for payment, as shown below, in conne	ection with the Contr	act.	Contract Documents, that all amounts have been paid by the Contractor for Work for which previous				
Continuation Sheet,	Form G703, is attached.			Certificates for Payment we	re issued and payments	received from the Ov	wner, and that current payment	
1. ORIGINAL CONTR	ACT SUM		\$583,767.96	shown herein is now due.				
2. NET CHANGE BY	CHANGE ORDERS		(\$8,218.97)	CONTRACTOR:				
3. CONTRACT SUM	TO DATE (Line 1 +/- 2)		\$575,548.99	By:		Date:		
4. TOTAL COMPLETI	ED & STORED TO DATE (Column G on	G703)	\$575,548.99			_		
5. RETAINAGE:				State of:				
a. 5 % of	Completed Work			County of:				
(Column D + I	E on G703: \$575,548.99)	\$28,777.45		Subscribed and sworn to bef	ore			
b. 5 % of	Stored Material		_	me this	day of			
(Column F on			_	Notary Public:				
Total Retainage (Lin	nes 5a + 5b or Total in Column I of G70	03)	\$28,777.45	My Commission expires:				
			*	OWNER'S REPRES	SENTATIVE CER	RTIFICATE FO	R PAYMENT	
	ESS RETAINAGE		\$546,771.54					
`	(Line 4 Less Line 5 Total)				In accordance with the Contract Documents, based on on-site observations and the data comprising			
	CERTIFICATES FOR PAYMENT		\$488,582.85	this application, the Owner's Representative certifies to the Owner that to the best of the Representative's knowledge, information and belief the Work has progressed as indicated, the quality				
,	prior Certificate)		Φ50 100 60					
			\$58,188.69	the AMOUNT CERTIFIED		cuments, and the Cor	mace is chimed to payment of	
	ISH, INCLUDING RETAINAGE	¢20 777 <i>15</i>					\$58,188.69	
(Line 3 Less L	ine 6)	\$28,777.45	_	AMOUNT CERTIFIED			. ,	
				(Attach explanation if amore Application and on the Cont	0 00 0	* *	ed. Initial all figures on this with the amount certified.)	
CHANGE ORDER S	UMMARY	ADDITIONS	DEDUCTIONS	OWNER'S REPRESENTATIVE	<u>:</u>			
Total changes appro	ved in previous months by Owner	\$0.00	\$0.00	By:		Date:		
Total approved this r	month. (CO numbers listed below)	\$0.00	(\$8,218.97)	This Cartificate is not recent	inhla Tha AMOUNT C	EDTIFIED is payable	a only to the Contractor named	
#s:	1 TOTALS	\$0.00	(\$8,218.97)	This Certificate is not negotiable. The AMOUNT CERTIFIED is payable only to the Contractor responsible. The Amount Certificate is payable only to the Contractor responsible. The Amount Certified is payable only to the Contractor responsible.			•	
NET CHANGES by Change Order			(\$8,218.97)					



GENERAL CONTRACTOR CERTIFICATION UPON APPLICATION FOR PAYMENT

GENERAL CONTRACTOR: CONTRACTOR: SITE NAME		King County Housing Authority	PAY RE	QUEST NUMBER	: 06		
		CONTRACTOR NAME	_	PERIOD FROM:		04.01.21 04.19.21 CCxxxxx65	
		SITE NAME	_	THROUGH:	0		
		PROJECT NAME	CONTR	ACT NUMBER:	CC		
1.	ORIGINAL CONTR	ACT AMOUNT:		\$		583,767.96 (8,218.97) 575,548.99 488,582.85 58,188.69	
2.	APPROVED CHAN			\$			
3.	CURRENT CONTR	, ,		\$			
4.	AMOUNT OF PRE	VIOUS CERTIFICATES FOR PAYMENT	- :	\$			
5.	AMOUNT OF CU	RRENT CERTIFICATE FOR PAYMENT	REQUEST:	\$			
By su follow	-	panying Application for Payment, t	he Contrac	ctor certifies, agr	ees and warran	ts to the Owner as	
1.	whose charges w	as made full payment to all labor ere included in any prior Applicati matters set forth below or on an att	on for Pay	ment, subject or	•	• •	
2.	2. The Contractor knows of no one making a claim for payment other than those included in the current Application for Payment, who will be paid when the current Application for Payment is paid by Owner, except as noted below or on an attachment hereto.						
3.	demands against for Payment, sub	of payments made by Owner, the of Owner and the Project for all periodict only to (a) receipt of payment of below or on an attachment hereto.	ods up to a of the curre	nd including the	period covered	by this Application	
	EXCEPTION(S) - DESCRI	PTION:				AMOUNT:	
GENE	RAL CONTRACTOR NA	ME:	COI	NTRACTOR N	AME		
BY AU	THORIZED SIGNER:	PRINT NAME		ТІ	TLE	DATE	
	of Washington ry of King						
and sa		satisfactory evidence that ged that (he/she) signed this instrumented in the instrument.	nt and ackno			opeared before me, voluntary act for the	
Signed	d before me on this _	Day of			9	SEAL	
	Notary Public in an	d for the State of Washington					
	Residing at:						
	My Commission Fy	alroc.					



SUBSTITUTION REQUEST Sub. Request #: Project: From: To: Date: A/E Project #: Contract For: Re: Specification Title: Description: Page: _____ Article / Paragraph: _____ Section: Proposed Substitution: Address: Phone: Model No.: Trade Name: Installer: Address: Phone: \square New Product \square 2 - 5 years old \square 5 - 10 years old \square More than 10 years old History: Differences between proposed substitution and specified product: ☐ Point-by-point comparative data attached - REQUIRED BY A/E Reason for not providing specified item: Similar Installation: _____ Architect: Project: Address: Owner: Data Installed: Proposed substitution affects other parts of Work: No Yes; Explain: Savings to Owner for accepting substitution: Proposed substitution changes Contract Time: \square No \square Yes (If Yes): \square Add \square Deduct *If Contract time is to be extended, a Change Order must be prepared. Supporting Data Attached: ☐ Drawings ☐ Product Data ☐ Samples ☐ Tests ☐ Reports ☐

1 of 2 KCHA / 4197 / 01-20-23



SUBSTITUTION REQUEST

The Undersigned certifies:

- Proposed substitution has been fully investigated and determined to be equal or superior in all respects to specified product.
- Same warranty will be furnished for proposed substitution as for specified product.
- Same maintenance service and source of replacement parts, as applicable, is available.
- Proposed substitution will have no adverse effect on other trades and will not affect or delay progress schedule.
- Cost data as stated above is complete. Claims for additional costs related to accepted substitution which may subsequently become apparent are to be waived.
- Proposed substitution does not affect dimensions and functional clearances.
- Payment will be made for changes to building design, included A/E design, and construction costs caused by the substitution.
- Coordination, installation, and changes in the Work as necessary for accepted substitution will be complete in all respects.

Submitted by:			
Signed by:			
Firm:			
Address:			
Telephone:			
Attachments:			
A/E's Review and Action:			
☐ Substitution approved - Make submittals in accordance	ce with Specification Section		
☐ Substitution approved as noted - Make submittals in a	accordance with Specification Section		
Substitution rejected - Use specified materials.			
$\ \square$ Substitution Request received too late - Use specified	materials.		
Signed by:	Date:		

PART 1 GENERAL

1.01 SECTION INCLUDES

- A. Selective demolition of building elements for alteration purposes as indicated on drawings including:
 - 1. Remove existing exterior siding and trim,
 - 2. Remove existing balcony half walls,
 - 3. Remove existing drywall at storage closets,
 - 4. Remove existing through wall vent hoods and crawlspace vent covers,
 - 5. Remove existing exterior doors, door frames, door hardware, exterior trim and interior trim,
 - 6. Remove existing windows, exterior trim, and window coverings,
 - 7. Remove existing building numbers,
 - 8. Remove existing hose bibb fixtures,
 - 9. Remove existing gutters & downspouts,
 - 10. Remove existing light fixtures,
 - 11. Salvage existing sliding doors for reinstallation,
 - 12. Salvage existing fire extinguishers and cabinets for reinstallation,
 - 13. Salvage existing pipe fittings for reinstallation,
 - 14. Salvage existing exterior electrical junction boxes, outlets, and conduit for reinstallation,
 - 15. Salvage existing exterior signage for reinstallation,
- B. Protect existing building and site elements to remain during demolition activities and while new work is being installed

1.02 DEFINITIONS

- A. Demolition: Dismantle, raze, destroy or wreck any building or structure or any part thereof.
- B. Remove: Detach or dismantle items from existing construction and dispose of them off site, unless items are indicated to be salvaged or reinstalled.
- C. Remove and Salvage: Detach or dismantle items from existing construction in a manner to prevent damage. Clean, package, label and deliver salvaged items to Owner in ready-for-reuse condition.
- D. Remove and Reinstall: Detach or dismantle items from existing construction in a manner to prevent damage. Clean and prepare for reuse and reinstall where indicated.
- E. Existing to Remain: Designation for existing items that are not to be removed and that are not otherwise indicated to be salvaged or reinstalled.

1.03 REFERENCE STANDARDS

- A. 29 CFR 1926 Safety and Health Regulations for Construction Current Edition.
- B. NFPA 241 Standard for Safeguarding Construction, Alteration, and Demolition Operations 2022, with Errata (2021).

1.04 SUBMITTALS

- A. Site Plan: Indicate:
 - 1. Vegetation to be protected.
 - 2. Areas for temporary construction and field offices.
- B. Demolition Plan: Submit demolition plan as required by OSHA and local AHJs.
 - 1. Indicate extent of demolition, removal sequencing, bracing and shoring, and location and construction of barricades and fences.
 - 2. Summary of safety procedures.
- C. Project Record Documents: Accurately record actual locations of capped and active utilities and subsurface construction.

Jul-12-2023 024100 - 1

PART 2 PRODUCTS -- NOT USED

PART 3 EXECUTION

3.01 DEMOLITION

A. Remove other items indicated, for salvage, relocation, and recycling.

3.02 GENERAL PROCEDURES AND PROJECT CONDITIONS

- A. Owner assumes no responsibility for condition of structures or portion of structures to be demolished.
- B. Comply with applicable codes and regulations for demolition operations and safety of adjacent structures and the public.
 - 1. Obtain required permits.
 - 2. Comply with applicable requirements of NFPA 241.
 - 3. Take precautions to prevent catastrophic or uncontrolled collapse of structures to be removed; do not allow worker or public access within range of potential collapse of unstable structures.
 - 4. Provide, erect, and maintain temporary barriers and security devices.
 - 5. Use physical barriers to prevent access to areas that could be hazardous to workers or the public.
 - 6. Conduct operations to minimize effects on and interference with adjacent structures and occupants.
 - 7. Do not close or obstruct roadways or sidewalks without permits from authority having jurisdiction.
 - Conduct operations to minimize obstruction of public and private entrances and exits. Do not
 obstruct required exits at any time. Protect persons using entrances and exits from removal
 operations.
 - 9. Obtain written permission from owners of adjacent properties when demolition equipment will traverse, infringe upon, or limit access to their property.
- C. Do not begin removal until receipt of notification to proceed from Owner.
- D. Do not begin removal until vegetation to be relocated has been removed and vegetation to remain has been protected from damage.
- E. Protect existing structures and other elements to remain in place and not removed.
 - 1. Provide bracing and shoring.
 - 2. Prevent movement or settlement of adjacent structures.
 - 3. Stop work immediately if adjacent structures appear to be in danger.
- F. Minimize production of dust due to demolition operations. Do not use water if that will result in ice, flooding, sedimentation of public waterways or storm sewers, or other pollution?
- G. Hazardous Materials:
 - 1. If hazardous materials are discovered during removal operations, stop work and notify the Owner; hazardous materials include regulated asbestos containing materials, lead, PCBs, and mercury.
- H. Perform demolition in a manner that maximizes salvage and recycling of materials.
 - 1. Dismantle existing construction and separate materials.
 - 2. Set aside reusable, recyclable, and salvageable materials; store and deliver to collection point or point of reuse.

3.03 EXISTING UTILITIES

- A. Coordinate work with utility companies. Notify utilities before starting work, comply with their requirements, and obtain required permits.
- B. Protect existing utilities to remain from damage.
- C. Do not disrupt public utilities without permit from authority having jurisdiction.
- D. Do not close, shut off, or disrupt existing life safety systems that are in use without at least 7 days prior written notification to Owner.
- E. Do not close, shut off, or disrupt existing utility branches or take-offs that are in use without at least 7 days prior written notification to Owner.

Jul-12-2023 024100 - 2

- F. Locate and mark utilities to remain; mark using highly visible tags or flags, with identification of utility type; protect from damage due to subsequent construction, using substantial barricades if necessary.
- G. Remove exposed piping, valves, meters, equipment, supports, and foundations of disconnected and abandoned utilities.

3.04 SELECTIVE DEMOLITION FOR ALTERATIONS

- A. Existing construction and utilities indicated on drawings are based on casual field observation and existing record documents only.
 - 1. Verify construction and utility arrangements are as indicated.
 - 2. Report discrepancies to Owner before disturbing existing installation.
 - 3. Beginning of demolition work constitutes acceptance of existing conditions that would be apparent upon examination prior to starting demolition.
- B. Maintain weatherproof exterior building enclosure, except for interruptions required for replacement or modifications; prevent water and humidity damage.
- C. Remove existing work as indicated and required to accomplish new work.
 - 1. Remove rotted wood, corroded metals, and deteriorated masonry and concrete; replace with new construction indicated.
 - 2. Remove items indicated on drawings.
- D. Services including, but not limited to, HVAC, Plumbing, Electrical, and Telecommunications: Remove existing systems and equipment as indicated.
 - 1. Maintain existing active systems to remain in operation, and maintain access to equipment and operational components.
 - 2. Where existing active systems serve occupied facilities but are to be replaced with new services, maintain existing systems in service until new systems are complete and ready for service.
 - 3. Verify that abandoned services serve only abandoned facilities before removal.
 - 4. Remove abandoned pipe, ducts, conduits, and equipment. Remove back to source of supply where possible, otherwise cap stub and tag with identification.
- E. Protect existing work to remain.
 - 1. Prevent movement of structure. Provide shoring and bracing as required.
 - 2. Perform cutting to accomplish removal work neatly and as specified for cutting new work.
 - 3. Repair adjacent construction and finishes damaged during removal work.
 - 4. Patch to match new work.

3.05 DEBRIS AND WASTE REMOVAL

- A. Remove debris, junk, and trash from site.
- B. Leave site in clean condition, ready for subsequent work.
- C. Clean up spillage and wind-blown debris from public and private lands.
- D. Unless otherwise indicated in Contract Documents or specified by Owner, items of salvageable value to Contractor shall be removed from site. Storage or sale of removed items on site will not be permitted and shall not interfere with other work specified.

END OF SECTION

Jul-12-2023 024100 - 3

1.01 SECTION INCLUDES

- A. Nonstructural dimension lumber framing.
- B. Rough opening framing for doors and windows.
- C. Fire-retardant wall sheathing
- D. Miscellaneous framing and sheathing.
- E. Concealed wood blocking, nailers, and supports.

1.02 REFERENCE STANDARDS

- A. ASTM A153/A153M Standard Specification for Zinc Coating (Hot-Dip) on Iron and Steel Hardware 2016a.
- B. ASTM C557 Standard Specification for Adhesives for Fastening Gypsum Wallboard to Wood Framing 2003 (Reapproved 2017).
- C. ASTM D3498 Standard Specification for Adhesives for Field-Gluing Wood Structural Panels (Plywood or Oriented Strand Board) to Wood Based Floor System Framing 2019a.
- D. AWPA U1 Use Category System: User Specification for Treated Wood 2022.
- E. ICC (IBC) International Building Code Most Recent Edition Adopted by Authority Having Jurisdiction, Including All Applicable Amendments and Supplements.
- F. PS 2 Performance Standard for Wood Structural Panels 2018.
- G. PS 20 American Softwood Lumber Standard 2021.
- H. WCLIB (GR) Standard Grading Rules for West Coast Lumber No. 17 2018.
- I. WWPA G-5 Western Lumber Grading Rules 2021.

1.03 SUBMITTALS

- A. Product Data: Provide technical data on wood preservative materials and application instructions.
- B. Test Reports: Certified test reports from recognized testing laboratories showing compliance with specified structural fire sound and performance characteristics and physical properties.

1.04 QUALITY ASSURANCE

A. Mock-Up: Construct a mock up with actual materials in sufficient time for Owner's review and to not delay construction progress. Locate mock-up as acceptable to Owner. Intent of mock-up is to demonstrate quality of workmanship and visual appearance. If mock-up is not acceptable, rebuild mock-up until satisfactory results are achieve. Retain mock-up during construction as a standard for comparison with completed work.

1.05 DELIVERY, STORAGE, AND HANDLING

- A. General: Cover wood products to protect against moisture. Support stacked products to prevent deformation and to allow air circulation.
- B. Fire Retardant Treated Wood: Prevent exposure to precipitation during shipping, storage, and installation.

1.06 WARRANTY

A. Manufacturer's Warranty: Provide manufacturer's standard limited warranty.

PART 2 PRODUCTS

2.01 GENERAL REQUIREMENTS

- A. Dimension Lumber: Comply with PS 20 and requirements of specified grading agencies.
 - 1. If no species is specified, provide species graded by the agency specified; if no grading agency is specified, provide lumber graded by grading agency meeting the specified requirements.

Jul-12-2023 061000 - 1

- 2. Grading Agency: Grading agency whose rules are approved by the Board of Review, American Lumber Standard Committee at www.alsc.org, and who provides grading service for the species and grade specified; provide lumber stamped with grade mark unless otherwise indicated.
- 3. Lumber of other species or grades is acceptable provided structural and appearance characteristics are equivalent to or better than products specified.

2.02 DIMENSION LUMBER FOR CONCEALED APPLICATIONS

- A. Grading Agency: West Coast Lumber Inspection Bureau; WCLIB (GR).
- B. Grading Agency: Western Wood Products Association; WWPA G-5.
- C. Sizes: Nominal sizes as indicated on drawings, S4S.
- D. Moisture Content: S-dry or MC19.
- E. Stud Framing (2 by 2 through 2 by 6):
 - 1. Species: Doug fir-larch No. 2 grade or Hem-fir No. 1 grade. Utility and standard grades not permitted..
- F. Miscellaneous Framing, Blocking, Nailers, Grounds, and Furring:
 - 1. Lumber: S4S, Doug fir-larch No. 2 grade or Hem-fir No. 1 grade. Utility and standard grades not permitted..

2.03 CONSTRUCTION PANELS

- A. Fire-Retardant Wall Sheathing:
 - 1. Structural 1 Performance Grade.
 - 2. Panel Thickness: 1/2 inch, nominal.
 - 3. Flame Spread: Less than 25 when tested in accordance with ASTM E84, UL 723, or NFPA 255.
 - 4. Smoke Developed: Less than 100 when tested in accordance with ASTM E84, UL 723, or NFPA 255.
 - 5. Advance of Flame: Not to exceed 10.5 feet after 30 minute test duration.
 - Thermal Barrier Index: Minimum 20 minutes when tested in accordance with ASTM E119, UBC26.2, and UL 1715.
 - 7. Products:
 - a. LP Building Products; LP FlameBlock: www.lpcorp.com/#sle.
 - b. Or approved equal.

2.04 ACCESSORIES

- A. Fasteners and Anchors:
 - 1. Metal and Finish: Hot-dipped galvanized steel complying with ASTM A153/A153M for high humidity and preservative-treated wood locations, unfinished steel elsewhere.
 - 2. Drywall Screws: Bugle head, hardened steel, power driven type, length three times thickness of sheathing.
- B. Subfloor Adhesives: Gap-filling construction adhesive for bonding wood structural panels to wood-based floor system framing; complying with ASTM D3498.
- C. General Purpose Construction Adhesives: Comply with ASTM C557.
- D. Water-Resistive Barrier: See Section 072500.

2.05 FACTORY WOOD TREATMENT

- A. Treated Lumber and Plywood: Comply with requirements of AWPA U1 Use Category System for wood treatments determined by use categories, expected service conditions, and specific applications.
 - Preservative-Treated Wood: Provide lumber and plywood marked or stamped by an ALSCaccredited testing agency, certifying level and type of treatment in accordance with AWPA standards.

Jul-12-2023 061000 - 2

PART 3 EXECUTION

3.01 INSTALLATION - GENERAL

- A. Select material sizes to minimize waste.
- B. Reuse scrap to the greatest extent possible; clearly separate scrap for use on site as accessory components, including: shims, bracing, and blocking.
- C. Where treated wood is used on interior, provide temporary ventilation during and immediately after installation sufficient to remove indoor air contaminants.

3.02 BLOCKING, NAILERS, AND SUPPORTS

- A. Provide framing and blocking members as indicated or as required to support finishes, fixtures, specialty items, and trim.
- B. In framed assemblies that have concealed spaces, provide solid wood fireblocking as required by applicable local code, to close concealed draft openings between floors and between top story and roof/attic space; other material acceptable to authorities having jurisdiction may be used in lieu of solid wood blocking.
- C. In walls, provide blocking attached to studs as backing and support for wall-mounted items, unless item can be securely fastened to two or more studs or other method of support is explicitly indicated.
- D. Provide the following specific nonstructural framing and blocking:
 - Wall-mounted door stops.
 - 2. Wall paneling and trim.
 - 3. Joints of rigid wall coverings that occur between studs.

3.03 INSTALLATION OF CONSTRUCTION PANELS

A. Subflooring: Glue and nail to framing; staples are not permitted.

3.04 TOLERANCES

- A. Framing Members: 1/4 inch from true position, maximum.
- B. Surface Flatness of Floor: 1/8 inch in 10 feet maximum, and 1/4 inch in 30 feet maximum.
- C. Variation from Plane, Other than Floors: 1/4 inch in 10 feet maximum, and 1/4 inch in 30 feet maximum.

3.05 CLEANING

- A. Waste Disposal: See Section 017419 Construction Waste Management and Disposal.
 - 1. Comply with applicable regulations.
 - 2. Do not burn scrap on project site.
 - 3. Do not burn scraps that have been pressure treated.
 - 4. Do not send materials treated with pentachlorophenol, CCA, or ACA to co-generation facilities or "waste-to-energy" facilities.
- B. Do not leave wood, shavings, sawdust, etc. on the ground or buried in fill.
- C. Prevent sawdust and wood shavings from entering the storm drainage system.

END OF SECTION

Jul-12-2023 061000 - 3

1.01 SECTION INCLUDES

- A. Exterior inside corner wood trim
- B. Wood casings and moldings at doors and windows.
- C. Hardware and attachment accessories including vent covers.

1.02 REFERENCE STANDARDS

- A. AWI/AWMAC/WI (AWS) Architectural Woodwork Standards, 2nd Edition 2014, with Errata (2016).
- B. AWMAC/WI (NAAWS) North American Architectural Woodwork Standards 2021, with Errata.
- C. PS 20 American Softwood Lumber Standard 2021.

1.03 SUBMITTALS

- A. Product Data:
 - 1. Provide instructions for attachment hardware and finish hardware.
- B. Samples: Submit twosamples of wood trim 6 inchlong.

1.04 QUALITY ASSURANCE

- A. Fabricator Qualifications: Company specializing in fabricating the products specified in this section with minimum three years of documented experience.
 - 1. Accredited participant in the specified certification program prior to the commencement of fabrication and throughout the duration of the project.

B. Quality Certification:

- 1. Provide labels or certificates indicating that work complies with AWI/AWMAC/WI (AWS) or AWMAC/WI (NAAWS) requirements for grade or grades specified.
- 2. Provide designated labels on shop drawings as required by certification program.
- 3. Provide designated labels on installed products as required by certification program.
- 4. Submit certifications upon completion of installation that verifies this work is in compliance with specified requirements.

1.05 MOCK-UPS

- A. Provide mock-up, full size, illustrating finish and construction.
- B. Locate where directed.
- C. Mock-up may remain as part of the work.

1.06 DELIVERY, STORAGE, AND HANDLING

- A. Store finish carpentry items under cover, elevated above grade, and in a dry, well-ventilated area not exposed to heat or sunlight.
- B. Protect from moisture damage.
- C. Handle materials and products to prevent damage to edges, ends, or surfaces.

PART 2 PRODUCTS

2.01 FINISH CARPENTRY ITEMS

- A. Quality Standard: Custom Grade, in accordance with AWI/AWMAC/WI (AWS) or AWMAC/WI (NAAWS), unless noted otherwise.
- B. Exterior Woodwork Items:
 - 1. Species and Grade: Western red cedar, Grade C and Better Clear.
 - 2. Maximum Moisture Content: Fifteen (15%) percent.
 - 3. Dimension and Surface Finish:
 - a. Inside corner wood trim: 2x2, S4S.

- 4. White wood (fir, hem
- C. Interior Woodwork Items:
 - 1. Moldings, Bases, Casings, and Miscellaneous Trim: Medium-density fiberboard, ANSI A208.2, Grade MD-Exterior Glue, prepare for paint finish.
 - 2. Casing Header: 1" x 3" MDF Flat stock.
 - 3. Casing Legs: 9/16" x 2-1/2" MDF Flat stock.
 - 4. Jamb Liner: 9/16" MDF Flat stock. Cut to fit opening.
 - 5. Moisture Content: 4 percent to 7 percent.
 - 6. Formaldehyde Content: Manufactured with no added formaldehyde, including formaldehyde free binders. Labeled by manufacturer as containing no added urea formaldehyde (NAUF).

2.02 FASTENINGS

- A. Fasteners: Of size and type to suit application; Recessed screws, finish, or casing nails in exposed locations.
- B. Fasteners for Exterior Applications: Stainless steel; length required to penetrate wood substrate 1-1/2 inch minimum.

2.03 ACCESSORIES

- A. Adhesive: Type recommended by fabricator to suit application.
- B. Lumber for Shimming and Blocking: Softwood lumber of indicated species.
- C. Primer: Alkyd primer sealer.
- D. Wood Filler: Solvent base, tinted to match surface finish color.
- E. Vent Covers
 - 1. Hooded Vent Cover: Famco Hooded Wall Vent with Screen: SWV6P or accepted.
 - 2. Rectangular Wall Vent: Famco Standard Rectangular Wall Vent with screen: WV310 or accepted.
 - 3. Crawlspace Louvered Foundation Vent with Screen: Famco VS Louvered Foundation vent with screen, 1/8" screen, 28 gauge galvanized steel or accepted.
 - 4. Fasteners: Stainless Steel Tamper Proof Screws: #8 minimum diameter.

2.04 FABRICATION

- A. Shop assemble work for delivery to site, permitting passage through building openings.
- B. When necessary to cut and fit on site, provide materials with ample allowance for cutting. Provide trim for scribing and site cutting.

2.05 SHOP FINISHING

- A. Sand work smooth and set exposed nails and screws.
- B. Apply wood filler in exposed nail and screw indentations.
- C. Prime paint surfaces in contact with cementitious materials.
- D. Back prime woodwork items to be field finished, prior to installation.

PART 3 EXECUTION

3.01 INSTALLATION

- A. Install custom fabrications in accordance with AWI/AWMAC/WI (AWS) or AWMAC/WI (NAAWS) requirements for grade indicated.
- B. Set and secure materials and components in place, plumb and level.
- C. Carefully scribe work abutting other components, with maximum gaps of 1/32 inch. Do not use additional overlay trim to conceal larger gaps.
- D. Install trim with minimum number of joints practical, using full-length pieces from maximum lengths of lumber available. Do not use pieces less than twenty-four (24") inches long except where necessary.

- E. Use blind fastening where indicated or practical. At face of finished work, use finish nails or finish head screws at face of finished installations.
- F. Unless otherwise indicated, countersink fasteners, fill surface flush, and sand where face fastening is unavoidable.
- G. Interface with adjacent system. Carefully bring together work of this Section with related work; transitions smooth, no abrupt rough edges or intersections. Stagger end joints in adjacent and related members.
- H. Space screws and nails at equal intervals at spacing to fasten permanently and securely in place, except not less than one fastener at each end and at center of each item.
- I. Install to detail with tight joints.
- J. Miter casings and moldings except as otherwise indicated.
- K. Cut butt splices at 30-degree angles.
- L. Make members and lines level, plumb, and square to line with adjacent construction. Use concealed shims where necessary for alignment.
- M. Select and cut material to exclude damaged, marked, or defective areas.
- N. Eased Edges: Ease exposed edges of finish work 1/16-inch minimum radius whether indicated or not.
- O. Close exposed joints, spaces, and openings against adjacent construction with scribes, fillers, and trim pieces of same material and finish as finish carpentry item.
- P. Prior to securing items, adjust to ensure proper matching at joints and correct alignment throughout their length. Shim as required using concealed shims.
- Q. Do not use additional overlay trim to conceal larger gaps unless specifically approved by Owner after review of conditions of installation.
- R. Do not use materials that are unsound, warped, improperly treated or finished, inadequately seasoned, or too small to fabricate with proper jointing arrangements.
 - 1. Do not use manufactured units with defective surfaces, sizes or patterns.
- S. Provide for thermal and building movements.

3.02 PREPARATION FOR SITE FINISHING

- A. Set exposed fasteners. Apply wood filler in exposed fastener indentations. Sand work smooth.
- B. Site Finishing: See Section 099113 and 099123.
- Before installation, prime paint surfaces of items or assemblies to be in contact with cementitious materials.

3.03 TOLERANCES

- A. Maximum Variation from True Position: 1/16 inch.
- B. Maximum Offset from True Alignment with Abutting Materials: 1/32 inch.

END OF SECTION

1.01 SECTION INCLUDES

 Exterior balcony fiberglass reinforced plastic railings and guardrails. Design and engineering by Contractor.

1.02 REFERENCE STANDARDS

1.03 SUBMITTALS

- A. Product Data: Submit manufacturer's product data and installation instructions for each material and product used.
- B. Shop Drawings: Indicate profiles, sizes, connection attachments, anchorage, size and type of fasteners, and accessories.
- C. Manufacturer's Instructions.
- D. Certification: Written statement signed by manufacturers authorized representative. Certify system is engineered and designed to accommodate structural requirements.

1.04 QUALITY ASSURANCE

- A. Designer Qualifications: Perform design under direct supervision of a Professional Engineer experienced in design of this type of work and licensed in the State in which the Project is located.
- B. Manufacturer Qualifications: Company specializing in manufacturing the products specified in this section with at least five years of documented experience employing complete engineering and technical personnel needed to engineer, design, and perform work of this Section.
- C. Installer Qualifications: Company specializing in performing work of the type specified in this section, with at least three years of documented experience.

1.05 DELIVERY, STORAGE, AND HANDLING

- A. Deliver and store products in manufacturer's unopened packaging bearing the brand name and manufacturer's identification until ready for installation.
- B. Comply with manufacturer's recommendations. Handle materials to avoid damage.

1.06 WARRANTY

A. Railing Warranty: Provide manufacturer's standard 25 year warranty.

PART 2 PRODUCTS

2.01 MANUFACTURERS

- A. Fiberglass Reinforced Plastic Handrails and Railings:
 - Glasrail: www.glasrail.com/#sle; 4215 Russel Road, Mukilteo, WA 98275; 425-349-3606.
 - 2. Or approved equal.

2.02 GENERAL

- A. All FRP products shall be manufactured using a pultruded process utilizing polyester resin with flame retardant and ultraviolet (UV) inhibitor additives. A synthetic surface veil shall be the outermost layer covering the exterior surface. The flame retardant FRP shapes shall achieve a flame spread rating of 25 or less in accordance with ASTM test method E-84.
- B. FRP products exposed to weather shall contain an ultraviolet inhibitor. Should additional ultraviolet protection be required, a one mil minimum UV coating can be applied.
- C. If required, after fabrication, all cut ends, holes, and abrasions of FRP shapes shall be sealed with a compatible resin coating.
- D. All exposed surfaces shall be smooth and true to form.

Jul-12-2023 068220 - 1

KCHA PEPPER TREE - ENVELOPE SHORELINE, WASHINGTON

SECTION 068220 FIBERGLASS REINFORCED PLASTIC RAILINGS

2.03 FIBERGLASS RAILINGS

A. Performance Requirements

- 1. Design, fabricate, and test railing assemblies in accordance with the most stringent requirements of ASTM E 985 and applicable local codes.
- 2. Design, fabricate, and test railing assemblies in accordance with Uniform Federal Accessibility Standards (UFAS)
- 3. Design railing assembly, wall rails, and attachments to resist lateral force of 75 lbs. at any point without damage or permanent set. Test in accordance with ASTM E 935.
- 4. Distributed Loads: Design railing assembly, wall rails, and attachments to resist distributed force of 125 pounds per linear foot applied to the top of the assembly and in any direction, without damage or permanent set, when tested in accordance with ASTM D7032.
- 5. Concentrated Loads: Design railing assembly, wall rails, and attachments to resist a concentrated force of 200 pounds applied at any point on the top of the assembly and in any direction, without damage or permanent set, when tested in accordance with ASTM D7032.
- 6. Allow for expansion and contraction of members and building movement without damage to connections or members.
- 7. Dimensions: See drawings for configurations and heights. Contractor to verify in field.
- 8. Provide anchors and other components as required to attach to structure, made of same materials as railing components unless otherwise indicated; where exposed fasteners are unavoidable provide flush countersink fasteners.
 - a. For anchorage to stud walls, provide backing plates, for bolting anchors.
- 9. Provide welding fittings to join lengths, seal open ends, and conceal exposed mounting bolts and nuts, including but not limited to elbows, T-shapes, splice connectors, flanges, escutcheons, and wall brackets.

B. Design

- 1. The FRP standard railing system shall be designed to meet the configuration and loading requirements of OSHA, IBC, or any required local codes, with a minimum factor of safety on loading of 2.0.
- 2. Mechanical properties shall meet or exceed the values listed in Table 2.

C. Material

- 1. The rails and posts shall be 4" x 4" x .156" square tube manufactured by the pultrusion process.
- 2. Type 1: Pickets shall a minimum of 1" square tube, where designated on drawings.
- 3. The pultruded parts shall be made with a fire-retardant resin that meets the ASTM E-84 test for a flame spread rating of 25 or less. The resin matrix shall be polyester and shall contain a UV inhibitor. The parts shall or shall coat with an industrial grade polyurethane coating for additional UV protection and wear resistance.
- 4. The color shall be chosen from manufacturer's standard colors.

D. Fabrication of Standard Railing System

1. The fiberglass standard railing system shall be fabricated into finished sections by fabricating and joining together the pultruded square tube using molded or pultruded components; epoxy bonded and connected as shown in the fabrication details. Railing sections shall be fabricated to the size shown on the approved fabrication drawings and shall be piece marked with a waterproof tag.

E. For Side Mount

1. Post shall be constructed with a square pultruded bottom plug. Length shall be sufficient to extend a minimum of 1" beyond the uppermost bolt hole to prevent crushing of post tubing. Bolt holes shall provide clearance of 1/16" for 1/2" diameter bolts/studs. On square tubes, holes shall be on longitudinal center line of post, 1" from bottom of post (minimum) and not less than 3" apart on center. Posts shall be fastened with stainless steel anchor bolts or studs, 1/2" diameter extending no less than 2-1/4" into the concrete, or into minimum thickness of 1/4" structural steel or pultruded fiberglass.

Jul-12-2023 068220 - 2

KCHA PEPPER TREE - ENVELOPE SHORELINE, WASHINGTON

SECTION 068220 FIBERGLASS REINFORCED PLASTIC RAILINGS

- 2. Post locations shall be no greater than 18", nor less than 9" from horizontal or vertical change in handrail direction. For square tubes, post centers shall be no greater than 72" apart on any straight run or rail, or 48" apart on any inclined rail section.
- 3. Other Attachment Methods
- 4. Base mount embedded and removable are also types of mounting procedures for railing pending design and approval by the Engineer.

F. Installation of Handrail Sections

- 1. The fabricated railing sections shall be supplied complete with fittings by the FRP manufacturer. The components used to join fabricated sections together may be shipped loose, to be epoxied and riveted, if required, together, if required in the field by the contractor.
- 2. The fabricated handrail sections shall be installed as shown on the approved shop drawings. The handrail sections shall be accurately located, erected plumb and level. The sections shall be fastened to the structure as shown on the approved shop drawings.

2.04 FIBERFLASS RAILING SYSTEM

- A. Fiberglass Tube: Sizes as shown on Drawings.
- B. Fiberglass Pipe: Color to be selected from manufacturer's standard colors.
- C. Welding Fittings: Factory- or shop-welded from matching pipe or tube; seams continuously welded; joints and seams ground smooth.
- D. Fasteners, anchors, inserts, end brackets, and center supports as required by manufacturer for complete installation. Non-corrosive. Match rail color.

2.05 FABRICATION

- Accurately form components to suit specific project conditions and for proper connection to building structure.
 - 1. Fit and shop assemble components in largest practical sizes for delivery to site.
 - 2. Fabricate components with joints tightly fitted and secured. Provide spigots and sleeves to accommodate site assembly and installation.

PART 3 EXECUTION

3.01 EXAMINATION

A. Field verify suitable substrate and structural conditions prior to install.

3.02 INSTALLATION

- A. Install according to manufacturer's written instructions, and applicable ICC-ES report.
- B. Install components plumb and level, accurately fitted, free from distortion or defects, with tight joints.
- C. Do not make connections that impose loads on roof deck incompatible with engineered calculations accepted by Owner.
- D. Anchor railings securely to structure.
- E. Conceal anchor bolts and screws whenever possible. Where not concealed, use flush countersunk fastenings.

3.03 CLEANING

A. Clean surfaces according to manufacturer's written instructions.

END OF SECTION

Jul-12-2023 068220 - 3

1.01 SECTION INCLUDES

- Board insulation at exterior wall.
- B. Batt insulation in exterior wall construction.

1.02 REFERENCE STANDARDS

- A. ASTM C518 Standard Test Method for Steady-State Thermal Transmission Properties by Means of the Heat Flow Meter Apparatus 2021.
- B. ASTM C612 Standard Specification for Mineral Fiber Block and Board Thermal Insulation 2014 (Reapproved 2019).
- C. ASTM E84 Standard Test Method for Surface Burning Characteristics of Building Materials 2023.

1.03 SUBMITTALS

- A. Product Data: Provide data on product characteristics, performance criteria, and product limitations.
- B. Manufacturer's Installation Instructions: Include information on special environmental conditions required for installation and installation techniques.

PART 2 PRODUCTS

2.01 MINERAL FIBER BOARD INSULATION MATERIALS

- A. Mineral Wool Block and Board Thermal Insulation: Complying with ASTM C612.
 - 1. Facing: None, unfaced.
 - 2. Flame Spread Index: 25 or less, when tested with facing, if any, in accordance with ASTM E84.
 - Smoke Developed Index: 50 or less, when tested with facing, if any, in accordance with ASTM E84.
 - 4. Board Thickness: 1 inch.
 - 5. Thermal Conductivity (k-factor): Btu inch/hr sq ft degrees F of 0.26 per inch, minimum, at 75 degrees F when tested in accordance with ASTM C518.
 - 6. Products:
 - a. Owens Corning Corporation; Versa Board: www.ocbuildingspec.com/#sle.
 - b. ROCKWOOL; COMFORTBOARD 80: www.rockwool.com/#sle.
 - c. Or approved equal.

2.02 BATT INSULATION MATERIALS

- A. Commercial Batt/Blanket Insulation
 - Manufacturers:
 - a. CertainTeed.
 - b. Knauf.
 - c. John Mnasville.
 - d. Owens-Corning.
 - e. Or approved equal.
 - Faced Batt/Blanket Insulation: ASTM C665, Type III, Category 1, foil-faced flexible glass-fiber, high-density batt/blanket insulation.
 - a. Physical Properties: Class B (faced surface with flame-propagation resistance of 0.12 W/sq. cm).
 - 3. Thickness to fill wall cavity. Widths and lengths as required for existing conditions.

2.03 ACCESSORIES

- A. Tape: Reinforced polyethylene film with acrylic pressure sensitive adhesive.
 - 1. Application: Sealing of interior circular penetrations, such as pipes or cables.
 - 2. Width: As required for application.

- B. Insulation Fasteners: Impaling clip of galvanized steelwith washer retainer and clips, to be adhered to surface to receive insulation, length to suit insulation thickness and substrate, capable of securely and rigidly fastening insulation in place.
- C. Adhesive: Type recommended by insulation manufacturer for application.

PART 3 EXECUTION

3.01 EXAMINATION

- A. Verify that substrate, adjacent materials, and insulation materials are dry and that substrates are ready to receive insulation.
- B. Verify substrate surfaces are flat, free of honeycomb, fins, irregularities, or materials or substances that may impede adhesive bond.

3.02 BOARD INSTALLATION AT EXTERIOR WALLS

- A. Install boards horizontally on walls.
 - 1. Place boards to maximize adhesive contact.
 - 2. Install in running bond pattern.
 - 3. Butt edges and ends tightly to adjacent boards and protrusions.
- B. Extend boards over expansion joints, unbonded to wall on one side of joint.
- C. Cut and fit insulation tightly to protrusions or interruptions to the insulation plane.
- D. Tape insulation board joints.

3.03 BATT INSTALLATION

- A. Install insulation and vapor retarder in accordance with manufacturer's instructions.
- B. Install in exterior wall and roof spaces without gaps or voids. Do not compress insulation.
- C. Trim insulation neatly to fit spaces. Insulate miscellaneous gaps and voids.
- D. Fit insulation tightly in cavities and tightly to exterior side of mechanical and electrical services within the plane of the insulation.
- E. Staple or nail facing flanges in place at maximum 6 inches on center.
- F. Pack insulation in spaces at perimeter of window assembly to maintain continuity of thermal barrier

3.04 PROTECTION

A. Do not permit installed insulation to be damaged prior to its concealment.

END OF SECTION

1.01 SECTION INCLUDES

Water-resistive barriers.

1.02 REFERENCE STANDARDS

- A. ASTM D1970/D1970M Standard Specification for Self-Adhering Polymer Modified Bituminous Sheet Materials Used as Steep Roofing Underlayment for Ice Dam Protection 2021.
- B. ASTM E84 Standard Test Method for Surface Burning Characteristics of Building Materials 2023.
- C. ASTM E96/E96M Standard Test Methods for Gravimetric Determination of Water Vapor Transmission Rate of Materials 2022a.
- D. ICC-ES AC38 Acceptance Criteria for Water-Resistive Barriers 2016, with Editorial Revision (2019).
- E. ICC-ES AC148 Acceptance Criteria for Flexible Flashing Materials 2017.

1.03 SUBMITTALS

- A. Product Data: Provide data on material characteristics.
- B. Manufacturer's Installation Instructions: Indicate preparation, installation methods, and storage and handling criteria.
- C. Warranty: Manufacturer's ten (10) year limited product and labor warranty.

1.04 MOCK-UPS

- A. Locate where directed.
- B. Mock-up may remain as part of work.
- C. Contractor responsible to coordinate mock up with certified Tyvek inspector.

PART 2 PRODUCTS

2.01 WATER-RESISTIVE BARRIER MATERIALS

- A. Basis of Design: Dupont Tyvek "DrainWrap," spunbonded polyolefin, non-woven, non-perforated, weather barrier and related assembly components or approved equal.
 - 1. Air Penetration: 0.004 cfm/ft² at 75 Pa, when tested in accordance with ASTM E2178. Type I per ASTM E1677.
 - 2. Drainage: >98%, when tested in accordance with ASTM E2273.
 - 3. Water Vapor Transmission: 50 perms, when tested in accordance with ASTM E96, Method B.
 - 4. Water Penetration Resistance: 210 cm when tested in accordance with AATCC Test Method 127.
 - 5. Basis Weight: 2.1 oz/yd², when tested in accordance with TAPPI Test Method T-410.
 - 6. Air Resistance: 300 seconds, when tested in accordance with TAPPI Test Method T-460.
 - 7. Tensile Strength: 30/30 lbs/in., when tested in accordance with ASTM D882, Method A.
 - 8. Tear Resistance: 7/9 lbs, when tested in accordance with ASTM D1117.
 - 9. Surface Burning Characteristics: Class A, when tested in accordance with ASTM E84. Flame Spread: 5, Smoke Developed: 25
 - 10. Manufacturers:
 - a. DuPont Tyvek,
 - b. Benjamin Obdyke,
 - c. Fortifiber Building Systems Group,
 - d. Kimberly-Clark,
 - e. Or approved equal.

2.02 ACCESSORIES

A. Sealants, Tapes, and Accessories Used for Sealing Water-Resistive Barrier and Adjacent Substrates: As indicated or complying with water-resistive barrier manufacturer's installation instructions.

- B. Flexible Flashing: Self-adhesive sheet flashing complying with ASTM D1970/D1970M, except slip resistance requirement is waived if not installed on a roof.
 - 1. Width: Size and type to suit application and conditions in field.
 - 2. Ultraviolet (UV) and Weathering Resistance: Approved by manufacturer for up to 30 days of weather exposure.
 - 3. Products:
 - a. DuPont de Nemours, Inc; FlexWrap: www.dupont.com/building/#sle.
 - b. DuPont de Nemours, Inc; StraightFlash: www.dupont.com/building/#sle.
 - c. DuPont de Nemours, Inc; QuickFlash: www.dupont.com/building/#sle.
 - d. Or approved equal.

C. Fasteners

1. Basis-of-Design: Tyvek® Wrap Caps for use with wood construction, as distributed by DuPont: #4 nails with large one (1")-inch plastic cap fasteners, or one (1")-inch plastic cap staples with leg length sufficient to achieve a minimum penetration of 5/8-inch into the wood stud or approved equal.

D. Sealants

1. Provide sealants that comply with ASTM C920, elastomeric polymer sealant to maintain watertight conditions. Reference Section 079200 - Joint Sealants.

E. Adhesives

- 1. Products:
 - a. Liquid Nails® LN-109.
 - b. Denso Butyl Liquid.
 - c. 3M High Strength 90.
 - d. SIA 655.
 - e. Or approved equal.

F. Primers

- 1. Provide flashing manufacturer recommended primer to assist in adhesion between substrate and flashing.
- 2. Products:
 - a. 3M High Strength 90.
 - b. Denso Butyl Spray.
 - c. SIA 655.
 - d. Permagrip 105.
 - e. ITW TACC Sta' Put SPH.
 - f. Or approved equal.

PART 3 EXECUTION

3.01 EXAMINATION

A. Verify that surfaces and conditions comply with requirements of this section.

3.02 PREPARATION

A. Remove projections, protruding fasteners, and loose or foreign matter that might interfere with proper installation.

3.03 INSTALLATION

- A. Install materials in accordance with manufacturer's installation instructions.
- B. Water-Resistive Barriers: Install continuous water-resistive barrier over surfaces indicated, with sheets lapped to shed water but with seams not sealed.
- C. Apply sealants and adhesives within recommended temperature range in accordance with manufacturer's installation instructions.
- D. Mechanically Fastened Exterior Sheets:

- 1. Install sheets shingle-fashion to shed water, with seams aligned horizontal.
- 2. Overlap seams as recommended by manufacturer, 6 inches, minimum.
- 3. Overlap at outside and inside corners as recommended by manufacturer, 12 inches, minimum.
- 4. Install water-resistive barrier over jamb flashings.
- 5. Install head flashings under water-resistive barrier.
- 6. At framed openings with frames having nailing flanges, extend sheet into opening and over flanges; at head of opening, seal sheet over flange and flashing.
- E. Openings and Penetrations in Exterior Water-Resistive Barriers:
 - 1. Install flashing over sills, covering entire sill framing member, and extend at least 5 inches onto water-resistive barrier and at least 6 inches up jambs; mechanically fasten stretched edges.
 - 2. At openings filled with frames having nailing flanges, seal head and jamb flanges using a continuous bead of sealant compressed by flange and cover flanges with sealing tape at least 4 inches wide; do not seal sill flange.
 - 3. At openings filled with nonflanged frames, seal water-resistive barrier to each side of framing at opening using flashing at least 9 inches wide, and covering entire depth of framing.
 - 4. At head of openings, install flashing under water-resistive barrier extending at least 2 inches beyond face of jambs; seal water-resistive barrier to flashing.
 - 5. At interior face of openings, seal gaps between window and door frames and rough framing using appropriate joint sealant over backer rod.
 - 6. Service and Other Penetrations: Form flashing around penetrating items and seal to surface of water-resistive barrier.

3.04 FIELD QUALITY CONTROL

A. Obtain approval of installation procedures from water-resistive barrier manufacturer based on a mock-up installed in place, prior to proceeding with remainder of installation.

3.05 PROTECTION

A. Do not leave materials exposed to weather longer than recommended by manufacturer.

END OF SECTION

1.01 SECTION INCLUDES

A. Fiber-cement siding.

1.02 REFERENCE STANDARDS

- A. ASTM C1186 Standard Specification for Flat Fiber-Cement Sheets 2022.
- B. ASTM E84 Standard Test Method for Surface Burning Characteristics of Building Materials 2023.

1.03 SUBMITTALS

- A. Product Data: Submit manufacturer's data sheets on each product to be used, including:
 - 1. Manufacturer's requirements for related materials to be installed by others.
 - 2. Preparation instructions and recommendations.
 - 3. Storage and handling requirements and recommendations.
 - 4. Installation methods, including nail patterns.
- B. Installer's qualification statement.
- C. Maintenance Instructions: Periodic inspection recommendations and maintenance procedures.
- D. Warranty: Submit copy of manufacturer's warranty, made out in Owner's name, showing that it has been registered with manufacturer.
- E. Warranty Documentation for Installation of Building Rain screen Assembly: Submit installer warranty and ensure that forms have been completed in Owner's name and registered with installer.

1.04 QUALITY ASSURANCE

- A. Installer Qualifications: Company specializing in performing work of type specified in this section with not less than three years of experience.
- B. Obtain all siding materials from a single source manufacturer.
- C. Mockup:
 - 1. Size: Minimum 4 x 8 feet
 - 2. Show: Weather resistant barrier, siding, trim, flashings and joint sealers. Include one (1) window, and one (1) external corner.
 - 3. Location to be coordinated with Owner.
 - 4. Approved mockup may remain as part of the Work.

D. Pre-Installation Conference:

- 1. Convene at site two (2) weeks prior to beginning work of this Section.
- 2. Attendance: Owner, Contractor, siding system installer and related trades.
- 3. Review and discuss: Contract Documents, siding system manufacturer's literature, moisture barrier requirements, project conditions, scheduling and other matters affecting installation.

1.05 DELIVERY, STORAGE, AND HANDLING

- A. Deliver and store materials in manufacturer's unopened packaging, with labels intact, until ready for installation.
- B. Store materials under dry and waterproof cover, well ventilated, and elevated above grade on a flat surface.
- C. Protect materials from harmful environmental elements, construction dust, and other potentially detrimental conditions.

1.06 WARRANTY

- A. Provide manufacturer's non-pro-rated thirty (30) year warranty providing coverage against hail and termite damage and defects in materials and workmanship.
- B. Provide installer's two (2) year warranty providing coverage against defects in installation. This is an extension of the Contractor's standard one (1) year warranty.

Jul-12-2023 074646 - 1

PART 2 PRODUCTS

2.01 FIBER-CEMENT SIDING

- A. Lap Siding: Individual horizontal boards made of cement and cellulose fiber formed under high pressure with integral surface texture, complying with ASTM C1186, Type A, Grade II; with machined edges, for nail attachment.
 - 1. Style: Standard lap style.
 - 2. Texture: Smooth.
 - 3. Length: 12 feet, nominal.
 - 4. Width (Height): 5-1/4 inches.
 - 5. Size: 8-1/4" plank with 7" exposure.
 - 6. Thickness: 5/16 inch, nominal.
 - 7. Finish: Factory applied primer.
 - 8. Warranty: 30 year limited; transferable.
 - 9. Products:
 - a. James Hardie Building Products, Inc: www.jameshardie.com/#sle.
 - b. Or approved equal.
- B. Panel Siding: Vertically oriented panels made of cement and cellulose fiber formed under high pressure with integral surface texture, complying with ASTM C1186, Type A, Grade II; with machined edges, for nail attachment.
 - 1. Texture: Smooth.
 - 2. Length (Height): 96 inches, nominal.
 - 3. Width: 48 inches.
 - 4. Thickness: 5/16 inch, nominal.
 - 5. Finish: Factory applied primer.
 - 6. Warranty: 30year limited; transferable.
 - 7. Products:
 - a. James Hardie Building Products, Inc: www.jameshardie.com/#sle.
 - b. Or approved equal.

2.02 ACCESSORIES

- A. Fiber Cement Trim: Same material and texture as siding.
 - 1. Length: 12 feet, nominal.
 - 2. 1" x various widths: 3-1/2", 5-1/2", 7-1/4", 9-1/4", and 11-1/4" noted per Drawings.
- B. Metal Trim:
 - 1. Material: Extruded aluminum, ASTM B221, 6063-T5 alloy and temper, clear anodized finish.
 - 2. Shapes:
 - a. Vertical Metal Trim:
 - 1) Basis of Design: Xtreme Trim "Vertical Bead Reveal", Item ID BRV14516, 1/4" wide with 5/16"flanges to receive 5/16" Fiber Cement Panel, 1/4" reveal.
 - 2) Exposed, vertical splines covering joints not acceptable, ½" reveal not acceptable.
 - b. Horizontal Metal Trim:
 - Basis of Design: Xtreme Trim "Horizontal Bead Reveal", Item ID BRH516, to receive 5/16" Fiber Cement Panel, 1/4" reveal.
 - 2) Exposed, horizontal splines covering joints not acceptable, ½" reveal not acceptable.
 - c. Metal J-Channel Trim:
 - 1) Basis of Design: Xtreme Trim "J-Mold", Item ID JMS5168, to receive 5/16" Fiber Cement Panel, 3/8" flange overlap.
 - d. Metal Inside Corner Trim:
 - 1) Basis of Design: Xtreme Trim "Low Profile Panel Inside Corner", Item ID XICLP516, 1 ½" interior leg with 1/2" exposed flange to receive 5/16" Fiber Cement Panel.
 - e. Metal Outside Corner Trim:

Jul-12-2023 074646 - 2

- 1) Basis of Design: Xtreme Trim "Low Profile Outside Corner", Item ID XOCLP516, 3/4" flange, to receive 5/16" Fiber Cement Panel.
- C. Fiber Cement Mounting Block: Mounting block made of cement and cellulose fiber formed under high pressure with integral surface texture, complying with ASTM C1186, Type A, Grade II.
 - 1. Application: Hose bibbs, HVAC drip lines, receptacle outlet, exterior wall mounted lights.
 - 2. Size: As recommended by manufacturer.
 - 3. Finish: Factory applied primer.
 - Basis of Design: Sturdi Mount; 29797 Beck Rd, Wixom, MI 48393; Toll Free Tel: 800-521-8486;
 Web: www.sturdimount.com
- D. Fasteners: Galvanized or corrosion resistant; length as required to penetrate, 1-1/4 inches, minimum.
 - 1. At fiber cement panel, use stainless steel T- or pan-head screws as recommended by panel manufacturer, of equal or greater holding power than required by manufacturer's Code compliance reports.
- E. Edge Sealer: Type recommended by siding manufacturer.
- F. Insect Screen: Cor-a-Vent SV-5 Rainscreen Siding Vent, 3/4-inch thick or approved equivalent.

PART 3 EXECUTION

3.01 INSTALLATION

- A. Install in accordance with manufacturer's instructions and recommendations.
 - 1. Read warranty and comply with terms necessary to maintain warranty coverage.
 - 2. Blind nailing (fastening each piece such that the lap above it covers the fastener) is to be done according to manufacturer's recommendations.
 - 3. Use trim details as indicated on drawings.
 - 4. Touch up field cut edges before installing.
 - 5. Pre-drill nail holes if necessary to prevent breakage.
- B. Over Wood and Wood-Composite Sheathing: Fasten siding through sheathing into studs.
- C. Joints in Horizontal Siding: Avoid joints in lap siding except at corners; where joints are inevitable stagger joints between successive courses. Follow manufacturer's installation instructions for treatment of butt joints.
- D. Joints in Vertical Siding: Install Z-flashing in horizontal joints between successive courses of vertical siding.
- E. Do not install siding less than 6 inches from ground surface, or closer than 1 inch to roofs, patios, porches, and other surfaces where water may collect.
- F. After installation, seal joints except lap joints of lap siding; seal around penetrations, and paint exposed cut edges.
- G. Leave gap between horizontal drainage flashings and bottom of siding above. Do not seal this space.
- H. Cut to fit around penetrations with maximum 1/4-inch gap. Smooth and seal cut edges.
- I. Finish Painting: See Section 099113.

3.02 TOLERANCES

- A. Maximum Variation from Plumb and Level: 1/4 inch per ten (10') feet.
- B. Maximum Offset From Joint Alignment: 1/16 inch.

3.03 CLEANING

A. Clean faced panels in accordance with manufacturer's maintenance instructions, using cleaning materials and methods acceptable to manufacturer.

END OF SECTION

Jul-12-2023 074646 - 3

1.01 SECTION INCLUDES

- A. Fabricated sheet metal items, including flashings, counterflashings, gutters, downspouts, exterior penetrations, and gutter guards.
- B. Sealants for joints within sheet metal fabrications.

1.02 REFERENCE STANDARDS

- A. AAMA 2605 Voluntary Specification, Performance Requirements and Test Procedures for Superior Performing Organic Coatings on Aluminum Extrusions and Panels (with Coil Coating Appendix) 2022.
- B. ASTM A653/A653M Standard Specification for Steel Sheet, Zinc-Coated (Galvanized) or Zinc-Iron Alloy-Coated (Galvannealed) by the Hot-Dip Process 2022.
- C. ASTM A666 Standard Specification for Annealed or Cold-Worked Austenitic Stainless Steel Sheet, Strip, Plate, and Flat Bar 2015.
- D. ASTM B32 Standard Specification for Solder Metal 2020.
- E. ASTM C920 Standard Specification for Elastomeric Joint Sealants 2018.
- F. CDA A4050 Copper in Architecture Handbook current edition.
- G. SMACNA (ASMM) Architectural Sheet Metal Manual 2012.

1.03 SUBMITTALS

- A. Shop Drawings: Indicate material profile, jointing pattern, jointing details, fastening methods, flashings, terminations, and installation details.
- 3. Samples: Submit two samples of each material specified, illustrating metal finish color.

1.04 QUALITY ASSURANCE

- A. Perform work in accordance with SMACNA (ASMM) and CDA A4050 requirements and standard details, except as otherwise indicated.
- B. Maintain one copy of each document on site.

1.05 DELIVERY, STORAGE, AND HANDLING

- A. Stack material to prevent twisting, bending, and abrasion, and to provide ventilation. Slope metal sheets to ensure drainage.
- B. Prevent contact with materials that could cause discoloration or staining.

1.06 WARRANTY

- A. Pre-Finished Steel Sheet and Coil Coating Warranty: Manufacturer's 20-year Warranty against fading, color change, chalking, peeling, cracking, or delaminating.
- B. Contractor Warranty: Warranty work of this Section to be waterproof and weather-tight against ordinary wear and usage for two (2) years from date of Substantial Completion, including material and labor. This is an extension of the standard one (1)-year warranty.

PART 2 PRODUCTS

2.01 SHEET MATERIALS

- A. Pre-Finished Galvanized Steel: ASTM A653/A653M, with G90/Z275 zinc coating; minimum 24-gauge, 0.0239-inch thick base metal, shop pre-coated with PVDF coating.
 - 1. Polyvinylidene Fluoride (PVDF) Coating: Superior performing organic powder coating, AAMA 2605; multiple coat, thermally cured fluoropolymer finish system.
 - 2. Color: To be determined by owner.
 - 3. Perimeter edge flashings: Fabricate to detail. Provide minimum six (6") inch end-laps set in two (2) continuous beads of sealant.
 - 4. Clips and cleats: 20 gauge minimum.

- 5. Miscellaneous flashings and counter-flashings not noted above.
- B. Stainless Steel: ASTM A666, Type 304 alloy, soft temper, 28 gauge, 0.0156 inch thick; smooth No. 4 Brushed finish.

2.02 FABRICATION

- A. Form sections true to shape, accurate in size, square, and free from distortion or defects.
- B. Fabricate cleats and starter strips same material as sheet, in widths required by SMACNA, inter-lockable with sheet.
- C. Form pieces in longest possible lengths.
- D. Provide expansion joints at minimum forty (40') foot intervals or as required by SMACNA or as indicated.
- E. Hem exposed edges on underside 1/2 inch; miter and seam corners.
- F. Form material with flat lock seams, except where otherwise indicated; at moving joints, use sealed lapped, bayonet-type or interlocking hooked seams.
- G. Seal laps. Provide a minimum six (6") inch end lap and seal with two (2) continuous beads of approved sealant.
- H. Fabricate corners from one piece with minimum 18-inch long legs; seam for rigidity, seal with sealant.
- I. Fabricate vertical faces with bottom edge formed outward 1/4 inch and hemmed to form drip.
- J. Provide folded end dams at ends of horizontal flashing.
- K. Cap neat ends.
- L. Solder and seal metal joints.
 - 1. After soldering, remove flux.
 - 2. Wipe and wash solder joints clean.

2.03 GUTTERS AND DOWNSPOUTS

- A. Gutters: SMACNA (ASMM) Rectangular profile.
 - 1. Site rolled. Provide continuous five (5") inch wide (seamless) "K" style gutters. Attach with concealed hangers at twenty-four (18") inches o.c. Install expansion joints in gutter lengths greater than forty (40') feet.
 - 2. Material: Fabricate from coil aluminum, .027 gauge, Kynar 500 (PVDF) finish.
 - 3. Color as selected by Owner from manufacturer's standard colors.
- B. Downspouts: Rectangular profile.
 - 1. Fabricate from coil aluminum, .027 Gauge, Kynar 500 (PVDF) finish
 - 2. Color- White
- C. Accessories: Profiled to suit gutters and downspouts.
 - 1. Anchorage Devices: In accordance with SMACNA (ASMM) requirements.
 - 2. Gutter Supports: Brackets.
 - 3. Downspout Supports: Brackets.
- D. Gutter Debris Protection: Amerimax Home Products Metal Lock-in Gutter Guard, Raptor Gutter Guard Stainless Steel screwed in gutter guard, or approved equal. Color as selected by Owner from manufacturer's standard white.
- E. Downspout Boots: Plastic.
- F. Seal metal joints.

2.04 EXTERIOR PENETRATION FLASHING PANELS

A. Flashing Panels for Exterior Wall Penetrations: Premanufactured components and accessories as required to preserve integrity of building envelope; suitable for conduits and facade materials to be installed.

KCHA PEPPER TREE - ENVELOPE SHORELINE, WASHINGTON

SECTION 076200 SHEET METAL FLASHING AND TRIM

2.05 ACCESSORIES

- A. Sill Pan Material: Fabricate from stainless steel, ASTM A240, Type 304, dead soft fully annealed, 0.018-inch thick, smooth surface, Number 4 finish. Fabricate to detail. Form end dams each side and solder to prevent water migration.
- B. Fasteners: Galvanized steel, with soft neoprene washers.
- C. Primer Type: Zinc chromate.
- D. Concealed Sealants: Non-curing butyl sealant.
- E. Exposed Sealants: ASTM C920; elastomeric sealant, with minimum movement capability as recommended by manufacturer for substrates to be sealed; color to match adjacent material.
- F. Electrolytic Protection to separate dissimilar materials: Cold-applied asphalt-mastic complying with SSPC-Paint 12 requirements, containing no asbestos, formulated for 30-mil thickness per coat.
- G. Solder: ASTM B32, Alloy Grade Sn50 (50/50).

PART 3 EXECUTION

3.01 INSTALLATION

- A. Install in conformance to SMACNA, NRCA, and provisions of the Contract Documents.
- B. Neatly form and finish joints and seams. Make lines, moldings, and edges sharp and true. Reinforce as required for stiffness.
- C. Make surfaces free from waves and buckles. Build in expansion joints and make other provisions to allow for thermal expansion and contraction to prevent distortion and oil-canning.
- D. Overlapping Metal Flashing Joints: Install lap sealant at copings, reglets, counterflashing, gutters, and other continuous flashing joint overlaps.
 - 1. Install minimum one bead of butyl bedding sealant between flashing overlaps.
 - 2. Seal exposed open ends of flashing with silicon joint sealant.
 - 3. Install bead of butyl or silicone sealant at joints under cap flashing and overlapped flashing. Install minimum one bead of butyl bedding sealant or silicone sealant on each side of joint.
 - 4. Install one bead of butyl bedding sealant or silicone sealant between substrate and flush mounted reglets, termination bars, and other overlaps or metal to metal to other construction.
 - 5. Do not compress sealant beads between overlapping flashing.
- E. Slope copings and other horizontal installations for positive drainage to shed water.
- F. Secure flashings in place using concealed fasteners, and use exposed fasteners only where permitted..
- G. Apply plastic cement compound between metal flashings and felt flashings.
- H. Fit flashings tight in place; make corners square, surfaces true and straight in planes, and lines accurate to profiles.
- I. Seal penetrations through sheet metal and flashings by lapping with air barrier or with sealant.
- J. Solder metal joints for full metal surface contact, and after soldering wash metal clean with neutralizing solution and rinse with water.

K. Sweat Soldering:

- 1. Pre-tin edges of sheet metal to a width of 1-1/2" inches before beginning soldering.
- 2. Fully sweat solder joints to a minimum depth of ½" by applying heat from iron to upper sheet, drawing solder fully into joint below.
- L. Electrolytic Protection: Prevent galvanic action where dissimilar metals are in galvanic range of each other. Separate with tape, bituminous protective backing, 2 coats of bituminous paint, or other isolation methods.

M. Downspouts

- 1. Secure gutters and downspouts in place with concealed fasteners.
- 2. Install continuous gutter cleats allowing for free thermal expansion and contraction.
- 3. Install steel gutter spacer straps and gutter brackets not exceeding 3 foot on center spacing.

KCHA PEPPER TREE - ENVELOPE SHORELINE, WASHINGTON

SECTION 076200 SHEET METAL FLASHING AND TRIM

- 4. Secure continuous eave hanger to solid wood framing.
- 5. Insert downspouts into downspout outlets and sweat solder into place.
- 6. Flash and seal with joint sealer for watertight connections and joints.
- 7. Install expansion joints and covers at continuous gutter sections at 50 foot on center. Provide exposed splice plates and expansion joint covers.
- 8. Support downspouts with downspout straps 8 to 10 foot on center, maximum, except not less than 2 per downspout. Space at even intervals.
- 9. Connect downspouts with neoprene downspout boot to below grade tight line storm drainage system. Do not connect into foundation drainage system.
- N. Slope gutters 1/4 inch per 10 feet, minimum.
- O. Connect downspouts to downspout boots, and grout connection watertight.

END OF SECTION

1.01 SECTION INCLUDES

- A. Nonsag gunnable joint sealants.
- B. Joint backings and accessories.

1.02 REFERENCE STANDARDS

- A. ASTM C661 Standard Test Method for Indentation Hardness of Elastomeric-Type Sealants by Means of a Durometer 2015 (Reapproved 2022).
- B. ASTM C834 Standard Specification for Latex Sealants 2017.
- C. ASTM C919 Standard Practice for Use of Sealants in Acoustical Applications 2022.
- D. ASTM C920 Standard Specification for Elastomeric Joint Sealants 2018.
- E. ASTM C1193 Standard Guide for Use of Joint Sealants 2016.
- F. ASTM C1521 Standard Practice for Evaluating Adhesion of Installed Weatherproofing Sealant Joints 2019 (Reapproved 2020).
- G. ASTM E119 Standard Test Methods for Fire Tests of Building Construction and Materials 2022.
- H. SCAQMD 1168 Adhesive and Sealant Applications 1989, with Amendment (2022).
- UL 263 Standard for Fire Tests of Building Construction and Materials Current Edition, Including All Revisions.

1.03 SUBMITTALS

- A. Product Data: Submit manufacturer's technical datasheets for each product to be used; include the following:
 - Physical characteristics, including movement capability, VOC content, hardness, cure time, and color availability.
 - 2. List of backing materials approved for use with the specific product.
 - 3. Substrates that product is known to satisfactorily adhere to and with which it is compatible.
 - 4. Substrates the product should not be used on.
- B. Color Cards for Selection: Where sealant color is not specified, submit manufacturer's color cards showing standard colors available for selection.
- C. Installation Plan: Submit at least four weeks prior to start of installation.
- D. Installation Log: Submit filled-out log for each length or instance of sealant installed.
- E. Installer's qualification statement.
- F. Executed warranty.

1.04 QUALITY ASSURANCE

- A. Single Source Responsibility for Joint Sealant Materials:
 - 1. Obtain joint sealants from a single manufacturer for each different product required to ensure compatibility.
 - 2. Manufacturer shall instruct applicator in procedures for intersecting sealants.
- B. Installer Qualifications: Company specializing in performing the work of this section and with at least three years of documented experience.
- C. Installation Plan: Include schedule of sealed joints, including the following:
 - 1. Installation Log Form: Include the following data fields, with known information filled out.
 - a. Location on project.
 - b. Substrates.
 - c. Sealant used.
 - d. Date of installation.
 - e. Name of installer.

- f. Actual joint width; provide space to indicate maximum and minimum width.
- g. Actual joint depth to face of backing material at centerline of joint.
- h. Air temperature.
- D. Field Adhesion Tests of Joints: Test for adhesion using most appropriate method in accordance with ASTM C1521, or another applicable method as recommended by manufacturer.

1.05 WARRANTY

- A. Manufacturer Warranty: Provide 5-year manufacturer warranty for installed sealants and accessories that fail to achieve a watertight seal, exhibit loss of adhesion or cohesion, or do not cure. Complete forms in Owner's name and register with manufacturer.
- B. Applicator's Warranty: Provide 2-year applicator warranty for installed sealants and accessories covering workmanship. Complete forms in Owner's name.

PART 2 PRODUCTS

2.01 MANUFACTURERS

- A. Nonsag Sealants:
 - 1. Dow: www.dow.com/#sle.
 - 2. Sika Corporation: www.usa.sika.com/#sle.
 - 3. Tremco Commercial Sealants & Waterproofing: www.tremcosealants.com/#sle.
 - 4. Or approved equal.

2.02 JOINT SEALANTS - GENERAL

- A. Sealants and Primers: Provide products having lower volatile organic compound (VOC) content than indicated in SCAOMD 1168.
- B. Colors: As selected by Owner from samples of manufacturer's standard color range.
- C. Compatibility:
 - 1. Provide joint sealants, joint fillers and accessory joint materials that are compatible with one another and with joint substrates under project conditions.
 - 2. Install joint sealants, joint fillers and related joint materials that are non-staining to visible joint surfaces and surrounding substrate surfaces.

2.03 NONSAG JOINT SEALANTS

- A. Silicone Sealant: ASTM C920, Grade NS, Uses M and A; not expected to withstand continuous water immersion or traffic.
 - 1. Movement Capability: Plus and minus 25 percent, minimum.
 - 2. Color: Match adjacent finished surfaces.
 - 3. Cure Type: Single component, neutral moisture curing.
- B. Mildew-Resistant Silicone Sealant: ASTM C920, Grade NS, Uses M and A; single component, mildew resistant; not expected to withstand continuous water immersion or traffic.
 - 1. Color: White.
- C. Acrylic-Urethane Sealant: ASTM C920, Grade NS, Uses M and A; single component; paintable; not expected to withstand continuous water immersion or traffic.
 - 1. Movement Capability: Plus and minus 12-1/2 percent, minimum.
 - 2. Color: White.
- D. Acrylic Emulsion Latex: Water-based; ASTM C834, single component, nonstaining, nonbleeding, nonsagging; not intended for exterior use.
 - 1. Color: Standard colors matching finished surfaces, Type OP (opaque).
 - 2. Grade: ASTM C834; Grade NF.
- E. Acrylic Latex Sealant: ASTM C834; for use as acoustical sealant and in firestopping systems for expansion joints and through penetrations.
 - 1. Color: Standard colors matching finished surfaces.

Fire Rated System: Complies with UL 263 and ASTM E119 with UL fire resistance classifications.

2.04 ACCESSORIES

- A. Backer Rod: Cylindrical cellular foam rod with surface that sealant will not adhere to, compatible with specific sealant used, and recommended by backing and sealant manufacturers for specific application.
 - 1. Closed Cell and Bi-Cellular: 25 to 33 percent larger in diameter than joint width.
 - 2. Polystyrene foam not acceptable.
- B. Backing Tape: Self-adhesive polyethylene tape with surface that sealant will not adhere to and recommended by tape and sealant manufacturers for specific application.
- C. Masking Tape: Self-adhesive, nonabsorbent, nonstaining, removable without adhesive residue, and compatible with surfaces adjacent to joints and sealants.
- D. Joint Cleaner: Noncorrosive and nonstaining type, type recommended by sealant manufacturer; compatible with joint forming materials.
- E. Primers: Type recommended by sealant manufacturer to suit application; nonstaining.

PART 3 EXECUTION

3.01 PREPARATION

- A. Remove loose materials and foreign matter that could impair adhesion of sealant.
- B. Clean joints, and prime as necessary, in accordance with manufacturer's instructions.
- C. Perform preparation in accordance with manufacturer's instructions and ASTM C1193.
- D. Mask elements and surfaces adjacent to joints from damage and disfigurement due to sealant work; be aware that sealant drips and smears may not be completely removable.

3.02 INSTALLATION

- A. Install this work in accordance with sealant manufacturer's requirements for preparation of surfaces and material installation instructions.
- B. Seal joints before final coat of finish is applied to adjacent surfaces.
- C. Provide joint sealant installations complying with ASTM C1193.
- D. Install acoustical sealant application work in accordance with ASTM C919.
- E. Measure joint dimensions and size joint backers to achieve the following, unless otherwise indicated:
 - 1. Width/depth ratio of 2:1.
 - 2. Neck dimension no greater than 1/3 of the joint width.
 - 3. Surface bond area on each side not less than 75 percent of joint width.
 - 4. Where more than 3/4" wide pack with foam backer rod material to within 1/2" of surface.
 - 5. Where less than 1/2" wide install foam rod backer rod material to within 1/4" of surface.
- F. Provide backing materials in as long lengths as practicable; install with proper tool. Force backing into joint to proper depth for sealant.
- G. Install bond breaker backing tape where backer rod cannot be used.
- H. Install sealant free of air pockets, foreign embedded matter, ridges, and sags, and without getting sealant on adjacent surfaces.
- I. Do not install sealant when ambient temperature is outside manufacturer's recommended temperature range, or will be outside that range during the entire curing period, unless manufacturer's approval is obtained and instructions are followed.
- J. Nonsag Sealants: Tool surface concave, unless otherwise indicated; remove masking tape immediately after tooling sealant surface.

K. Curing

1. Prior to painting or coating, allow sealant joints to cure as directed by sealant manufacturer, minimum seven (7) days for a single component and three (3) days for a multi-component.

2. Ambient temperatures and humidity affect the cure rate and time required for joint to be "tack-free". Notify Owner if cure times exceed the minimums listed.

3.03 FIELD QUALITY CONTROL

- A. Field-Adhesion Testing: Field test joint-sealnt adhesion to joint substrates in accordance with manufacturer's instructions and ASTM C1193, Method A, Field-Applied Sealnt Joint Hand-Pull Tab. Perform 5 tests for each 1,000 linear feet of applied sealant.
 - 1. For sealants applied between dissimilar materials, test both sides of joint.
- B. Sealants failing adhesion test shall be removed, substrateds cleaned, sealants re-installed, and re-testing performed.

3.04 SCHEDULE

JOINT SEALANT	APPLICATION
Single-Component Neutral Curing Silicone Sealant	 Exterior joins in exterior finish systems Exterior perimeter joints at frames of doors and windows. Exterior control and expansion joints in ceilings and other overhead surfaces All other exterior vertical and horizontal non-traffic joints unless noted otherwise
Single-Component Mildew-Resistant Neutral- Curing Silicone Sealant	Exterior joints with galvanized steel
Single-Component Nonsag Uretane Sealant	Interior joints of exterior openings
Latex Sealant	Perimeter joints between interior wall surfaces and frames of interior doors and windows

END OF SECTION

1.01 SECTION INCLUDES

- A. Fiberglass doors.
- B. Composite door frames.

1.02 REFERENCE STANDARDS

- A. ASTM E331 Standard Test Method for Water Penetration of Exterior Windows, Skylights, Doors, and Curtain Walls by Uniform Static Air Pressure Difference 2000 (Reapproved 2023).
- B. ASTM E2112 Standard Practice for Installation of Exterior Windows, Doors and Skylights 2019c.

1.03 SUBMITTALS

- A. Product Data: Provide manufacturer's standard details, installation instructions, and hardware and anchor recommendations.
- B. Shop Drawings: Indicate layout and profiles; include assembly methods.
 - Indicate product components, including hardware reinforcement locations and preparations, accessories, finish colors, patterns, and textures.
 - 2. Indicate wall conditions, door and frame elevations, sections, materials, gauges, finishes, location of door hardware by dimension, and details of openings; use same reference numbers indicated on drawings to identify details and openings.
- C. Installer's qualification statement.
- D. Maintenance Data: Include instructions for repair of minor scratches and damage.
- E. Warranty: Submit manufacturer warranty and ensure that forms have been completed in Owner's name and registered with manufacturer; include detailed terms of warranty.

1.04 QUALITY ASSURANCE

A. Installer Qualifications: Company specializing in performing work of the type specified and with at least three years of documented experience.

1.05 DELIVERY, STORAGE, AND HANDLING

- A. Deliver materials in manufacturer's original, unopened, undamaged containers with identification labels intact.
- B. Store materials in original packaging, under cover, protected from exposure to harmful weather conditions and from direct contact with water.
 - 1. Store at temperature and humidity conditions recommended by manufacturer.
 - 2. Do not use non-vented plastic or canvas shelters.
 - 3. Immediately remove wet wrappers.
- C. Store in position recommended by manufacturer, elevated minimum 4 inches above grade, with minimum 1/4 inch space between doors.

1.06 WARRANTY

A. Provide five (5) year manufacturer warranty covering materials and workmanship, including degradation or failure due to chemical contact.

PART 2 PRODUCTS

2.01 MANUFACTURERS

- A. Fiberglass Composite Doors:
 - 1. Therma-Tru Corp; Fiberglass Entry Door: thermatru.com/#sle.
 - 2. Or approved equal.

2.02 COMPONENTS

A. Doors: Fiberglass construction with reinforced core.

Jul-12-2023 081613 - 1

- 1. Thickness: 1-3/4 inch, nominal.
- 2. Door Panel Configuration: As indicated on drawings.
- 3. Subframe and Reinforcements: Manufacturer's standard materials.
- 4. Waterproof Integrity: Provide factory fabricated edges, cut-outs, and hardware preparations of fiberglass reinforced plastic (FRP); provide cut-outs with joints sealed independently of glazing, louver inserts, or trim.
- 5. Hardware Preparations: Factory reinforce, machine, and prepare for door hardware including field installed items; provide solid blocking for each item; field cutting, drilling or tapping is not permitted; obtain manufacturer's hardware templates for preparation as necessary.
- B. Door Frames: Composite construction with performance requirements specified for doors.
 - 1. Type: Factory assembled with chemically welded joints.
 - 2. Profiles: 5-1/2" inches. Jamb extensions if needed.
 - 3. Hinges: Pre-hung for specified hinges.
 - 4. Reinforcing: Provide manufacturer's standard reinforcing at hinge, strike, and closer locations.
 - 5. Include manufacturer's integral door gasket.
 - 6. Finish: Factory primed.
- C. Threshold: Manufacturer's adjustable composite threshold to match door swing.
- D. Sweep: Therma-Tru bottom sweep.

2.03 HARDWARE

A. Door Hardware: See Section 087100.

PART 3 EXECUTION

3.01 INSTALLATION

- A. Install in accordance with manufacturer's instructions; do not penetrate frames with anchors.
- B. Pre-hang doors in framed specified.
- C. Install exterior doors in accordance with ASTM E2112.
- D. Set units plumb, level, and true-to-line, without warping or racking doors, and with specified clearances; anchor in place.
- E. Set thresholds in continuous bed of sealant.
- F. Separate aluminum and other metal surfaces from sources of corrosion of electrolytic action at points of contact with other materials.

3.02 ADJUSTING

- A. Lubricate, test, and adjust doors to operate easily, free from warp, twist or distortion, and to fit watertight for entire perimeter.
- B. Adjust hardware for smooth and quiet operation.
- C. Adjust doors to fit snugly and close without sticking or binding.

END OF SECTION

Jul-12-2023 081613 - 2

1.01 SECTION INCLUDES

- A. Vinyl-framed, factory-glazed windows.
- B. Vinyl-framed, factory-glazed sliding patio doors.
- C. Operating hardware.
- D. Insect screens.
- E. Passive fresh air vents

1.02 REFERENCE STANDARDS

- A. AAMA/WDMA/CSA 101/I.S.2/A440 North American Fenestration Standard/Specification for Windows, Doors, and Skylights 2017.
- B. AAMA 502 Voluntary Specification for Field Testing of Newly Installed Fenestration Products 2021.
- C. ASTM E90 Standard Test Method for Laboratory Measurement of Airborne Sound Transmission Loss of Building Partitions and Elements 2009 (Reapproved 2016).
- D. ASTM E783 Standard Test Method for Field Measurement of Air Leakage Through Installed Exterior Windows and Doors 2002 (Reapproved 2018).
- E. ASTM E1105 Standard Test Method for Field Determination of Water Penetration of Installed Exterior Windows, Skylights, Doors, and Curtain Walls, by Uniform or Cyclic Static Air Pressure Difference 2015 (Reapproved 2023).
- F. ASTM E2112 Standard Practice for Installation of Exterior Windows, Doors and Skylights 2019c.

1.03 SUBMITTALS

- A. Product Data: Provide component dimensions, anchors, fasteners, glass, and internal drainage.
- B. Shop Drawings: Indicate opening dimensions, framed opening tolerances, affected related work, and installation requirements. Include window schedule, elevations, sections, and details. Include head, sill, and jamb conditions, operable parts, and direction/handing.
- C. Field Quality Control Submittals: Report of field testing for water penetration and air leakage.

1.04 QUALITY ASSURANCE

- A. Manufacturer Qualifications: Company specializing in manufacturing products specified in this section, with not less than ten years of documented experience and a member of the AAMA & NFRC.
- B. Installer Qualifications: Company specializing in performing of type specified and with at least three experience.
- C. Certifications for Insulated Glass Units: Insulated glass units are certified to ASTM E2188/E2190 per the Associated Laboratories Incorporated (ALI) guidelines.
- D. AAMA: Windows shall be Gold Label certified with label attached to frame per AAMA requirements.
- E. NFRC: Windows shall be NFRC certified with temporary U-factor label applied to glass and an NFRC tab added to permanent AAMA frame label.
- F. Source Limitations: Obtain vinyl windows through one source from a single manufacturer.
- G. Inspect windows in accordance with Manufacturer's Quality Control Program as required by AAMA Gold Label Certification.

1.05 DELIVERY, STORAGE, AND HANDLING

- A. Protect finished surfaces with wrapping. Do not use adhesive papers or sprayed coatings that bond when exposed to sunlight or weather.
- B. Jig, brace, and box the window frame assemblies for transport to minimize flexing of members or joints.

1.06 FIELD CONDITIONS

- A. Do not install sealants when ambient temperature is less than 40 degrees F.
- B. Maintain this minimum temperature during and after installation of sealants.
- C. Field Measurements: Verify vinyl window openings by field measurements before fabrication and indicate measurements on Shop Drawings. Confirm flashing dimensions.

1.07 WARRANTY

- A. Correct defective work within a 5-year period after Date of Substantial Completion.
- B. Manufacturer's Warranty: Provide 10-yearmanufacturer warranty for insulated glass units from seal failure, inter pane dusting or misting, and replacement of same. Include coverage for degradation of vinyl color finish. Complete form in Owner's name and register with manufacturer.

PART 2 PRODUCTS

2.01 MANUFACTURERS

- A. Vinyl Windows:
 - 1. Milgard Manufacturing; www.milgard.com/#sle; 1010 54th Avenue East, Tacoma, WA 98424.

2.02 GENERAL REQUIREMENTS

- A. Windows shall be ENERGY STAR qualified products that meet or exceed the ENERGY STAR performance rating or better.
- B. Air Leakage, Water Resistance, Structural Test: Comply with ANSI/AAMA /NWWDA 101/I.S.2.
- C. Forced-Entry Resistance: Comply with CAWM 301-90.
- D. Thermal Transmittance: Provide vinyl windows with a whole-window, U-factor maximum indicated at 15-mph exterior wind velocity and winter condition temperatures when tested according to AAMA 1503 and NFRC 100.
 - 1. U-Factor: 0.3 Btu/sq. ft. x h x deg. F or better.
 - 2. Alternate glazing U-factor: 0.22 or better
- E. Solar Heat-Gain Coefficient (SHGC): Provide vinyl windows with a whole-window SHGC maximum of 0.40, determined according to NFRC 200 procedures.

2.03 MATERIALS

- Integral color PVC compound containing impact-resistant solid plasticizer, titanium dioxide UV inhibitor, and surface and color stabilizers.
- B. Weather stripping:
 - Vinyl compression bulb seal

2.04 WINDOW TYPES

- A. Per list below and as indicated on the Drawings.
- B. Horizontal Sliding Window 1-7/8-inch nail fin setback. TUSCANY SERIES 8120
 - 1. Frame: Minimum 2-7/8 inch deep, multi-chambered vinyl profile.
 - 2. Sash: Minimum 1-3/16 inch deep, multi-chambered vinyl profile, includes vent stops located in fixed sash.
 - 3. Sightlines: Equal for operating and fixed sash.
 - 4. Structural Class:
 - a. 71-1/2" x 59-1/2" and smaller: HS-LC25.
 - b. Larger than 71-1/2" x 59-1/2": HS-R20.
 - 5. Hardware:
 - a. Positive action locking mechanism.
 - b. Nylon rollers with stainless steel axles, extruded vinyl Snap-On monorail roller track.
 - 6. Weather stripping: Fin seal polypropylene pile.

- C. Fixed/Picture Window with Horizontal Slider Frame 1-7/8-inch nail fin setback. TUSCANY SERIES 8120T
 - 1. Frame: Minimum 2-7/8 inch inch deep, multi-chambered vinyl profile.
 - 2. Structural Class: F-C40.
- D. E. Horizontal Sliding Patio Doors-1-3/8 inch nail fin setback. TRINSIC Series 2610
 - 1. Frame: Minimum 4-1/8 inch deep multi-chambered vinyl profile.
 - 2. Panel: Minimum 2-1/4 x 1-3/16 inch, multi-chambered vinyl profile
 - 3. Sill: 4-1/8" x 1-9/16" high. Multi-chambered vinyl profile.
 - 4. Structural Class: SD-LC35.
 - Hardware:
 - a. Handle and lock: Interior and outside pull with lever-operated 1 point jamb lock.
 - b. Rollers: Two sets of dual stainless steel, 1-1/2" diameter rollers on raised monorail stainless steel track.
 - 6. Weather stripping: Fin seal polypropylene pile.

2.05 GLAZING

- A. Insulated Glass Units: ASTM E 774, Class A, 7/8 inch thick overall. Clear, insulating- glass units, with low-E coating pyrolytic on second surface, double pane or sputtered on second or third surface.
 - 1. Glazing Type: Sun Coat Low E / Clear
- B. Glazing System: Manufacturer's standard factory-glazing system that produces weather tight seal. Units shall be able to be re-glazed without dismantling sash framing.
- C. Spacer Type: Warm edge stainless steel spacer.
- D. Gas Filled: Argon.
- E. Glass Thickness: Per Manufacturer's Specifications.

2.06 HARDWARE

- A. General: Provide manufacturer's standard hardware fabricated from aluminum, stainless steel, carbon steel complying with AAMA 907, or other corrosion-resistant material compatible with vinyl; designed to smoothly operate, tightly close, and securely lock vinyl windows, and sized to accommodate sash or ventilator weight and dimensions. Do not use aluminum in frictional contact with other metals. Smart Touch direct action locking mechanism is to be used. Nylon rollers with stainless steel axles, extruded vinyl Snap-On monorail roller track. Dual pull rails.
- B. Locks and Latches: Designed to allow unobstructed movement of the sash across adjacent sash in direction indicated and operated from the inside only.
- C. Sash lock: Lever handle with cam lock.

2.07 ACCESSORIES

- A. Insect Screens:
 - Rolled formed Aluminum insect screen frames: Manufacture's standard aluminum alloy complying with SMA 1004. Fabricate frames with mitered or coped joints or corner extrusions, concealed fasteners and removable PVC spline/anchor concealing edge of frame.
 - 2. Screen Cloth: Pure View High Visibility fiberglass mesh.
- B. Passive Fresh Air Ventilation System: All windows to have fresh air ventilation system. Vents to be vinyl construction which match color of new windows and meet following features:
 - 1. No hood design.
 - 2. Positive open and close design.
 - 3. Full operation of window shall not be limited by vent. Installed insect screen.
 - 4. Meets Washington State Energy Code for fresh air ventilation.

2.08 FABRICATION

- A. Fabricate frames and sash with mitered and fusion welded corners and joints.
- B. Trim and finish corners and welds to match adjacent surfaces.

- C. Provide concealed metal reinforcements in sash frame for attachment of lock mechanism.
- D. Factory interior glaze (except Double Hung and Double Slider) with Snap-on mitered PVC glazing stops matching bevels on the sash and frame. Insulated glass units shall be re-glaze able without dismantling sash framing.
- E. Note: Field glazing is required for large window units (over 40 sq. ft.).

2.09 FINISHES

- A. Frame and Sash Color:
 - 1. Exterior: White
 - 2. Interior: As selected by Owner from Manufacturer's standard finish options.
- B. Hardware: Manufacturer's standard
- C. Screen Frame Color:
 - Matched to exterior frame color

2.10 SOURCE OUALITY CONTROL:

A. Inspect windows in accordance with Manufacturer's Quality Control Program as required by AAMA Gold Label Certification.

PART 3 EXECUTION

3.01 INSTALLATION

- Install window unit assemblies in accordance with manufacturer's instructions and applicable building codes.
- B. Install windows in accordance with ASTM E2112.
- C. Attach window frame and shims to perimeter opening to accommodate construction tolerances and other irregularities as necessary.
- D. Align window plumb and level, free of warp or twist, and maintain dimensional tolerances and alignment with adjacent work.
- E. Set sill members and sill flashing in continuous bead of sealant.
- F. Provide thermal isolation where components penetrate or disrupt building insulation. Pack fibrous insulation in shim spaces at perimeter of assembly to maintain continuity of thermal barrier.
- G. Install operating hardware.

3.02 TOLERANCES

A. Maximum Variation from Level or Plumb: 0.06 inches every 3 ft. non-cumulative or 0.5 inches per 100 ft., whichever is less.

3.03 ADJUSTING

A. Adjust hardware for smooth operation and secure weather tight closure.

3.04 CLEANING

- A. Remove protective material from pre-finished surfaces.
- Wash surfaces by method recommended and acceptable to window manufacturer; rinse and wipe surfaces clean.
- C. Remove excess glazing sealant by moderate use of mineral spirits or other solvent acceptable to sealant manufacturer and appropriate for application indicated.

END OF SECTION

1.01 SECTION INCLUDES

- A. Hardware for fiberglass doors.
- B. Weather stripping and gaskets.

1.02 REFERENCE STANDARDS

- A. ADA Standards 2010 ADA Standards for Accessible Design 2010.
- B. BHMA A156.1 Standard for Butts and Hinges 2021.
- C. BHMA A156.2 Bored and Preassembled Locks and Latches 2017.
- D. BHMA A156.4 Door Controls Closers 2019.
- E. BHMA A156.6 Standard for Architectural Door Trim 2021.
- F. BHMA A156.7 Template Hinge Dimensions 2016.
- G. BHMA A156.8 Door Controls Overhead Stops and Holders 2021.
- H. BHMA A156.13 Mortise Locks & Latches Series 1000 2017.
- I. BHMA A156.17 Self Closing Hinges & Pivots 2019.
- J. BHMA A156.18 Materials and Finishes 2020.
- K. BHMA A156.22 Standard for Gasketing 2021.
- L. DHI (LOCS) Recommended Locations for Architectural Hardware for Standard Steel Doors and Frames 2004.
- M. ICC A117.1 Accessible and Usable Buildings and Facilities 2017.
- N. UL 437 Standard for Key Locks Current Edition, Including All Revisions.
- O. UL 1784 Standard for Air Leakage Tests of Door Assemblies Current Edition, Including All Revisions.

1.03 ADMINISTRATIVE REQUIREMENTS

- A. Coordinate the manufacture, fabrication, and installation of products that door hardware is installed on.
- B. Sequence installation to ensure utility connections are achieved in an orderly and expeditious manner.
- C. Furnish templates for door and frame preparation to manufacturers and fabricators of products requiring internal reinforcement for door hardware.
- D. Convey Owner's keying requirements to manufacturer.

1.04 SUBMITTALS

- A. Product Data: Manufacturer's catalog literature for each type of hardware, marked to clearly show products to be furnished for this project, and includes construction details, material descriptions, finishes, and dimensions and profiles of individual components.
- B. Door Hardware Schedule: Submit detailed listing that includes each item of hardware to be installed on each door. Use door numbering scheme as included in Contract Documents.
 - 1. Prepared by or under supervision of Architectural Hardware Consultant (AHC).
 - 2. Provide complete description for each door listed.
 - 3. Provide manufacturer name, product names, and catalog numbers; include functions, types, styles, sizes and finishes of each item.
 - 4. Include account of abbreviations and symbols used in schedule.
- C. Manufacturer's Installation Instructions: Indicate special procedures and perimeter conditions requiring special attention.
- D. Maintenance Data: Include data on operating hardware, lubrication requirements, and inspection procedures related to preventative maintenance.
 - 1. Submit manufacturer's parts lists and templates.

E. Keying Schedule:

- 1. Submit three (1) copy of Keying Biting Schedule in compliance with requirements established during Keying Requirements Meeting unless otherwise indicated.
- F. Specimen warranty.
- G. Maintenance Materials and Tools: Furnish the following for Owner's use in maintenance of project.
 - 1. Tools: One set of each special wrench or tool applicable for each different or special hardware component, whether supplied by hardware component manufacturer or not.

1.05 QUALITY ASSURANCE

- A. Manufacturer Qualifications: Company specializing in manufacturing products specified in this section with minimum three years of documented experience..
- B. Supplier Qualifications: Company with certified Architectural Hardware Consultant (AHC)to assist in work of this section.

1.06 DELIVERY, STORAGE, AND HANDLING

A. Package hardware items individually; label and identify each package with door opening code to match door hardware schedule.

1.07 WARRANTY

- A. Manufacturer's Warranty: Provide warranty against defects in material and workmanship for period indicated. Complete forms in Owner's name and register with manufacturer.
 - 1. Closers: 25 years, minimum.
 - a. Concealed: 5 years, minimum
 - 2. Exit Devices: Three years, minimum.
 - 3. Locksets and Cylinders: Three years, minimum.
 - 4. Other Hardware: Two years, minimum.

PART 2 PRODUCTS

2.01 DOOR HARDWARE – GENERAL

- A. Provide all hardware specified or required to make doors fully functional, compliant with applicable codes and secure to the extent indicated.
- B. Provide all items of a single type of the same model by the same manufacturer.
- C. Provide products that comply with the following:
 - 1. Applicable provisions of Federal, State and local codes.
 - 2. ADA Standards for Accessible Design.
 - ANSI/ICC A117.1, American National Standard for Accessible and Usable Buildings and Facilities.
 - 4. Applicable provisions of NFPA 101, Life Safety Code.
 - 5. All Hardware on Fire-Rated Doors: Listed and classified by UL as suitable for the purpose specified and indicated.
 - Products Requiring Electrical Connection: Listed and classified by UL as suitable for the purpose specified and indicated.
- D. Finishes: All door hardware the same finish unless otherwise indicated.
 - 1. Primary Finish: Satin chrome plated, 626 (approx. US26D).
 - 2. Finish Definitions: BHMA A156.18.
 - 3. Exceptions:
 - a. Where base metal is specified to be different, provide finish that is an appearance equivalent according to BHMA A156.18.

2.02 HINGES AND PIVOTS

- A. Hinges, Pivots and Butts: Provide hinges on every swinging door.
 - 1. Provide five-knuckle full mortise butt hinges unless otherwise indicated.

- 2. Provide ball bearing hinges for in-swinging doors.
- 3. Provide hinges in the quantities indicated.
- 4. Provide non-removable pins on exterior out-swinging doors.
- 5. Provide hinges in the quantities indicated.
- B. Butt Hinges: Comply with BHMA A156.1 and A156.7; standard weight, unless otherwise indicated.
 - 1. Provide hinge width required to clear surrounding trim.
- C. Quantity of Hinges Per Door:
 - 1. Three (3) hinges per leaf to 7 feet, 6-inch height. Add one for each additional 30 inches in height or any fraction.

2.03 LOCKS

- A. Locks: Provide a lock for every door, unless specifically indicated as not requiring locking.
 - 1. Hardware Sets indicate locking functions required for each door.
 - Trim: Provide lever handle or pull trim on outside of all locks unless specifically stated to have no outside trim.
 - 3. Lock Cylinders: Provide key access on outside of all locks unless specifically stated to have no locking or no outside trim.
- B. Lock Cylinders: Manufacturer's full size interchangeable core (FSIC) six (6) pin cylinder.
 - 1. Provide cams and/or tailpieces as required for locking devices required.
- C. Keying: Grand master keyed per Owner's approval. Match Owners Key Schedule.

2.04 CYLINDRICAL LOCKSETS

A. Locking Functions: As defined in BHMA A156.2, and as selected by Owner.

2.05 CLOSERS

- A. Closers: Complying with BHMA A156.4.
 - 1. Provide surface-mounted, door-mounted closers unless otherwise indicated.
 - 2. Provide a door closer on every exterior entry door.
 - 3. Furnish sex nuts and bolts for all doors.
 - 4. Closers shall have a 10-year guarantee.

2.06 STOPS AND HOLDERS

- Stops/Holders: Complying with BHMA A156.8; provide a stop for every swinging door, unless otherwise indicated.
 - 1. Provide wall mounted stops and floor mounted stops where wall mounted is impractical. Where no stop can be installed provide closer with cushion type arm. Anvils to be sufficient length to permit closers to be mounted on the pull side of the door.
 - 2. If wall stops are not practical, due to configuration of room or furnishings, provide overhead stop.
 - 3. Stop is not required if positive stop feature is specified for door closer; positive stop feature of door closer is not an acceptable substitute for a stop unless specifically so stated.

2.07 GASKETING, DOOR BOTTOMS, AND THRESHOLDS

- A. Gaskets: Comply with BHMA A156.22
 - 1. On each exterior door, provide weather-stripping gaskets, unless otherwise indicated; top, sides, and meeting stiles of pairs.
 - 2. Where exterior door is also required to have fire or smoke rating, provide gaskets functioning as both smoke and weather seals.
- B. Door Bottoms:
 - 1. On each exterior door, provide door bottom shoe or sweep, unless otherwise indicated.
- C. Thresholds:
 - 1. At each exterior door, provide door manufacturers standard threshold.
 - 2. Provide threshold elevator at exterior doors as needed.

3. Use Pemko 183_SN for gaps over ¼" between threshold and Fiber Cement trim board or concrete slab.

D. Silencers:

1. Quantity: Furnish three (3) for each single door frame.

2.08 PROTECTION PLATES

- A. Protection Plates: Comply with BHMA A156.6.
- B. Metal Properties: Stainless steelmaterial.
 - 1. Metal, Standard Duty: Thickness 0.050 inch, minimum.
- C. Edges: Beveled, on four sides unless otherwise indicated.
- D. Fasteners: Countersunk screw fasteners.

2.09 KEY REQUIREMENTS

- A. Key Management System: For each keyed lock on project, provide one set of consecutively numbered duplicated key tags with hanging hole and snap catch.
- B. All keyed cylinders shall be subject to the existing Schlage Grand Masterkey system, coordinate with Owner.
- C. Furnish three sets of two (keyed alike) cylinders with construction cores. Following construction supply permanent keyed cores.
- D. Key Quantities
 - 1. Four (4) Keys per lock keyed alike
 - 2. Four (4) Master Keys.
 - 3. Four (4) Control Keys.

2.10 FIRE DEPARTMENT LOCK BOX

- A. Knox Residential Box-
 - 1. Surface Mount Model #1662
 - 2. Coordinate with Local Fire Department for location and series.

2.11 PANIC HARDWARE

- A. As required under hardware schedule
- B. Pair Openings: Furnish two panic devices for paired openings.
- C. Rated Openings: Provide UL Listed Fire Exit Hardware at rated openings
- D. Sizes: Provide Panic Hardware sized in accordance with manufacturer's recommendations

PART 3 EXECUTION

3.01 INSTALLATION

- A. Install hardware in accordance with manufacturer's instructions and applicable codes.
- B. Use templates provided by hardware item manufacturer.
- C. Door Hardware Mounting Heights: Distance from finished floor to center line of hardware item. As indicated in following list; unless noted otherwise in Door Hardware Schedule or on drawings.
- D. Set exterior door thresholds with full-width bead of elastomeric sealant at each point of contact with floor providing a continuous weather seal; anchor thresholds with stainless steel countersunk screws.

3.02 ADJUSTING

- A. Adjust hardware for smooth operation.
- B. Adjust gasketing for complete, continuous seal; replace if unable to make complete seal.

3.03 CLEANING

- A. Clean finished hardware in accordance with manufacturer's written instructions after final adjustments have been made.
- B. Clean adjacent surfaces soiled by hardware installation.

PART 4 HARDWARE SETS

4.01 GENERAL

A. These Hardware Sets indicate requirements for single doors that type with conditional requirements for pairs and other situations.

MANUFACTURER LIST

CODE	<u>NAME</u>
AB	ABH MANUFACTURING INC.
BE	BEST ACCESS SYSTEMS
DM	DORMA DOOR CONTROLS
NA	NATIONAL GUARD
SC	SCHLAGE

ST**BEST HINGES AND SLIDING**

TRIMCO TR VON **VON DUPRIN**

OPTION LIST

CODE DESCRIPTION

B4E-HEAVY-KP

CSK INV

FINISH LIST

CODE	<u>DESCRIPTION</u>
26D	SATIN CHROME
32D	SATIN STAINLESS STEEL
626	SATIN CHROMIUM PLATED
630	SATIN STAINLESS STEEL
689	ALUMINUM PAINTED
AL	ALUMINUM

BLACK BLACK

US32D STAINLESS STEEL, DULL

4.02 HARDWARE SETS

A. SET #01, DOORS: BUILDING ENTRY

3 Hinges	5BB1 4"x4" NRP	652	IVES
1 Keyless Entry Lock	Salvage Existing		
1 Entrance Set	ND80PD	626	SC
1 FISC CORE	23-030	626	SC
1 Lock Guard	LG10	630	IVE
1 Panic Hardware	98-EO	626	VON
1 Closer	ITS 9613 INV	626	DM
1 Overhead Stop	9024	US32D	AB
1 Kick Plate	K0050 8" X2" LDW B4E CSK	630	TR
1 Gasketing	700 NA @ HEAD & JAMBS	AL	PEM
1 Door Shoe	819NA		NA
1 Threshold	BY DOOR MFR	AL	

Jul-12-2023 087100 - 5

	EPPER TREE - ENVELOPE LINE, WASHINGTON		SECTION DOOR HAR	N 087100 RDWARE
В.	SET #02, DOORS: UNIT PATIOS			
Δ.	3 Hinges	5BB1 4"x4" NRP	652	IVES
	1 Passage Set	F10ELA	626	SC
	1 Deadbolt	B660R	626	SC
	1 FSIC Core	23-030 Match existing key bite	626	SC
	1 Wall Bumper	1270WV	630	TR
	1 Gasketing	700 NA@ HEAD & JAMBS		NA
	1 Door Shoe	819 NA		NA
	1 Threshold	BY DOOR MFR	AL	- 11-2
C				
C.	SET #03, DOORS: UNIT STORAG 3 Hinges	5BB1 4"x4" NRP	652	IVES
	1 Passage Set	F10ELA	626	SC
	1 Deadbolt	B660R	626	SC
	1 FSIC Core	23-030 Match Existing key bite	626	SC
	1 Wall Bumper	1270WV	630	TR
	1 Gasketing	700 NA @ HEAD & JAMBS	030	NA
	1 Door Shoe	819 NA		NA NA
	1 Threshold	BY DOOR MFR	AL	INA
			AL	
D.	SET #04, DOORS: ELECTRICAL		(50	IVEC
	3 Hinges	5BB1 4"x4"NRP	652	IVES
	1 Storeroom Lock	AL80RD SAT	626	SC
	1 FSIC Core	23-030 Match existing key bite	626	SC
		LG10	630	IVE
		ITS 9613 INV	626	DM
	1 Overhead Stop	9024	US32D	AB
	1 Rain Drip	346C	AL	PEMKO
	1 Seal	700 NA @ HEAD & JAMBS		NA
	1 Threshold	BY DOOR MFR	AL	
E.	SET #05, DOOR: ELECTRICAL ((DOUBLE)		
	6 Hinges	5BB1 4":x4"" NRP	652	IVES
	1 Semi-Auto Flush bolt	3820 x 3810	626	TR
	1 Storeroom Lockset	AL80RD SAT	626	SC
	1 FSIC Core	23-030 Match existing key bite	626	SC
	1 Coordinator	3094B3	BLACK	TR
	2 Closer	ITS 9613 INV	626	DM
	2 Overhead Stop	9026	US32D	AB
	1 Dust Proof Strike	3910	626	TR
	1 Mounting Bracket	3095/3096 AS REQ'D	BLACK	TR
	1 Gasketing	700 NA @ HEAD & JAMBS		NA
	1 Gasketing	5050 B @ ASTRAGAL		NA
	1 Security Astragal	1390 SP		NA
	2 Door Shoes	819 NA		NA
	1 Threshold	BY DOOR MFR	AL	

Jul-12-2023 087100 - 6

END OF SECTION

1.01 SECTION INCLUDES

1.02 SUBMITTALS

- A. Product Data: Provide data describing design characteristics, maximum recommended air velocity, design free area, materials and finishes.
- B. Shop Drawings: Indicate louver layout plan and elevations, opening and clearance dimensions, and tolerances; head, jamb and sill details; blade configuration, screens, blank-off areas required, and frames.

1.03 WARRANTY

- A. Provide five year manufacturer's warranty against distortion, metal degradation, and connection failures of louver components.
 - 1. Finish: Include twenty year coverage against degradation of exterior finish.

PART 2 PRODUCTS

2.01 MANUFACTURERS

A. Source Limitation: Obtain louvers from a single source from a single manufacturer where indicated to be of the same type, design, and factory-applied color finish.

2.02 PERFORMANCE REQUIREMENTS

- A. Structural Performance: Louvers shall withstand the effects of gravity loads and the following loads and stresses within limits and under conditions indicated without permanent deformation of louver components, noise or metal fatigue caused by louver-blade rattle or flutter, or permanent damage to fasteners and anchors. Wind pressures shall be considered to act normal to the face of the building.
- B. SMACNA Standard: Comply with recommendations in SMACNA's "Architectural Sheet Metal Manual" for fabrication, construction details, and installation procedures.

2.03 FIXED, EXTRUDED-ALUMINUM LOUVERS

- A. A. Vertical, Wind-Driven-Rain-Resistant Louver:
 - 1. Manufacturers: Subject to compliance with requirements, available manufacturers offering products that may be incorporated into the Work include, but are not limited to, the following:
 - a. Louver Depth: 4 inches.
 - b. Frame and Blade Nominal Thickness: Not less than 0.060 inch for blades and 0.080 inch for frames
 - c. c. AMCA Seal: Mark units with AMCA Certified Ratings Seal.

2.04 LOUVER SCREENS

- A. General: Provide screen at each exterior louver:
 - 1. Screen Location for Fixed Louvers: Interior face.
 - 2. Screening Type: Insect screening.
- B. Secure screen frames to louver frames with machine screws with heads finished to match louver, spaced a maximum of 6 inches from each corner and at 12 inches o.c.
- C. Louver Screen Frames: Fabricate with mitered corners to louver sizes indicated.
 - Metal: Same type and form of metal as indicated for louver to which screens are attached.
 - 2. Finish: Same finishes as louver frames to which louver screens are attached.
 - 3. Type: Rewirable frames with a driven spline or insert.
- D. Louver Screening for Aluminum Louvers:
 - 1. Insect Screening: Stainless steel, 18-by-18 mesh, 0.009-inch (0.23-mm) wire.

2.05 BLANK-OFF PANELS

A. Insulated, Blank-Off Panels: Laminated panels consisting of an insulating core surfaced on back and front with metal sheets and attached to back of louver.

Jul-12-2023 089100 - 1

- 1. Thickness: 2 inches.
- 2. Metal Facing Sheets: Aluminum sheet, not less than 0.032-inch nominal thickness.
- 3. Insulating Core: extruded-polystyrene foam.
- 4. Edge Treatment: Trim perimeter edges of blank-off panels with louver manufacturer's standard extruded-aluminum-channel frames, with corners mitered and with same finish as panels.
- 5. Seal perimeter joints between panel faces and louver frames with gaskets or sealant.
- 6. Panel Finish: Same finish applied to louvers.
- 7. Attach blank-off panels with sheet metal screws.
- 8. Locations: All louver locations not part of mechanical ventilation system, or locations noted as blank-off panels.

2.06 MATERIALS

- A. Aluminum Extrusions: ASTM B 221 (ASTM B 221M), Alloy 6063-T5, T-52, or T6.
- B. Aluminum Sheet: ASTM B 209 (ASTM B 209M), Alloy 3003 or 5005 with temper as required for forming, or as otherwise recommended by metal producer for required finish.
- C. Fasteners: Use types and sizes to suit unit installation conditions.
 - 1. For color-finished louvers, use fasteners with heads that match color of louvers.

2.07 FABRICATION

- A. Factory assemble louvers to minimize field splicing and assembly. Disassemble units as necessary for shipping and handling limitations. Clearly mark units for reassembly and coordinated installation.
- B. Maintain equal louver blade spacing, including separation between blades and frames at head and sill, to produce uniform appearance.
- C. Fabricate frames, including integral sills, to fit in openings of sizes indicated, with allowances made for fabrication and installation tolerances, adjoining material tolerances, and perimeter sealant joints.
 - 1. Frame Type: Channel unless otherwise indicated.
- D. Include supports, anchorages, and accessories required for complete assembly.
- E. Provide vertical mullions of type and at spacing's indicated, but not more than is recommended by manufacturer, or 72 inches o.c., whichever is less.
 - 1. Fully Recessed Mullions: Where indicated, provide mullions fully recessed behind louver blades. Where length of louver exceeds fabrication and handling limitations, fabricate with close-fitting blade splices designed to permit expansion and contraction.
 - Exterior Corners: Prefabricated corner units with mitered and with fully recessed mullions at corners.
- F. Provide subsills made of same material as louvers or extended sills for recessed louvers.
- G. Join frame members to each other and to fixed louver blades with fillet welds concealed from view unless otherwise indicated or size of louver assembly makes bolted connections between frame members necessary.

2.08 ALUMINUM FINISHES

- A. A. Finish louvers after assembly.
- B. Color Anodic Finish: AAMA 611, AA-M12C22A42/A44, Class I, 0.018 mm or thicker.
 - 1. Colors: To match adjacent, non-louver material finish per Drawings.

PART 3 EXECUTION

3.01 INSTALLATION

- A. Install louver assembly in accordance with manufacturer's instructions.
- B. Install louvers level and plumb.
- C. Set sill members and sill flashing in continuous bead of sealant.
- D. Alignlouver assembly to ensure moisture shed from flashings and diversion of moisture to exterior.

Jul-12-2023 089100 - 2

- E. Secure louver frames in openings with concealed fasteners.
- F. Coordinate with installation of mechanical ductwork.

END OF SECTION

Jul-12-2023 089100 - 3

1.01 SECTION INCLUDES

- A. Gypsum wallboard repairs necessary to repair damage on the interior of the unit that occurs during the removal and installation of windows and doors.
- B. Joint treatment and accessories.

1.02 REFERENCE STANDARDS

- A. ASTM C475/C475M Standard Specification for Joint Compound and Joint Tape for Finishing Gypsum Board 2017 (Reapproved 2022).
- B. ASTM C514 Standard Specification for Nails for the Application of Gypsum Board 2004 (Reapproved 2020).
- C. ASTM C840 Standard Specification for Application and Finishing of Gypsum Board 2020.
- D. ASTM C1047 Standard Specification for Accessories for Gypsum Wallboard and Gypsum Veneer Base 2019.
- E. ASTM C1177/C1177M Standard Specification for Glass Mat Gypsum Substrate for Use as Sheathing 2017.
- F. ASTM C1280 Standard Specification for Application of Exterior Gypsum Panel Products for Use as Sheathing 2018.
- G. ASTM C1396/C1396M Standard Specification for Gypsum Board 2017.
- H. GA-216 Application and Finishing of Gypsum Panel Products 2021.

1.03 SUBMITTALS

- A. Product Data:
 - 1. Provide data on gypsum board, accessories, and joint finishing system.

1.04 QUALITY ASSURANCE

- A. Gypsum panel products shall be manufactured in the USA and shall carry a certification stamp on the product.
- B. Installer Qualifications: Company specializing in performing work of the type specified and with at least three years of documented experience.

1.05 DELIVERY, STORAGE, AND HANDLING

A. Store gypsum products and accessories indoors and keep above freezing. Elevate boards above floor, on nonwicking supports, in accordance with manufacturer's recommendations.

PART 2 PRODUCTS

2.01 GYPSUM BOARD ASSEMBLIES

A. Provide completed assemblies complying with ASTM C840 and GA-216.

2.02 BOARD MATERIALS

- A. Manufacturers Gypsum-Based Board:
 - 1. CertainTeed Corporation: www.certainteed.com/#sle.
 - 2. Georgia-Pacific Gypsum: www.gpgypsum.com/#sle.
 - 3. USG Corporation: www.usg.com/#sle.
 - 4. Or approved equal.
- B. Gypsum Wallboard: Paper-faced gypsum panels as defined in ASTM C1396/C1396M; sizes to minimize joints in place; ends square cut.
 - 1. Application: Use for patch and repair of interior surfaces, unless otherwise indicated.
 - 2. Replace/repair interior window wrap.
 - 3. Thickness: Match existing.

Jul-12-2023 092116 - 1

2.03 GYPSUM BOARD ACCESSORIES

- A. Beads, Joint Accessories, and Other Trim: ASTM C1047, rigid plastic, galvanized steel, or rolled zinc, unless noted otherwise.
- B. Joint Materials: ASTM C475/C475M and as recommended by gypsum board manufacturer for project conditions.
- C. Nails for Attachment to Wood Members: ASTM C514.

PART 3 EXECUTION

3.01 EXAMINATION

A. Verify that project conditions are appropriate for work of this section to commence.

3.02 BOARD INSTALLATION

- A. Comply with ASTM C840, GA-216, and manufacturer's instructions. Install to minimize butt end joints, especially in highly visible locations.
- B. Single-Layer Nonrated: Install gypsum board in most economical direction, with ends and edges occurring over firm bearing.

3.03 INSTALLATION OF TRIM AND ACCESSORIES

- A. Control Joints: Place control joints consistent with lines of building spaces and as indicated.
 - 1. Not more than 30 feetapart on walls over 50 feetlong.
- B. Corner Beads: Install at external corners, using longest practical lengths.

3.04 JOINT TREATMENT

- A. Paper Faced Gypsum Board: Use paper joint tape, embed with drying type joint compound and finish with drying type joint compound.
- B. Finish gypsum board in accordance with levels defined in ASTM C840, as follows:
 - 1. Level 4: Walls and ceilings to receive paint finish or wall coverings, unless otherwise indicated.
- Tape, fill, and sand exposed joints, edges, and corners to produce smooth surface ready to receive finishes.
 - 1. Feather coats of joint compound so that camber is maximum 1/32 inch.

3.05 TOLERANCES

A. Maximum Variation of Finished Gypsum Board Surface from True Flatness: 1/8 inch in 10 feet in any direction.

3.06 CLEANING

A. Clean soiled surfaces with cleaning solution.

3.07 PROTECTION

- A. Protect installed gypsum board assemblies from subsequent construction operations.
- B. Touch-up, repair, or replace damaged products, materials, and connections prior to Substantial Completion.

END OF SECTION

Jul-12-2023 092116 - 2

1.01 SECTION INCLUDES

A. Fluid-applied deck coating and floor preparation at exterior balconies.

1.02 REFERENCE STANDARDS

- A. ASTM D570 Standard Test Method for Water Absorption of Plastics 2022.
- B. ASTM D4060 Standard Test Method for Abrasion Resistance of Organic Coatings by the Taber Abraser 2019.
- C. ASTM F710 Standard Practice for Preparing Concrete Floors to Receive Resilient Flooring 2022.
- D. ASTM F1869 Standard Test Method for Measuring Moisture Vapor Emission Rate of Concrete Subfloor Using Anhydrous Calcium Chloride 2022.
- E. ASTM F2170 Standard Test Method for Determining Relative Humidity in Concrete Floor Slabs Using in situ Probes 2019a.
- F. ICRI 310.2R Selecting and Specifying Concrete Surface Preparation for Sealers, Coatings, Polymer Overlays, and Concrete Repair 2013.

1.03 SUBMITTALS

- A. Product Data: Provide data on specified products, describing physical and performance characteristics; sizes, patterns and colors available.
- B. Samples: Submit two samples, 6 by 6 inches in size illustrating color and pattern for each floor material for each color specified.
- C. Concrete Subfloor Test Report: Submit a copy of the moisture and alkalinity (pH) test reports.
- D. Manufacturer's Installation Instructions: Indicate special procedures, perimeter conditions requiring special attention, and application rate for each coat.
- E. Maintenance Data: Include maintenance procedures, recommended maintenance materials, procedures for stain removal, repairing surface, and suggested schedule for cleaning.

1.04 OUALITY ASSURANCE

- A. Manufacturer Qualifications: Company specializing in manufacturing products specified in this section with minimum 5 years documented experience.
- B. Applicator Qualifications: Company specializing in performing the work of this section.
 - 1. Minimum 3 years of documented experience.

1.05 MOCK-UPS

- A. Construct mock-up(s) of fluid applied flooring to serve as basis for evaluation of texture and workmanship.
 - 1. Number of Mock-Ups to be Prepared: One.
 - 2. Use same materials and methods for use in the work.
 - 3. Locate where directed.
 - 4. Minimum Size: 48 inches by 48 inches.
- B. Obtain approval of mock-up by Owner before proceeding with work.
- C. Approved mock-up may remain as part of the work.

1.06 DELIVERY, STORAGE, AND HANDLING

- A. Store resin materials in a dry, secure area.
- B. Store materials for three days prior to installation in area of installation to achieve temperature stability.

1.07 FIELD CONDITIONS

- A. Maintain minimum temperature in storage area of 55 degrees F.
- B. Store materials in area of installation for minimum period of 24 hours prior to installation.

Jul-12-2023 096700 - 1

C. Maintain ambient temperature required by manufacturer 72 hours prior to, during, and 24 hours after installation of materials.

PART 2 PRODUCTS

2.01 FLUID-APPLIED FLOORING SYSTEMS

- A. Deck Liner: Two-component, rapid curing, elastomeric polyurea lining system
 - 1. System Thickness: 80 mils (0.80 inches) minimum.
 - 2. Hardness: 50+/-5 when tested in accordance with ASTM D2240.
 - 3. Tensile Strength: 2800-3200 psi when tested in accordance with ASTM D412.
 - 4. Compressive Strength: 800 psi when tested in accordance with ASTM D695.
 - Water Absorption: Less than or equal to 1 percent when tested in accordance with ASTM D570 for 24 hours.
 - Abrasion Resistance: Maximum weight loss of 10-15 mg/1000 cycles when tested in accordance with ASTM D4060.
 - 7. Color: Selected by Owner from manufacturer's standard line.
 - 8. Products:
 - a. Rhino Linings Corporation; Rhino Extreme 11-50 GT Iso, Part #60062-1 and 11-50 GT Resin, Part #60067-1: www.rhinolinings.com/#sle.
 - b. Or approved equal.
 - c. Color selected by Owner from manufacturer's standard line.

2.02 ACCESSORIES

- A. All items incorporated into this system shall be compatible with and approved by the coating manufacturer.
- B. Primer and Cleaner: Type recommended by fluid-applied flooring manufacturer.

PART 3 EXECUTION

3.01 EXAMINATION

- A. Verify that subfloor surfaces are smooth and flat within the tolerances specified for that type of work and are ready to receive flooring.
- B. Verify that wall surfaces are smooth and flat within the tolerances specified for that type of work, are dust-free, and are ready to receive flooring.
- C. Verify that subfloor surfaces are dust-free and free of substances that could impair bonding of materials to subfloor surfaces.
- D. Cementitious Subfloor Surfaces: Verify that substrates are ready for fluid-applied flooring installation by testing for moisture and alkalinity (pH).
 - 1. Test as Follows:
 - a. Alkalinity (pH): ASTM F710.
 - b. Internal Relative Humidity: ASTM F2170.
 - c. Moisture Vapor Emission: ASTM F1869.

3.02 PREPARATION

- A. Remove subfloor ridges and bumps, including any adhesive or existing flooring material. Fill low spots, cracks, joints, holes, and other defects with subfloor filler.
- B. Prepare concrete surfaces according to ICRI 310.2R.
- C. Apply, trowel, and float filler to achieve smooth, flat, hard surface. Grind irregularities above the surface level. Prohibit traffic until filler is cured.
- D. Vacuum clean substrate.
- E. Apply primer to surfaces required by flooring manufacturer.

Jul-12-2023 096700 - 2

SECTION 096700 FLUID-APPLIED COATING

3.03 INSTALLATION - ACCESSORIES

- A. Seal joints with bond breaker and acceptable sealant in accordance with manufacturer.
- B. Install cant strips at base of walls where flooring is to be extended up wall as base.

3.04 INSTALLATION - FLOORING

- A. Apply in accordance with manufacturer's instructions.
- B. Apply each coat to minimum thickness required by manufacturer.
- C. Finish to smooth level surface.
- D. Cove at vertical surfaces.
- E. Extend into door openings and into storage units as indicated in drawings.
- F. Slope to drain.
- G. Install in a weather tight manner.

3.05 PROTECTION

A. Barricade area to protect flooring until fully cured.

END OF SECTION

Jul-12-2023 096700 - 3

1.01 SECTION INCLUDES

- A. Surface preparation.
- B. Field application of paints.
- Scope: Finish exterior surfaces exposed to view, unless fully factory-finished and unless otherwise indicated.
- D. Do Not Paint or Finish the Following Items:
 - 1. Items factory-finished unless otherwise indicated; materials and products having factory-applied primers are not considered factory finished.
 - 2. Items indicated to receive other finishes.
 - 3. Items indicated to remain unfinished.
 - 4. Fire rating labels, equipment serial number and capacity labels, and operating parts of equipment.
 - 5. Non-metallic roofing and flashing.
 - 6. Stainless steel, anodized aluminum, bronze, terne-coated stainless steel, zinc, and lead.
 - 7. Floors, unless specifically indicated.
 - 8. Glass.

1.02 REFERENCE STANDARDS

- A. 40 CFR 59, Subpart D National Volatile Organic Compound Emission Standards for Architectural Coatings; U.S. Environmental Protection Agency current edition.
- B. ASTM D4442 Standard Test Methods for Direct Moisture Content Measurement of Wood and Wood-Based Materials 2020.
- C. MPI (APL) Master Painters Institute Approved Products List; Master Painters and Decorators Association Current Edition.
- D. MPI (APSM) Master Painters Institute Architectural Painting Specification Manual Current Edition.
- E. SSPC V1 (PM1) Good Painting Practice: Painting Manual Volume 1 2016.
- F. SSPC-SP 1 Solvent Cleaning 2015, with Editorial Revision (2016).
- G. SSPC-SP 2 Hand Tool Cleaning 2018.
- H. SSPC-SP 6 Commercial Blast Cleaning 2007.

1.03 SUBMITTALS

- A. Product Data: Provide complete list of products to be used, with the following information for each:
 - 1. Manufacturer's name, product name and/or catalog number, and general product category (e.g. "alkyd enamel").
 - 2. MPI product number (e.g. MPI #47).
 - 3. Cross-reference to specified paint system(s) product is to be used in; include description of each system.
 - 4. Manufacturer's installation instructions.
- B. Samples: Submit three paper "draw down" samples, 8-1/2 by 11 inches in size, illustrating range of colors available for each finishing product specified.
 - 1. Where sheen is specified, submit samples in only that sheen.
- C. Maintenance Data: Submit data including finish schedule showing where each product/color/finish was used, product technical data sheets, material safety data sheets (MSDS), care and cleaning instructions, touch-up procedures, repair of painted and finished surfaces, and color samples of each color and finish used.
- D. Maintenance Materials: Furnish the following for Owner's use in maintenance of project.
 - Extra Paint and Finish Materials: 1 gallon of each color; from the same product run, store where directed.
 - 2. Label each container with color in addition to the manufacturer's label.

1.04 QUALITY ASSURANCE

A. Applicator Qualifications: Company specializing in performing the type of work specified with minimum 3 years experience and approved by manufacturer.

1.05 MOCK-UPS

- A. Provide panel, 8 feet long by 8 feet wide, illustrating paint color, texture, and finish.
- B. Locate where directed by Owner.
- C. Mock-up may remain as part of the work.

1.06 DELIVERY, STORAGE, AND HANDLING

- A. Deliver products to site in sealed and labeled containers; inspect to verify acceptability.
- B. Container Label: Include manufacturer's name, type of paint, brand name, lot number, brand code, coverage, surface preparation, drying time, cleanup requirements, color designation, and instructions for mixing and reducing.
- C. Paint Materials: Store at minimum ambient temperature of 45 degrees F and a maximum of 90 degrees F, in ventilated area, and as required by manufacturer's instructions.

1.07 FIELD CONDITIONS

- A. Do not apply materials when surface and ambient temperatures are outside the paint product manufacturer's temperature ranges.
- B. Follow manufacturer's recommended procedures for producing best results, including testing of substrates, moisture in substrates, and humidity and temperature limitations.
- C. Do not apply exterior paint and finishes during rain or snow, or when relative humidity is outside the humidity ranges required by the paint product manufacturer.
- D. Minimum Application Temperatures for Latex Paints: 50 degrees F for exterior; unless required otherwise by manufacturer's instructions.
- E. Provide lighting level of 80 ft candles measured mid-height at substrate surface.

PART 2 PRODUCTS

2.01 MANUFACTURERS

- A. Provide paints and finishes used in any individual system from the same manufacturer; no exceptions.
- B. Paints:
 - 1. Behr Process Corporation: www.behr.com/#sle.
 - 2. Rodda Paint Company: www.roddapaint.com/#sle.
 - 3. Sherwin-Williams Company: www.sherwin-williams.com/#sle.
- C. Primer Sealers: Same manufacturer as top coats.

2.02 PAINTS AND FINISHES - GENERAL

- A. Paints and Finishes: Ready-mixed, unless required to be a field-catalyzed paint.
 - Where MPI paint numbers are specified, provide products listed in Master Painters Institute
 Approved Product List, current edition available at www.paintinfo.com, for specified MPI
 categories, except as otherwise indicated.
 - 2. Provide paints and finishes of a soft paste consistency, capable of being readily and uniformly dispersed to a homogeneous coating, with good flow and brushing properties, and capable of drying or curing free of streaks or sags.
 - 3. Provide materials that are compatible with one another and the substrates indicated under conditions of service and application, as demonstrated by manufacturer based on testing and field experience.
 - 4. Supply each paint material in quantity required to complete entire project's work from a single production run.

5. Do not reduce, thin, or dilute paint or finishes or add materials unless such procedure is described explicitly in manufacturer's product instructions.

2.03 PAINT SYSTEMS - EXTERIOR

- A. Exterior Surfaces to be Painted, Unless Otherwise Indicated: Including fiber cement siding, primed wood, primed metal, and fiber cement trim.
 - 1. Two top coats and one coat primer.
 - 2. Top Coat(s): Exterior Latex; MPI #10, 11, 15, 119, or 214.
 - 3. Top Coat Sheen:
 - a. Eggshell: MPI gloss level 3; use this sheen at siding and trim...
 - b. Semi-Gloss: MPI gloss level 5; use this sheen at doors.

2.04 PRIMERS

- A. Primers: Provide the following unless other primer is required or recommended by manufacturer of top
 - 1. Latex Primer for Exterior Wood and cut ends; MPI #6.

2.05 ACCESSORY MATERIALS

- A. Accessory Materials: Provide primers, sealers, cleaning agents, cleaning cloths, sanding materials, and clean-up materials as required for final completion of painted surfaces.
- B. Patching Material: Latex filler.
- C. Fastener Head Cover Material: Latex filler.

PART 3 EXECUTION

3.01 EXAMINATION

- A. Verify that surfaces are ready to receive work as instructed by the product manufacturer.
- B. Examine surfaces scheduled to be finished prior to commencement of work. Report any condition that may potentially effect proper application.
- C. Test shop-applied primer for compatibility with subsequent cover materials.
- D. Measure moisture content of surfaces using an electronic moisture meter. Do not apply finishes unless moisture content of surfaces are below the following maximums:
 - 1. Fiber Cement Siding: 12 percent.
 - 2. Exterior Wood: 15 percent, measured in accordance with ASTM D4442.

3.02 PREPARATION

- A. Clean surfaces thoroughly and correct defects prior to application.
- B. Prepare surfaces using the methods recommended by the manufacturer for achieving the best result for the substrate under the project conditions.
- C. Remove or repair existing paints or finishes that exhibit surface defects.
- D. Remove or mask surface appurtenances, including electrical plates, hardware, light fixture trim, escutcheons, and fittings, prior to preparing surfaces for finishing.
- E. Seal surfaces that might cause bleed through or staining of topcoat.
- F. Remove mildew from impervious surfaces by scrubbing with solution of tetra-sodium phosphate and bleach. Rinse with clean water and allow surface to dry.
- G. Fiber Cement Siding: Remove dirt, dust and other foreign matter with a stiff fiber brush. Do not coat surfaces if moisture content or alkalinity of surfaces to be coated exceeds that permitted in manufacturer's written instructions.
- H. Galvanized Surfaces:
 - 1. Remove surface contamination and oils and wash with solvent according to SSPC-SP 1.
 - 2. Prepare surface according to SSPC-SP 2.

I. Ferrous Metal:

- 1. Solvent clean according to SSPC-SP 1.
- 2. Shop-Primed Surfaces: Sand and scrape to remove loose primer and rust. Feather edges to make touch-up patches inconspicuous. Clean surfaces with solvent. Prime bare steel surfaces.
- 3. Remove rust, loose mill scale, and other foreign substances using methods recommended in writing by paint manufacturer and blast cleaning according to SSPC-SP 6 Commercial Blast Cleaning. Protect from corrosion until coated.
- J. Exterior Wood Surfaces to Receive Opaque Finish: Remove dust, grit, and foreign matter. Seal knots, pitch streaks, and sappy sections. Fill nail holes with tinted exterior calking compound after prime coat has been applied. Back prime concealed surfaces before installation.
- K. Fiberglass Doors to be Painted: Prime door top and bottom edge surfaces.
- L. Exterior metal handrails located at east and west building entrance and along west sidewalk will be prepped, primed and painted.

3.03 APPLICATION

- A. Remove unfinished louvers, grilles, covers, and access panels on mechanical and electrical components and paint separately.
- B. Exterior Wood to Receive Opaque Finish: If final painting must be delayed more than 2 weeks after installation of woodwork, apply primer within 2 weeks and final coating within 4 weeks.
- C. Apply products in accordance with manufacturer's written instructions and recommendations in "MPI Architectural Painting Specification Manual".
- D. Where adjacent sealant is to be painted, do not apply finish coats until sealant is applied.
- E. Do not apply finishes to surfaces that are not dry. Allow applied coats to dry before next coat is applied.
- F. Apply each coat to uniform appearance.
- G. Sand wood and metal surfaces lightly between coats to achieve required finish.
- H. Vacuum clean surfaces of loose particles. Use tack cloth to remove dust and particles just prior to applying next coat.
- I. Reinstall electrical cover plates, hardware, light fixture trim, escutcheons, and fittings removed prior to finishing.

3.04 PROTECTION

- A. Protect finishes until completion of project.
- B. Touch-up damaged finishes after Substantial Completion.

3.05 COLOR COATING SCHEDULES

- A. Schedule: Refer to Finish Schedule on Drawings for colors and locations.
 - 1. PNT-1: Benjamin Moore Newburyport Blue HC-155.
 - 2. PNT-2: Benjaming Moore Normandy 2129-40.
 - 3. PNT-3: Benjamin Moore Adirondack Green 453.
 - 4. PNT-4: Benjamin Moore Dalila 319.
 - 5. PNT-5: Benjamin Moore BM Calm OC-22

END OF SECTION

1.01 SECTION INCLUDES

- A. Surface preparation.
- B. Field application of paints.
- Scope: Finish interior surfaces exposed to view, unless fully factory-finished and unless otherwise indicated.
- D. Do Not Paint or Finish the Following Items:
 - 1. Items factory-finished unless otherwise indicated; materials and products having factory-applied primers are not considered factory finished.
 - 2. Items indicated to receive other finishes.
 - 3. Items indicated to remain unfinished.
 - 4. Fire rating labels, equipment serial number and capacity labels, bar code labels, and operating parts of equipment.
 - 5. Stainless steel, anodized aluminum, bronze, terne-coated stainless steel, and lead items.
 - 6. Floors, unless specifically indicated.
 - 7. Glass
 - Concealed pipes, ducts, and conduits.

1.02 REFERENCE STANDARDS

- A. 40 CFR 59, Subpart D National Volatile Organic Compound Emission Standards for Architectural Coatings; U.S. Environmental Protection Agency current edition.
- B. ASTM D4442 Standard Test Methods for Direct Moisture Content Measurement of Wood and Wood-Based Materials 2020.
- C. MPI (APL) Master Painters Institute Approved Products List; Master Painters and Decorators Association Current Edition.
- D. MPI (APSM) Master Painters Institute Architectural Painting Specification Manual Current Edition.
- E. SCAQMD 1113 Architectural Coatings 1977, with Amendment (2016).
- F. SSPC V1 (PM1) Good Painting Practice: Painting Manual Volume 1 2016.
- G. SSPC-SP 1 Solvent Cleaning 2015, with Editorial Revision (2016).
- H. SSPC-SP 6 Commercial Blast Cleaning 2007.

1.03 SUBMITTALS

- A. Product Data: Provide complete list of products to be used, with the following information for each:
 - 1. Manufacturer's name, product name and/or catalog number, and general product category (e.g., "alkyd enamel").
 - 2. MPI product number (e.g., MPI #47).
 - Cross-reference to specified paint system products to be used in project; include description of each system.
 - 4. Manufacturer's installation instructions.
- B. Samples: Submit three paper "draw down" samples, 8-1/2 by 11 inches in size, illustrating range of colors available for each finishing product specified.
 - 1. Where sheen is specified, submit samples in only that sheen.
- C. Manufacturer's Instructions: Indicate special surface preparation procedures.
- D. Maintenance Data: Submit data including finish schedule showing where each product/color/finish was used, product technical data sheets, material safety data sheets (MSDS), care and cleaning instructions, touch-up procedures, repair of painted and finished surfaces, and color samples of each color and finish used
- E. Maintenance Materials: Furnish the following for Owner's use in maintenance of project.

- Extra Paint and Finish Materials: 1 gal of each color; from the same product run, store where directed.
- 2. Label each container with color in addition to the manufacturer's label.

1.04 QUALITY ASSURANCE

A. Applicator Qualifications: Company specializing in performing the type of work specified with minimum 3 years experience and approved by manufacturer.

1.05 DELIVERY, STORAGE, AND HANDLING

- A. Deliver products to site in sealed and labeled containers; inspect to verify acceptability.
- B. Container Label: Include manufacturer's name, type of paint, brand name, lot number, brand code, coverage, surface preparation, drying time, cleanup requirements, color designation, and instructions for mixing and reducing.
- C. Paint Materials: Store at minimum ambient temperature of 45 degrees F and a maximum of 90 degrees F, in ventilated area, and as required by manufacturer's instructions.

1.06 FIELD CONDITIONS

- A. Do not apply materials when surface and ambient temperatures are outside the temperature ranges required by the paint product manufacturer.
- B. Follow manufacturer's recommended procedures for producing best results, including testing of substrates, moisture in substrates, and humidity and temperature limitations.
- C. Do not apply materials when relative humidity exceeds 85 percent, at temperatures less than 5 degrees F above the dew point, or to damp or wet surfaces.
- D. Minimum Application Temperatures for Paints: 50 degrees F for interiors unless required otherwise by manufacturer's instructions.
- E. Provide lighting level of 80 fc measured mid-height at substrate surface.

PART 2 PRODUCTS

2.01 MANUFACTURERS

- A. Provide paints and finishes used in any individual system from the same manufacturer; no exceptions.
- B. Paints:
 - 1. Behr Process Corporation: www.behr.com/#sle.
 - 2. Rodda Paint Co: www.roddapaint.com/#sle.
 - 3. Sherwin-Williams Company: www.sherwin-williams.com/#sle.
 - 4. Benjamin Moore & Co.: www.benjaminmoore.com/#sle.
- C. Primer Sealers: Same manufacturer as top coats.

2.02 PAINTS AND FINISHES - GENERAL

- A. Paints and Finishes: Ready-mixed, unless intended to be a field-catalyzed paint.
 - 1. Where MPI paint numbers are specified, provide products listed in Master Painters Institute Approved Product List, current edition available at www.paintinfo.com, for specified MPI categories, except as otherwise indicated.
 - Provide paints and finishes of a soft paste consistency, capable of being readily and uniformly
 dispersed to a homogeneous coating, with good flow and brushing properties, and capable of
 drying or curing free of streaks or sags.
 - 3. Provide materials that are compatible with one another and the substrates indicated under conditions of service and application, as demonstrated by manufacturer based on testing and field experience.
 - 4. Supply each paint material in quantity required to complete entire project's work from a single production run.
 - 5. Do not reduce, thin, or dilute paint or finishes or add materials unless such procedure is specifically described in manufacturer's product instructions.

- B. Volatile Organic Compound (VOC) Content:
 - 1. Provide paints and finishes that comply with the most stringent requirements specified in the following:
 - a. 40 CFR 59, Subpart D--National Volatile Organic Compound Emission Standards for Architectural Coatings.
 - b. Ozone Transport Commission (OTC) Model Rule, Architectural, Industrial, and Maintenance Coatings; www.otcair.org; specifically:
 - 1) Opaque, Flat: 50 g/L, maximum.
 - 2) Opaque, Nonflat: 150 g/L, maximum.
 - 3) Opaque, High Gloss: 250 g/L, maximum.
 - 2. Determination of VOC Content: Testing and calculation in accordance with 40 CFR 59, Subpart D (EPA Method 24), exclusive of colorants added to a tint base and water added at project site; or other method acceptable to authorities having jurisdiction.

2.03 PAINT SYSTEMS - INTERIOR

- A. Interior Surfaces to be Painted, Unless Otherwise Indicated: Including gypsum board and wood.
 - 1. Two top coats and one coat primer.
 - 2. Top Coat(s): High Performance Architectural Interior Latex; MPI #138, 139, 140, 141, or 142.
 - 3. Top Coat Sheen:
 - a. Eggshell: MPI gloss level 3; use this sheen at all locations unless noted otherwise.
 - b. Satin: MPI gloss level 4; use this sheen for items subject to frequent touching by occupants, including door frames and railings.
- B. Medium Duty Door/Trim: For surfaces subject to frequent contact by occupants, including metals and wood:
 - 1. Two top coats and one coat primer.
 - 2. Top Coat(s): Interior Epoxy-Modified Latex; MPI #115 or 215.

2.04 PRIMERS

- A. Primers: Provide the following unless other primer is required or recommended by manufacturer of top
 - 1. Interior Latex Primer Sealer; MPI #50.
 - 2. Interior Drywall Primer Sealer.
 - 3. Latex Primer for Interior Wood; MPI #39.

2.05 ACCESSORY MATERIALS

- A. Accessory Materials: Provide primers, sealers, cleaning agents, cleaning cloths, sanding materials, and clean-up materials as required for final completion of painted surfaces.
- B. Patching Material: Latex filler.
- C. Fastener Head Cover Material: Latex filler.

PART 3 EXECUTION

3.01 EXAMINATION

- A. Verify that surfaces are ready to receive work as instructed by the product manufacturer.
- B. Examine surfaces scheduled to be finished prior to commencement of work. Report any condition that may potentially affect proper application.
- C. Test shop-applied primer for compatibility with subsequent cover materials.
- D. Measure moisture content of surfaces using an electronic moisture meter. Do not apply finishes unless moisture content of surfaces is below the following maximums:
 - 1. Gypsum Wallboard: 12 percent.
 - 2. Interior Wood: 15 percent, measured in accordance with ASTM D4442.

3.02 PREPARATION

- A. Clean surfaces thoroughly and correct defects prior to application.
- B. Prepare surfaces using the methods recommended by the manufacturer for achieving the best result for the substrate under the project conditions.
- C. Remove or repair existing paints or finishes that exhibit surface defects.
- D. Remove or mask surface appurtenances, including electrical plates, hardware, light fixture trim, escutcheons, and fittings, prior to preparing surfaces or finishing.
- E. Seal surfaces that might cause bleed through or staining of topcoat.
- F. Gypsum Board: Fill minor defects with filler compound. Spot prime defects after repair.
- G. Ferrous Metal:
 - 1. Solvent clean according to SSPC-SP 1.
 - 2. Shop-Primed Surfaces: Sand and scrape to remove loose primer and rust. Feather edges to make touch-up patches inconspicuous. Clean surfaces with solvent. Prime bare steel surfaces. Re-prime entire shop-primed item.
 - 3. Remove rust, loose mill scale, and other foreign substances using methods recommended in writing by paint manufacturer and blast cleaning according to SSPC-SP 6 Commercial Blast Cleaning. Protect from corrosion until coated.
- H. Wood Surfaces to Receive Opaque Finish: Wipe off dust and grit prior to priming. Seal knots, pitch streaks, and sappy sections with sealer. Fill nail holes and cracks after primer has dried; sand between coats. Back prime concealed surfaces before installation.
- I. Metal Doors to be painted: Prime metal door top and bottom edge surfaces.

3.03 APPLICATION

- A. Apply products in accordance with manufacturer's written instructions and recommendations in "MPI Architectural Painting Specification Manual".
- B. Where adjacent sealant is to be painted, do not apply finish coats until sealant is applied.
- C. Do not apply finishes to surfaces that are not dry. Allow applied coats to dry before next coat is applied.
- D. Apply each coat to uniform appearance in thicknesses specified by manufacturer...
- E. Sand surfaces lightly between coats to achieve required finish.
- F. Vacuum clean surfaces of loose particles. Use tack cloth to remove dust and particles just prior to applying next coat.
- G. Reinstall electrical cover plates, hardware, light fixture trim, escutcheons, and fittings removed prior to finishing.

3.04 PROTECTION

- A. Protect finishes until completion of project.
- B. Touch-up damaged finishes after Substantial Completion.

3.05 COLOR COATING SCHEDULE

- A. Schedule: Refer to Finish Schedule on Drawings for colors and locations.
 - 1. Field Paint. Benjamin Moore White Dove OC-17.
 - 2. Door and Window Frames. Benjamin Moore White Dove OC-17.

END OF SECTION

1.01 SECTION INCLUDES

- A. Horizontal slat louver blinds at windows.
- B. Vertical louver blinds at sliding patio doors.
- C. Operating hardware.

1.02 REFERENCE STANDARDS

A. WCMA A100.1 - Standard for Safety of Window Covering Products 2022.

1.03 SUBMITTALS

- A. See Section 013000 Administrative Requirements, for submittal procedures.
- B. Product Data: Provide data indicating physical and dimensional characteristics.
- C. Samples: Submit two samples, 6 inch long illustrating slat materials and finish, cord type and color.
- D. Manufacturer's Installation Instructions: Indicate special procedures.

1.04 QUALITY ASSURANCE

A. Field verify opening sizes, method of attachment, operation, and interface with adjacent construction, tolerances, and clearances required for installation prior to fabrication.

1.05 WARRANTY

A. Provide Manufacturer standard lifetime warranty.

PART 2 PRODUCTS

2.01 MANUFACTURERS

- A. Louver Blinds Without Side Guides:
 - 1. Hunter Douglas Architectural; www.hunterdouglasarchitectural.com/#sle.
 - 2. Levolor; www.commercial.levolor.com/#sle.
 - 3. Graber; Aluminum Blinds: www.graberblinds.com/#sle..
 - 4. Or accepted equal.

2.02 HORIZONTAL LOUVER BLINDS

- A. Description: Horizontal slat louvers hung from full-width headrail with full-width bottom rail.
- B. Manual Operation: Control of raising and lowering by cord with full range locking; blade angle adjustable by control wand.
- C. Plastic Slats: Polymer composite, radiused slat corners.
 - 1. Width: 2 inch.
 - 2. Color: White.
 - Texture: Smooth.
- D. Slat Support: Woven polypropylene cord, ladder configuration.
- E. Head Rail: Pre-finished, formed aluminum box, with end caps; internally fitted with hardware, pulleys, and bearings for operation; same depth as width of slats.
- F. Lift Cord: Braided nylon; continuous loop; complying with WCMA A100.1.
- G. Control Wand: Extruded hollow plastic; hexagonal shape.
- H. Headrail Attachment: Wall brackets.
- I. Accessory Hardware: Type recommended by blind manufacturer.

2.03 VERTICAL LOUVER BLINDS

A. Description: Horizontal travel, vertical vane louver units complete with tracks, pivot and traversing mechanisms, and accessories, as follows:

Jun-30-2023 122116 - 1

- B. Manual operation.
- C. PVC Vanes: Integrally colored, extruded PVC; flat, 3-1/2 inches wide.
 - 1. Color: White.
 - 2. Texture: Smooth.
 - 3. Not less than 3/8 inch overlap when vanes are rotated fully closed.
 - 4. Weighted at bottom. Chains not accepted.
 - 5. Fire-resistant, conforming to NFPA 701.
- D. Tracks: Cannel tracks for type of operation, extruded aluminum with baked enamel finish, with end caps.
- E. Direction of Travel: Match existing.
- F. Wand: Pultruded fiberglass to rotate louverse and transverse louvers. Include clutch to prevent damage from over-rotation.
- G. Accessory Hardware: Type recommended by blind manufacturer.

2.04 FABRICATION

- A. Determine sizes by field measurement.
- B. Fabricate blinds to cover window frames completely.
- C. At openings requiring multiple blind units, provide separate blind assemblies with space of 3/8 inch between blinds, located at window mullion centers.

PART 3 EXECUTION

3.01 INSTALLATION

- A. Install blinds in accordance with manufacturer's instructions.
- B. Secure in place with flush countersunk fasteners.
- C. Install sufficient bracks to prevent deflection of headrail.

3.02 TOLERANCES

- A. Maximum Variation of Gap at Window Opening Perimeter: 1/4 inch.
- B. Maximum Offset From Level: 1/8 inch.

3.03 ADJUSTING

A. Adjust blinds for smooth operation.

3.04 CLEANING

A. Clean blind surfaces just prior to occupancy.

END OF SECTION

Jun-30-2023 122116 - 2

1.01 SECTION INCLUDES

A. Existing electrical lighting, power and signal systems are to be altered as detailed on the drawings.

PART 2 PRODUCTS

2.01 EXISTING MATERIALS

A. Existing materials which are a part of the building shall remain the property of the Owner.

2.02 EXISTING MATERIALS RE-INSTALLED

A. Existing materials and equipment that are removed as a part of the work or stored in surplus may be reinstalled as a part of the new system subject to approval of condition suitability by the Owner. The requirements of the specifications (i.e. installation, warranty, testing, etc.) shall apply as if the materials were new, supplied by the Contractor.

2.03 EXISTING MATERIALS NOT TO BE RE-INSTALLED

- A. In coordination with the Owner, these materials shall be made available for his inspection and decision as to whether the Owner will retain possession. Items selected for retention shall be delivered to a location on the premises selected by the Owner and turned over to him. Take reasonable care to avoid damage to this material. If the Contractor fails to conform to this requirement, he shall purchase and turn over to the Owner replacement materials of like kind and quality.
- B. All material not selected for retention by the Owner and debris shall be disposed of by the Contractor. This shall include, but not be limited to, removal of PCB type ballasts and fluorescent lamps which shall be disposed of in accordance with EPA requirements.

PART 3 EXECUTION

3.01 EXISTING CONDITIONS

- A. Examine the structure, building, and conditions under which Division 26 work is to be installed for conditions detrimental to proper and timely completion of the work. Do not proceed with work until deficiencies encountered in installation have been corrected. Report any delay or difficulties encountered in installation of Division 26 work which might be unsuitable to connect with work by other divisions of this specification. Failure to report conditions shall constitute acceptance of other work as being fit and proper for the installation of Division 26 work.
- B. Maintain continuity of existing circuits of equipment to remain. Existing circuits of equipment shall remain energized. Circuits which are to remain but were disturbed during demolition shall have circuits, wiring, and power restored back to original condition.

3.02 DEMOLITION

A. Switchboards, panel boards, signaling systems, other electrical equipment free standing (or surface mounted), raceway (exposed) and conductor's no longer in service as a result of this Contract shall be removed. Unused raceways or sleeves shall be cut flush at ceiling, floor or wall and filled with grout.

3.03 EXISTING PANELBOARD

- A. Any modifications made to existing panels must be incorporated into the existing circuit index on the panel. If more than three circuits are modified a new typewritten index incorporating the changes to the existing index shall be installed in the existing panel.
- B. Listing shall match circuit breaker arrangements, typically with odd numbers on the left and even numbers on the right. Room numbers used shall be final room numbers used in the building as verified with the Owner.

END OF SECTION

Jul-12-2023 260005 - 1

1.01 SECTION INCLUDES

A. Provide all wire, cable, and terminations complete.

PART 2 PRODUCTS

2.01 WIRE AND CABLE (COPPER, 600-VOLT)

- A. Interior and Above Grade: All wires to be Type THW or RHW. Type THWN/THHN or XHHW wire may be utilized at Contractors option, subject to code requirements. Wire and cables shall be brought to project in original containers bearing the underwriters label. Provide Type AVA wire where conductors are subject to temperature above 167 Degrees F.
- B. Underground: All conductors to be type USE. Increase Raceway size when necessary to accommodate conductors per code. Exception: Underground conductors completely contained in code recognized Raceway and boxes may be Type THW, THWN or XHHW.
- C. Non-metallic sheathed cable (Romex) may be used at the Contractor's option subject to all code requirements and the local AHJ.

2.02 SPLICES

- A. Above Grade: Solderless type only. Preinsulated "twist-on" type (limited to size #10 and smaller). Bolt on compression type with application of preformed insulated cover, heat shrinkable tubing or plastic insulated tape acceptable for all sizes.
- B. Below Grade: Splices below grade shall be in handholes and shall be made watertight with epoxy resin type splicing kits similar to Scotchcast.

2.03 TERMINATIONS

- A. Compression set, bolted or screw terminal.
- B. Conductors #12 and smaller shall utilize eye or forked tongue type compression set terminator when termination is to a bolted or screw set type terminal block or terminal cabinet.

2.04 PLASTIC CABLE TIES

A. Nylon or Equivalent, locking type.

PART 3 EXECUTION

3.01 GENERAL

A. Install all wiring in Raceway unless shown or specifically authorized otherwise.

3.02 WIRE SIZE

- A. No. 12 AWG minimum for power and lighting circuits.
- B. Provide solid wire for No. 10 AWG and smaller, and stranded conductors for No. 8 AWG and larger (600) volts.

3.03 TESTS

- A. In addition to the factory testing of all equipment and cable, the Contractor shall test all wiring connections for continuity and ground before any fixtures or other loads are connected. Tests shall be made with a 500V. Minimum DC "Megger" type tester. If tests indicate faulty insulation (less that 2 megohms), such defects shall be corrected and tested again. Contractor shall provide all apparatus to make tests and shall bear all expenses of required testing. Routine operation tests shall be made on all pieces of equipment to demonstrate that working parts are in operating condition. Results of all tests shall be recorded and submitted to the Architect. The Contractor shall immediately replace all parts, which fail to pass the test.
- B. All circuits both in and out of the building shall test out free of grounds, short circuits and other defects.

Jul-12-2023 260519 - 1

- C. Check and record catalog number and ampere size of controller overload heaters installed, nameplate full-load amperes, and actual operating amperes of each motor. IMPORTANT: Submit recorded data in triplicate to the Owner. Check proper load balance on the electrical system, direction of rotation, lubrication, and overload protection of all motors before placing in operation.
- D. Provide a log of ampere reading for all panels from phase to neutral for 4 wire panels and from phase to phase for 3 wire panels. These readings shall be taken with all loads activated.
- E. The final test of all equipment shall be made on dates designated by the Owner and all readings shall be made in his presence.
- F. Feeders shall be checked to ensure all phases are energized before connecting to their respective motors. Each motor shall rotate in the proper direction for its respective load. Prior to rotation test, all bearings shall be inspected for proper lubrication.
- G. Minimum megger test for equipment shall be as follows:

Equipment Maximum	Minimum Test
Voltage Rating	Resistance
1,000-Volts or less	2 Megohms

H. Provide certification of torque values for feeder and service entrance conductors per equipment manufacturer's recommendation.

3.04 CONDUCTOR SIZES, REFERENCED ON PLANS

A. Copper, type THW or RHW unless noted.

3.05 PULLING

A. Use no mechanical means for pulling No. 8 AWG conductors and smaller. Powdered soap stone or approved spray cream shall be the only lubricant used.

3.06 STRIPPING INSULATION

A. Do not ring the cable, always pare or pencil.

3.07 TAPING

A. If used shall be half lapped synthetic tape.

3.08 CONDUCTORS IN PANELS AND SWITCHBOARDS

A. Conductors in panels, switchboards, and terminal cabinets shall be neatly grouped and formed in a manner to "Fan" into terminals with regular spacing.

3.09 CABLE SUPPORTS

A. Provide conductor support devices as required by code in vertical cable runs.

3.10 RACEWAY SIZES REFERENCED ON DRAWINGS

A. Raceways are sized for copper, type THW, unless otherwise noted. Size all Raceways per code unless specifically noted to be larger on the drawings.

3.11 NON-METALLIC SHEATHED CABLE PROTECTION

- A. Install non-metallic sheathed cable in at least a 2 ¾" deep chase as measured from the finished wall surface per WAC requirements.
- B. Provide a steel plate recessed in the cavity, covered with plaster, adobe or similar finish between the finished wall surface and the cable if the cable cannot be recessed at least 2 3/4" deep.

END OF SECTION

Jul-12-2023 260519 - 2

1.01 SECTION INCLUDES

A. A grounding system shall be provided for neutral ground and equipment ground as required by code.

PART 2 PRODUCTS

2.01 GROUNDING CONDUCTORS

A. Copper, code size, with physical protection where subject to damage. Bare or green insulated.

PART 3 EXECUTION

- 3.01 GENERAL
- 3.02 PROVIDE ALL GROUNDING FOR ELECTRICAL SYSTEMS AND EQUIPMENT AS REQUIRED BY CODES AND AS SPECIFIED HEREIN.
- 3.03 SIZE OF GROUND WIRE
 - A. As required by code. Where ground wire is exposed to physical damage or is used outside of building or underground, protect with rigid non-metallic conduit.

3.04 GROUND CONNECTION OF WATER PIPING

A. Metal internal piping shall be grounded, as part of this Contract. This includes jumpers for dielectric fittings.

3.05 CONNECTION TO THE GROUND BUS

A. Provide connections in accordance with the codes; including but not limited to conduit system, switchboard frame, service neutral and electrically operated equipment and devices. No device or equipment shall be connected for electrical service which has a neutral conductor connected to a grounding conductor or to the frame within the device or equipment.

3.06 METHOD OF CONNECTION

- A. Make all ground connections and ground cable splices by thermal welding. Grounding lugs, where provided as standard Manufacturer's items on equipment furnished, may be used.
- 3.07 FLEXIBLE RACEWAY
- 3.08 SHALL NOT BE USED FOR GROUNDING. INSTALL SEPARATE GROUND CONDUCTOR IN ALL FLEXIBLE RACEWAY.
- 3.09 PVC RACEWAY
 - A. Install separate ground conductor in all PVC raceway as required per code.

END OF SECTION

Jul-12-2023 260526 - 1

1.01 SECTION INCLUDES

A. Provide outlet and pull boxes to enclose devices, permit the pulling of conductors and for wire splices and branches.

PART 2 PRODUCTS

2.01 INTERIOR WIRING

- A. General: Outlet and pull boxes shall be pressed drawn steel, zinc coated with plaster ring where applicable. Welded boxes not allowed. Four-inch size minimum. Large pull boxes shall be fabricated sheet steel, zinc coated or baked enamel finish, with return flange and screw retained cover. Non-metallic boxes may be used within dwelling units as permitted by code.
- B. Surface Metal Raceway: Boxes of same manufacture and to match Raceway. Boxes to accommodate standard devices and device plate.
- C. Install pull boxes so as to be accessible after completion of building construction.

2.02 EXTERIOR WIRING

- A. Above Grade: Outlet and junction boxes shall be cast or malleable iron or shall be cast of corrosion resistant alloy compatible with Raceway to which it is connected. Pull boxes shall be fabricated of heavy gauge steel and hot dipped galvanized. All boxes shall have gasketed covers.
- B. Below Grade: Where exposed to earth, boxes (handholes) shall be constructed of precast concrete with size, configuration, cover, grates and reinforcing as required by the particular installation. Manufacturer: Similar to Utility Vault 3030LA with base or Fogtite J11 Type 2 with base. Lid shall be H-20 rated where installed in traffic areas. Where not exposed to earth shall comply with Paragraph 2.02A above.
- Exterior outlet boxes shall be weather resistant and rain tight, with appropriate covers, gaskets and screws.

PART 3 EXECUTION

3.01 ANCHORING

A. All boxes shall be firmly anchored directly or with concealed bracing to building studs or joints. Boxes must be so attached so that they will not "Rock" or "Shift" when devices are operated.

3.02 FLUSH MOUNTING

A. Except for surface mounted boxes or boxes above accessible ceilings, all boxes shall have front edge (box or plaster ring) even with the finished surface of the wall or ceiling.

3.03 ELECTRICAL OUTLETS

- A. General: Coordinate the work of this section with the work of other sections and trades. Study all Drawings that form a part of this Contract and confer with various trades involved to eliminate conflicts between the work of this section and the work of other trades. Check and verify outlet locations indicated on Drawings, door swings, installation details, layouts of suspended ceilings and locations of all plumbing, heating and ventilating equipment.
- B. Centered on Built-In Work: In the case of doors, cabinets, recessed or similar features, or where outlets are centered between such features, such as between a door jamb and a cabinet, make these outlet locations exact. Relocate any outlets which are located off center.
- C. Vertical and Horizontal Relationships: Where more than one outlet is shown or specified to be at the same elevation or one above the other, align them exactly on centerlines horizontally or vertically. Relocate as directed all such outlets (including lighting, receptacle, power signal and thermostat outlets) which are not so installed, at no additional cost to Owner.
- D. Device Outlet Height: Measure from the finished floor to the top of the rough-in box, unless otherwise noted.

Jul-12-2023 260532 - 1

- 1. Switches: 4 Feet to top of rough-in box, Set Vertically
- 2. Receptacles & Telephone: 18 Inches to center, Set Vertically or as Indicated
- 3. Other: As Noted or as Directed by Owner

3.04 ELECTRICAL WORK IN COUNTERBACKS, MILLWORK AND CASEWORK

A. Provide as shown and/or specified. Provide templates, where required, to other trades for drilling and cutting to ensure accurate location of electrical fixtures (outlets and devices) as verified with the Architect. Provide all wiring, devices, plates, and connections required by said fixture.

3.05 CONNECTION TO EQUIPMENT

A. For equipment furnished under this or other Divisions of the Specifications, or by others. Provide outlet boxes of sizes and at locations necessary to serve such equipment. An outlet box is required if the equipment has pigtail wires for external connection, does not have space to accommodate circuit wiring used. Study equipment details to assure proper coordination.

3.06 BLANK COVERS

A. Provide blank covers or plates over all boxes not covered by equipment.

3.07 JUNCTION OR PULL BOXES

- A. Pull and junction boxes shall be installed as shown, and to facilitate pulling of wire and to limit the number of bends within code requirements. Boxes shall be permanently accessible and shall be placed only at locations approved by the Architect.
- B. In suspended ceiling spaces, boxes shall be supported from the structure independently from ceiling suspension system.
- C. The Drawings do not necessarily show every pull or Junction Box required. The Contractor is permitted to provide boxes deemed necessary by him for his work when installed in accordance with these Specifications.

3.08 BOXES CONTAINING MULTIPLE DEVICES

- A. Boxes containing emergency and normal devices are permitted only with steel barriers manufactured especially for the purpose of dividing the box into two completely separate compartments.
- B. Device boxes containing multiple devices and wiring rated over 150 volts to ground and over 300 volts between conductors are permitted only with steel barrier manufactured especially for the purpose of dividing the box into separate compartments for each device having exposed live parts.

3.09 BOXES IN EARTH

A. Provide for all wire splices and as required to pull conductors. Boxes (handholes) shall be set in place on a 3" sand bed. Coverplates shall be flush to, and match the slope of, the final surface grade.

END OF SECTION

Jul-12-2023 260532 - 2

1.01 SECTION INCLUDES

A. Provide Raceway System complete.

PART 2 PRODUCTS

2.01 GALVANIZED RIGID STEEL CONDUIT (GRS)

- A. General: Hot dipped galvanized.
- B. Fittings: Galvanized malleable iron or noncorrosive alloy compatible with galvanized conduit. Erickson couplings, watertight split couplings (O.Z. type or equivalent) permitted. Running thread or set screw type fittings not approved.

2.02 INTERMEDIATE METAL CONDUIT (IMC)

- A. General: Hot Dipped galvanized.
- B. Fittings: Galvanized malleable iron or noncorrosive alloy compatible with galvanized conduit. Erickson couplings, watertight split couplings (O.Z. type or equivalent) permitted. Running thread or set screw type fittings not approved.

2.03 ELECTRICAL METALLIC TUBING (EMT)

- A. General: Hot dipped galvanized.
- B. Fittings: Raintight; steel or malleable iron type using a split corrugated compression ring and tightening nut or stainless steel locking disc. Steel set screw fittings are acceptable. Indenter, drive-on and pressure cast or die cast type set screw are not acceptable.

2.04 FLEXIBLE METAL CONDUIT

- A. Dry Locations:
 - 1. General: Galvanized flexible steel for dry locations.
 - 2. Fittings: Malleable iron or steel, Thomas and Betts "squeeze" type or equal.
- B. Damp and Wet Locations:
 - 1. Liquid Tight: Polyvinyl chloride (PVC) weatherproof cover over flexible steel conduit.
 - 2. Fittings: Thomas and Betts "Super-Tite" or equal.

2.05 SURFACE METAL RACEWAY

A. Formed steel or aluminum type. Standard factory finish. Where color choice is available, consult Owner for selection prior to ordering.

2.06 RIGID NON-METALLIC CONDUIT (PVC)

A. Schedule 40 rigid polyvinyl chloride type unless otherwise noted.

PART 3 EXECUTION

3.01 GENERAL

- A. Install Raceway concealed in construction unless noted otherwise on the Drawings or specifically approved in writing by the Owner.
- B. Cut Raceway ends square, ream and extend maximum distance into all couplings and connectors.
- C. Provide and install manufactured end caps on all Raceway ends during construction to prevent the entrance of water or dirt. Tape, as a cover, not permitted.
- D. Swab out all Raceways before pulling wires.
- E. All elbows for GRS and PVC Raceway shall be factory elbows. For all other Raceway, use factory ells for bends of 1-1/4" and larger diameter.

Jul-12-2023 260533 - 1

- F. Raceway shall not penetrate sheet metal ducts unless permission is granted by Owner. All sleeves shall be provided for Raceway installation.
- G. Provide 2 3/4" C.O. stub into accessible ceiling space from all recessed panelboards or systems terminal boxes.

3.02 GALVANIZED RIGID STEEL CONDUIT

A. All Connections shall be watertight. Install for all Raceways in concrete or where subject to damage.

3.03 INTERMEDIATE METAL CONDUIT

A. Intermediate metal conduit is permitted as a substitute for galvanized rigid steel conduit except where GRS is required by code.

3.04 ELECTRICAL METALLIC TUBING

A. Install for wiring in frame construction, furred ceilings and above suspended ceilings. May be used for exposed work in unfinished areas where not subject to damage.

3.05 RACEWAYS UNDERGROUND

- A. Galvanized rigid steel conduit painted with two coats of bitumastic paint or galvanized rigid steel conduit with 15 mil. polyvinyl chloride (PVC) jacket (repair abrasions with PVC base paint or PVC)
- B. PVC Raceways may be used for underground runs when permitted by code. Field bends, when necessary, shall be formed only with factory recommended heater. Penetrations through floor and walls shall be galvanized rigid steel conduit. PVC, if used, shall be increased in size from that shown to include code required ground wire. Bends in excess of 10 degrees shall be GRS.
- C. Arrange and slope Raceways entering building to drain away from building.
- D. Ground wires shall be provided in all PVC Raceway.

3.06 INSERTS, SHIELDS AND SLEEVES

- A. Furnish and set in place, in advance of pouring slabs and walls, all inserts and sleeves needed to execute Division 16 equipment installation.
- B. Where supports in slabs are required after wall has been poured, use a drilled-in threaded insert, installed as recommended by Manufacturer.
- C. Sleeves shall be provided for all wall penetrations.

3.07 RACEWAYS THAT STUB UP THROUGH FLOOR

- A. Install at such depth that the exposed Raceway is vertical and no curved section of the elbow is visible.
- B. PVC Raceway shall not be stubbed through floors.

3.08 SEALING OF RACEWAY PENETRATIONS

- A. Exterior Wall Surfaces Above Grade: Seal around all penetrations with caulking approved by Engineer. For concrete construction above ground level, cast Raceway in wall or core drill wall and hard pack with a mixture of equal parts of sand and cement.
- B. Exterior Surfaces Below Grade: Cast Raceway into wall (or floor) or use manufactured seal assembly (such as O.Z. type "FSK") cast in place.
- C. Roofs: Provide mopped, lead, roof jack where Raceway penetrates roof membrane.
- D. Fire Rated Floors, Walls, Ceiling/Roofs: At gypsum wallboard, seal around Raceway penetration with plaster, fire tape per local Fire Marshal's requirements.

3.09 SEALING OF RACEWAYS

A. Seal interior of all Raceways which pass through buildings roofs or through outside walls of the building, above or below grade. Seal on the end inside the building using duct sealing mastic, non-hardening compound type, specially designed for such service. Pack around the wires in the Raceways.

Jul-12-2023 260533 - 2

3.10 HANGARS FOR RACEWAYS

- A. In suspended ceiling spaces Contractor may, at his option, attach 1/2" or 3/4" EMT Raceways to the ceiling suspension system where such system is structurally suitable; in which case, provide clips manufactured for the purpose.
- B. When more than two Raceways will use the same routing, group together on a patented channel support system (such as Unistrut).

3.11 SURFACE METAL RACEWAY

A. Install parallel to building surface (i.e., wall, ceiling, floor). Fasten to surface as recommended by Manufacturer. Mount so Raceway is in the least obvious location.

3.12 FLEXIBLE CONDUIT

A. Flexible conduit shall be used only for connection to motors and equipment subject to vibration with 90 degrees loop minimum to allow for isolation and for lay-in fluorescent fixtures above T-Bar ceilings. For fixture installations, one end of flex must terminate in rough-in junction box. Flex conduit shall not be installed over 6' long or used to connect from fixture to fixture. Use liquid tight for pumps, equipment which is regularly washed down, and equipment in damp locations. Provide ground wire when required by code.

3.13 PULL CORDS

A. Nylon type shall be included in all installed empty Raceway.

END OF SECTION

Jul-12-2023 260533 - 3

1.01 SECTION INCLUDES

A. Exterior light fixtures, drivers, LED's, and associated appurtenances.

1.02 DEFINITIONS

- A. Average Life: The time after which 50 percent will have failed and 50 percent will have survived under normal conditions.
- B. CCT: Correlated color temperature.
- C. CRI: Color-rendering index.
- D. Fixture: A complete lighting unit or exit sign. Fixtures include lamps and parts required to distribute the light, position and protect lamps, and connect lamps to the power supply.
- E. LER: Luminaire efficacy rating.
- F. Lumen: Measured output of lamp and luminaire, or both.
- G. Luminaire: Fixture.

1.03 SUBMITTALS

- A. Product Data: Submit manufacturer's technical product data and maintenance data for each type of lighting fixtures and appurtenance. Submit product data for each lamp type and each ballast type, with a matrix indicating which fixtures apply to submitted ballast and lamp type.
- B. Shop Drawings:
 - 1. Submit dimensioned drawings of each type of lighting fixtures. Submit in booklet form with separate sheet for each fixture, assembled in luminaire "type" in alphabetical order with proposed fixture and appurtenance clearly indicated on each sheet.
- C. Test Reports:
 - 1. Field test reports.
 - 2. Submit completed copy of reports and include copy in the Operation and Maintenance Manual.

1.04 CLOSEOUT SUBMITTALS

A. Operation and Maintenance Data: For luminaires to include in emergency, operation, and maintenance manuals.

1.05 OUALITY ASSURANCE

- A. Regulatory Requirements: Comply with applicable city, county, and state codes and ordinances.
- B. Codes and Standards: NFPA 70, National Electrical Code (NEC).
- C. Comply with NEC and NEMA for installation and construction of lighting fixtures. Comply with NEC for recessed incandescent lighting fixtures. Lighting fixtures UL listed and labeled.

PART 2 PRODUCTS

2.01 MANUFACTURERS

- A. Products:
 - 1. Unit Light Fixture: Luminaire LED Swoop 610, Series SWP610 or approved equal.
 - 2. Security Light Fixture: Cooper McGraw Edison GWC SA1 B800mA 740
 - a. T2 MS/DIM or approved equal.
- B. Comply with manufacturer's written recommendations for lamp and ballast combinations.

2.02 FIXTURE COMPONENTS, GENERAL

- A. Metal Parts: Free from burrs and sharp corners and edges.
- B. Sheet Metal Components: Steel, except as indicated. Components are formed and supported to prevent warping and sagging.

Jul-12-2023 265600 - 1

- C. Doors, Frames, and Other Internal Access: Smooth operating and free from light leakage under operating conditions. Arrange to permit relamping without use of tools. Arrange doors, frames, lenses, diffusers, and other pieces to prevent accidental falling during relamping and when secured in the operating position.
- D. Lenses, Diffusers, Covers, and Globes: 100 percent virgin acrylic plastic or water white, annealed crystal glass except as indicated.
 - Plastic: Highly resistant to yellowing and other changes due to aging, exposure to heat and UV radiation.
 - 2. Lens Thickness: 0.156 inches minimum.

2.03 EXTERIOR LIGHT FIXTURES

A. A. General:

- 1. Light fixtures of sizes, types, and ratings indicated on the Drawings complete with, but not necessarily limited to, housings, lamps, reflectors, starters, and wiring.
- 2. Label each fixture with manufacturer's name and catalog number.
- 3. Include positive latch mechanisms for enclosed fixtures. Spring tension clips not acceptable.
- 4. Include exterior fixtures with damp or wet location label as required by application.
- B. LED's: Rated for utilization voltage.

C. Diffusers:

- 1. 100 percent virgin acrylic compound.
- 2. Minimum thickness 0.125 inches.

D. Support Requirements:

- 1. Include flexible ball joint hangers for pendant and stem hung fixtures at points of support.
- 2. Equip hooks used to hang fixtures with safety latches. Include supports, brackets, clips, screws, and miscellaneous items for mounting fixtures.
- 3. Include locking catches, screws, safety chain, or safety cable for detachable fixture parts, luminous ceiling accessories, louvers, diffusers, lenses, and reflectors.

PART 3 EXECUTION

3.01 PREPARATION

- A. Field verify locations of new and existing work prior to commencing work of this section.
- B. Protect surrounding areas and surfaces to preclude damage from work of this section.

3.02 INSTALLATION

A. Install, apply, erect, and perform the work in accordance with specifications and manufacturer's installation instructions and directions. Where these may be in conflict, the more stringent requirements govern.

3.03 LIGHTING FIXTURE INSTALLATION

- A. Install lighting fixtures at locations and heights of existing fixtures, as indicated on the Drawings, in accordance with fixture manufacturer's written instructions, applicable requirements of NEC, NESC, NECA's "Standards of Installation", NEMA standards, and recognized industry practices to ensure that lighting fixtures fulfill requirements.
- B. Coordinate with other work as appropriate to properly interface installation of lighting fixtures with other work. Consult architectural reflected ceiling plan and interior elevations for location of lighting fixtures.
- C. Lighting Fixture Supports:
 - 1. General: Comply with NEC as interpreted by AHJ or IBC, whichever is more stringent, for fixtures mounted in suspended ceilings.
 - 2. Seismic Restraints:
 - a. For Lighting Fixtures Weighing Less than 10 Pounds: Install 1 slack No. 12 gage hanger wire from fixture to structure above.

Jul-12-2023 265600 - 2

- b. For Lighting Fixtures Weighing 10 to 56 Pounds: Install 2 slack No. 12 gage hanger wires from fixture to structure above.
- 3. For Lighting Fixtures Weighing More than 56 Pounds: Support directly from the structure above by hangers approved by the AHJ. Comply with requirements in Section 260548 for seismic restraints.
- D. Clean lighting fixtures of dirt and debris upon completion of installation.
- E. Protect installed fixtures from damage during construction period. Repair nicks and scratches to appearance of original finish.

3.04 FIELD QUALITY CONTROL

A. Upon completion of installation of lighting fixtures and electrical circuitry, energize circuitry and demonstrate capability and compliance with requirements. Repair malfunctioning units on site, then retest to demonstrate compliance. If not possible to repair on site, remove and provide new units and retest. Include copy of test reports in the Operation and Maintenance Manual.

END OF SECTION

Jul-12-2023 265600 - 3